



FCC ID: XCO-CEXUT2  
IC: 7756A-CEXUT2

## Statement of compliance to Maximum Permissible Exposure (MPE)

Equipment : CEX wireless range extender  
Type/Model : Sonab CEX unit 2  
Applicant : Hansong(Nanjing) Technology Ltd.  
8th Kangping Road, Jiangning Economy and Technology  
Development Zone, Nanjing, China, 211100

Here assuming a worst-case prediction of power density (100% reflection), then

$$S = 4P_{\text{EIRP}} / (4\pi R^2) = P_{\text{EIRP}} / (\pi R^2).$$

Where S = power density in mW/cm<sup>2</sup>

$P_{\text{EIRP}}$  = EIRP in mW

R = distance (cm)

As we can see from the test report SH11110050-002:

The maximum  $P_{\text{EIRP}}$  of 2.4GHz transmitter = 15.95dBm + 1.0dBi = 16.95dBm = 49.56mW

The maximum  $P_{\text{EIRP}}$  of 5.8GHz transmitter = 13.30dBm + 1.0dBi = 14.30dBm = 26.92mW

For the two transmitters work simultaneously, the worst total  $P_{\text{EIRP}}$  = 49.56 + 26.92 = 76.48mW

Here R is chosen to be 20cm,

$$S = P_{\text{EIRP}} / (\pi R^2) = 76.48 / (3.14 * 20 * 20) = 0.06\text{mW/cm}^2$$

This level is below the 1 mW/cm<sup>2</sup> MPE for General Population / Uncontrolled Exposure as stated in OET BULLETIN 65 Edition 97-01.

Date of issue: March 2, 2012

Prepared by:

Wakeyou Wang (Project Engineer)

Reviewed by:

Daniel Zhao (Reviewer)



**FCC ID: XCO-CEXUT2**  
**IC: 7756A-CEXUT2**

## **Appendix I**

**Definition below must be outlined in the User Manual:**

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.  
To ensure compliance, operations at closer than this distance is not recommended.