



TEST REPORT

APPLICANT : Shenzhen Tinno Mobile Technology Corp.

PRODUCT NAME : onn. 10.4" Tablet Pro

MODEL NAME : TBSPG100097968, TBGGL100097968,
TBMMS100097968, TBBGD100097968,
TBSPG100110603, TBGGL100110603,
TBMMS100110603, TBBGD100110603,
100097968, 100110603

BRAND NAME : onn.

FCC ID : XD6T5100A

STANDARD(S) : 47 CFR Part 15 Subpart B

RECEIPT DATE : 2022-09-20

TEST DATE : 2022-10-12 to 2022-10-19

ISSUE DATE : 2022-11-09

Edited by: Chen Bilian
Chen Bilian(Rapporteur)

Approved by: Xiao Xiong
Xiao Xiong(Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3**
- 1.1. Applicant and Manufacturer Information 3**
- 1.2. Equipment Under Test (EUT) Description 3**
- 2. Test Results 5**
- 2.1. Applied Reference Documents 5**
- 2.2. EUT Setup and Operating Conditions 6**
- 3. 47 CFR Part 15B Requirements 7**
- 3.1. Conducted Emission 7**
- 3.2. Radiated Emission 11**
- Annex A Test Uncertainty 18**
- Annex B Testing Laboratory Information 19**

Change History		
Version	Date	Reason for change
1.0	2022-11-09	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Shenzhen Tinno Mobile Technology Corp.
Applicant Address:	27-001, South Side of Tianlong Mobile Headquarters Building, Tongfa South Road, Xili Community, Xili Street, Nanshan District, Shenzhen ,PRC
Manufacturer:	Shenzhen Tinno Mobile Technology Corp.
Manufacturer Address:	27-001, South Side of Tianlong Mobile Headquarters Building, Tongfa South Road, Xili Community, Xili Street, Nanshan District, Shenzhen ,PRC

1.2. Equipment Under Test (EUT) Description

Product Name:	onn. 10.4" Tablet Pro	
EUT No.:	8#	
Hardware Version:	V0.3	
Software Version:	100110603_20221015	
Frequency Range:	Bluetooth: 2402 MHz ~ 2480 MHz 802.11b/g/n: 2412 MHz ~ 2472 MHz 802.11a/ac/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz	
Accessory:	AC Adapter	
	Brand Name:	Onn.
	Model No.:	LACA216
	Serial No.:	(N/A, marked #1 by test site)
	Rated Input:	100-240V~ 50/60Hz, 0.3A
	Rated Output:	5V=2A
	Manufacturer:	ASAP Technology(Jiangxi) Co., Ltd
	Battery	
	Brand Name:	N/A
	Model No.:	U309395PV-1S2P
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	7300mAh
	Rated Voltage:	3.8V



	Charge Limit:	4.35V
	Manufacturer:	SHENZHEN UTILITY ENERGY CO., LTD.
	USB Cable	
	Model:	WIABLK100008354
	Manufacturer:	Luxshare-ICT

Note:

1. According to the certificate holder, they declared that the product name: onn. 10.4" Tablet Pro, with model name: TBSPG100097968, TBGGL100097968, TBMMS100097968, TBBGD100097968, TBSPG100110603, TBGGL100110603, TBMMS100110603, TBBGD100110603, 100097968, 100110603 have the same hardware and software, the only differences are the appearance, trade name, model name and memory room for trading purpose. The difference appearance is for color and silk-screen only. The main test model name is TBSPG100110603, only the result for TBSPG100110603 was recorded in this report.
2. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.

2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination Remark
1	15.107	Conducted Emission	2022.10.19	Fan Zehang	PASS	No deviation
2	15.109	Radiated Emission	2022.10.12	Li Hanbin	PASS	No deviation

Note 1:The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.

Note 2:Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3:When the test result is a critical value,we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



2.2. EUT Setup and Operating Conditions

Test Item	
Radiated Emission	
Mode 1	: Bluetooth Link + 2.4G WLAN Link + AC Adapter + Battery + USB Cable + Earphone
Mode 2	: Bluetooth Idle + 2.4G WLAN Idle + AC Adapter + Battery + USB Cable + Earphone
Mode 3	: Bluetooth Link + 5G WLAN Link + AC Adapter + Battery + USB Cable + Earphone
Mode 4	: Bluetooth Idle + 5G WLAN Idle + AC Adapter + Battery + USB Cable + Earphone
Mode 5	: Bluetooth Idle + 5.8G WLAN Idle + AC Adapter + Battery + USB Cable + Earphone + Rear Camera Recording Mode
Mode 6	: Bluetooth Idle + 2.4G WLAN Idle + Battery + USB Cable + Earphone + PC + PC Adapter + Data Transmission Mode
Conducted Emission	
Mode 1	: Bluetooth Link + 2.4G WLAN Link + AC Adapter + Battery + USB Cable + Earphone
Mode 2	: Bluetooth Idle + 2.4G WLAN Idle + AC Adapter + Battery + USB Cable + Earphone
Mode 3	: Bluetooth Link + 5G WLAN Link + AC Adapter + Battery + USB Cable + Earphone
Mode 4	: Bluetooth Idle + 5G WLAN Idle + AC Adapter + Battery + USB Cable + Earphone
Mode 5	: Bluetooth Idle + 5.8G WLAN Idle + AC Adapter + Battery + USB Cable + Earphone + Rear Camera Recording Mode
Mode 6	: Bluetooth Idle + 2.4G WLAN Idle + Battery + USB Cable + Earphone + PC + PC Adapter + Data Transmission Mode
Remark: The above test mode in boldface (Mode 5) was the worst case of conducted emission test, only the test data of these modes were reported. The above test mode in boldface (Mode 5) was the worst case of radiated emission test, only the test data of these modes were reported.	

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.






The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


3.1.3. Test Result

Set RBW=9 kHz, VBW=30 kHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

A. Test Plot and Suspicious Points:



No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quasi-peak	Average	Quasi-peak	Average		
1	0.1729	49.15	35.88	64.82	54.82	Line	PASS
2	0.1942	51.86	27.72	63.85	53.85		PASS
3	0.3436	42.70	29.73	59.12	49.12		PASS
4	0.5198	37.80	31.72	56.00	46.00		PASS
5	0.6279	37.37	30.73	56.00	46.00		PASS
6	22.9655	45.58	18.26	60.00	50.00		PASS



No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quasi-peak	Average	Quasi-peak	Average		
1	0.1682	55.92	33.39	65.05	55.05	Neutral	PASS
2	0.2848	48.46	32.27	60.68	50.68		PASS
3	0.5173	40.79	31.11	56.00	46.00		PASS
4	0.6373	40.34	29.90	56.00	46.00		PASS
5	0.6932	39.57	27.48	56.00	46.00		PASS
6	22.9643	43.69	16.93	60.00	50.00		PASS



3.2. Radiated Emission

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency Range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	($\mu\text{V/m}$)	($\text{dB}\mu\text{V/m}$)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in $\text{dB}\mu\text{V/m}$ is calculated by $20\log$ Emission Level($\mu\text{V/m}$).


3.2.2. Frequency Range of Measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

For measurements below 1GHz the resolution bandwidth is set to 120 kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video bandwidth is set to 3MHz for peak measurements and as applicable for average measurements.

3.2.4. Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions (6GHz-30GHz) which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




No.	Fre. MHz	PK dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	34.3654	30.61	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
2	68.9979	33.32	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
3	92.0862	24.80	N.A.	N.A.	N.A.	43.50	N.A.	V	PASS
4	153.8814	33.91	N.A.	N.A.	N.A.	43.50	N.A.	V	PASS
5	360.0270	26.97	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS
6	759.9980	27.43	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS



No.	Fre. MHz	PK dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	1078.0156	34.73	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
2	1585.1170	34.86	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
3	2604.3209	39.10	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
4	3727.5455	42.50	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
5	4756.7514	44.68	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
6	5993.9988	47.22	N.A.	N.A.	74.00	N.A.	54.00	V	PASS



No.	Fre. MHz	PK dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	33.4923	32.39	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
2	50.8571	22.88	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
3	153.4933	31.77	N.A.	N.A.	N.A.	43.50	N.A.	H	PASS
4	199.7670	27.19	N.A.	N.A.	N.A.	43.50	N.A.	H	PASS
5	317.3427	27.66	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS
6	949.4579	27.44	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS



No.	Fre. MHz	PK dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	1241.0482	35.47	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
2	1670.1340	36.40	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
3	2679.3359	38.88	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
4	3826.5653	43.08	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
5	4635.7271	44.66	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
6	5475.8952	47.00	N.A.	N.A.	74.00	N.A.	54.00	H	PASS

Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	9kHz-150kHz	±3.3dB
	150kHz-30MHz	±2.8dB

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	±5.06dB
	200MHz-1000MHz	±5.04dB
	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. Test firm registration number is 226174. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
TS+ -[JS32-RE]	Version 2.5.0.6	Tonscend
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend

**5. Test Equipments Utilized**

Description	Model	Serial No.	Manufacturer	Cal. Date	Due. Date
Bi-Log Antenna	VULB 9163	9163-519	SCHWARZBECK	2022/5/25	2025/5/24
Horn Antenna	BBHA 9120D	01774	SCHWARZBECK	2022/7/13	2025/7/12
Receiver	N9038A	MY564000 93	KEYSIGHT	2022/3/3	2023/3/2
6db Attenuator	BW-N6W5+	E191001	Mini-circuits	2021/10/18	2022/10/17
6db Attenuator	BW-N6W5+	E191001	Mini-circuits	2022/10/11	2023/10/10
Preamplifier	S020180L3203	61171/611 72	LUCIX CORP.	2022/7/8	2023/7/7
Preamplifier	S10M100L3802	46732	LUCIX CORP.	2022/7/8	2023/7/7
Receiver	ESPI	101052	R&S	2022/7/7	2023/7/6
LISN	NSLK 8127	8127449	Schwarzbeck	2022/3/3	2023/3/2
10dB Pulse Limiter	VTSD 9561-F	VTSD 9561 F-B #206	SCHWARZBECK	2022/7/6	2023/7/5

6. Ancillary Equipment Utilized

Description	Manufacturer	Model	Serial No.
Notebook Computer	DELL	P144G	20210357
Computer Adapter	DELL	HA65NM190	N/A
Earphone	VIVO	N/A	N/A

————— END OF REPORT —————