

Fig.A.6.1.23 Transmitter Spurious Emission - Conducted (802.11b, Ch11, 15 GHz-20 GHz)




Fig.A.6.1.24 Transmitter Spurious Emission - Conducted (802.11b, Ch11, 20 GHz-26 GHz)




Fig.A.6.1.25 Transmitter Spurious Emission - Conducted (802.11g, Ch1, Center Frequency)




Fig.A.6.1.26 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 30 MHz-1 GHz)




Fig.A.6.1.27 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 1 GHz-2.5 GHz)




Fig.A.6.1.28 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 2.5 GHz-7.5 GHz)




Fig.A.6.1.29 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 7.5 GHz-10 GHz)




Fig.A.6.1.30 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 10 GHz-15 GHz)




Fig.A.6.1.31 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 15 GHz-20 GHz)




Fig.A.6.1.32 Transmitter Spurious Emission - Conducted (802.11g, Ch1, 20 GHz-26 GHz)




Fig.A.6.1.33 Transmitter Spurious Emission - Conducted (802.11g, Ch6, Center Frequency)




Fig.A.6.1.34 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 30 MHz-1 GHz)




Fig.A.6.1.35 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 1 GHz-2.5 GHz)




Fig.A.6.1.36 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 2.5 GHz-7.5 GHz)




Fig.A.6.1.37 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 7.5 GHz-10 GHz)




Fig.A.6.1.38 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 10 GHz-15 GHz)




Fig.A.6.1.39 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 15 GHz-20 GHz)




Fig.A.6.1.40 Transmitter Spurious Emission - Conducted (802.11g, Ch6, 20 GHz-26 GHz)




Fig.A.6.1.41 Transmitter Spurious Emission - Conducted (802.11g, Ch11, Center Frequency)




Fig.A.6.1.42 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 30 MHz-1 GHz)




Fig.A.6.1.43 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 1 GHz-2.5 GHz)




Fig.A.6.1.44 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 2.5 GHz-7.5 GHz)




Fig.A.6.1.45 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 7.5 GHz-10 GHz)




Fig.A.6.1.46 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 10 GHz-15 GHz)




Fig.A.6.1.47 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 15 GHz-20 GHz)




Fig.A.6.1.48 Transmitter Spurious Emission - Conducted (802.11g, Ch11, 20 GHz-26 GHz)




Fig.A.6.1.49 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, Center Frequency)




Fig.A.6.1.50 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 30 MHz-1 GHz)




Fig.A.6.1.51 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 1 GHz-2.5 GHz)




Fig.A.6.1.52 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 2.5 GHz-7.5 GHz)




Fig.A.6.1.53 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 7.5 GHz-10 GHz)




Fig.A.6.1.54 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 10 GHz-15 GHz)




Fig.A.6.1.55 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 15 GHz-20 GHz)




Fig.A.6.1.56 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch1, 20 GHz-26 GHz)




Fig.A.6.1.57 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, Center Frequency)




Fig.A.6.1.58 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 30 MHz-1 GHz)




Fig.A.6.1.59 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 1 GHz-2.5 GHz)




Fig.A.6.1.60 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 2.5 GHz-7.5 GHz)




Fig.A.6.1.61 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 7.5 GHz-10 GHz)




Fig.A.6.1.62 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 10 GHz-15 GHz)




Fig.A.6.1.63 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 15 GHz-20 GHz)




Fig.A.6.1.64 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch6, 20 GHz-26 GHz)




Fig.A.6.1.65 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, Center Frequency)




Fig.A.6.1.66 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 30 MHz-1 GHz)




Fig.A.6.1.67 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 1 GHz-2.5 GHz)




Fig.A.6.1.68 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 2.5 GHz-7.5 GHz)




Fig.A.6.1.69 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 7.5 GHz-10 GHz)




Fig.A.6.1.70 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 10 GHz-15 GHz)




Fig.A.6.1.71 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 15 GHz-20 GHz)




Fig.A.6.1.72 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 20 GHz-26 GHz)

A.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:


Frequency (MHz)	Field strength(μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Set up:

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m

The EUT and transmitting antenna shall be centered on the turntable.



Test Condition

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as

appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Exploratory radiated emissions measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360° . For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

Final radiated emissions measurements

The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.

For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.

This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

The receiver references:

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Measurement Results:**EUT ID: EUT2/EUT3****Conclusion: Pass**

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= P_{Mea} + Cable Loss + Antenna Factor

Where:

P_{Mea} field strength recorded from the instrument

Peak
802.11b

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17964.000	57.10	-25.50	46.70	35.90	74.00	16.90	V
17967.000	57.00	-25.50	46.70	35.80	74.00	17.00	H
17940.000	56.60	-25.50	46.70	35.40	74.00	17.40	V
17965.500	56.30	-25.50	46.70	35.10	74.00	17.70	V
17989.500	56.30	-25.50	46.70	35.10	74.00	17.70	H
2369.200	55.20	-14.30	28.00	41.50	74.00	18.80	V

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17845.500	56.70	-25.50	46.70	35.50	74.00	17.30	V
17902.500	56.50	-25.50	46.70	35.30	74.00	17.50	V
17967.000	56.40	-25.50	46.70	35.20	74.00	17.60	V
17913.000	56.30	-25.50	46.70	35.10	74.00	17.70	V
17992.500	56.30	-25.50	46.70	35.10	74.00	17.70	H
17848.500	56.20	-25.50	46.70	35.00	74.00	17.80	H

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17938.500	57.60	-25.50	46.70	36.40	74.00	16.40	H
17961.000	57.10	-25.50	46.70	35.90	74.00	16.90	V
17953.500	56.30	-25.50	46.70	35.10	74.00	17.70	H
17737.500	56.10	-25.50	46.70	34.90	74.00	17.90	V
17877.000	56.10	-25.50	46.70	34.90	74.00	17.90	H
2492.200	57.80	-14.20	28.30	43.70	74.00	16.20	H

802.11g

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17761.500	56.60	-25.50	46.70	35.40	74.00	17.40	H
17953.500	56.60	-25.50	46.70	35.40	74.00	17.40	V
17997.000	56.60	-25.50	46.70	35.40	74.00	17.40	V
17991.000	56.40	-25.50	46.70	35.20	74.00	17.60	V
17646.000	56.20	-25.70	46.00	36.00	74.00	17.80	H
2389.400	57.20	-14.20	28.10	43.30	74.00	16.80	V

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17952.000	57.00	-25.50	46.70	35.80	74.00	17.00	H
17959.500	56.50	-25.50	46.70	35.30	74.00	17.50	H
17583.000	56.40	-25.70	46.00	36.20	74.00	17.60	V
17898.000	56.40	-25.50	46.70	35.20	74.00	17.60	H
17994.000	56.40	-25.50	46.70	35.20	74.00	17.60	H
17956.500	56.30	-25.50	46.70	35.10	74.00	17.70	H

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17917.500	56.40	-25.50	46.70	35.20	74.00	17.60	V
17919.000	56.40	-25.50	46.70	35.20	74.00	17.60	V
17959.500	56.40	-25.50	46.70	35.20	74.00	17.60	H
17974.500	56.30	-25.50	46.70	35.10	74.00	17.70	V
17982.000	56.30	-25.50	46.70	35.10	74.00	17.70	H
2485.200	63.00	-14.20	28.30	48.90	74.00	11.00	V

802.11n-HT20

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17926.500	56.50	-25.50	46.70	35.30	74.00	17.50	V
17974.500	56.20	-25.50	46.70	35.00	74.00	17.80	H
17994.000	56.20	-25.50	46.70	35.00	74.00	17.80	H
17958.000	56.10	-25.50	46.70	34.90	74.00	17.90	H
17613.000	56.00	-25.70	46.00	35.80	74.00	18.00	V
2389.600	70.00	-14.20	28.10	56.10	74.00	4.00	H

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17986.500	56.90	-25.50	46.70	35.70	74.00	17.10	V
17964.000	56.60	-25.50	46.70	35.40	74.00	17.40	H
17919.000	56.20	-25.50	46.70	35.00	74.00	17.80	V
17859.000	56.10	-25.50	46.70	34.90	74.00	17.90	H
17587.500	56.00	-25.70	46.00	35.80	74.00	18.00	H
17886.000	56.00	-25.50	46.70	34.80	74.00	18.00	V

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17970.000	57.70	-25.50	46.70	36.50	74.00	16.30	H
17914.500	56.40	-25.50	46.70	35.20	74.00	17.60	V
17949.000	56.40	-25.50	46.70	35.20	74.00	17.60	H
17989.500	56.40	-25.50	46.70	35.20	74.00	17.60	V
17976.000	56.20	-25.50	46.70	35.00	74.00	17.80	V
2485.000	72.10	-14.20	28.30	58.00	74.00	1.90	H

Average
802.11b

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17947.500	44.70	-25.50	46.70	23.50	54.00	9.30	H
17959.500	44.60	-25.50	46.70	23.40	54.00	9.40	V
17964.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17968.500	44.60	-25.50	46.70	23.40	54.00	9.40	V
17973.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
2322.000	42.50	-14.50	27.90	29.10	54.00	11.50	V

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17961.000	44.80	-25.50	46.70	23.60	54.00	9.20	V
17946.000	44.70	-25.50	46.70	23.50	54.00	9.30	H
17949.000	44.70	-25.50	46.70	23.50	54.00	9.30	V
17956.500	44.70	-25.50	46.70	23.50	54.00	9.30	V
17941.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
17944.500	44.60	-25.50	46.70	23.40	54.00	9.40	V

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17949.000	44.70	-25.50	46.70	23.50	54.00	9.30	V
17956.500	44.60	-25.50	46.70	23.40	54.00	9.40	V
17968.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
17971.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
17974.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
2485.100	45.30	-14.20	28.30	31.20	54.00	8.70	H

802.11g

Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17962.500	44.70	-25.50	46.70	23.50	54.00	9.30	V
17968.500	44.70	-25.50	46.70	23.50	54.00	9.30	H
17944.500	44.60	-25.50	46.70	23.40	54.00	9.40	V
17946.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17977.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
2389.800	43.70	-14.20	28.10	29.80	54.00	10.30	V

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17943.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17952.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17953.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
17958.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17961.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17965.500	44.60	-25.50	46.70	23.40	54.00	9.40	H

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17949.000	44.70	-25.50	46.70	23.50	54.00	9.30	V
17946.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17950.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
17952.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17965.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
2485.000	49.00	-14.20	28.30	34.90	54.00	5.00	V

802.11n-HT20
Ch1

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17941.500	44.80	-25.50	46.70	23.60	54.00	9.20	V
17956.500	44.70	-25.50	46.70	23.50	54.00	9.30	V
17958.000	44.70	-25.50	46.70	23.50	54.00	9.30	H
17949.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17952.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
2389.600	50.40	-14.20	28.10	36.50	54.00	3.60	H

Ch6

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17946.000	44.70	-25.50	46.70	23.50	54.00	9.30	H
17965.500	44.70	-25.50	46.70	23.50	54.00	9.30	V
17943.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17949.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17955.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17958.000	44.60	-25.50	46.70	23.40	54.00	9.40	H

Ch11

Frequency (MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Polarization
17949.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17953.500	44.60	-25.50	46.70	23.40	54.00	9.40	H
17964.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
17970.000	44.60	-25.50	46.70	23.40	54.00	9.40	H
17976.000	44.60	-25.50	46.70	23.40	54.00	9.40	V
2485.100	50.00	-14.20	28.30	35.90	54.00	4.00	H

Sample calculation:

$$\text{Peak Result} = P_{\text{Mea}}(23.40\text{dBuV/m}) + \text{Cable Loss}(-25.50) + \text{Antenna Factor}(46.70) = 44.60\text{dBuV/m}$$


A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

Setup:

A stand-alone EUT shall be placed in the center along the back edge of the tabletop. For multiunit tabletop systems, the EUT shall be centered laterally (left to right facing the tabletop) on the tabletop and its rear shall be flush with the rear of the table.

Accessories that are part of an EUT system tested on a tabletop shall be placed in a test arrangement on one or both sides of the host with a 10 cm separation between the nearest points of the cabinets. The rear of the host and accessories shall be flush with the back of the supporting tabletop unless that would not be typical of normal use. If more than two accessories are present, then an equipment test arrangement shall be chosen that maintains 10 cm spacing between cabinets unless the equipment is normally located closer together.



Exploratory ac power-line conducted emission measurements

Exploratory measurements shall be used to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement. For each mode of operation and for each ac power current-carrying conductor, cable manipulation shall be performed within the range of likely configurations. For this measurement or series of measurements, the frequency spectrum of interest shall be monitored looking for the emission that has the highest amplitude relative to the limit. Once that emission is found for each current-carrying conductor of each power cord associated with the EUT (but not the cords

associated with non-EUT equipment in the overall system), the one configuration and arrangement and mode of operation that produces the emission closest to the limit over all of the measured conductors shall be recorded.

Final ac power-line conducted emission measurements

Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation. If the EUT is composed of equipment units that have their own separate ac power connections (e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network), then each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be measured separately. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

EUT ID: EUT2

Measurement Result and limit:

TN-050100U6 (Dong Guan City GangQi Electronic CO.,Ltd.)

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

TN-050100U6 (Guangdong Beicom Electronics Co.,Ltd.)

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	67 to 56	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.3	Fig.A.7.4	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:




Fig.A.7.1 AC Powerline Conducted Emission-802.11b TN-050100U6 (Dong Guan City GangQi Electronic CO.,Ltd.)

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.186000	51.8	L1	20.1	12.4	64.2
3.489000	44.2	N	20.2	11.8	56.0
4.294500	46.1	L1	20.7	9.9	56.0
10.365000	45.9	N	23.0	14.1	60.0
17.533500	52.2	N	24.8	7.8	60.0
17.763000	52.2	L1	24.8	7.8	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.505500	35.6	L1	20.1	10.4	46.0
3.565500	35.7	L1	20.5	10.3	46.0
3.970500	36.7	L1	20.6	9.3	46.0
10.221000	35.9	N	22.9	14.1	50.0
17.286000	42.0	L1	24.7	8.0	50.0
17.835000	42.4	L1	24.8	7.6	50.0




Fig.A.7.2 AC Powerline Conducted Emission-Idle TN-050100U6 (Dong Guan City GangQi Electronic CO.,Ltd.)

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.186000	53.9	L1	20.1	10.3	64.2
0.280500	46.0	L1	20.0	14.8	60.8
3.507000	44.5	N	20.2	11.5	56.0
4.276500	45.7	N	20.4	10.3	56.0
17.115000	52.4	L1	24.7	7.6	60.0
19.050000	51.9	L1	25.0	8.1	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.505500	35.2	L1	20.1	10.8	46.0
1.873500	32.7	N	19.9	13.3	46.0
3.507000	34.6	N	20.2	11.4	46.0
3.948000	36.7	L1	20.6	9.3	46.0
16.521000	42.0	L1	24.5	8.0	50.0
18.154500	42.9	L1	24.9	7.1	50.0




Fig.A.7.3 AC Powerline Conducted Emission-802.11b TN-050100U6 (Guangdong Beicom Electronics Co.,Ltd.)

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.981500	40.1	N	19.9	15.9	56.0
3.372000	44.4	L1	20.4	11.6	56.0
4.434000	46.6	N	20.5	9.4	56.0
9.951000	47.4	L1	22.9	12.6	60.0
14.428500	51.0	L1	23.8	9.0	60.0
18.870000	42.4	N	24.9	17.6	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.067000	31.1	N	19.9	14.9	46.0
3.471000	34.7	L1	20.4	11.3	46.0
4.434000	38.2	N	20.5	7.8	46.0
10.338000	39.1	L1	22.9	10.9	50.0
14.370000	41.4	L1	23.8	8.6	50.0
17.844000	34.6	L1	24.8	15.4	50.0




Fig.A.7.4 AC Powerline Conducted Emission-Idle TN-050100U6 (Guangdong Beicom Electronics Co.,Ltd.)

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.004000	40.4	L1	20.1	15.6	56.0
3.354000	44.0	N	20.2	12.0	56.0
4.420500	46.9	N	20.4	9.1	56.0
10.378500	48.1	N	23.0	11.9	60.0
13.906500	50.7	N	23.5	9.3	60.0
17.839500	43.4	L1	24.8	16.6	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
2.062500	31.1	N	19.9	14.9	46.0
3.448500	35.0	L1	20.4	11.0	46.0
4.335000	37.9	N	20.4	8.1	46.0
10.315500	39.1	L1	22.9	10.9	50.0
14.347500	41.4	L1	23.7	8.6	50.0
17.677500	35.1	N	24.8	14.9	50.0

ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p> 	
<hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/>	
<p>NVLAP LAB CODE: 600118-0</p>	
<p>Telecommunication Technology Labs, CAICT Beijing China</p>	
<p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p>	
<p>Electromagnetic Compatibility & Telecommunications</p>	
<p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p>	
<hr/> <p>2019-09-26 through 2020-09-30 <i>Effective Dates</i></p>	 <hr/> <p><i>[Signature]</i> For the National Voluntary Laboratory Accreditation Program</p>

END OF REPORT