

Report No.: SZEM140100040801

1 of 95

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page:

FCC REPORT

Application No: SZEM1401000408RF

Applicant: TEAC Corporation **Manufacturer:** TEAC Corporation

Factory: Dongguan TEAC Electronics Co., Ltd.

Product Name: USB AUDIO DAC

Model No.(EUT): AI-301DA

Trade mark: TEAC

FCC ID: XEG-Al301DA

Standards: 47 CFR Part 15, Subpart C (2013)

Date of Receipt: 2014-01-29

Date of Test: 2014-02-28 to 2014-03-14

Date of Issue: 2014-04-01

Test Result: PASS *

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM140100040801

Page: 2 of 95

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS



Report No.: SZEM140100040801

Page: 3 of 95

3 Contents

		Page
1	1 COVER PAGE	1
2	2 TEST SUMMARY	2
3		
4		
	4.1 CLIENT INFORMATION 4.2 GENERAL DESCRIPTION OF EUT 4.3 TEST ENVIRONMENT 4.4 DESCRIPTION OF SUPPORT UNITS 4.5 TEST LOCATION 4.6 TEST FACILITY 4.7 DEVIATION FROM STANDARDS 4.8 ABNORMALITIES FROM STANDARD CONDITIONS 4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER 4.10 EQUIPMENT LIST	
5	5 TEST RESULTS AND MEASUREMENT DATA	13
	5.1 ANTENNA REQUIREMENT 5.2 CONDUCTED EMISSIONS 5.3 CONDUCTED PEAK OUTPUT POWER 5.4 20DB OCCUPY BANDWIDTH 5.5 CARRIER FREQUENCIES SEPARATION 5.6 HOPPING CHANNEL NUMBER 5.7 DWELL TIME 5.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS 5.9 SPURIOUS RF CONDUCTED EMISSIONS 5.10 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 5.11 RADIATED SPURIOUS EMISSION	
	5.11.1 Radiated Emission below 1GHz	
	5.11.2 Transmitter Emission above 1GHz	



Report No.: SZEM140100040801

Page: 4 of 95

4 General Information

4.1 Client Information

Applicant:	TEAC Corporation
Address of Applicant:	1-47 Ochiai, Tama-shi, Tokyo, Japan
Manufacturer:	TEAC Corporation
Address of Manufacturer:	1-47 Ochiai, Tama-shi, Tokyo, Japan
Factory:	Dongguan TEAC Electronics Co., Ltd.
Address of Factory:	Shang-sha, Chang-an District Dongguan City, Guangdong, P.R.China

4.2 General Description of EUT

Product Name:	USB AUDIO DAC
Model No.	AI-301DA
Trade Mark:	TEAC
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V2.1+EDR
EUT Function:	USB AUDIO DAC
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Fixed production
Test Power Grade:	255, 38 (manufacturer declare)
Test Software of EUT:	Bluetest3 (manufacturer declare)
Antenna Type	Integral
Antenna Gain	2.4dBi
Power Supply:	Input: 120V~60Hz 38W
	DC 3.0V (2 x 1.5V "AAA" Size Battery) for remote control
Test Voltage:	AC 120V 60Hz
AC Cable:	190cm (Unshielded)



Report No.: SZEM140100040801

Page: 5 of 95

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



Report No.: SZEM140100040801

Page: 6 of 95

4.3 Test Environment

Operating Environment:		
Temperature:	24.0 °C	
Humidity:	52 % RH	
Atmospheric Pressure:	1010 mbar	

4.4 Description of Support Units

The EUT has been tested independent unit.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059



Report No.: SZEM140100040801

Page: 7 of 95

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP (Lab Code: 200611-0)

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

CNAS (Lab Code: L0167)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

FCC (Registration No.: 282399)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

Industry Canada (Registration No.: 4620B-1)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.



Report No.: SZEM140100040801

Page: 8 of 95

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None

4.9 Other Information Requested by the Customer

None.



Report No.: SZEM140100040801

Page: 9 of 95

4.10 Equipment List

C	onducted Emissi	on				
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM- DD)	Calibration Interval
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m ³	N/A	N/A	N/A
EMC0118	Two-line v- netwok	R&S	ENV216	100359	2015-03- 03	1Y
EMC0102	LISN	SCHAFFNER CHASE	MN2050D/1	1421	2014-08- 31	1Y
EMC2046	Artificial Mains Network (LISN)	AFJ Instruments	LT32C	S.N.32031120150	2015-03- 03	1Y
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	2015-03- 03	1Y
EMC0107	Coaxial Cable	SGS	2m	N/A	2014-07- 25	2Y
EMC0106	Voltage Probe	SGS	N/A	N/A	N/A	1Y
EMC0120	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T8-02	20550	2014-08- 31	1Y
EMC0121	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T4-02	20549	2014-08- 31	1Y
EMC0122	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T2-02	20548	2014-08- 31	1Y
EMC2047	CDN	Elektronik- Feinmechanik	L-801:AF2	2793	2014-11- 11	3Y
EMC2048	CDN	Elektronik- Feinmechanik	L-801:M2/M3	2738	2014-11- 11	3Y
EMC2062	6dB Attenuator	HP	8491A	24487	2015-01- 04	1Y
EMC167	Conical metal housing	SGS-EMC	N/A	N/A	2016-02- 16	2Y



Report No.: SZEM140100040801

Page: 10 of 95

R	E in Chamber					
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM- DD)	Calibration Interval
EMC0525	Compact Semi- Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-08-30	2Y
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-05-06	1Y
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2015-03-03	1Y
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2014-05-09	1Y
EMC2025	Trilog Broadband Antenna 30-3000MHz	SCHWARZBECK MESS- ELEKTRONIK	VULB 9163	9163-450	2016-08-31	3Y
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2016-08-31	3Y
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-06-02	2Y
EMC2026	Horn Antenna 1-18GHz	SCHWARZBECK MESS- ELEKTRONIK	BBHA 9120D	9120D-841	2016-08-31	3Y
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2014-07-01	2Y
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2015-03-03	1Y
EMC2065	Amplifier	HP	8447F	N/A	2014-08-31	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26- 48	6279.628	2014-07-29	1Y
EMC0075	310N Amplifier	Sonama	310N	272683	2015-03-03	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-04-07	2Y
EMC2041	Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS- ELEKTRONI	BBHA 9170	9170-375	2014-06-01	3Y
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2014-06-05	1Y
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	2014-04-27	2Y
EMC2041	Broad-Band Horn Antenna(14)15- 26.5(40)GHz	SCHWARZBECK MESS- ELEKTRONIK	BBHA 9170	9170-375	2014-06-11	3Y



Report No.: SZEM140100040801

Page: 11 of 95

	RF connected test				T.	
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Due date (YYYY-MM- DD)	Calibration Interval
EMC0039	Temperature Chamber	GZ GongWen Co.Ltd.	GDJW-100	118	2014-08- 31	1Y
EMC2022	DC Power Supply	KIKUSUI ELECTRONICS CORP.	PAN60-20A	HH000269	2014-05- 06	1Y
EMC0007	DMM	Fluke	73	70671122	2014-09- 13	1Y
EMC0006	DMM	Fluke	73	70681569	2014-09- 13	1Y
EMC0525	Compact Semi- Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	N/A	N/A
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	2014-04- 27	2Y
EMC0502	Biconical Antenna (Rx)	Rohde & Schwarz	HK116	100032	2014-08- 30	2Y
EMC0503	Biconical Antenna (Tx)	Rohde & Schwarz	HK116	100033	2014-07- 01	2Y
EMC0504	Log-Perd. Dipole Antenna (Rx)	Rohde & Schwarz	HL223	100039	2014-08- 30	2Y
EMC0518	Horn Antenna (Rx)	Rohde & Schwarz	HF906	100096	2014-07- 01	2Y
EMC0519	Bilog Type Antenna	Schaffner Chase	CBL6143	5070	2014-06- 02	2Y
EMC0521	1-26.5GHz Pre Amplifier	Agilent	8449B	3008A01649	2015-03- 03	1Y
EMC2063	1-26GHz Pre Amplifier	Compliance Direction System Inc.	PAP-1G26- 48	6279.628	2014-07- 29	1Y
EMC0075	9KHz-1GHz Pre Amplifier	SONOMA INSTRUMENT Co.	310N	272683	2015-03- 03	1Y
EMC0507	Antenna Mask (Tx)	HD-GmbH	AS620M	620/408	N/A	N/A
EMC0508	Antenna Mask (Rx)	HD-GmbH	MA240	240/619	N/A	N/A
EMC0509	Turntable	HD-GmbH	DT430	N/A	N/A	N/A
EMC0510	Turntable & Antenna Mask Controller	HD-GmbH	HD100	N/A	N/A	N/A
EMC0512	EMI Test Software	Rohde & Schwarz	ES-K1	N/A	N/A	N/A
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-05- 06	1Y
EMC0516	Signal Generator	Rohde & Schwarz	SMR20	100416	2014-05- 06	1Y
EMC0032	Radio Communication Monitor	Rohde & Schwarz	CMS54	100137	2014-08- 31	1Y
EMC0904	Power Meter	Rohde & Schwarz	NRVS	825770/074	2015-03- 03	1Y



Report No.: SZEM140100040801

Page: 12 of 95

EMC0071	URV5-Z2 Insert. Unit	Rohde & Schwarz	URV5-Z2	100309	2015-03- 03	1Y
EMC0906	Dual Directional Coupler	Werlatone Inc.	C1795	6634	2014-08- 31	1Y
EMC2012	Power-Electronics Measurement System	Tektronix	TDS 744A	N/A	2015-03- 03	1Y
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-04- 07	2Y
EMC0069	Signal Analyzer (20Hz ~ 26.5Ghz	R&S	FSIQ26	100312	2015-03- 03	1Y
EMC2041	Broad-Band Horn Antenna(14)15- 26.5(40)GHz	SCHWARZBECK MESS-ELEKTRONI	BBHA 9170	9170-375	2014-06- 01	3Y
EMC0078	Temperature, & Humidity	Shanghai Meteorological Instrument factory Co., Ltd.	ZJ1-2B	709131	2014-09- 13	1Y

Note: The calibration interval is one year, all the instruments are valid.



Report No.: SZEM140100040801

Page: 13 of 95

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.4dBi.





Report No.: SZEM140100040801

Page: 14 of 95


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207			
Test Method:	ANSI C63.10: 2009			
Test Frequency Range:	150kHz to 30MHz			
Limit:	Fraguenov range (MUT)	Limit (c	lBuV)	
	Frequency range (MHz)	Quasi-peak	Average	
	0.15-0.5	66 to 56*	56 to 46*	
	0.5-5	56	46	
	5-30	60	50	
	* Decreases with the logarithn	n of the frequency.		-
Test Procedure:	The mains terminal disturbance voltage test was conducted in a sh room.			
	 The EUT was connected to Impedance Stabilization N impedance. The power cal connected to a second LIS reference plane in the sam measured. A multiple sock power cables to a single Lexceeded. The tabletop EUT was place ground reference plane. A placed on the horizontal ground reference with the EUT shall be 0.4 m in vertical ground reference plane. The LISN unit under test and bonded mounted on top of the ground between the closest points the EUT and associated experience to find the maximule equipment and all of the in ANSI C63.10: 2009 on control 	etwork) which provides oles of all other units of SN 2, which was bonde he way as the LISN 1 for et outlet strip was used ISN provided the rating ced upon a non-metallimed for floor-standing arround reference plane, the a vertical ground reference plane was bonded to the strip was placed 0.8 m from the vertical ground reference plane. The strip is of the LISN 1 and the quipment was at least the strip is of the capter on, the relative terface cables must be	s a 50Ω/50μH + 5Ω lift the EUT were do to the ground or the unit being do to connect multiple gof the LISN was not contained the connect multiple gof the LISN was not contained the EUT defence plane. The red reference plane. The end reference plane. The horizontal ground om the boundary of the plane for LISNs his distance was EUT. All other units the positions of	he was ear ne he of 2.



Report No.: SZEM140100040801

Page: 15 of 95





Report No.: SZEM140100040801


Page: 16 of 95

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.





Site : Shielding Room

Condition : 47 CFR PART 15 B QP GZ LISN EMC0118 2014 LINE

Job No. : 0408RF Test mode : TX


		Cable	LISN	Read		Limit	Over		
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark	
	MHz	dB	dB	dBuV	dBuV	dBuV	dB		-
1	0.15321	0.07	9.60	45.64	55.32	65.82	-10.51	QP	
2	0.15321	0.07	9.60	36.13	45.81	55.82	-10.02	Average	
3	0.17900	0.10	9.60	41.22	50.92	54.53	-3.61	Average	
4	0.17900	0.10	9.60	46.92	56.62	64.53	-7.91	QP	
5	0.26583	0.11	9.63	31.40	41.13	61.25	-20.11	QP	
6	0.26583	0.11	9.63	22.12	31.86	51.25	-19.39	Average	
7	0.53782	0.07	9.70	34.29	44.06	56.00	-11.94	QP	
8	0.53782	0.07	9.70	25.12	34.89	46.00	-11.11	Average	
9	1.610	0.05	9.70	19.02	28.77	46.00	-17.23	Average	
10	1.610	0.05	9.70	27.86	37.61	56.00	-18.39	QP	
11	16.661	0.38	10.00	31.43	41.81	60.00	-18.19	QP	
12	16.661	0.38	10.00	22.21	32.60	50.00	-17.40	Average	



Report No.: SZEM140100040801

Page: 17 of 95

Neutral line:



Site : Shielding Room

Condition : 47 CFR PART 15 B QP GZ LISN EMC0118 2014 NEUTRAL

Job No. : 0408RF Test mode : TX

			Cable	LISN	Read		Limit	Over	
		Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	-	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1		0.18056	0.10	9.66	48.50	58.26	64.46	-6.20	QP
2		0.18056	0.10	9.66	39.01	48.77	54.46	-5.69	Average
3		0.21967	0.12	9.66	32.46	42.24	52.83	-10.59	Average
4		0.21967	0.12	9.66	40.55	50.33	62.83	-12.51	QP
5		0.27009	0.11	9.66	26.60	36.36	51.12	-14.75	Average
6		0.27009	0.11	9.66	35.49	45.25	61.12	-15.86	QP
7		0.53900	0.07	9.66	35.48	45.21	56.00	-10.79	QP
8	@	0.53900	0.07	9.66	33.18	42.91	46.00	-3.09	Average
9		1.636	0.05	9.68	22.16	31.89	46.00	-14.11	Average
10		1.636	0.05	9.68	31.82	41.55	56.00	-14.45	QP
11		14.672	0.30	10.00	33.88	44.19	60.00	-15.81	QP
12		14.672	0.30	10.00	25.35	35.65	50.00	-14.35	Average

Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM140100040801

Page: 18 of 95

5.3 Conducted Peak Output Power





Report No.: SZEM140100040801

Page: 19 of 95

Measurement Data

WCasarcincin Data	weasurement Data						
GFSK mode							
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	-0.36	30.00	Pass				
Middle	-0.42	30.00	Pass				
Highest	-0.89	30.00	Pass				
	π/4DQPSK mode						
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	Lowest -0.45		Pass				
Middle	Middle -0.38		Pass				
Highest	Highest -1.06		Pass				
8DPSK mode							
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result				
Lowest	Lowest -0.23		Pass				
Middle	Middle -0.36		Pass				
Highest	-0.94	30.00	Pass				




Report No.: SZEM140100040801


Page: 20 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Middle







Report No.: SZEM140100040801

Page: 21 of 95

Test mode: GFSK Test channel: Highest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM140100040801

Page: 22 of 95

Test mode: $\pi/4DQPSK$ Test channel: Middle



Test mode: π/4DQPSK Test channel: Highest




[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM140100040801

Page: 23 of 95

Test mode: 8DPSK Test channel: Lowest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 24 of 95

Test mode: 8DPSK Test channel: Highest








Report No.: SZEM140100040801

Page: 25 of 95

5.4 20dB Occupy Bandwidth



Measurement Data

Toot chonnel	20dB Occupy Bandwidth (kHz)				
Test channel	GFSK	π/4DQPSK	8DPSK		
Lowest	884.615384593	1264.423077	1221.153846		
Middle	879.807692285	1264.423077	1225.961538		
Highest	879.807692284	1230.769231	1221.153846		

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM140100040801


Page: 26 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Middle








Report No.: SZEM140100040801

Page: 27 of 95

Test mode: GFSK Test channel: Highest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."





Report No.: SZEM140100040801

Page: 28 of 95

Test mode: $\pi/4DQPSK$ Test channel: Middle








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."





Report No.: SZEM140100040801

Page: 29 of 95

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM140100040801

Page: 30 of 95

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM140100040801

Page: 31 of 95

5.5 Carrier Frequencies Separation





Report No.: SZEM140100040801

Page: 32 of 95

Measurement Data

GFSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1002	≥843	Pass		
Middle	1002	≥843	Pass		
Highest	1002	≥843	Pass		
	π/4DQPSK m	node			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	Lowest 1002		Pass		
Middle	Middle 1006		Pass		
Highest	Highest 1002		Pass		
8DPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result		
Lowest	1002	≥843	Pass		
Middle	Middle 1010		Pass		
Highest	1006	≥843	Pass		

Note: According to section 5.4,

Mode	20dB bandwidth (kHz)	Limit (kHz)		
eee	(worse case)	(Carrier Frequencies Separation)		
GFSK	879.807692285	587		
π/4DQPSK	1264.423077	843		
8DPSK	1225.961538	817		




Report No.: SZEM140100040801


Page: 33 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM140100040801

Page: 34 of 95

Test mode: GFSK Test channel: Highest



Test mode: $\pi/4DQPSK$ Test channel: Lowest










Report No.: SZEM140100040801

Page: 35 of 95

Test mode: $\pi/4DQPSK$ Test channel: Middle








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM140100040801

Page: 36 of 95

Test mode: 8DPSK Test channel: Lowest








[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 37 of 95

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM140100040801

Page: 38 of 95

5.6 Hopping Channel Number



Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15





Report No.: SZEM140100040801


Page: 39 of 95

Test plot as follows












Report No.: SZEM140100040801

Page: 40 of 95








Report No.: SZEM140100040801

Page: 41 of 95

5.7 Dwell Time



Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.16282	0.4
	DH3	0.28397	0.4
	DH5	0.32265	0.4
π/4DQPSK	2-DH1	0.12821	0.4
	2-DH3	0.28462	0.4
	2-DH5	0.18803	0.4
8DPSK	3-DH1	0.16667	0.4
	3-DH3	0.28333	0.4
	3-DH5	0.32222	0.4

Test Result:

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

The lowest channel (2402MHz), middle channel (2441MHz), highest channel (2480MHz) as below

DH1 time slot=0.509(ms)*(1600/ (2*79))*31.6=162.82 ms

DH3 time slot=1.775(ms)*(1600/ (4*79))*31.6=283.97 ms

DH5 time slot=3.025(ms)*(1600/ (6*79))*31.6=322.65 ms




Report No.: SZEM140100040801


Page: 42 of 95

Test plot as follows:





Test Packet: _____ DH3







Report No.: SZEM140100040801

Page: 43 of 95

Test Packet: DH5



Test Packet: 2-DH1




[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM140100040801

Page: 44 of 95

Test Packet: 2-DH3



Test Packet: 2-DH5









Report No.: SZEM140100040801

Page: 45 of 95

Test Packet: 3-DH1



Test Packet: 3-DH3




[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 46 of 95

Test Packet: 3-DH5






Report No.: SZEM140100040801

Page: 47 of 95

5.8 Band-edge for RF Conducted Emissions







Report No.: SZEM140100040801

Page: 48 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM140100040801

Page: 49 of 95

Test mode: GFSK Test channel: Highest









Report No.: SZEM140100040801

Page: 50 of 95

Test mode: $\pi/4DQPSK$ Test channel: Lowest









Report No.: SZEM140100040801

Page: 51 of 95

Test mode: π/4DQPSK Test channel: Highest









Report No.: SZEM140100040801

Page: 52 of 95

Test mode: 8DPSK Test channel: Lowest









Report No.: SZEM140100040801

Page: 53 of 95

Test mode: 8DPSK Test channel: Highest







Report No.: SZEM140100040801

Page: 54 of 95

5.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)		
Test Method:	ANSI C63.10:2009		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane		
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.		
Instruments Used:	Refer to section 4.10 for details		
Test Results:	Pass		







Report No.: SZEM140100040801

Page: 55 of 95

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM140100040801

Page: 56 of 95









Report No.: SZEM140100040801

Page: 57 of 95




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------






Report No.: SZEM140100040801

Page: 58 of 95









Report No.: SZEM140100040801

Page: 59 of 95









Report No.: SZEM140100040801

Page: 60 of 95

Test mode: GFSK Test channel: Highest







[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 61 of 95









Report No.: SZEM140100040801

Page: 62 of 95







[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 63 of 95









Report No.: SZEM140100040801

Page: 64 of 95











Report No.: SZEM140100040801

Page: 65 of 95

Test mode: π/4DQPSK Test channel: Middle







[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 66 of 95









Report No.: SZEM140100040801

Page: 67 of 95




Test mode:	π/4DQPSK	Test channel:	Highest
------------	----------	---------------	---------






Report No.: SZEM140100040801

Page: 68 of 95









Report No.: SZEM140100040801

Page: 69 of 95









Report No.: SZEM140100040801

Page: 70 of 95

Test mode: 8DPSK Test channel: Lowest









Report No.: SZEM140100040801

Page: 71 of 95






[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




Report No.: SZEM140100040801

Page: 72 of 95











Report No.: SZEM140100040801

Page: 73 of 95









Report No.: SZEM140100040801

Page: 74 of 95











Report No.: SZEM140100040801

Page: 75 of 95

Test mode: 8DPSK Test channel: Highest









Report No.: SZEM140100040801

Page: 76 of 95






[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM140100040801

Page: 77 of 95



Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report.



Report No.: SZEM140100040801

Page: 78 of 95

5.10 Pseudorandom Frequency Hopping Sequence

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- · Number of shift register stages: 9
- Length of pseudo-random sequence: 29 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

The device does not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.



Report No.: SZEM140100040801

Page: 79 of 95

5.11 Radiated Spurious Emission


Test Requirement:	47 CFR Part 15C Secti	on 1	15.209 and 15.	205				
Test Method:	ANSI C63.10: 2009							
Test Site:	Measurement Distance	: 3n	n (Semi-Anech	oic Cham	ıber)			
Receiver Setup:	Frequency		Detector	RBW	VBW	Remark		
	0.009MHz-0.090MH	Z	Peak	10kHz	z 30kHz	Peak		
	0.009MHz-0.090MH	Average	10kHz	z 30kHz	Average			
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	z 30kHz	Quasi-peak		
	0.110MHz-0.490MH	Z	Peak	10kHz	z 30kHz	Peak		
	0.110MHz-0.490MH	Z	Average	10kHz	z 30kHz	Average		
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak		
	30MHz-1GHz		Quasi-peak	100 kH	lz 300kHz	Quasi-peak		
	Abovo 1GHz	Above 1GHz			z 3MHz	Peak		
	Above IGHZ	Peak	1MHz	10Hz	Average			
Limit:	Frequency		eld strength crovolt/meter)	Limit (dBuV/m)	Remark	Measureme distance (m		
	0.009MHz-0.490MHz	2	400/F(kHz)	-	-	300		
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30		
	1.705MHz-30MHz		30	-	-	30		
	30MHz-88MHz		100	40.0	Quasi-peak	3		
	88MHz-216MHz		150	43.5	Quasi-peak	3		
	216MHz-960MHz		200	46.0	Quasi-peak	3		
	960MHz-1GHz		500	54.0	Quasi-peak	3		
	Above 1GHz	500	54.0	Average	3			
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limi applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.							



Report No.: SZEM140100040801

Page: 80 of 95

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB



Report No.: SZEM140100040801

Page: 81 of 95

	margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass




Report No.: SZEM140100040801

Page: 82 of 95

5.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)							
Test mode:	Transmitting	Vertical					



Condition: 47 CFR PART 15B 3m GZ VULB 9163 3M 2010 VERTICAL

Job No. : 0408RF Mode : TX


ouc	Freq			Preamp Read Factor Level			Limit Line	Over Limit
-	MHz	d₿	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	dBuV/m	d B
1 2 3 4 5	31. 95 123. 27 172. 60 270. 37 468. 88 566. 62	0.85 1.57 1.79 2.23 2.99 3.15	12. 32 10. 00 9. 16 12. 38 15. 83 17. 88	31.60 31.54 31.34 31.30 31.18 31.27	48. 46 51. 55 54. 15 50. 86 48. 26 44. 49	30. 03 31. 58 33. 76 34. 17 35. 90 34. 25	43.50 46.00 46.00	-9.97 -11.92 -9.74 -11.83 -10.10 -11.75



Report No.: SZEM140100040801

Page: 83 of 95

Test mode: Transmitting Horizontal



Condition: 47 CFR PART 15B 3m GZ VULB 9163 3M 2010 HORIZONTAL

Job No. : 0408RF Mode : TX

ouc	Freq	CableAntenna F Loss Factor F						Over Limit
_	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 3 4 5	197. 20 222. 17 270. 37 319. 94 368. 11 468. 88	1.87 2.01 2.23 2.44 2.62 2.99	13.33 14.49	31.30	47. 93 48. 81 47. 25 48. 12	27. 71 29. 89 32. 12 31. 76 34. 09 34. 02	46.00 46.00	



Report No.: SZEM140100040801

Page: 84 of 95

5.11.2 Transmitter Emission above 1GHz

Worse case i	mode:	GFSK(DH1)	Test	channel:	Lowest	Rema	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1593.340	5.60	25.00	44.96	61.12	46.76	74	-27.24	Vertical
3588.939	9.32	29.14	44.88	52.52	46.10	74	-27.90	Vertical
4804.000	11.11	31.53	45.16	48.56	46.04	74	-27.96	Vertical
7206.000	12.90	36.47	45.44	46.40	50.33	74	-23.67	Vertical
9608.000	15.16	38.08	45.87	43.80	51.17	74	-22.83	Vertical
11842.690	16.77	39.48	47.04	43.12	52.33	74	-21.67	Vertical
3080.601	8.09	28.66	45.09	53.92	45.58	74	-28.42	Horizontal
4138.802	11.09	30.09	44.84	50.30	46.64	74	-27.36	Horizontal
4804.000	11.11	31.53	45.16	48.84	46.32	74	-27.68	Horizontal
7206.000	12.90	36.47	45.44	45.51	49.44	74	-24.56	Horizontal
9608.000	15.16	38.08	45.87	43.11	50.48	74	-23.52	Horizontal
12055.600	17.21	39.32	47.06	43.11	52.58	74	-21.42	Horizontal

Worse case r	mode:	GFSK(DH1)) Tes	t channel:	Middle	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1621.985	5.66	24.98	44.95	60.06	45.75	74	-28.25	Vertical
2987.923	7.91	28.47	45.10	54.18	45.46	74	-28.54	Vertical
4882.000	11.26	31.58	45.18	47.40	45.06	74	-28.94	Vertical
7323.000	13.28	36.50	45.54	44.51	48.75	74	-25.25	Vertical
9764.000	15.05	38.46	45.88	42.83	50.46	74	-23.54	Vertical
12334.980	17.61	39.35	47.08	42.31	52.19	74	-21.81	Vertical
1621.985	5.66	24.98	44.95	55.40	41.09	74	-32.91	Horizontal
3598.087	9.36	29.16	44.88	52.40	46.04	74	-27.96	Horizontal
4882.000	11.26	31.58	45.18	48.97	46.63	74	-27.37	Horizontal
7323.000	13.28	36.50	45.54	45.55	49.79	74	-24.21	Horizontal
9764.000	15.05	38.46	45.88	42.14	49.77	74	-24.23	Horizontal
12429.540	17.76	39.36	47.08	41.98	52.02	74	-21.98	Horizontal



Report No.: SZEM140100040801

Page: 85 of 95

Worse case r	node:	GFSK(DH1) Tes	t channel:	Highest	Rem	ark:	Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1642.761	5.71	24.98	44.94	58.15	43.90	74	-30.10	Vertical
3738.129	9.97	29.35	44.84	51.20	45.68	74	-28.32	Vertical
4960.000	11.39	31.70	45.19	47.32	45.22	74	-28.78	Vertical
7440.000	13.60	36.60	45.68	45.34	49.86	74	-24.14	Vertical
9920.000	14.92	38.65	45.89	42.92	50.60	74	-23.40	Vertical
12556.750	17.91	39.38	47.09	42.18	52.38	74	-21.62	Vertical
1642.761	5.71	24.98	44.94	54.91	40.66	74	-33.34	Horizontal
3738.129	9.97	29.35	44.84	50.82	45.30	74	-28.70	Horizontal
4960.000	11.39	31.70	45.19	48.94	46.84	74	-27.16	Horizontal
7440.000	13.60	36.60	45.68	44.65	49.17	74	-24.83	Horizontal
9920.000	14.92	38.65	45.89	43.39	51.07	74	-22.93	Horizontal
12086.330	17.26	39.33	47.06	42.95	52.48	74	-21.52	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
 - Final Test Level = Receiver Reading + Antenna Factor + Cable Factor Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.




Report No.: SZEM140100040801

Page: 86 of 95

5.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2009									
Test Site:	Measurement Distance: 3m	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Limit:	Frequency	Limit (dBuV/m @3m)	Remark							
	30MHz-88MHz	40.0	Quasi-peak Value							
	88MHz-216MHz	43.5	Quasi-peak Value							
	216MHz-960MHz	46.0	Quasi-peak Value							
	960MHz-1GHz	54.0	Quasi-peak Value							
	Above 1GHz	54.0	Average Value							
	Above IGHZ	74.0	Peak Value							
			·							
Test Setup:										






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM140100040801

Page: 87 of 95

Test Procedure:	 a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode,And found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was
Exploratory Test Mode:	complete. Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH5 of data type is the worse case of
Tilla Tost Wood.	GFSK modulation type
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass




Report No.: SZEM140100040801

Page: 88 of 95

Test plot as follows:

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Vertical



Condition : FCC PART15(>1G) PK 3m VERTICAL

Job No. : 0408RF Mode : 2402


1046	. 2402	Freq			•			Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2	x	2390.000 2401.865				52.95 106.56			



Report No.: SZEM140100040801

Page: 89 of 95

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Horizontal



Condition : FCC PART15(>1G) PK 3m HORIZONTAL

Job No. : 0408RF Mode : 2402


	. 2102	Freq			-	Read Level		Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	X	2390.000 2402.245				53.15 108.41			-31.63 23.57



Report No.: SZEM140100040801

Page: 90 of 95

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Vertical



Condition : FCC PART15(>1G) AV 3m VERTICAL

Job No. : 0408RF Mode : 2402


		Cablei	Antenna	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	6.55	27.63	44.97	45.90	35.11	54.00	-18.89
2 X	2402.150	6.56	27.58	44.98	88.64	77.80	54.00	23.80



Report No.: SZEM140100040801

Page: 91 of 95

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Average Horizontal



Condition : FCC PART15(>1G) AV 3m HORIZONTAL

Job No. : 0408RF Mode : 2402


	Freq			Preamp Factor			Limit Line	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 @	2390.000 2402.150			44.97 44.98				



Report No.: SZEM140100040801

Page: 92 of 95

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Vertical



Condition : FCC PART15(>1G) PK 3m VERTICAL

Job No. : 0408RF Mode : 2480


.040	. 2-100	Freq			•	Read Level		Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 X		2479.850 2483.500							17.70 -20.91



Report No.: SZEM140100040801

Page: 93 of 95

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Horizontal



Condition : FCC PART15(>1G) PK 3m HORIZONTAL

Job No. : 0408RF Mode : 2480


		Freq			•	Read Level		Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	X	2479.975 2483.500				105.60			21.12 -17.51



Report No.: SZEM140100040801

Page: 94 of 95

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Average Vertical



Condition : FCC PART15(>1G) AV 3m VERTICAL

Job No. : 0408RF Mode : 2480

	Freq			Preamp Factor			Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 X 2	2479.875 2483.500			45.02 45.02				






Report No.: SZEM140100040801

Page: 95 of 95

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Average Horizontal



Condition : FCC PART15(>1G) AV 3m HORIZONTAL

Job No. : 0408RF Mode : 2480

1040	. 2400	Freq			Preamp Factor			Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	$\overline{\text{dBuV/m}}$	dB
1 0		2480.050						54.00	
2		2483.500	6.99	27.55	45.02	59.71	49.24	54.00	-4.76

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."