

Report No.: SZEM150500298802

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 158

#### FCC REPORT

Application No: SZEM1505002988CR

**Applicant:** TEAC Corporation **Manufacturer:** TEAC Corporation

Factory: Dongguan TEAC Electronics Co., Ltd.

Product Name: USB DAC / NETWORK PLAYER

Model No.(EUT): NT-503
Trade Mark: TEAC

FCC ID: XEG-NT503

**Standards:** 47 CFR Part 15, Subpart C (2014)

**Date of Receipt:** 2015-06-03

**Date of Test:** 2015-06-29 to 2015-07-10

**Date of Issue:** 2015-08-03

Test Result: PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

#### Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM150500298802

Page: 2 of 158

#### 2 Version

| Revision Record |         |            |          |          |  |  |
|-----------------|---------|------------|----------|----------|--|--|
| Version         | Chapter | Date       | Modifier | Remark   |  |  |
| 00              |         | 2015-08-03 |          | Original |  |  |
|                 |         |            |          |          |  |  |
|                 |         |            |          |          |  |  |

| Authorized for issue by: |                             |            |
|--------------------------|-----------------------------|------------|
| Tested By                | Eric Fu                     | 2015-07-10 |
|                          | (Eric Fu) /Project Engineer | Date       |
| Prepared By              | Jarole Chen                 | 2015-08-03 |
|                          | (Jade Chen) /Clerk          | Date       |
| Checked By               | Owen Zhou                   | 2015-08-03 |
|                          | (Owen Zhou) /Reviewer       | Date       |



Report No.: SZEM150500298802

Page: 3 of 158

#### 3 Test Summary

| Test Item                                                         | Test Requirement                                                                      | Test method        | Result |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------|--------|
| Antenna Requirement                                               | 47 CFR Part 15, Subpart C Section<br>15.203/15.247 (c)                                | ANSI C63.10 (2009) | PASS   |
| AC Power Line Conducted<br>Emission                               | 47 CFR Part 15, Subpart C Section<br>15.207                                           | ANSI C63.10 (2009) | PASS   |
| Conducted Peak Output<br>Power                                    | 47 CFR Part 15, Subpart C Section<br>15.247 (b)(1)                                    | ANSI C63.10 (2009) | PASS   |
| 20dB Occupied Bandwidth                                           | 47 CFR Part 15, Subpart C Section<br>15.247 (a)(1)                                    | ANSI C63.10 (2009) | PASS   |
| Carrier Frequencies Separation                                    | 47 CFR Part 15, Subpart C Section<br>15.247 (a)(1)                                    | ANSI C63.10 (2009) | PASS   |
| Hopping Channel Number                                            | 47 CFR Part 15, Subpart C Section<br>15.247 (a)(1)                                    | ANSI C63.10 (2009) | PASS   |
| Dwell Time                                                        | 47 CFR Part 15, Subpart C Section<br>15.247 (a)(1)                                    | ANSI C63.10 (2009) | PASS   |
| Pseudorandom Frequency<br>Hopping Sequence                        | 47 CFR Part 15, Subpart C Section<br>15.247(b)(4)&TCB Exclusion List<br>(7 July 2002) | ANSI C63.10 (2009) | PASS   |
| Band-edge for RF<br>Conducted Emissions                           | 47 CFR Part 15, Subpart C Section 15.247(d)                                           | ANSI C63.10 (2009) | PASS   |
| RF Conducted Spurious<br>Emissions                                | 47 CFR Part 15, Subpart C Section 15.247(d)                                           | ANSI C63.10 (2009) | PASS   |
| Radiated Spurious emissions                                       | 47 CFR Part 15, Subpart C Section<br>15.205/15.209                                    | ANSI C63.10 (2009) | PASS   |
| Restricted bands around fundamental frequency (Radiated Emission) | 47 CFR Part 15, Subpart C Section<br>15.205/15.209                                    | ANSI C63.10 (2009) | PASS   |



Report No.: SZEM150500298802

Page: 4 of 158

#### 4 Contents

|   |             |                                               | Page |
|---|-------------|-----------------------------------------------|------|
| 1 | CO          | VER PAGE                                      | 1    |
| 2 | ٧E          | RSION                                         | 2    |
| 3 | TE:         | ST SUMMARY                                    | 3    |
| 4 | CO          | ONTENTS                                       | 4    |
| 5 |             | NERAL INFORMATION                             |      |
| • | 5.1         | CLIENT INFORMATION                            | _    |
|   | 5.1         | GENERAL DESCRIPTION OF EUT                    |      |
|   | 5.3         | TEST ENVIRONMENT                              |      |
|   | 5.4         | DESCRIPTION OF SUPPORT UNITS                  |      |
|   | 5.5         | TEST LOCATION                                 |      |
|   | 5.6         | TEST FACILITY                                 |      |
|   | 5.7         | DEVIATION FROM STANDARDS                      |      |
|   | 5.8<br>5.9  | ABNORMALITIES FROM STANDARD CONDITIONS        |      |
|   | 5.10        | EQUIPMENT LIST                                |      |
| 6 |             | ST RESULTS AND MEASUREMENT DATA               |      |
| O |             |                                               |      |
|   | 6.1         | ANTENNA REQUIREMENT                           |      |
|   | 6.2<br>6.3  | CONDUCTED EMISSIONS                           |      |
|   | 6.4         | 20DB OCCUPY BANDWIDTH                         |      |
|   | 6.5         | CARRIER FREQUENCIES SEPARATION                |      |
|   | 6.6         | HOPPING CHANNEL NUMBER                        | 41   |
|   | 6.7         | DWELL TIME                                    |      |
|   | 6.8         | BAND-EDGE FOR RF CONDUCTED EMISSIONS          |      |
|   | 6.9<br>6.10 | SPURIOUS RF CONDUCTED EMISSIONS               |      |
|   | 6.11        | RADIATED SPURIOUS EMISSION                    |      |
|   | •           | 1.1 Duty cycle                                |      |
|   | 6.1         | 1.2 Radiated Emission below 1GHz              |      |
|   | 6.1         | 1.3 Transmitter Emission above 1GHz           |      |
|   | 6.12        | RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY | 151  |
| 7 | PH          | OTOGRAPHS - EUT TEST SETUP                    | 157  |
|   | 7.1         | CONDUCTED EMISSION                            | 157  |
|   | 7.2         | RADIATED EMISSION                             | 157  |
|   | 7.3         | RADIATED SPURIOUS EMISSION                    | 158  |
| 8 | PH          | OTOGRAPHS - EUT CONSTRUCTIONAL DETAILS        | 158  |



Report No.: SZEM150500298802

Page: 5 of 158

#### 5 General Information

#### 5.1 Client Information

| Applicant:               | TEAC Corporation                                                  |  |
|--------------------------|-------------------------------------------------------------------|--|
| Address of Applicant:    | 1-47 Ochiai, Tama-shi, Tokyo, Japan                               |  |
| Manufacturer:            | TEAC Corporation                                                  |  |
| Address of Manufacturer: | 1-47 Ochiai, Tama-shi, Tokyo, Japan                               |  |
| Factory:                 | Dongguan TEAC Electronics Co., Ltd.                               |  |
| Address of Factory:      | Shang-sha, Chang-an District, Dongguan City, Guangdong, P.R.China |  |

#### 5.2 General Description of EUT

| •                     |                                         |
|-----------------------|-----------------------------------------|
| Product Name:         | USB DAC / NETWORK PLAYER                |
| Model No.:            | NT-503                                  |
| Trade Mark:           | TEAC                                    |
| Operation Frequency:  | 2402MHz~2480MHz                         |
| Bluetooth Version:    | V2.1+EDR                                |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Modulation Type:      | GFSK, π/4DQPSK, 8DPSK                   |
| Number of Channel:    | 79                                      |
| Hopping Channel Type: | Adaptive Frequency Hopping systems      |
| Sample Type:          | Fixed production                        |
| Test Power Grade:     | Class II (manufacturer declare)         |
| Test Software of EUT: | Blue test 3                             |
| Antenna Type and Gain | Type :Integral                          |
|                       | Gain: 2.4dBi                            |
| Power Supply:         | AC 120V 60Hz                            |



Report No.: SZEM150500298802

Page: 6 of 158

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2402MHz   | 21      | 2422MHz   | 41      | 2442MHz   | 61      | 2462MHz   |
| 2                                   | 2403MHz   | 22      | 2423MHz   | 42      | 2443MHz   | 62      | 2463MHz   |
| 3                                   | 2404MHz   | 23      | 2424MHz   | 43      | 2444MHz   | 63      | 2464MHz   |
| 4                                   | 2405MHz   | 24      | 2425MHz   | 44      | 2445MHz   | 64      | 2465MHz   |
| 5                                   | 2406MHz   | 25      | 2426MHz   | 45      | 2446MHz   | 65      | 2466MHz   |
| 6                                   | 2407MHz   | 26      | 2427MHz   | 46      | 2447MHz   | 66      | 2467MHz   |
| 7                                   | 2408MHz   | 27      | 2428MHz   | 47      | 2448MHz   | 67      | 2468MHz   |
| 8                                   | 2409MHz   | 28      | 2429MHz   | 48      | 2449MHz   | 68      | 2469MHz   |
| 9                                   | 2410MHz   | 29      | 2430MHz   | 49      | 2450MHz   | 69      | 2470MHz   |
| 10                                  | 2411MHz   | 30      | 2431MHz   | 50      | 2451MHz   | 70      | 2471MHz   |
| 11                                  | 2412MHz   | 31      | 2432MHz   | 51      | 2452MHz   | 71      | 2472MHz   |
| 12                                  | 2413MHz   | 32      | 2433MHz   | 52      | 2453MHz   | 72      | 2473MHz   |
| 13                                  | 2414MHz   | 33      | 2434MHz   | 53      | 2454MHz   | 73      | 2474MHz   |
| 14                                  | 2415MHz   | 34      | 2435MHz   | 54      | 2455MHz   | 74      | 2475MHz   |
| 15                                  | 2416MHz   | 35      | 2436MHz   | 55      | 2456MHz   | 75      | 2476MHz   |
| 16                                  | 2417MHz   | 36      | 2437MHz   | 56      | 2457MHz   | 76      | 2477MHz   |
| 17                                  | 2418MHz   | 37      | 2438MHz   | 57      | 2458MHz   | 77      | 2478MHz   |
| 18                                  | 2419MHz   | 38      | 2439MHz   | 58      | 2459MHz   | 78      | 2479MHz   |
| 19                                  | 2420MHz   | 39      | 2440MHz   | 59      | 2460MHz   | 79      | 2480MHz   |
| 20                                  | 2421MHz   | 40      | 2441MHz   | 60      | 2461MHz   |         |           |

#### Note

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel             | Frequency |  |
|---------------------|-----------|--|
| The Lowest channel  | 2402MHz   |  |
| The Middle channel  | 2441MHz   |  |
| The Highest channel | 2480MHz   |  |



Report No.: SZEM150500298802

Page: 7 of 158

#### 5.3 Test Environment

| Operating Environment: |           |  |  |  |
|------------------------|-----------|--|--|--|
| Temperature:           | 25.0 °C   |  |  |  |
| Humidity:              | 53 % RH   |  |  |  |
| Atmospheric Pressure:  | 1005 mbar |  |  |  |

#### 5.4 Description of Support Units

The EUT has been tested independent unit.

#### 5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM150500298802

Page: 8 of 158

#### 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### VCCI

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

#### • FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

#### Industry Canada (IC)

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2.

#### 5.7 Deviation from Standards

None.

#### 5.8 Abnormalities from Standard Conditions

None.

#### 5.9 Other Information Requested by the Customer

None.





Report No.: SZEM150500298802

Page: 9 of 158

#### 5.10 Equipment List

|      | Conducted Emission                    |                                          |                     |                  |                           |  |  |
|------|---------------------------------------|------------------------------------------|---------------------|------------------|---------------------------|--|--|
| Item | Test Equipment                        | Manufacturer                             | Model No.           | Inventory<br>No. | Cal.Due date (yyyy-mm-dd) |  |  |
| 1    | Shielding Room                        | ZhongYu Electron                         | GB-88               | SEL0042          | 2016-05-13                |  |  |
| 2    | LISN                                  | Rohde & Schwarz                          | ENV216              | SEL0152          | 2015-10-24                |  |  |
| 3    | LISN                                  | ETS-LINDGREN                             | 3816/2              | SEL0021          | 2016-05-13                |  |  |
| 4    | 8 Line ISN                            | Fischer Custom<br>Communications<br>Inc. | FCC-TLISN-<br>T8-02 | SEL0162          | 2015-08-30                |  |  |
| 5    | 4 Line ISN                            | Fischer Custom<br>Communications<br>Inc. | FCC-TLISN-<br>T4-02 | SEL0163          | 2015-08-30                |  |  |
| 6    | 2 Line ISN                            | Fischer Custom<br>Communications<br>Inc. | FCC-TLISN-<br>T2-02 | SEL0164          | 2015-08-30                |  |  |
| 7    | EMI Test Receiver                     | Rohde & Schwarz                          | ESCI                | SEL0022          | 2016-05-13                |  |  |
| 8    | Coaxial Cable                         | SGS                                      | N/A                 | SEL0025          | 2016-05-13                |  |  |
| 9    | DC Power Supply                       | Zhao Xin                                 | RXN-305D            | SEL0117          | 2015-10-24                |  |  |
| 10   | Humidity/<br>Temperature<br>Indicator | Shanhai Qixiang                          | ZJ1-2B              | SEL0103          | 2015-10-24                |  |  |
| 11   | Barometer                             | Chang Chun                               | DYM3                | SEL0088          | 2016-05-13                |  |  |



Report No.: SZEM150500298802

Page: 10 of 158

|      | RE in Chamber                      |                                          |           |                  |                           |  |
|------|------------------------------------|------------------------------------------|-----------|------------------|---------------------------|--|
| Item | Test Equipment                     | Manufacturer                             | Model No. | Inventory<br>No. | Cal.Due date (yyyy-mm-dd) |  |
| 1    | 3m Semi-Anechoic<br>Chamber        | ETS-LINDGREN                             | N/A       | SEL0017          | 2016-05-13                |  |
| 2    | EMI Test Receiver                  | Agilent<br>Technologies                  | N9038A    | SEL0312          | 2015-09-16                |  |
| 3    | EMI Test software                  | AUDIX                                    | E3        | SEL0050          | N/A                       |  |
| 4    | BiConiLog Antenna<br>(26-3000MHz)  | ETS-LINDGREN                             | 3142C     | SEL0015          | 2015-10-24                |  |
| 5    | Double-ridged horn<br>(1-18GHz)    | ETS-LINDGREN                             | 3117      | SEL0006          | 2015-10-24                |  |
| 6    | Horn Antenna<br>(18-26GHz)         | ETS-LINDGREN                             | 3160      | SEL0076          | 2015-10-24                |  |
| 7    | Pre-amplifier<br>(0.1-1300MHz)     | Agilent<br>Technologies                  | 8447D     | SEL0053          | 2016-05-13                |  |
| 8    | Pre-Amplifier<br>(0.1-26.5GHz)     | Compliance<br>Directions Systems<br>Inc. | PAP-0126  | SEL0168          | 2015-10-24                |  |
| 9    | Coaxial cable                      | SGS                                      | N/A       | SEL0027          | 2016-05-13                |  |
| 10   | Coaxial cable                      | SGS                                      | N/A       | SEL0189          | 2016-05-13                |  |
| 11   | Coaxial cable                      | SGS                                      | N/A       | SEL0121          | 2016-05-13                |  |
| 12   | Coaxial cable                      | SGS                                      | N/A       | SEL0178          | 2016-05-13                |  |
| 13   | Band filter                        | Amindeon                                 | 82346     | SEL0094          | 2016-05-13                |  |
| 14   | Barometer                          | Chang Chun                               | DYM3      | SEL0088          | 2016-05-13                |  |
| 15   | DC Power Supply                    | Zhao Xin                                 | RXN-305D  | SEL0117          | 2015-10-24                |  |
| 16   | Humidity/<br>Temperature Indicator | Shanhai Qixiang                          | ZJ1-2B    | SEL0103          | 2015-10-24                |  |
| 17   | Signal Generator<br>(10M-27GHz)    | Rohde & Schwarz                          | SMR27     | SEL0067          | 2016-05-13                |  |
| 18   | Signal Generator                   | Rohde & Schwarz                          | SMY01     | SEL0155          | 2015-10-24                |  |
| 19   | Loop Antenna                       | Beijing Daze                             | ZN30401   | SEL0203          | 2016-05-13                |  |



Report No.: SZEM150500298802

Page: 11 of 158

|      | RF connected test                     |                         |           |                  |                           |
|------|---------------------------------------|-------------------------|-----------|------------------|---------------------------|
| Item | Test Equipment                        | Manufacturer            | Model No. | Inventory<br>No. | Cal.Due date (yyyy-mm-dd) |
| 1    | DC Power Supply                       | Zhao Xin                | RXN-305D  | SEL0117          | 2015-10-24                |
| 2    | Humidity/<br>Temperature<br>Indicator | HYGRO                   | ZJ1-2B    | SEL0033          | 2015-10-24                |
| 3    | Spectrum Analyzer                     | Rohde & Schwarz         | FSP       | SEL0154          | 2015-10-24                |
| 4    | Coaxial cable                         | SGS                     | N/A       | SEL0178          | 2016-05-13                |
| 5    | Coaxial cable                         | SGS                     | N/A       | SEL0179          | 2016-05-13                |
| 6    | Barometer                             | ChangChun               | DYM3      | SEL0088          | 2016-05-13                |
| 7    | Signal Generator                      | Rohde & Schwarz         | SML03     | SEL0068          | 2016-04-25                |
| 8    | Band filter                           | amideon                 | 82346     | SEL0094          | 2016-05-13                |
| 9    | POWER METER                           | R&S                     | NRVS      | SEL0144          | 2015-10-24                |
| 10   | Attenuator                            | Beijin feihang taida    | TST-2-6dB | SEL0205          | 2016-04-25                |
| 11   | Power<br>Divider(splitter)            | Agilent<br>Technologies | 11636B    | SEL0130          | 2015-10-24                |

Note: The calibration interval is one year, all the instruments are valid.



Report No.: SZEM150500298802

Page: 12 of 158

#### 6 Test results and Measurement Data

#### 6.1 Antenna Requirement

**Standard requirement:** 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **EUT Antenna:**



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.4dBi.



Report No.: SZEM150500298802

Page: 13 of 158


#### 6.2 Conducted Emissions

| Test Requirement:     | 47 CFR Part 15C Section 15.207                                    |                        |                                                                                                                                                                                                                                                                                                                                                                                     |                                    |
|-----------------------|-------------------------------------------------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Test Method:          | ANSI C63.10: 2009                                                 |                        |                                                                                                                                                                                                                                                                                                                                                                                     |                                    |
| Test Frequency Range: | 150kHz to 30MHz                                                   |                        |                                                                                                                                                                                                                                                                                                                                                                                     |                                    |
| Limit:                | Francisco (MIII-)                                                 | Limit (d               | lBuV)                                                                                                                                                                                                                                                                                                                                                                               |                                    |
|                       | Frequency range (MHz)                                             | Quasi-peak             | Average                                                                                                                                                                                                                                                                                                                                                                             |                                    |
|                       | 0.15-0.5                                                          | 66 to 56*              | 56 to 46*                                                                                                                                                                                                                                                                                                                                                                           |                                    |
|                       | 0.5-5                                                             | 56                     | 46                                                                                                                                                                                                                                                                                                                                                                                  |                                    |
|                       | 5-30                                                              | 60                     | 50                                                                                                                                                                                                                                                                                                                                                                                  |                                    |
|                       | * Decreases with the logarithm                                    | n of the frequency.    |                                                                                                                                                                                                                                                                                                                                                                                     | _                                  |
| Test Procedure:       | The mains terminal disturb room.                                  | oance voltage test was | s conducted in a shie                                                                                                                                                                                                                                                                                                                                                               | elded                              |
|                       | 1) The mains terminal disturbance voltage test was conducted in a |                        | is a 50Ω/50μH + 5Ω lift the EUT were do to the ground or the unit being do to connect multiple of the LISN was not contained the table 0.8m above the table 0.8m above the table 0.8m above the rangement, the EUT deference plane. The red reference plane. The horizontal ground om the boundary of the plane for LISNs his distance was EUT. All other units of the positions of | he<br>was<br>ear<br>he<br>of<br>2. |



Report No.: SZEM150500298802

Page: 14 of 158





Report No.: SZEM150500298802


Page: 15 of 158

#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

#### Live line:



Site : Shielding Room

Condition : 47 CFR PART 15 B QP CE LINE

Job No. : 2988CR

Test Mode


|    |   | Frea    | Cable<br>Loss | LISN<br>Factor | Read<br>Level |       | Limit<br>Line | Over<br>Limit | Remark  |
|----|---|---------|---------------|----------------|---------------|-------|---------------|---------------|---------|
|    |   |         |               |                |               |       |               |               |         |
|    |   | MHz     | dB            | dB             | dBuV          | dBuV  | dBuV          | dB            |         |
| 1  | @ | 0.16944 | 0.02          | 9.82           | 48.40         | 58.24 | 64.99         | -6.74         | QP      |
| 2  |   | 0.16944 | 0.02          | 9.82           | 32.30         | 42.14 | 54.99         | -12.84        | Average |
| 3  | @ | 0.22556 | 0.02          | 9.83           | 46.30         | 56.15 | 62.61         | -6.46         | QP      |
| 4  |   | 0.22556 | 0.02          | 9.83           | 33.00         | 42.85 | 52.61         | -9.76         | Average |
| 5  |   | 0.23784 | 0.02          | 9.84           | 42.50         | 52.35 | 62.17         | -9.82         | QP      |
| 6  |   | 0.23784 | 0.02          | 9.84           | 29.00         | 38.85 | 52.17         | -13.32        | Average |
| 7  |   | 0.52654 | 0.01          | 9.86           | 18.60         | 28.48 | 46.00         | -17.52        | Average |
| 8  |   | 0.52654 | 0.01          | 9.86           | 26.63         | 36.50 | 56.00         | -19.50        | QP      |
| 9  |   | 4.114   | 0.01          | 10.08          | 18.61         | 28.71 | 46.00         | -17.29        | Average |
| 10 |   | 4.114   | 0.01          | 10.08          | 26.89         | 36.99 | 56.00         | -19.01        | QP      |
| 11 |   | 13.623  | 0.01          | 10.16          | 32.46         | 42.63 | 60.00         | -17.37        | QP      |
| 12 |   | 13.623  | 0.01          | 10.16          | 23.55         | 33.72 | 50.00         | -16.28        | Average |



Report No.: SZEM150500298802

Page: 16 of 158

#### Neutral line:



Site : Shielding Room

Condition : 47 CFR PART 15 B QP CE NEUTRAL

Job No. : 2988CR

Test Mode :

|    |   | _       | Cable | LISN   | Read  |       | Limit | Over   | _       |
|----|---|---------|-------|--------|-------|-------|-------|--------|---------|
|    |   | Freq    | Loss  | Factor | Level | Level | Line  | Limit  | Remark  |
|    |   | MHz     | dB    | dB     | dBuV  | dBuV  | dBuV  | dB     |         |
| 1  |   | 0.17215 | 0.02  | 9.81   | 47.20 | 57.03 | 64.86 | -7.82  | QP      |
| 2  |   | 0.17215 | 0.02  | 9.81   | 32.20 | 42.03 | 54.86 | -12.82 | Average |
| 3  | @ | 0.21735 | 0.02  | 9.85   | 45.80 | 55.67 | 62.92 | -7.25  | QP      |
| 4  |   | 0.21735 | 0.02  | 9.85   | 32.90 | 42.77 | 52.92 | -10.15 | Average |
| 5  |   | 0.23040 | 0.02  | 9.85   | 44.40 | 54.27 | 62.44 | -8.16  | QP      |
| 6  |   | 0.23040 | 0.02  | 9.85   | 29.00 | 38.87 | 52.44 | -13.56 | Average |
| 7  |   | 0.28178 | 0.01  | 9.86   | 35.91 | 45.78 | 60.76 | -14.98 | QP      |
| 8  |   | 0.28178 | 0.01  | 9.86   | 24.90 | 34.77 | 50.76 | -15.99 | Average |
| 9  |   | 4.224   | 0.01  | 10.13  | 26.71 | 36.85 | 56.00 | -19.15 | QP      |
| 10 |   | 4.224   | 0.01  | 10.13  | 19.26 | 29.41 | 46.00 | -16.59 | Average |
| 11 |   | 13.197  | 0.01  | 10.19  | 22.70 | 32.90 | 50.00 | -17.10 | Average |
| 12 |   | 13.197  | 0.01  | 10.19  | 32.40 | 42.60 | 60.00 | -17.40 | QP      |

#### Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM150500298802

Page: 17 of 158

#### 6.3 Conducted Peak Output Power





Report No.: SZEM150500298802

Page: 18 of 158

#### **Measurement Data**

| GFSK mode    |                         |             |        |  |  |
|--------------|-------------------------|-------------|--------|--|--|
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |  |  |
| Lowest       | 1.01                    | 30.00       | Pass   |  |  |
| Middle       | 0.18                    | 30.00       | Pass   |  |  |
| Highest      | 0.99                    | 30.00       | Pass   |  |  |
|              | π/4DQPSK m              | node        |        |  |  |
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |  |  |
| Lowest       | -0.22                   | 30.00       | Pass   |  |  |
| Middle       | -1.29                   | 30.00       | Pass   |  |  |
| Highest      | -1.54                   | 30.00       | Pass   |  |  |
|              | 8DPSK mod               | de          |        |  |  |
| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |  |  |
| Lowest       | 0.05                    | 30.00       | Pass   |  |  |
| Middle       | -0.88                   | 30.00       | Pass   |  |  |
| Highest      | -1.24                   | 30.00       | Pass   |  |  |






Report No.: SZEM150500298802


Page: 19 of 158

#### Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM150500298802

Page: 20 of 158

Test mode: GFSK Test channel: Highest











Report No.: SZEM150500298802

Page: 21 of 158

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM150500298802

Page: 22 of 158





Test mode: 8DPSK Test channel: Middle






Report No.: SZEM150500298802

Page: 23 of 158








Report No.: SZEM150500298802

Page: 24 of 158

#### 6.4 20dB Occupy Bandwidth



#### **Measurement Data**


|              | 20dB Occupy Bandwidth (kHz) |          |       |  |  |
|--------------|-----------------------------|----------|-------|--|--|
| Test channel | GFSK                        | π/4DQPSK | 8DPSK |  |  |
| Lowest       | 897                         | 1224     | 1218  |  |  |
| Middle       | 891                         | 1224     | 1218  |  |  |
| Highest      | 894                         | 1227     | 1221  |  |  |



Report No.: SZEM150500298802

Page: 25 of 158

Test plot as follows:





| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.5470      | -20.88      | -20.70     | -0.18       |
| 2   | 2402.0240      | -0.70       | -20.70     | 20.00       |
| 3   | 2402.4440      | -20.86      | -20.70     | -0.16       |


| No. |         | 〉Frequency(MHz) | 〉Level(dB) |
|-----|---------|-----------------|------------|
| 1   | mk3-mk1 | 0.897           | 0.02       |



Report No.: SZEM150500298802

Page: 26 of 158

| Test mode: | GFSK | Test channel: | Middle |
|------------|------|---------------|--------|
|            |      |               |        |




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.5500      | -21.32      | -21.31     | -0.01       |
| 2   | 2441.0300      | -1.31       | -21.31     | 20.00       |
| 3   | 2441.4410      | -21.56      | -21.31     | -0.25       |

| No. |         | 〉Frequency(MHz) | 〉Level(dB) |
|-----|---------|-----------------|------------|
| 1   | mk3-mk1 | 0.891           | -0.24      |



Report No.: SZEM150500298802

Page: 27 of 158



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.5470      | -21.64      | -21.42     | -0.22       |
| 2   | 2480.0300      | -1.42       | -21.42     | 20.00       |
| 3   | 2480.4410      | -21.63      | -21.42     | -0.21       |


| No. |         | > Frequency(MHz) | › Level(dB) |
|-----|---------|------------------|-------------|
| 1   | mk3-mk1 | 0.894            | 0.01        |



Report No.: SZEM150500298802

Page: 28 of 158

| Test mode: | π/4DQPSK | Test channel: | Lowest |
|------------|----------|---------------|--------|
|            |          |               |        |



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.3820      | -22.86      | -22.58     | -0.28       |
| 2   | 2402.0330      | -2.58       | -22.58     | 20.00       |
| 3   | 2402.6060      | -23.01      | -22.58     | -0.43       |

| No. |         | > Frequency(MHz) | › Level(dB) |
|-----|---------|------------------|-------------|
| 1   | mk3-mk1 | 1.224            | -0.15       |






Report No.: SZEM150500298802

Page: 29 of 158

| Test mode: $\pi/4DQPSK$ Test channel: Mid | Middle |
|-------------------------------------------|--------|
|-------------------------------------------|--------|




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.3790      | -23.80      | -23.61     | -0.19       |
| 2   | 2441.0360      | -3.61       | -23.61     | 20.00       |
| 3   | 2441.6030      | -23.77      | -23.61     | -0.16       |

| No. |         | 〉Frequency(MHz) | 〉Level(dB) |
|-----|---------|-----------------|------------|
| 1   | mk3-mk1 | 1.224           | 0.03       |



Report No.: SZEM150500298802

Page: 30 of 158



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.3790      | -24.09      | -23.88     | -0.21       |
| 2   | 2480.0330      | -3.88       | -23.88     | 20.00       |
| 3   | 2480.6060      | -24.44      | -23.88     | -0.56       |


| No |         | > Frequency(MHz) | › Level(dB) |
|----|---------|------------------|-------------|
| 1  | mk3-mk1 | 1.227            | -0.35       |



Report No.: SZEM150500298802

Page: 31 of 158





| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.4150      | -22.59      | -22.50     | -0.09       |
| 2   | 2402.0300      | -2.50       | -22.50     | 20.00       |
| 3   | 2402.6330      | -23.30      | -22.50     | -0.80       |


| No. |         | 〉Frequency(MHz) | 〉Level(dB) |
|-----|---------|-----------------|------------|
| 1   | mk3-mk1 | 1.218           | -0.71      |



Report No.: SZEM150500298802

Page: 32 of 158

| Test mode:   8DPSK   Test channel:   Middle | Test mode: | 8DPSK | Test channel: | Middle |
|---------------------------------------------|------------|-------|---------------|--------|
|---------------------------------------------|------------|-------|---------------|--------|



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.4120      | -23.56      | -23.56     | 0.00        |
| 2   | 2441.0300      | -3.56       | -23.56     | 20.00       |
| 3   | 2441.6300      | -24.17      | -23.56     | -0.61       |


| No. |         | > Frequency(MHz) | › Level(dB) |
|-----|---------|------------------|-------------|
| 1   | mk3-mk1 | 1.218            | -0.61       |



Report No.: SZEM150500298802

Page: 33 of 158

| Test mode: | 8DPSK | Test channel: | Highest |
|------------|-------|---------------|---------|
|            |       |               | 9       |



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.4090      | -24.24      | -23.83     | -0.41       |
| 2   | 2480.0300      | -3.83       | -23.83     | 20.00       |
| 3   | 2480.6300      | -24.33      | -23.83     | -0.50       |


| No. |         | 〉Frequency(MHz) | 〉Level(dB) |
|-----|---------|-----------------|------------|
| 1   | mk3-mk1 | 1.221           | -0.09      |



Report No.: SZEM150500298802

Page: 34 of 158

#### 6.5 Carrier Frequencies Separation





Report No.: SZEM150500298802

Page: 35 of 158

| GFSK mode    |                                         |             |        |  |
|--------------|-----------------------------------------|-------------|--------|--|
| Test channel | Carrier Frequencies<br>Separation (kHz) | Limit (kHz) | Result |  |
| Lowest       | 1002                                    | ≥859        | Pass   |  |
| Middle       | 1006                                    | ≥859        | Pass   |  |
| Highest      | 1002                                    | ≥859        | Pass   |  |
|              | π/4DQPSK mode                           |             |        |  |
| Test channel | Carrier Frequencies<br>Separation (kHz) | Limit (kHz) | Result |  |
| Lowest       | 1002                                    | ≥818        | Pass   |  |
| Middle       | 1010                                    | ≥818        | Pass   |  |
| Highest      | 1002                                    | ≥818        | Pass   |  |
| 8DPSK mode   |                                         |             |        |  |
| Test channel | Carrier Frequencies<br>Separation (kHz) | Limit (kHz) | Result |  |
| Lowest       | 1002                                    | ≥814        | Pass   |  |
| Middle       | 1010                                    | ≥814        | Pass   |  |
| Highest      | 1002                                    | ≥814        | Pass   |  |

Note: According to section 6,4

| Mode     | 20dB bandwidth (kHz)  Limit (kHz) |                                  |
|----------|-----------------------------------|----------------------------------|
|          | (worse case)                      | (Carrier Frequencies Separation) |
| GFSK     | 897                               | 598                              |
| π/4DQPSK | 1227                              | 818                              |
| 8DPSK    | 1221                              | 814                              |




Report No.: SZEM150500298802


Page: 36 of 158


#### Test plot as follows:

Test plot as follows:

| Test mode: GFSK | Test channel: | Lowest |
|-----------------|---------------|--------|
|-----------------|---------------|--------|











Report No.: SZEM150500298802

Page: 37 of 158

Test mode: GFSK Test channel: Highest











Report No.: SZEM150500298802

Page: 38 of 158

Test mode: π/4DQPSK Test channel: Middle



Test mode: π/4DQPSK Test channel: Highest









Report No.: SZEM150500298802

Page: 39 of 158

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM150500298802

Page: 40 of 158








Report No.: SZEM150500298802

Page: 41 of 158

#### 6.6 Hopping Channel Number



#### **Measurement Data**

| Mode     | Hopping channel numbers | Limit |
|----------|-------------------------|-------|
| GFSK     | 79                      | ≥15   |
| π/4DQPSK | 79                      | ≥15   |
| 8DPSK    | 79                      | ≥15   |




Report No.: SZEM150500298802

Page: 42 of 158

Test plot as follows:








Report No.: SZEM150500298802

Page: 43 of 158








Report No.: SZEM150500298802

Page: 44 of 158








Report No.: SZEM150500298802

Page: 45 of 158

#### 6.7 Dwell Time



#### **Measurement Data**

| Mode     | Packet | Dwell time (second) | Limit (second) |
|----------|--------|---------------------|----------------|
|          | DH1    | 0.131               | 0.4            |
| GFSK     | DH3    | 0.251               | 0.4            |
|          | DH5    | 0.293               | 0.4            |
|          | 2-DH1  | 0.135               | 0.4            |
| π/4DQPSK | 2-DH3  | 0.252               | 0.4            |
|          | 2-DH5  | 0.294               | 0.4            |
|          | 3-DH1  | 0.135               | 0.4            |
| 8DPSK    | 3-DH3  | 0.252               | 0.4            |
|          | 3-DH5  | 0.294               | 0.4            |



Report No.: SZEM150500298802

Page: 46 of 158

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

On (ms)\*total number=dwell time (ms)

The lowest channel (2402MHz), as below:

DH1 time slot=0.409 (ms)\*total number=130.88(ms)

DH3 time slot= $1.671 \text{ (ms)}^*$  total number = 250.65 (ms)

DH5 time slot=2.928 (ms)\* total number =292.8 (ms)

2-DH1 time slot=0.422 (ms)\*total number=135.04 (ms)

2-DH3 time slot=1.683 (ms)\* total number =252.45(ms)

2-DH5 time slot=2.936 (ms)\* total number =293.60(ms)

3-DH1 time slot=0.422 (ms)\*total number=135.04 (ms)

3-DH3 time slot=1.68 (ms)\* total number = 252.00(ms)


3-DH5 time slot=2.936 (ms)\* total number = 293.6 (ms)




Report No.: SZEM150500298802

Page: 47 of 158

Test plot as follows:








Report No.: SZEM150500298802

Page: 48 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.1940         | -12.04      |
| 2   | 0.2020         | 0.36        |
| 3   | 0.6030         | -10.54      |


| No. |         | 〉Time(ms) | › Level(dB) |
|-----|---------|-----------|-------------|
| 1   | mk3-mk1 | 0.409     | 1.5         |





Report No.: SZEM150500298802


Page: 49 of 158





Report No.: SZEM150500298802

Page: 50 of 158




| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.7920         | -9.98       |
| 2   | 0.8010         | 0.32        |
| 3   | 2.4630         | -15.39      |

| No. |         | 〉Time(ms) | 〉Level(dB) |
|-----|---------|-----------|------------|
| 1   | mk3-mk1 | 1.671     | -5.41      |



Report No.: SZEM150500298802


Page: 51 of 158





Report No.: SZEM150500298802

Page: 52 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.7880         | -12.93      |
| 2   | 0.8000         | 0.34        |
| 3   | 3.7160         | -18.28      |


| No. |         | 〉Time(ms) | › Level(dB) |
|-----|---------|-----------|-------------|
| 1   | mk3-mk1 | 2.928     | -5.35       |



Report No.: SZEM150500298802

Page: 53 of 158








Report No.: SZEM150500298802

Page: 54 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.1940         | -12.86      |
| 2   | 0.4060         | -2.20       |
| 3   | 0.6160         | -12.93      |


| No. |         | 〉Time(ms) | 〉Level(dB) |
|-----|---------|-----------|------------|
| 1   | mk3-mk1 | 0.422     | -0.07      |



Report No.: SZEM150500298802

Page: 55 of 158








Report No.: SZEM150500298802

Page: 56 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.7890         | -17.90      |
| 2   | 2.2410         | -2.07       |
| 3   | 2.4720         | -15.00      |


| No. |         | 〉Time(ms) | 〉Level(dB) |
|-----|---------|-----------|------------|
| 1   | mk3-mk1 | 1.683     | 2.9        |



Report No.: SZEM150500298802

Page: 57 of 158


| Test Packet: | 2-DH5 |
|--------------|-------|





Report No.: SZEM150500298802

Page: 58 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.7880         | -13.06      |
| 2   | 1.7320         | -2.06       |
| 3   | 3.7240         | -16.14      |

| No. |         | 〉Time(ms) | 〉Level(dB) |  |
|-----|---------|-----------|------------|--|
| 1   | mk3-mk1 | 2.936     | -3.08      |  |






Report No.: SZEM150500298802

Page: 59 of 158


| Test Packet: | 3-DH1 |
|--------------|-------|





Report No.: SZEM150500298802

Page: 60 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.1940         | -12.23      |
| 2   | 0.4320         | -1.59       |
| 3   | 0.6160         | -13.39      |


| No. |         | 〉Time(ms) | 〉Level(dB) |
|-----|---------|-----------|------------|
| 1   | mk3-mk1 | 0.422     | -1.16      |



Report No.: SZEM150500298802

Page: 61 of 158








Report No.: SZEM150500298802

Page: 62 of 158




| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.7890         | -17.64      |
| 2   | 2.0520         | -1.69       |
| 3   | 2.4690         | -13.92      |

| No. |         | 〉Time(ms) | › Level(dB) |
|-----|---------|-----------|-------------|
| 1   | mk3-mk1 | 1.68      | 3.72        |



Report No.: SZEM150500298802


Page: 63 of 158





Report No.: SZEM150500298802

Page: 64 of 158



| No. | Sweep time(ms) | Result(dBm) |
|-----|----------------|-------------|
| 1   | 0.7880         | -12.83      |
| 2   | 2.0560         | -1.60       |
| 3   | 3.7240         | -15.54      |

| No. |         | 〉Time(ms) | 〉Level(dB) |
|-----|---------|-----------|------------|
| 1   | mk3-mk1 | 2.936     | -2.71      |



Report No.: SZEM150500298802

Page: 65 of 158

#### 6.8 Band-edge for RF Conducted Emissions

| Test Requirement:      | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                      |  |  |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| Test Method:           | ANSI C63.10:2009                                                                                                                                                                                                                                                                                                                                                                        |  |  |
| Test Setup:            | Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane                                                                                                                                                                                                                                                                                                                   |  |  |
|                        | Remark:                                                                                                                                                                                                                                                                                                                                                                                 |  |  |
|                        | Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.                                                                                                                                                                                                                                                                                                                    |  |  |
| Limit:                 | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |  |  |
| Exploratory Test Mode: | Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                              |  |  |
| Final Test Mode:       | Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                             |  |  |
| Instruments Used:      | Refer to section 5.10 for details                                                                                                                                                                                                                                                                                                                                                       |  |  |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                    |  |  |




Report No.: SZEM150500298802

Page: 66 of 158

Test plot as follows:






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2362.8280      | -39.22      | -19.08     | -20.14      |
| 2   | 2402.0260      | 0.92        | -19.08     | 20.00       |



Report No.: SZEM150500298802

Page: 67 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2399.6800      | -52.41      | -20.24     | -32.17      |
| 2   | 2403.1000      | -0.24       | -20.24     | 20.00       |
| 3   | 2403.2900      | -0.26       | -20.24     | 19.98       |



Report No.: SZEM150500298802

Page: 68 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.8480      | -0.41       | -20.41     | 20.00       |
| 2   | 2483.9840      | -39.23      | -20.41     | -18.82      |





Report No.: SZEM150500298802

Page: 69 of 158





| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2477.8280      | -0.22       | -20.22     | 20.00       |
| 2   | 2478.9550      | -1.29       | -20.22     | 18.93       |
| 3   | 2493.7670      | -52.31      | -20.22     | -32.09      |



Report No.: SZEM150500298802

Page: 70 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2373.3560      | -40.69      | -21.20     | -19.49      |
| 2   | 2402.0260      | -1.20       | -21.20     | 20.00       |



Report No.: SZEM150500298802

Page: 71 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2399.6800      | -48.04      | -21.64     | -26.40      |
| 2   | 2402.0550      | -2.98       | -21.64     | 18.66       |
| 3   | 2403.1000      | -1.64       | -21.64     | 20.00       |



Report No.: SZEM150500298802

Page: 72 of 158

| Test mode: | π/4DQPSK | Test channel: | Highest |  |
|------------|----------|---------------|---------|--|
|            |          |               |         |  |




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2480.0240      | -2.92       | -22.92     | 20.00       |
| 2   | 2488.0980      | -39.23      | -22.92     | -16.31      |



Report No.: SZEM150500298802

Page: 73 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2478.0350      | -2.84       | -22.84     | 20.00       |
| 2   | 2480.0360      | -2.88       | -22.84     | 19.96       |
| 3   | 2489.3050      | -52.52      | -22.84     | -29.68      |



Report No.: SZEM150500298802

Page: 74 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2365.6480      | -40.03      | -21.62     | -18.41      |
| 2   | 2401.8380      | -1.62       | -21.62     | 20.00       |



Report No.: SZEM150500298802

Page: 75 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2399.3950      | -46.01      | -21.71     | -24.30      |
| 2   | 2402.9100      | -1.71       | -21.71     | 20.00       |



Report No.: SZEM150500298802

Page: 76 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2480.0240      | -2.90       | -22.90     | 20.00       |
| 2   | 2494.8740      | -40.22      | -22.90     | -17.32      |



Report No.: SZEM150500298802

Page: 77 of 158



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2477.9660      | -2.68       | -22.68     | 20.00       |
| 2   | 2484.2450      | -56.61      | -22.68     | -33.93      |



Report No.: SZEM150500298802

Page: 78 of 158

#### 6.9 Spurious RF Conducted Emissions

| Test Requirement:      | 47 CFR Part 15C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Method:           | ANSI C63.10:2009                                                                                                                                                                                                                                                                                                                                                                        |
| Test Setup:            | Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane                                                                                                                                                                                                                                                                                                                   |
|                        | Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.                                                                                                                                                                                                                                                                                                            |
| Limit:                 | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Exploratory Test Mode: | Non-hopping transmitting with all kind of modulation and all kind of data type                                                                                                                                                                                                                                                                                                          |
| Final Test Mode:       | Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.                                                                                                                                                             |
| Instruments Used:      | Refer to section 5.10 for details                                                                                                                                                                                                                                                                                                                                                       |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                    |






Report No.: SZEM150500298802

Page: 79 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.3177      | -0.96       | -20.96     | 20.00       |
| 2   | 2770.0413      | -40.70      | -20.96     | -19.74      |



Report No.: SZEM150500298802

Page: 80 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1492.6593      | -43.00      | -20.01     | -22.99      |



Report No.: SZEM150500298802

Page: 81 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.8667      | -0.01       | -20.01     | 20.00       |
| 2   | 3408.8667      | -40.52      | -20.01     | -20.51      |



Report No.: SZEM150500298802

Page: 82 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 5541.6000      | -44.21      | -20.01     | -24.20      |



Report No.: SZEM150500298802

Page: 83 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 6970.2000      | -44.09      | -20.01     | -24.08      |



Report No.: SZEM150500298802

Page: 84 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 9389.9333      | -44.24      | -20.01     | -24.23      |



Report No.: SZEM150500298802

Page: 85 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.4373      | -1.72       | -21.72     | 20.00       |
| 2   | 19360.9417     | -40.35      | -21.72     | -18.63      |



Report No.: SZEM150500298802

Page: 86 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1426.4673      | -42.66      | -20.08     | -22.58      |



Report No.: SZEM150500298802

Page: 87 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.9333      | -0.08       | -20.08     | 20.00       |
| 2   | 2819.6667      | -40.97      | -20.08     | -20.89      |



Report No.: SZEM150500298802

Page: 88 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 5568.0000      | -43.74      | -20.08     | -23.66      |





Report No.: SZEM150500298802

Page: 89 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 6798.9333      | -43.63      | -20.08     | -23.55      |



Report No.: SZEM150500298802

Page: 90 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 9252.6667      | -44.03      | -20.08     | -23.95      |



Report No.: SZEM150500298802

Page: 91 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.5570      | -1.83       | -21.83     | 20.00       |
| 2   | 2599.4130      | -41.03      | -21.83     | -19.20      |



Report No.: SZEM150500298802

Page: 92 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 975.4030       | -42.72      | -21.51     | -21.21      |



Report No.: SZEM150500298802

Page: 93 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.8000      | -1.51       | -21.51     | 20.00       |
| 2   | 2634.7333      | -40.97      | -21.51     | -19.46      |



Report No.: SZEM150500298802

Page: 94 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4356.4667      | -44.18      | -21.51     | -22.67      |



Report No.: SZEM150500298802

Page: 95 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 7628.4000      | -43.66      | -21.51     | -22.15      |



Report No.: SZEM150500298802

Page: 96 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 8642.4000      | -43.21      | -21.51     | -21.70      |



Report No.: SZEM150500298802

Page: 97 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.3177      | -1.84       | -21.84     | 20.00       |
| 2   | 2544.4790      | -40.64      | -21.84     | -18.80      |



Report No.: SZEM150500298802

Page: 98 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1758.9377      | -42.70      | -24.42     | -18.28      |





Report No.: SZEM150500298802

Page: 99 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.8000      | -4.42       | -24.42     | 20.00       |
| 2   | 2549.2000      | -40.69      | -24.42     | -16.27      |



Report No.: SZEM150500298802

Page: 100 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4000.0000      | -43.55      | -24.42     | -19.13      |



Report No.: SZEM150500298802

Page: 101 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 6966.1333      | -44.03      | -24.42     | -19.61      |



Report No.: SZEM150500298802

Page: 102 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 9659.9333      | -43.98      | -24.42     | -19.56      |



Report No.: SZEM150500298802

Page: 103 of 158

Test mode: π/4DQPSK Test channel: Middle




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.4373      | -3.49       | -23.49     | 20.00       |
| 2   | 3311.8903      | -40.95      | -23.49     | -17.46      |



Report No.: SZEM150500298802

Page: 104 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1828.5443      | -41.77      | -22.17     | -19.60      |



Report No.: SZEM150500298802

Page: 105 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.9333      | -2.17       | -22.17     | 20.00       |
| 2   | 3155.1333      | -41.06      | -22.17     | -18.89      |



Report No.: SZEM150500298802

Page: 106 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4418.4667      | -43.72      | -22.17     | -21.55      |



Report No.: SZEM150500298802

Page: 107 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 6502.9333      | -43.53      | -22.17     | -21.36      |



Report No.: SZEM150500298802

Page: 108 of 158



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 9144.2000      | -43.59      | -22.17     | -21.42      |






Report No.: SZEM150500298802

Page: 109 of 158

| Test mode: | π/4DQPSK | Test channel: | Highest |
|------------|----------|---------------|---------|
|------------|----------|---------------|---------|




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.5570      | -6.03       | -26.03     | 20.00       |
| 2   | 2614.3950      | -40.60      | -26.03     | -14.57      |



Report No.: SZEM150500298802

Page: 110 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1797.2213      | -42.52      | -23.04     | -19.48      |



Report No.: SZEM150500298802

Page: 111 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.9333      | -3.04       | -23.04     | 20.00       |
| 2   | 3477.3333      | -41.11      | -23.04     | -18.07      |



Report No.: SZEM150500298802

Page: 112 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4411.3333      | -43.73      | -23.04     | -20.69      |



Report No.: SZEM150500298802

Page: 113 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 7759.2667      | -44.12      | -23.04     | -21.08      |



Report No.: SZEM150500298802

Page: 114 of 158





| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 8026.9333      | -43.71      | -23.04     | -20.67      |



Report No.: SZEM150500298802

Page: 115 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.3177      | -6.38       | -26.38     | 20.00       |
| 2   | 3490.0097      | -40.45      | -26.38     | -14.07      |



Report No.: SZEM150500298802

Page: 116 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1685.3253      | -42.20      | -22.42     | -19.78      |



Report No.: SZEM150500298802

Page: 117 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2401.9333      | -2.42       | -22.42     | 20.00       |
| 2   | 2799.5333      | -40.43      | -22.42     | -18.01      |



Report No.: SZEM150500298802

Page: 118 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4485.4000      | -43.73      | -22.42     | -21.31      |





Report No.: SZEM150500298802

Page: 119 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 6088.0000      | -43.78      | -22.42     | -21.36      |



Report No.: SZEM150500298802

Page: 120 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 8653.4000      | -44.07      | -22.42     | -21.65      |



Report No.: SZEM150500298802

Page: 121 of 158






| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.4373      | -3.80       | -23.80     | 20.00       |
| 2   | 2589.4250      | -41.15      | -23.80     | -17.35      |



Report No.: SZEM150500298802

Page: 122 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 1679.8093      | -42.84      | -22.25     | -20.59      |



Report No.: SZEM150500298802

Page: 123 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2440.9333      | -2.25       | -22.25     | 20.00       |
| 2   | 2992.0000      | -41.10      | -22.25     | -18.85      |



Report No.: SZEM150500298802

Page: 124 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4383.8667      | -43.57      | -22.25     | -21.32      |



Report No.: SZEM150500298802

Page: 125 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 7005.5333      | -42.98      | -22.25     | -20.73      |



Report No.: SZEM150500298802

Page: 126 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 9401.7333      | -43.51      | -22.25     | -21.26      |



Report No.: SZEM150500298802

Page: 127 of 158

| Test mode: | 8DPSK | Test channel: | Highest |
|------------|-------|---------------|---------|
|            |       |               | 0       |




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2479.5570      | -2.81       | -22.81     | 20.00       |
| 2   | 3534.1233      | -40.19      | -22.81     | -17.38      |



Report No.: SZEM150500298802

Page: 128 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 148.5940       | -42.89      | -23.24     | -19.65      |





Report No.: SZEM150500298802

Page: 129 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 2411.1333      | -40.71      | -23.24     | -17.47      |
| 2   | 2480.0000      | -3.24       | -23.24     | 20.00       |



Report No.: SZEM150500298802

Page: 130 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 4258.4667      | -43.87      | -23.24     | -20.63      |



Report No.: SZEM150500298802

Page: 131 of 158




| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 7167.2667      | -44.04      | -23.24     | -20.80      |



Report No.: SZEM150500298802

Page: 132 of 158



| No. | Frequency(MHz) | Result(dBm) | Limit(dBm) | Margin(dBm) |
|-----|----------------|-------------|------------|-------------|
| 1   | 8851.3333      | -44.17      | -23.24     | -20.93      |

#### Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



Report No.: SZEM150500298802

Page: 133 of 158

### 6.10 Other requirements Frequency Hopping Spread Spectrum System

### Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.



Report No.: SZEM150500298802

Page: 134 of 158

### Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

#### Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM150500298802

Page: 135 of 158

### **6.11** Radiated Spurious Emission


| Test Requirement: | 47 CFR Part 15C Section             | 7 CFR Part 15C Section 15.209 and 15.205                                                                                                                                                                                                                                    |                                |                   |            |                         |    |  |  |  |
|-------------------|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|-------------------|------------|-------------------------|----|--|--|--|
| Test Method:      | ANSI C63.10: 2009                   | NSI C63.10: 2009 easurement Distance: 3m (Semi-Anechoic Chamber)                                                                                                                                                                                                            |                                |                   |            |                         |    |  |  |  |
| Test Site:        | Measurement Distance                | : 3m                                                                                                                                                                                                                                                                        | ı (Semi-Anech                  | oic Cham          | ber)       |                         |    |  |  |  |
| Receiver Setup:   | Frequency                           |                                                                                                                                                                                                                                                                             | Detector                       | RBW               | VBW        | Remark                  |    |  |  |  |
|                   | 0.009MHz-0.090MHz                   |                                                                                                                                                                                                                                                                             | Peak                           | 10kHz             | z 30kHz    | Peak                    |    |  |  |  |
|                   | 0.009MHz-0.090MHz                   |                                                                                                                                                                                                                                                                             | Average                        | 10kHz             | z 30kHz    | Average                 |    |  |  |  |
|                   | 0.090MHz-0.110MHz                   |                                                                                                                                                                                                                                                                             | Quasi-peak                     | 10kHz             | z 30kHz    | Quasi-peak              |    |  |  |  |
|                   | 0.110MHz-0.490MH                    | Peak                                                                                                                                                                                                                                                                        | 10kHz                          | z 30kHz           | Peak       |                         |    |  |  |  |
|                   | 0.110MHz-0.490MH                    | Average                                                                                                                                                                                                                                                                     | 10kHz                          | z 30kHz           | Average    |                         |    |  |  |  |
|                   | 0.490MHz -30MHz                     | Quasi-peak                                                                                                                                                                                                                                                                  | 10kHz                          | 30kHz             | Quasi-peak |                         |    |  |  |  |
|                   | 30MHz-1GHz                          | 30MHz-1GHz                                                                                                                                                                                                                                                                  |                                |                   | Iz 300kHz  | Quasi-peak              |    |  |  |  |
|                   | Above 1CHz                          | Ab 4 O I I -                                                                                                                                                                                                                                                                |                                | 1MHz              | 3MHz       | Peak                    |    |  |  |  |
|                   | Above 1GHz                          |                                                                                                                                                                                                                                                                             | Peak                           | 1MHz              | 10Hz       | Average                 |    |  |  |  |
| Limit:            | Frequency                           |                                                                                                                                                                                                                                                                             | eld strength<br>crovolt/meter) | Limit<br>(dBuV/m) | Remark     | Measurement distance (m | 11 |  |  |  |
|                   | 0.009MHz-0.490MHz                   | 2                                                                                                                                                                                                                                                                           | 400/F(kHz)                     | -                 | -          | 300                     |    |  |  |  |
|                   | 0.490MHz-1.705MHz                   | 24                                                                                                                                                                                                                                                                          | 1000/F(kHz)                    | -                 | -          | 30                      |    |  |  |  |
|                   | 1.705MHz-30MHz                      |                                                                                                                                                                                                                                                                             | 30                             | -                 | -          | 30                      |    |  |  |  |
|                   | 30MHz-88MHz                         |                                                                                                                                                                                                                                                                             | 100                            | 40.0              | Quasi-peak | 3                       |    |  |  |  |
|                   | 88MHz-216MHz                        |                                                                                                                                                                                                                                                                             | 150                            | 43.5              | Quasi-peak | 3                       |    |  |  |  |
|                   | 216MHz-960MHz                       |                                                                                                                                                                                                                                                                             | 200                            | 46.0              | Quasi-peak | 3                       |    |  |  |  |
|                   | 960MHz-1GHz                         |                                                                                                                                                                                                                                                                             | 500                            | 54.0              | Quasi-peak | 3                       |    |  |  |  |
|                   | Above 1GHz                          | 500                                                                                                                                                                                                                                                                         | 54.0                           | Average           | 3          |                         |    |  |  |  |
|                   | emissions is 20dE applicable to the | Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device. |                                |                   |            |                         |    |  |  |  |



Report No.: SZEM150500298802

Page: 136 of 158

#### Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

#### Test Procedure:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB



Report No.: SZEM150500298802

Page: 137 of 158

| margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.                               |  |  |  |  |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|
| g. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz)                                                  |  |  |  |  |  |
| h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. |  |  |  |  |  |
| i. Repeat above procedures until all frequencies measured was complete.                                                                                     |  |  |  |  |  |
| Non-hopping transmitting mode with all kind of modulation and all kind of                                                                                   |  |  |  |  |  |
| data type .Transmitting mode.                                                                                                                               |  |  |  |  |  |
| Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case.                                                                          |  |  |  |  |  |
| For below 1GHz part, through pre-scan, the worst case is the lowest channel.                                                                                |  |  |  |  |  |
| Only the worst case is recorded in the report.                                                                                                              |  |  |  |  |  |
| Refer to section 5.10 for details                                                                                                                           |  |  |  |  |  |
| Pass                                                                                                                                                        |  |  |  |  |  |
|                                                                                                                                                             |  |  |  |  |  |



Report No.: SZEM150500298802

Page: 138 of 158

### 6.11.1 Duty cycle

| Test Requirement: | RSS-Gen Issue 4                               |
|-------------------|-----------------------------------------------|
| Test Method:      | ANSI C63.10:2013                              |
| Test Setup:       | Spectrum Analyzer  E.U.T  Non-Conducted Table |
|                   | Ground Reference Plane                        |
| Instruments Used: | Refer to section 5.10 for details             |
| Limit:            | N/A                                           |
| Test Mode:        | Transmitter mode                              |
| Test Results:     | Pass                                          |

#### **Measurement Data**

| Measurement Data   |                                  |  |  |  |  |
|--------------------|----------------------------------|--|--|--|--|
|                    | PDCF=20 log(Duty cycle)          |  |  |  |  |
| Calculate Formula: | Duty cycle= T on time / T period |  |  |  |  |
| (DH1)Test data:    | Ton time =0.397                  |  |  |  |  |
|                    | T period =100                    |  |  |  |  |
|                    | PDCF=-48.02                      |  |  |  |  |

|                 | Ton time =1.65 |
|-----------------|----------------|
| (DH3)Test data: | T period =100  |
|                 | PDCF=-35.65    |


|                 |                | SGS IT    |
|-----------------|----------------|-----------|
|                 | Ton time =2.89 | S 添加 AB   |
| (DH5)Test data: | T period =100  | 10 th 411 |
|                 | PDCF=-30.78    | ENZHE     |
|                 |                |           |




Report No.: SZEM150500298802

Page: 139 of 158











Report No.: SZEM150500298802

Page: 140 of 158











Report No.: SZEM150500298802

Page: 141 of 158

### DH-5








Report No.: SZEM150500298802

Page: 142 of 158

#### 6.11.2 Radiated Emission below 1GHz

| 30MHz~1GHz (QP) |              |          |
|-----------------|--------------|----------|
| Test mode:      | Transmitting | Vertical |



Condition: 47 CFR PART 15B 3m VERTICAL


Job No. : 2988CR Test Mode:


|                       | Freq                                                     |                                                    |                                                         | Preamp<br>Factor                                         | Read<br>Level                                            |                                                          | Limit<br>Line              | Over<br>Limit                                         |
|-----------------------|----------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|----------------------------|-------------------------------------------------------|
| _                     | MHz                                                      | d₿                                                 | dB/m                                                    | dB                                                       | dBuV                                                     | $\overline{\text{dBuV/m}}$                               | $\overline{\text{dBuV/m}}$ | dB                                                    |
| 1<br>2<br>3<br>4<br>5 | 180.65<br>338.40<br>489.03<br>609.92<br>701.76<br>722.59 | 2. 03<br>2. 97<br>3. 64<br>4. 23<br>4. 58<br>4. 60 | 9. 91<br>15. 18<br>17. 64<br>19. 94<br>21. 69<br>21. 61 | 25. 59<br>24. 50<br>26. 58<br>26. 73<br>26. 33<br>26. 41 | 38. 76<br>36. 62<br>39. 33<br>39. 98<br>42. 61<br>42. 39 | 25. 11<br>30. 27<br>34. 03<br>37. 42<br>42. 55<br>42. 19 | 46.00                      | -18.39<br>-15.73<br>-11.97<br>-8.58<br>-3.45<br>-3.81 |



Report No.: SZEM150500298802

Page: 143 of 158





Condition: 47 CFR PART 15B 3m HORIZONTAL

Job No. : 2988CR

Test Mode:

|                            | Freq                                                     |                                                    |                                                         | Preamp<br>Factor                                         | Read<br>Level                                            |                                                          | Limit<br>Line              | Over<br>Limit                                              |
|----------------------------|----------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|----------------------------|------------------------------------------------------------|
| ,                          | MHz                                                      | d₿                                                 | dB/m                                                    | dB                                                       | dBuV                                                     | $\overline{\text{dBuV/m}}$                               | $\overline{\text{dBuV/m}}$ | dB                                                         |
| 1<br>2<br>3<br>4<br>5<br>6 | 180.65<br>226.10<br>338.40<br>677.58<br>724.26<br>747.48 | 2. 03<br>2. 30<br>2. 97<br>4. 44<br>4. 61<br>4. 89 | 9. 91<br>11. 44<br>15. 18<br>21. 34<br>21. 60<br>21. 60 | 25. 59<br>24. 75<br>24. 50<br>26. 38<br>26. 42<br>26. 51 | 39. 22<br>44. 77<br>44. 72<br>38. 97<br>42. 83<br>40. 82 | 25. 57<br>33. 76<br>38. 37<br>38. 37<br>42. 62<br>40. 80 |                            | -17. 93<br>-12. 24<br>-7. 63<br>-7. 63<br>-3. 38<br>-5. 20 |




Report No.: SZEM150500298802

Page: 144 of 158

#### 6.11.3 Transmitter Emission above 1GHz

2402 Horizontal - Worst case GFSK (DH5)



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Deg.(deg. | Hi.(cm) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Aux.F.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|-----------|---------|--------------|------------|------------|------------|------|
| Peak: |            |               |               |            | )         |         |              |            |            |            |      |
| 1     | 3870.000   | 42.8          | 74.0          | 31.2       | 210       | 0       | 33.3         | 0.0        | -32.5      | 0.0        | Н    |
| 2     | 4804       | 59.6          | 74.0          | 14.4       | 357       | 0       | 34.3         | 0.0        | -31.8      | 0.0        | Н    |
| 3     | 6000.000   | 46.1          | 74.0          | 27.9       | 352       | 0       | 34.9         | 0.0        | -30.3      | 0.0        | Н    |
| 4     | 7206       | 44.9          | 74.0          | 29.1       | 63        | 0       | 35.8         | 0.0        | -30.2      | 0.0        | Н    |
| 5     | 9608       | 46.5          | 74.0          | 27.5       | 259       | 0       | 37.2         | 0.0        | -27.9      | 0.0        | Н    |
| 6     | 12705.000  | 49.4          | 74.0          | 24.6       | 140       | 0       | 38.1         | 0.0        | -26.7      | 0.0        | Н    |
|       |            |               |               |            |           |         |              |            |            |            |      |


4804MHz AV=PK+PDCF=59.6-30.78=28.82<54



Report No.: SZEM150500298802

Page: 145 of 158

2402 Vertical -Worst case GFSK (DH5)



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Deg.(deg. | Hi.(cm) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Aux.F.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|-----------|---------|--------------|------------|------------|------------|------|
| Peak: |            |               |               |            | )         |         |              |            |            |            |      |
| 1     | 3840.000   | 42.1          | 74.0          | 31.9       | 75        |         | 33.3         | 0.0        | -32.5      | 0.0        | ٧    |
| 2     | 4804       | 61.8          | 74.0          | 12.2       | 4         |         | 34.3         | 0.0        | -31.8      | 0.0        | V    |
| 3     | 5925.000   | 46.3          | 74.0          | 27.7       | 21        |         | 34.7         | 0.0        | -30.4      | 0.0        | V    |
| 4     | 7206       | 45.4          | 74.0          | 28.6       | 123       |         | 35.8         | 0.0        | -30.2      | 0.0        | V    |
| 5     | 9608       | 46.3          | 74.0          | 27.7       | 86        |         | 37.2         | 0.0        | -27.9      | 0.0        | V    |
| 6     | 12540.000  | 48.7          | 74.0          | 25.3       | 357       |         | 38.0         | 0.0        | -26.4      | 0.0        | V    |


4804MHz AV=PK+PDCF=61.8-30.78=31.02<54



Report No.: SZEM150500298802

Page: 146 of 158

2441 Horizontal -Worst case GFSK (DH5)



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Deg.(deg. | Hi.(cm) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Aux.F.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|-----------|---------|--------------|------------|------------|------------|------|
| Peak: |            |               |               |            | )         |         |              |            |            |            |      |
| 1     | 3885.000   | 42.3          | 74.0          | 31.7       | 157       | 0       | 33.2         | 0.0        | -32.5      | 0.0        | Н    |
| 2     | 4882       | 61.6          | 74.0          | 12.4       | 353       | 0       | 34.6         | 0.0        | -31.8      | 0.0        | Н    |
| 3     | 6075.000   | 46.0          | 74.0          | 28.0       | 96        | 0       | 35.0         | 0.0        | -30.5      | 0.0        | Н    |
| 4     | 7323       | 45.2          | 74.0          | 28.8       | 75        | 0       | 35.7         | 0.0        | -30.1      | 0.0        | Н    |
| 5     | 9764       | 47.9          | 74.0          | 26.1       | 205       | 0       | 37.3         | 0.0        | -27.3      | 0.0        | Н    |
| 6     | 12645.000  | 48.7          | 74.0          | 25.3       | 15        | 0       | 38.1         | 0.0        | -26.5      | 0.0        | Н    |


4804MHz AV=PK+PDCF=61.6-30.78=30.82<54



Report No.: SZEM150500298802

Page: 147 of 158

#### 2441 Vertical -Worst case GFSK (DH5)



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Deg.(deg. | Hi.(cm) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Aux.F.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|-----------|---------|--------------|------------|------------|------------|------|
| Peak: |            |               |               |            | )         |         |              |            |            |            |      |
| 1     | 3855.000   | 42.2          | 74.0          | 31.8       | 352       |         | 33.3         | 0.0        | -32.5      | 0.0        | V    |
| 2     | 4882       | 65.7          | 74.0          | 8.3        | 359       |         | 34.6         | 0.0        | -31.8      | 0.0        | V    |
| 3     | 6000.000   | 45.9          | 74.0          | 28.1       | 320       |         | 34.9         | 0.0        | -30.3      | 0.0        | V    |
| 4     | 7323       | 45.4          | 74.0          | 28.6       | 180       |         | 35.7         | 0.0        | -30.1      | 0.0        | V    |
| 5     | 9764       | 46.8          | 74.0          | 27.2       | 131       | -       | 37.3         | 0.0        | -27.3      | 0.0        | V    |
| 6     | 11985.000  | 49.5          | 74.0          | 24.5       | 331       |         | 37.7         | 0.0        | -26.5      | 0.0        | V    |


4804MHz AV=PK+PDCF=65.7-30.78=34.92<54



Report No.: SZEM150500298802

Page: 148 of 158

#### 2480 Horizontal -Worst case GFSK (DH5)



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Deg.(deg. | Hi.(cm) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Aux.F.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|-----------|---------|--------------|------------|------------|------------|------|
| Peak: |            |               |               |            | )         |         |              |            |            |            |      |
| 1     | 3810.000   | 42.1          | 74.0          | 31.9       | 226       | 0       | 33.1         | 0.0        | -32.4      | 0.0        | Н    |
| 2     | 4960       | 58.5          | 74.0          | 15.5       | 351       | 0       | 34.6         | 0.0        | -31.7      | 0.0        | Н    |
| 3     | 6060.000   | 45.6          | 74.0          | 28.4       | 359       | 0       | 35.0         | 0.0        | -30.5      | 0.0        | Н    |
| 4     | 7440       | 45.4          | 74.0          | 28.6       | 57        | 0       | 35.8         | 0.0        | -30.0      | 0.0        | Н    |
| 5     | 9920       | 47.6          | 74.0          | 26.4       | 199       | 0       | 37.3         | 0.0        | -26.6      | 0.0        | Н    |
| 6     | 12645.000  | 49.8          | 74.0          | 24.2       | 3         | 0       | 38.1         | 0.0        | -26.5      | 0.0        | Н    |
|       |            |               |               |            |           |         |              |            |            |            |      |

4804MHz AV=PK+PDCF=58.5-30.78=27.72<54






Report No.: SZEM150500298802

Page: 149 of 158

2480 Vertical -Worst case GFSK (DH5)



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Deg.(deg. | Hi.(cm) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Aux.F.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|-----------|---------|--------------|------------|------------|------------|------|
| Peak: |            |               |               |            | )         |         |              |            |            |            |      |
| 1     | 3825.000   | 43.0          | 74.0          | 31.0       | 94        |         | 33.2         | 0.0        | -32.5      | 0.0        | ٧    |
| 2     | 4960       | 63.3          | 74.0          | 10.7       | 351       |         | 34.6         | 0.0        | -31.7      | 0.0        | V    |
| 3     | 6045.000   | 45.8          | 74.0          | 28.2       | 306       |         | 35.0         | 0.0        | -30.4      | 0.0        | V    |
| 4     | 7440       | 45.5          | 74.0          | 28.5       | 13        |         | 35.8         | 0.0        | -30.0      | 0.0        | V    |
| 5     | 9920       | 47.8          | 74.0          | 26.2       | 359       |         | 37.3         | 0.0        | -26.6      | 0.0        | V    |
| 6     | 12645.000  | 49.0          | 74.0          | 25.0       | 40        | 0       | 34.6         | 0.0        | -31.7      | 0.0        | V    |

4804MHz AV=PK+PDCF=63.3-30.78=32.52<54

#### Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
   Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Report No.: SZEM150500298802

Page: 150 of 158

3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the above measurement data were shown in the report.




Report No.: SZEM150500298802

Page: 151 of 158

#### 6.12Restricted bands around fundamental frequency

| Test Requirement: | 47 CFR Part 15C Section 15                       | 5.209 and 15.205   |                  |  |  |  |  |  |  |  |  |
|-------------------|--------------------------------------------------|--------------------|------------------|--|--|--|--|--|--|--|--|
| Test Method:      | ANSI C63.10: 2009                                | NSI C63.10: 2009   |                  |  |  |  |  |  |  |  |  |
| Test Site:        | Measurement Distance: 3m (Semi-Anechoic Chamber) |                    |                  |  |  |  |  |  |  |  |  |
| Limit:            | Frequency                                        | Limit (dBuV/m @3m) | Remark           |  |  |  |  |  |  |  |  |
|                   | 30MHz-88MHz                                      | 40.0               | Quasi-peak Value |  |  |  |  |  |  |  |  |
|                   | 88MHz-216MHz                                     | 43.5               | Quasi-peak Value |  |  |  |  |  |  |  |  |
|                   | 216MHz-960MHz                                    | 46.0               | Quasi-peak Value |  |  |  |  |  |  |  |  |
|                   | 960MHz-1GHz                                      | 54.0               | Quasi-peak Value |  |  |  |  |  |  |  |  |
|                   | Above 1GHz                                       | 54.0               | Average Value    |  |  |  |  |  |  |  |  |
|                   | Above IGHZ                                       | 74.0               | Peak Value       |  |  |  |  |  |  |  |  |
|                   |                                                  |                    |                  |  |  |  |  |  |  |  |  |
| Test Setup:       |                                                  |                    |                  |  |  |  |  |  |  |  |  |






Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz



Report No.: SZEM150500298802

Page: 152 of 158


| Test Procedure:        | <ul> <li>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> <li>g. Test the EUT in the lowest channel, the Highest channel</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>i. Repeat above procedures until all frequencies measured was complete.</li> </ul> |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Exploratory Test Mode: | Non-hopping transmitting mode with all kind of modulation and all kind of data type. Transmitting mode.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Final Test Mode:       | Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case.  Only the worst case is recorded in the report.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Instruments Used:      | Refer to section 5.10 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Test Results:          | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|                        | ·                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |



Report No.: SZEM150500298802

Page: 153 of 158

#### Test plot as follows:




| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|--------------|------------|------------|------|
| Peak: |            |               |               |            |              |            |            |      |
| 1     | 2390       | 46.6          | 74.0          | 27.4       | 32.5         | 0.0        | -20.8      | Н    |
| 2 F   | 2402.055   | 86.4          | 74.0          | -12.4      | 32.6         | 0.0        | -21.0      | Н    |
| Avg   |            |               |               |            |              |            |            |      |
| 1     | 2390       | 31.8          | 54.0          | 22.2       | 32.5         | 0.0        | -20.9      |      |
| 2 F   | 2402.055   | 74.6          | 54.0          | -20.6      | 32.6         | 0.0        | -21.1      | Н    |



Report No.: SZEM150500298802

Page: 154 of 158




| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|--------------|------------|------------|------|
| Peak: |            |               |               |            |              |            |            |      |
| 1     | 2390       | 45.7          | 74.0          | 28.3       | 32.5         | 0.0        | -20.8      | ٧    |
| 2 F   | 2401.865   | 86.5          | 74.0          | -12.5      | 32.5         | 0.0        | -20.8      | V    |
| Avg   |            |               |               |            |              |            |            |      |
| 1     | 2390       | 31.7          | 54.0          | 22.3       | 32.5         | 0.0        | -20.8      |      |
| 2 F   | 2401.865   | 74.9          | 54.0          | -20.9      | 32.6         | 0.0        | -21.0      | V    |



Report No.: SZEM150500298802

Page: 155 of 158




| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|--------------|------------|------------|------|
| Peak: |            |               |               |            |              |            |            |      |
| 1 F   | 2480.075   | 74.9          | 74.0          | -0.9       | 32.5         | 0.0        | -20.5      | Н    |
| 2     | 2483.5     | 45.1          | 74.0          | 28.9       | 32.5         | 0.0        | -20.5      | Н    |
| Avg   |            |               |               |            |              |            |            |      |
| 1 F   | 2480.075   | 65.7          | 54.0          | -11.7      | 32.5         | 0.0        | -20.5      |      |
| 2     | 2483.5     | 31.6          | 54.0          | 22.4       | 32.5         | 0.0        | -20.5      | Н    |



Report No.: SZEM150500298802

Page: 156 of 158



| Mk.   | Freq.(MHz) | Level(dBuV/m) | Limit(dBuV/m) | Margin(dB) | Ant.F.(dB/m) | Amp.G.(dB) | Cbl.L.(dB) | Pol. |
|-------|------------|---------------|---------------|------------|--------------|------------|------------|------|
| Peak: |            |               |               |            |              |            |            |      |
| 1     | 2480.125   | 73.9          | 74.0          | 0.1        | 32.5         | 0.0        | -20.5      | ٧    |
| 2     | 2483.5     | 45.1          | 74.0          | 28.9       | 32.5         | 0.0        | -20.5      | ٧    |
| Avg   |            |               |               |            |              |            |            |      |
| 1 F   | 2480.125   | 64.6          | 54.0          | -10.6      | 32.5         | 0.0        | -20.5      | V    |
| 2     | 2483.5     | 31.5          | 54.0          | 22.5       | 32.5         | 0.0        | -20.5      | V    |

#### Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: SZEM150500298802

Page: 157 of 158

### 7 Photographs - EUT Test Setup

Test model No.:NT-503

#### 7.1 Conducted Emission



#### 7.2 Radiated Emission





Report No.: SZEM150500298802

Page: 158 of 158

### 7.3 Radiated Spurious Emission



### 8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1505002988CR.

