

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	D/A Converter
<b>Model Number</b>	UD-701N
<b>FCC ID</b>	XEG-UD701N
<b>Antenna gain (Max)</b>	1.54 dBi
<b>Operation Frequency</b>	2.4G:2402MHz-2480MHz
<b>Input Rating</b>	AC 120V
<b>Classification Per Stipulated Test Standard</b>	§ 15.247(i), § 2.1093
<b>Modulation</b>	GFSK, pi/4-DQPSK , 8-DPSK
<b>Max. output power</b>	8.58 dBm(0.007211 W)
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

### Test Requirement:

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

## 1 Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## 2 Measurement Result

Antenna gain: 1.54 dBi

Mode	Frequency (MHz)	Output Power (dBm)	Target Power W/tolerance (dBm)	Max tune up power tolerance (dBm)	Max tune up power tolerance (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Verdict
GFSK	2402	5.85	5±1	6	3.98	0.001129	1	PASS
	2441	6.71	5±1	7	5.01	0.001421	1	PASS
	2480	8.58	8±1	9	7.94	0.002253	1	PASS
pi/4-DQPSK	2402	4.23	4±1	5	3.16	0.000897	1	PASS
	2441	5.84	5±1	6	3.98	0.001129	1	PASS
	2480	7.57	7±1	8	6.31	0.001789	1	PASS
8-DPSK	2402	4.50	4±1	5	3.16	0.000897	1	PASS
	2441	5.87	5±1	6	3.98	0.001129	1	PASS
	2480	7.70	7±1	8	6.31	0.001789	1	PASS

Signature:

A handwritten signature in black ink is written over a circular purple stamp. The stamp contains the text "EMTEK (HONGGUAN) CO., LTD." around the top edge and "TESTING" at the bottom. In the center of the stamp is a stylized logo consisting of a circle with a checkmark-like shape inside.

Sam Lv

Date: 2021-10-08