

# **FCC RF EXPOSURE REPORT**

**FCC ID: XEG-VLS3BT**

**Project No. : 1512C186**  
**Equipment : Powered Desktop Monitors, Powered Speakers**  
**Model : VL-S3BT, LS-M100BT**  
**Applicant : TEAC Corporation**  
**Address : 1-47 Ochiai,Tama-shi,Tokyo 206-8530,Japan**  
**According: : FCC Guidelines for Human Exposure IEEE**  
**C95.1**

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.  
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

## MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Printed	N/A	0

## TEST RESULTS

EUT :	Powered Desktop Monitors,Powered Speakers	Model Name :	VL-S3BT, LS-M100BT
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode _1Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
0	1.0000	-3.87	0.4102	0.00008165	1	Complies
0	1.0000	-1.84	0.6546	0.00013030	1	Complies
0	1.0000	-1.82	0.6577	0.00013090	1	Complies

EUT :	Powered Desktop Monitors,Powered Speakers	Model Name :	VL-S3BT, LS-M100BT
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode _3Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
0	1.0000	-4.87	0.3258	0.00006486	1	Complies
0	1.0000	-2.64	0.5445	0.00010838	1	Complies
0	1.0000	-2.74	0.5321	0.00010591	1	Complies

Note: the calculated distance is 20 cm.