



## STC Test Report

**Date :** 2015-07-21

**No. :** HM169818

**Page 1 of 73**

**Applicant** Heng Yu Electronic Manufacturing Co., Ltd.  
Room 1503-5, Nan Fung Commercial Centre, 19 Lam Lok Street,  
Kowloon Bay, Hong Kong.

**Manufacturer:** Zhuhai Heng Yu New Technology Company Limited.  
Heng Ke Campus, Jin Hai Avenue, San Zao, Zhuhai, Guang Dong,  
P.R.C.: 8109040

**Description of Sample(s):** Product: The Recreated Sinclair ZX Spectrum  
Brand Name: Elite  
Model No.: KYB-ZXSPECTRUMBT  
FCC ID: XENZXSPECTRUM

**Date Sample(s) Received:** 2015-05-07

**Date Tested:** 2015-05-21 to 2015-05-22

**Investigation Requested:** Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2014 and ANSI C63.4:2009 for FCC Certification.

**Conclusion(s):** The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

**Remark(s):** ---

  
\_\_\_\_\_  
Dr. LEE Kam Chuen  
Authorized Signatory  
ElectroMagnetic Compatibility Department  
For and on behalf of  
The Hong Kong Standards and Testing Centre Ltd.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 2 of 73

### CONTENT:

Cover	Page 1 of 73
Content	Page 2 of 73
<b><u>1.0</u></b> <b><u>General Details</u></b>	
1.1 Test Laboratory	Page 3 of 73
1.2 Equipment Under Test [EUT] Description of EUT operation	Page 3 of 73
1.3 Date of Order	Page 3 of 73
1.4 Submitted Sample	Page 3 of 73
1.5 Test Duration	Page 3 of 73
1.6 Country of Origin	Page 3 of 73
1.7 RF Module Details	Page 4 of 73
1.8 Antenna Details	Page 4 of 73
<b><u>2.0</u></b> <b><u>Technical Details</u></b>	
2.1 Investigations Requested	Page 5 of 73
2.2 Test Standards and Results Summary	Page 5 of 73
2.3 Table for Test Modes	Page 6 of 73
<b><u>3.0</u></b> <b><u>Test Results</u></b>	
3.1 Emission	Page 7 - 65 of 73
<b><u>Appendix A</u></b>	
List of Measurement Equipment	Page 66 of 73
<b><u>Appendix B</u></b>	
Ancillary Equipment	Page 67 of 73
<b><u>Appendix C</u></b>	
Photographs	Page 68 - 73 of 73

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

**Date : 2015-07-21**

**Page 3 of 73**

**No. : HM169818**

### **1.0 General Details**

#### **1.1 Test Laboratory**

The Hong Kong Standards and Testing Centre Ltd.  
EMC Laboratory  
10 Dai Wang Street, Taipo Industrial Estate  
New Territories, Hong Kong

#### **1.2 Equipment Under Test [EUT] Description of Sample(s)**

Product: The Recreated Sinclair ZX Spectrum  
Manufacturer: Zhuhai Heng Yu New Technology Company Limited.  
Heng Ke Campus, Jin Hai Avenue, San Zao, Zhuhai, Guang Dong,  
P.R.C.: 8109040  
Brand Name: Elite  
Model Number: KYB-ZXSPECTRUMBT  
Input Voltage: 5.0Vd.c. (powered by USB)  
2.4Vd.c. ("AA" Size Rechargeable Battery x 2)

##### **1.2.1 Description of EUT Operation**

The Equipment Under Test (EUT) is a bluetooth keyboard of Heng Yu Electronic Manufacturing Co., Ltd.. The RF signal was modulation by IC; and type of modulation use is frequency hopping spread spectrum Modulation.

#### **1.3 Date of Order**

2015-05-07

#### **1.4 Submitted Sample(s):**

1 Sample

#### **1.5 Test Duration**

2015-05-21 to 2015-05-22

#### **1.6 Country of Origin**

China

The Hong Kong Standards and Testing Centre Limited  
10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 4 of 73

### 1.7 RF Module Details

Module Model Number: BM52HIDBR  
Module FCC ID: N/A  
Module Transmission Type: Bluetooth V3.0  
Modulation: FHSS (GFSK /  $\pi/4$ -DQPSK / 8DPSK)  
Data Rates:  
1Mbps: GFSK  
2 Mbps:  $\pi/4$ -DQPSK  
3 Mbps: 8DPSK  
Frequency Range: 2400-2483.5MHz  
Carrier Frequencies: 2402MHz – 2480MHz

Module Specification (specification provided by manufacturer)

### 1.8 Antenna Details

Antenna Type: PCB antenna  
Antenna Length: 30 mm  
Antenna Gain: -2dBi

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 5 of 73

### 2.0 Technical Details

#### 2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2014 Regulations and ANSI C63.4:2009 for FCC Certification.

#### 2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Fail	N/A
Output Power of Fundamental Emissions*	FCC 47CFR 15.247(b)(1)	ANSI C63.4:2009	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
RF Conducted Spurious Emission*	FCC 47CFR 15.247(d)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Spurious Emissions	FCC 47CFR 15.209	ANSI C63.4:2009	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
AC Mains Conducted Emissions	FCC 47CFR 15.207	ANSI C63.4:2009	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Number of Operating Channel	FCC 47CFR 15.247 (b)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Band-edge compliance of Conducted Emission*	FCC 47CFR 15.247(d)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Pseudorandom Hopping Algorithm	FCC 47CFR 15.247(a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Time of Occupancy*	FCC 47CFR 15.247(a)(1)(iii)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20dB Bandwidth*	FCC 47CFR 15.247(a)(2)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hopping Channel Separation*	FCC 47CFR 15.247(a)(1)	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

\*Remark: The conducted measurements were performed with a temporary antenna connector soldered to the RF Output of the EUT.

Note: N/A – Not Applicable

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

Page 6 of 73

No. : HM169818

### 2.3 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate in the table below is the worst case rate with respect to the specific test item.

Investigation has been done on all the possible configurations for searching the worst cases.

The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Max. Conducted Output Power	GFSK / $\pi/4$ -DQPSK / 8DPSK	1MBps / 2MBps / 3MBps
Hopping Channel Separation	GFSK / $\pi/4$ -DQPSK / 8DPSK	1MBps / 2MBps / 3MBps
Number of Hopping Frequency	8DPSK	3MBps
Dwell Time	DH1 / DH3 / DH5	3MBps
Radiated Emissions Below 1GHz	GFSK	1MBps
Radiated Emission Above 1GHz	GFSK	1MBps
Band Edge Emissions	GFSK / $\pi/4$ -DQPSK / 8DPSK	1MBps / 2MBps / 3MBps

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 7 of 73

### 3.0 Test Results

#### 3.1 Emission

##### 3.1.1 Maximum Peak Output Power

Test Requirement:	FCC 47CFR 15.247(b)(1)
Test Method:	N/A
Test Date:	2015-05-22
Mode of Operation:	Tx mode


#### **Test Method:**

The RF output of the EUT was connected to the spectrum analyzer. All the attenuation or cable loss will be added to the measured maximum output power. The results are recorded in dBm.

#### **Spectrum Analyzer Setting:**

RBW = 3 MHz, VBW = 3MHz, Sweep = Auto, Span = 10MHz  
Detector = Peak, Trace = Max. hold

#### **Test Setup:**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

Page 8 of 73

No. : HM169818

### Limits for Peak Output Power of Fundamental & Harmonics Emissions [FCC 47CFR 15.247]:

The maximum peak output power shall not exceeded the following limits: For frequency hopping systems employing at least 75 hopping channels: 1 Watt For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts For Digital Transmission systems in 2400-2483.5 MHz Band: 1 Watt
--

### Results of Bluetooth Communication mode (GFSK) (Fundamental Power): Pass Maximum conducted output power

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.00157

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.00175

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.00149

### Results of Bluetooth Communication mode ( $\pi/4$ -DQPSK) (Fundamental Power): Pass Maximum conducted output power

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.00118

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2442	0.00113

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.00126

### Results of Bluetooth Communication mode (8 DPSK) (Fundamental Power): Pass Maximum conducted output power

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.00116

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2442	0.00117

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.00120

Limit: 0.125W (125mW)

Calculated measurement uncertainty	:	30MHz to 1GHz	1.7dB
		1GHz to 18GHz	1.7dB

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## STC Test Report

**Date : 2015-07-21**

**No. : HM169818**

**Page 9 of 73**

### **3.1.2 Radiated Spurious Emissions**

Test Requirement: FCC 47CFR 15.209  
Test Method: ANSI C63.4:2009  
Test Date: 2015-05-22  
Mode of Operation: Bluetooth communication mode

#### **Test Method:**

The sample was placed 0.8m above the ground plane of semi-anechoic Chamber\*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

\*: Semi-anechoic chamber located on the STC (Dongguan) Company Ltd. 68 Fumin Nan Road, Dalang, Dongguan, Guangdong, PRC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 629686.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21


No. : HM169818

Page 10 of 73

### Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)	RBW: 10kHz
	VBW: 30kHz
	Sweep: Auto
	Span: Fully capture the emissions being measured
	Trace: Max. hold
30MHz – 1GHz (QP)	RBW: 120kHz
	VBW: 120kHz
	Sweep: Auto
	Span: Fully capture the emissions being measured
	Trace: Max. hold
Above 1GHz (Pk & Av)	RBW: 3MHz
	VBW: 3MHz
	Sweep: Auto
	Span: Fully capture the emissions being measured
	Trace: Max. hold

### Test Setup:



- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

Page 11 of 73

No. : HM169818

### Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [ $\mu$ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

### Result of Bluetooth communication mode (2402.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
MHz	Level	Factor	Strength	Strength	uV/m	Polarity
	dBuV	dB/m	dBuV/m	uV/m	uV/m	
<b>Emissions detected are more than 20 dB below the FCC Limits</b>						

### Result of Bluetooth communication mode (2402.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
MHz	Level	Factor	Strength	Strength	uV/m	Polarity
	dBuV	dB/m	dBuV/m	uV/m	uV/m	
<b>Emissions detected are more than 20 dB below the FCC Limits</b>						

### Result of Bluetooth communication mode (2402.0 MHz) (GFSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
MHz	Level	Factor	Strength	Strength	uV/m	Polarity
	dBuV	dB/m	dBuV/m	uV/m	uV/m	
<b>Emissions detected are more than 20 dB below the FCC Limits</b>						

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 12 of 73

No. : HM169818

### Result of Bluetooth communication mode (2402.0 MHz) (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4804.0	11.6	32.1	43.7	74.0	30.3	Horizontal
7206.0	7.8	38.6	46.4	77.6	31.2	Horizontal

### Result of Bluetooth communication mode (2402.0 MHz) (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4804.0	7.1	32.1	39.2	54.0	14.8	Horizontal
7206.0	2.3	38.6	40.9	62.3	21.4	Horizontal

### Result of Bluetooth communication mode (2441.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) (GFSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 13 of 73

No. : HM169818

### Result of Bluetooth communication mode (2441.0 MHz) (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB $\mu$ V	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Limit @3m dB $\mu$ V/m	Margin dB $\mu$ V/m	E-Field Polarity
4882.0	10.8	32.1	42.9	74.0	31.1	Horizontal
7323.0	6.6	38.6	45.2	74.0	28.8	Horizontal

### Result of Bluetooth communication mode (2441.0 MHz) (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB $\mu$ V	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Limit @3m dB $\mu$ V/m	Margin dB $\mu$ V/m	E-Field Polarity
4882.0	7.2	32.1	39.3	54.0	14.7	Horizontal
7323.0	2.3	38.6	40.9	54.0	13.1	Horizontal

### Result of Bluetooth communication mode (2480.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) (GFSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) (GFSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 14 of 73

No. : HM169818

### Result of Bluetooth communication mode (2480.0 MHz) (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4960.0	11.9	32.0	43.9	74.0	30.1	Horizontal
7440.0	7.3	38.6	45.9	74.0	28.1	Horizontal

### Result of Bluetooth communication mode (2480.0 MHz) (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4960.0	8.3	32.0	40.3	54.0	13.7	Horizontal
7440.0	2.9	38.6	41.5	54.0	12.5	Horizontal

### Result of Bluetooth communication mode Band Edge measurement (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
2399.0	17.5	27.6	45.1	46.3	1.2	Horizontal
2484.1	15.0	27.5	42.5	74.0	31.5	Horizontal

### Result of Bluetooth communication mode Band Edge measurement (GFSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
2399.0	10.9	27.6	38.5	38.9	0.4	Horizontal
2484.1	10.6	27.5	38.1	54.0	15.9	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 15 of 73

No. : HM169818

### Result of Bluetooth communication mode (2402.0 MHz) ( $\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2402.0 MHz) ( $\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2402.0 MHz) ( $\pi/4$ -DQPSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2402.0 MHz) ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4804.0	10.2	32.1	42.3	74.0	31.7	Horizontal
7206.0	6.5	38.6	45.1	76.7	31.6	Horizontal

### Result of Bluetooth communication mode (2402.0 MHz) ( $\pi/4$ -DQPSK mode) (1 – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4804.0	7.0	32.1	39.1	54.0	14.9	Horizontal
7206.0	1.7	38.6	40.3	61.1	20.8	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 16 of 73

No. : HM169818

### Result of Bluetooth communication mode (2441.0 MHz) ( $\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) ( $\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) ( $\pi/4$ -DQPSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4882.0	11.0	32.1	43.1	74.0	30.9	Horizontal
7323.0	5.7	38.6	44.3	74.0	29.7	Horizontal

### Result of Bluetooth communication mode (2441.0 MHz) ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4882.0	7.6	32.1	39.7	54.0	14.3	Horizontal
7323.0	1.9	38.6	40.5	54.0	13.5	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





# STC Test Report

Date : 2015-07-21

Page 17 of 73

No. : HM169818

### Result of Bluetooth communication mode (2480.0 MHz) ( $\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) ( $\pi/4$ -DQPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) ( $\pi/4$ -DQPSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	uV/m	uV/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4960.0	11.3	32.0	43.3	74.0	30.7	Horizontal
7440.0	4.6	38.6	43.2	74.0	30.8	Horizontal

### Result of Bluetooth communication mode (2480.0 MHz) ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4960.0	7.5	32.0	39.5	54.0	14.5	Horizontal
7440.0	1.7	38.6	40.3	54.0	13.7	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 18 of 73

No. : HM169818

**Result of Bluetooth communication mode Band Edge measurement ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass**

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
2399.0	18.5	27.6	46.1	76.7	30.6	Horizontal
2485.0	16.5	27.5	44.0	74.0	30.0	Horizontal

**Result of Bluetooth communication mode Band Edge measurement ( $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass**

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
2399.0	11.7	27.6	39.3	61.1	21.8	Horizontal
2485.0	12.0	27.5	39.5	54.0	14.5	Horizontal

**Result of Bluetooth communication mode (2402.0 MHz) (8DPSK mode) (9kHz – 30MHz): Pass**

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

**Result of Bluetooth communication mode (2402.0 MHz) (8DPSK mode) (9kHz – 30MHz): Pass**

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

**Result of Bluetooth communication mode (2402.0 MHz) (8DPSK mode) (30MHz – 1GHz): Pass**

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured Level	Correction Factor	Field Strength	Field Strength	Limit	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 19 of 73

No. : HM169818

### Result of Bluetooth communication mode (2402.0 MHz) (8DPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4804.0	11.4	32.1	43.5	74.0	30.5	Horizontal
7206.0	4.7	38.6	43.3	76.1	32.8	Horizontal

### Result of Bluetooth communication mode (2402.0 MHz) (8DPSK mode) (1 – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4804.0	7.0	32.1	39.1	54.0	14.9	Horizontal
7206.0	1.9	38.6	40.5	59.5	19.0	Horizontal

### Result of Bluetooth communication mode (2441.0 MHz) (8DPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) (8DPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2441.0 MHz) (8DPSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 20 of 73

No. : HM169818

### Result of Bluetooth communication mode (2441.0 MHz) (8DPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4882.0	11.8	32.1	43.9	74.0	30.1	Horizontal
7323.0	5.5	38.6	44.1	74.0	29.9	Horizontal

### Result of Bluetooth communication mode (2441.0 MHz) (8DPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4882.0	7.6	32.1	39.7	54.0	14.3	Horizontal
7323.0	2.6	38.6	41.2	54.0	12.8	Horizontal

### Result of Bluetooth communication mode (2480.0 MHz) (8DPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) (8DPSK mode) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

### Result of Bluetooth communication mode (2480.0 MHz) (8DPSK mode) (30MHz – 1GHz): Pass

Field Strength of Spurious Emissions						
Quasi-Peak Value						
Frequency	Measured	Correction	Field	Field	Limit	E-Field
	Level	Factor	Strength	Strength		Polarity
MHz	dBuV	dB/m	dBuV/m	$\mu$ V/m	$\mu$ V/m	
Emissions detected are more than 20 dB below the FCC Limits						

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 21 of 73

No. : HM169818

### Result of Bluetooth communication mode (2480.0 MHz) (8DPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4960.0	12.1	32.0	44.1	74.0	29.9	Horizontal
7440.0	4.6	38.6	43.2	74.0	30.8	Horizontal

### Result of Bluetooth communication mode (2480.0 MHz) (8DPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
4960.0	7.5	32.0	39.5	54.0	14.5	Horizontal
7440.0	2.9	38.6	41.5	54.0	12.5	Horizontal

### Result of Bluetooth communication mode Band Edge measurement (8DPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Peak Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
2398.0	18.9	27.6	46.5	76.1	29.6	Horizontal
2485.0	16.0	27.5	43.5	74.0	30.5	Horizontal

### Result of Bluetooth communication mode Band Edge measurement (8DPSK $\pi/4$ -DQPSK mode) (1GHz – 18GHz): Pass

Field Strength of Spurious Emissions						
Average Value						
Frequency	Measured	Correction	Field	Limit	Margin	E-Field
	Level @ 3m	Factor	Strength	@ 3m		Polarity
MHz	dB $\mu$ V	dB/m	dB $\mu$ V/m	dB $\mu$ V/m	dB $\mu$ V/m	
2398.0	11.5	27.6	39.1	59.5	20.4	Horizontal
2485.0	12.2	27.5	39.7	54.0	14.3	Horizontal

Remarks:

\* Denotes restricted band of operation.

Measurements were made using a peak detector. Any emission less than 1000MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty: (9kHz – 30MHz): 2.4dB

(30MHz - 1GHz): 4.6dB

(1GHz - 26GHz): 4.4dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 22 of 73

No. : HM169818

### Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [ $\mu$ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

### Result of Bluetooth communication mode (30MHz – 1GHz): Pass

Radiated Emissions						
Quasi-Peak Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m	
54.9	1.4	9.5	10.9	40.0	29.1	Vertical
121.4	2.1	9.3	11.4	43.5	32.1	Vertical
200.3	1.7	13.6	15.3	43.5	28.2	Horizontal
477.6	0.9	22.5	23.4	46.0	22.6	Horizontal
531.1	2.1	23.8	25.9	46.0	20.1	Horizontal
679.9	1.3	27	28.3	46.0	17.7	Horizontal

### Result of On mode connected to PC with charging function (30MHz – 1GHz): Pass

Radiated Emissions						
Quasi-Peak Value						
Frequency	Measured Level @ 3m	Correction Factor	Field Strength	Limit @ 3m	Margin	E-Field Polarity
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dBuV/m	
66.1	3.1	9.2	12.3	40.0	27.7	Vertical
130.2	1.2	8.8	10.0	43.5	33.5	Vertical
211.4	4.2	14.2	18.4	43.5	25.1	Vertical
541.3	1.1	24.1	25.2	46.0	20.8	Vertical
654.7	2.3	25.7	28.0	46.0	18.0	Vertical
861.3	2.1	29.2	31.3	46.0	14.7	Horizontal

### Remarks:

Calculated measurement uncertainty (30MHz – 1GHz): 4.6dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 23 of 73


### 3.1.3 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.207
Test Method:	ANSI C63.4:2009
Test Date:	2015-05-21
Mode of Operation:	On mode connected to PC with charging function
Test Voltage:	120V a.c., 60Hz

#### Test Method:

The test was performed in accordance with ANSI C63.4: 2009, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

#### Test Setup:



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 24 of 73

## Limit for Conducted Emissions (FCC 47 CFR 15.207):


Frequency Range [MHz]	Quasi-Peak Limits [dB $\mu$ V]	Average [dB $\mu$ V]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

\* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

## Results of On mode connected to PC with charging function - Live: PASS

Please refer to the following diagram for individual results.



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## STC Test Report

Date : 2015-07-21

Page 25 of 73

No. : HM169818

### Results of On mode connected to PC with charging function - Live: PASS

Conductor	Frequency	Quasi-peak		Average	
		Level	Limit	Level	Limit
Live or Neutral	MHz	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V
Live	0.165	51.2	65.0	31.5	55.0
Live	0.255	43.1	62.0	-*-	-*-
Live	0.430	-*-	-*-	20.9	47.0
Live	0.455	34.6	57.0	20.9	47.0
Live	1.035	-*-	-*-	17.4	46.0
Live	1.075	23.8	56.0	-*-	-*-
Live	1.530	21.8	56.0	15.7	46.0
Live	2.390	-*-	-*-	16.5	46.0
Live	3.270	23.1	56.0	-*-	-*-
Live	4.095	19.3	56.0	-*-	-*-
Live	4.540	-*-	-*-	15.3	46.0
Live	9.725	-*-	-*-	16.6	50.0
Live	10.090	23.6	60.0	-*-	-*-
Live	17.315	25.9	60.0	-*-	-*-
Live	17.415	-*-	-*-	20.2	50.0
Live	18.435	28.3	60.0	-*-	-*-
Live	26.625	-*-	-*-	7.1	50.0

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 26 of 73

## Results of On mode connected to PC with charging function - Neutral: PASS

Please refer to the following diagram for individual results.



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

Page 27 of 73

No. : HM169818

### Results of On mode connected to PC with charging function - Neutral: PASS

Conductor	Frequency	Quasi-peak		Average	
		Level	Limit	Level	Limit
Live or Neutral	MHz	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V	dB $\mu$ V
Neutral	0.150	51.9	66.0	32.8	56.0
Neutral	0.255	43.4	62.0	-*-	-*-
Neutral	0.260	-*-	-*-	25.2	51.0
Neutral	0.445	-*-	-*-	22.5	47.0
Neutral	0.460	33.4	57.0	-*-	-*-
Neutral	0.745	18.0	56.0	-*-	-*-
Neutral	1.120	-*-	-*-	11.0	46.0
Neutral	1.970	23.1	56.0	-*-	-*-
Neutral	2.050	-*-	-*-	17.9	46.0
Neutral	2.430	-*-	-*-	17.5	46.0
Neutral	2.560	21.0	56.0	-*-	-*-
Neutral	3.805	-*-	-*-	16.1	46.0
Neutral	4.285	19.8	56.0	-*-	-*-
Neutral	10.060	-*-	-*-	14.1	50.0
Neutral	10.385	19.8	60.0	-*-	-*-
Neutral	17.470	26.1	60.0	20.0	50.0
Neutral	17.670	26.4	60.0	-*-	-*-
Neutral	17.730	-*-	-*-	19.9	50.0

#### Remarks:

Calculated measurement uncertainty (0.15MHz – 30MHz): 3.25dB

-\*- Emission(s) that is far below the corresponding limit line.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

**Date : 2015-07-21**

**No. : HM169818**

**Page 28 of 73**

### **3.1.4 20dB Bandwidth Measurement**

Test Requirement: FCC 47CFR 15.247(a)(1)  
Test Method: ANSI C63.4:2009  
Test Date: 2015-05-22  
Mode of Operation: Bluetooth communication mode

#### **Remark:**

The result has been done on all the possible configurations for searching the worst cases.

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

#### **Test Setup:**

As Test Setup of clause 3.1.1 in this test report.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report


Date : 2015-07-21  
No. : HM169818

Page 29 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.15	Within 2400-2483.5

## (Lowest Operating Frequency) - (GFSK)

	Marker 1 [T1 ndB]	RBW	100 kHz	RF Att	30 dB
Ref Lvl	ndB	20.00 dB	VBW	300 kHz	
127 dBmV	BW	1.14829659 MHz	SWT	5 ms	Unit
					dBmV



Date: 22.MAY.2015 14:51:38




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 30 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.14	Within 2400-2483.5

## (Middle Operating Frequency) - (GFSK)



Date: 22.MAY.2015 14:31:55



# STC Test Report


Date : 2015-07-21  
 No. : HM169818

Page 31 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.14	Within 2400-2483.5

## (Highest Operating Frequency) - (GFSK)

Marker 1 [T1 ndB] RBW 100 kHz RF Att 30 dB  
 Ref Lvl 127 dBV ndB 20.00 dB VBW 300 kHz  
 BW 1.14228457 MHz SWT 5 ms Unit dBV



Date: 22.MAY.2015 15:34:50




# STC Test Report

Date : 2015-07-21  
 No. : HM169818

Page 32 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.41	Within 2400-2483.5

**(Lowest Operating Frequency) - ( $\pi/4$  DQPSK)**



Date: 22.MAY.2015 14:53:06






# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 33 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.42	Within 2400-2483.5

## (Middle Operating Frequency) - ( $\pi/4$ DQPSK)



Date: 22.MAY.2015 15:16:55




# STC Test Report

Date : 2015-07-21  
 No. : HM169818

Page 34 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.40	Within 2400-2483.5

**(Highest Operating Frequency) - ( $\pi/4$  DQPSK)**



Date: 22.MAY.2015 15:18:53




# STC Test Report

Date : 2015-07-21  
 No. : HM169818

Page 35 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.41	Within 2400-2483.5

## (Lowest Operating Frequency) - (8DPSK)



Date: 22.MAY.2015 15:09:22




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 36 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.41	Within 2400-2483.5

## (Middle Operating Frequency) - (8DPSK)



Date: 22.MAY.2015 15:10:46




# STC Test Report

Date : 2015-07-21  
 No. : HM169818

Page 37 of 73

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.40	Within 2400-2483.5

## (Highest Operating Frequency) - (8DPSK)





## STC Test Report

**Date : 2015-07-21**

**Page 38 of 73**

**No. : HM169818**

### **Channel Centre Frequency**

#### **Requirements:**

Frequency hopping system in the 2400-2483.5MHz band shall use at least 79 (Channel 0 to 78) non-overlapping channels.

The EUT operates in according with the Bluetooth system specification within the 2400 - 2483.5 MHz frequency band.

RF channels for Bluetooth systems are spaced 1 MHz and are ordered in channel number k. In order to comply with out-of-band regulations, a lower frequency guard band of 2.0 MHz and a higher frequency guard band of 3.5MHz is used.

The operating frequencies of each channel are as follows:

First RF channel start from 2400MHz + 2MHz guard band = 2402MHz

Frequency of RF Channel = 2402+k MHz, k = 0, ..., 78 (Channel separation = 1MHz)

### **Hopping Channel Separation**

#### **Requirements:**

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### **Limit:**

The measured minimum bandwidth \* 2/3 = 1.42MHz \* 2/3 = 947kHz

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 39 of 73

Channel separation = 1.01MHz (GFSK)

Channel 0 – Channel 1, Pass



Date: 22.MAY.2015 15:50:05

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 40 of 73

Channel separation = 1.01MHz (GFSK)

Channel 38 – Channel 40, Pass



Date: 22.MAY.2015 15:48:22

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.






# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 41 of 73

Channel separation = 1.01MHz (GFSK)

Channel 78 – Channel 79, Pass



Date: 22.MAY.2015 15:38:51




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 42 of 73

Channel separation = 1.01MHz ( $\pi/4$  DQPSK)

Channel 0 – Channel 1, Pass



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 43 of 73

Channel separation = 1.01MHz ( $\pi/4$  DQPSK)

Channel 39 – Channel 40, Pass



Date: 22.MAY.2015 15:44:31

The Hong Kong Standards and Testing Centre Limited  
10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 44 of 73

Channel separation = 1.01MHz ( $\pi/4$  DQPSK)

Channel 78 – Channel 79, Pass



Date: 22.MAY.2015 15:40:12



# STC Test Report


Date : 2015-07-21  
No. : HM169818

Page 45 of 73

## Channel separation = 1.01MHz (8DPSK)

Channel 0 – Channel 1, Pass

Ref Lvl	127 dBV	Marker 1 [T1]	98.85 dBV	RBW	100 kHz	RF Att	30 dB
			2.40198196 GHz	VBW	300 kHz		
				SWT	5 ms	Unit	dBV



Date: 22.MAY.2015 15:53:55

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 46 of 73

Channel separation = 1.01MHz (8DPSK)

Channel 39 – Channel 40, Pass



Date: 22.MAY.2015 15:43:16

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 47 of 73

Channel separation = 1.01MHz (8DPSK)

Channel 78 – Channel 79, Pass



Date: 22.MAY.2015 15:41:23

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 48 of 73

## Band-edge Compliance of RF Emissions – Lowest (GFSK) (50.7dB reduction at lower band edge)



Date: 22.MAY.2015 16:11:39

The Hong Kong Standards and Testing Centre Limited  
10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.






# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 49 of 73

## Band-edge Compliance of RF Emissions – Highest (GFSK) (58.0dB reduction at upper band edge)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 50 of 73

## Band-edge Compliance of RF Emissions – Lowest ( $\pi/4$ DQPSK) (50.0dB reduction at lower band edge)



Date: 22.MAY.2015 16:13:30




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 51 of 73

## Band-edge Compliance of RF Emissions – Highest ( $\pi/4$ DQPSK) (57.6dB reduction at upper band edge)



Date: 22.MAY.2015 16:29:02




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 52 of 73

## Band-edge Compliance of RF Emissions – Lowest (8DPSK) (51.7dB reduction at lower band edge)



Date: 22.MAY.2015 16:16:38




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 53 of 73

## Band-edge Compliance of RF Emissions – Highest (8DPSK) (57.4dB reduction at upper band edge)



Date: 22.MAY.2015 16:32:12



## STC Test Report

**Date : 2015-07-21**

**No. : HM169818**

**Page 54 of 73**

### **Antenna Requirement**

**Test Requirements: § 15.203**

### **Test Specification:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Test Results:**

The EUT has 1 [Inverted-F Antenna (PCB layout)] which is permanently attached to the main unit and attached on PCB board, the antenna gain =-2.0dBi. All component install on inside of EUT. User unable to remove or changed the Antenna.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## **STC Test Report**

**Date : 2015-07-21**

**No. : HM169818**

**Page 55 of 73**

### **Pseudorandom Hopping Algorithm**

#### **Requirements:**

The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally by the transmitter.

### **EUT Pseudorandom Hopping Algorithm**

The EUT is a Bluetooth device, the Pseudo-random hopping pattern; hopping characteristics and algorithm are based on the Bluetooth specification.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report

Date : 2015-07-21

Page 56 of 73

No. : HM169818

## Occupancy Time (Dwell time)

### Requirements:


The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channel employed.  
No requirements for Digital Transmission System.

**Dwell Time = Pulse Duration \* hop rate / number of channel \* observation duration**

**Observed duration: 0.4s x79 = 31.6s**

### Measurement Data:

**Channel Occupied in 8DPSK: 79 of 79 Channel**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





# STC Test Report

Date : 2015-07-21  
No. : HM169818


Page 57 of 73

## DH5 Packet:

DH5 Packet permit maximum  $1600/79/6 = 3.37$  hops per second in each channel (5 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds

**Fig. A**  
**[Pulse duration of Lowest Channel]**

**Pulse duration = 2.896ms**



Date: 22.MAY.2015 17:00:14




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 58 of 73

**Fig. B**  
**[Pulse duration of Middle Channel]**  
**Pulse duration = 2.896ms**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 59 of 73

**Fig. C**  
**[Pulse duration of Highest Channel]**  
**Pulse duration = 2.896ms**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



# STC Test Report


Date : 2015-07-21  
No. : HM169818

Page 60 of 73

### DH3 Packet:

DH3 Packet permit maximum  $1600/79/4 = 5.06$  hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds

**Fig. D**  
**[Pulse duration of Lowest Channel]**  
**Pulse duration = 1.660ms**



Date: 22.MAY.2015 17:04:31




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 61 of 73

**Fig. E**  
**[Pulse duration of Middle Channel]**  
**Pulse duration = 1.660ms**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 62 of 73

**Fig. F**  
**[Pulse duration of Highest Channel]**  
**Pulse duration = 1.660ms**



Date: 22.MAY.2015 17:02:08



# STC Test Report


Date : 2015-07-21  
No. : HM169818

Page 63 of 73

## DH1 Packet:

DH1 Packet permit maximum  $1600/79/2 = 10.12$  hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds

**Fig. G**  
**[Pulse duration of Lowest Channel]**  
**Pulse duration = 0.391ms**



Date: 22.MAY.2015 17:05:56




# STC Test Report

Date : 2015-07-21  
No. : HM169818

Page 64 of 73

**Fig. H**  
**[Pulse duration of Middle Channel]**  
**Pulse duration = 0.391ms**



Date: 22.MAY.2015 17:06:30






# STC Test Report

Date : 2015-07-21

Page 65 of 73

No. : HM169818

**Fig. I**  
**[Pulse duration of Highest Channel]**  
**Pulse duration = 0.391ms**



Date: 22.MAY.2015 17:07:04

**Time of occupancy (Dwell Time):**

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Results
DH5	2402	2.896	0.308	0.400	Complies
DH5	2442	2.896	0.308	0.400	Complies
DH5	2480	2.916	0.308	0.400	Complies
DH3	2402	1.660	0.267	0.400	Complies
DH3	2442	1.660	0.267	0.400	Complies
DH3	2480	1.660	0.267	0.400	Complies
DH1	2402	0.391	0.125	0.400	Complies
DH1	2442	0.391	0.125	0.400	Complies
DH1	2480	0.391	0.125	0.400	Complies

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 66 of 73

### Appendix A

#### List of Measurement Equipment

### LIST OF MEASUREMENT EQUIPMENT

#### Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM299	DOUBLE-RIDGED WAVEGUIDE HORN ANTENNA	ETS-LINDGREN	3115	00114120	2014/01/15	2016/01/15
EM300	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-09	00130130	2014/01/23	2016/01/23
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM216	MINI MAST SYSTEM	EMCO	2075	00026842	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3	--	2014/09/29	2015/09/29
EM320	BICONILOG ANTENNA	ETS-LINDGREN	3142D	00094856	2014/08/06	2016/08/06
EM229	EMI TEST RECEIVER	R&S	ESIB40	100248	2014/05/26	2015/05/26
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	2014/01/15	2016/01/15

#### Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM119	LISN	R & S	ESH3-Z5	0831.5518.52	2014/05/26	2015/05/26
EM181	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB7	100072	2014/05/26	2015/05/26
EM179	IMPULSE LIMITER	ROHDE & SCHWARZ	ESH3-Z2	357-8810.52/54	2015/01/14	2016/01/14
EM154	SHIELDING ROOM	SIEMENS MATSUSHITA COMPONENTS	N/A	803-740-057-99A	2012/02/03	2017/02/03

#### Remarks:-

CM Corrective Maintenance

N/A Not Applicable or Not Available

TBD To Be Determined

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@hkstc.org Website: www.stc-group.org

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 67 of 73

### Appendix B

#### Ancillary Equipment

ITEM NO.	DESCRIPTION	MODEL NO.	FCC ID	REMARK
1	LENOVO COMPUTER	M2B	N/A	N/A
2	LENOVO KEYBOARD	KU-0225	N/A	1.8M SHIELDED COILED CABLE CONNECTED TO THE COMPUTER
3	DELL MOUSE	N/A	N/A	2.4M UNSHIELDED CABLE CONNECTED TO THE COMPUTER
4	PHILIPS MONITOR	170S7FB/00	N/A	N/A

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 68 of 73

### Appendix C

#### Photographs of EUT

**Front View of the product**



**Back View of the product**



**Rear View of the product (Left)**



**Rear View of the product (Right)**



**Top View of the product**



**Bottom View of the product**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report


Date : 2015-07-21

Page 69 of 73


No. : HM169818

### Photographs of EUT


**Inner Circuit Top View – All PCBs**





**Inner Circuit Top View**



**Inner Circuit Bottom View - - All PCBs**



**Inner Circuit Bottom View**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report


Date : 2015-07-21

No. : HM169818

Page 70 of 73

Photographs of EUT

Measurement of Radiated Emission Test Set Up



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## STC Test Report


Date : 2015-07-21

No. : HM169818

Page 71 of 73

### Photographs of EUT

Measurement of Radiated Emission Test Set Up (30MHz – 1GHz)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 72 of 73

### Photographs of EUT

**Measurement of Radiated Emission Test Set Up**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## STC Test Report

Date : 2015-07-21

No. : HM169818

Page 73 of 73

### Photographs of EUT

**Measurement of Conducted Emission Test Set Up**



**\*\*\*\*\* End of Test Report \*\*\*\*\***

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@hkstc.org](mailto:hkstc@hkstc.org) Website: [www.stc-group.org](http://www.stc-group.org)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## **STC Test Report**

### **Conditions of Issuance of Test Reports**

1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").
2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
4. The Report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
5. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
6. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
7. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
9. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
10. Issuance records of the Report are available on the internet at [www.stc-group.org](http://www.stc-group.org). Further enquiry of validity or verification of the Reports should be addressed to the Company.