



Emissions Test Report

EUT Name: USB Wireless Audio Transmitter

Model No.: Stealth600P-MAX-TX

CFR 47 Part 15.247: 2021 and RSS 247: 2017

Prepared for:

Voyetra Turtle Beach, Inc.
44 South Broadway, 4th Floor
White Plains NY 10601 USA

Prepared by:

Bureau Veritas Consumer Products Services, Inc.
775 Montague Expressway,
Milpitas, CA 95035
Tel: (408) 526-1188

Report/Issue Date: May 8, 2022
Revision Number 0
Report Number: SL22030401-CCP-201_6PPlus_TX_RF

Revisions

Revision No.	Date MM/DD/YYYY	Reason for Change	Author
0	05/08/2022	Original Document	N/A

Note: Latest revision report will replace all previous reports.

Statement of Compliance

Manufacturer: Voyetra Turtle Beach, Inc.
44 South Broadway, 4th Floor
White Plains NY 10601 USA

Requester / Applicant: Tim Blaney
(530) 277-3482

Name of Equipment: USB Wireless Audio Transmitter
Model No's: Stealth600P-MAX-TX
Type of Equipment: Intentional Radiator
Application of Regulations: CFR 47 Part 15.247: 2021 and RSS 247: 2017
Test Dates: April 11, 2022 to May 6, 2022

Guidance Documents:

Emissions: ANSI C63.10-2013, KDB 558074 D01 DTS Measurement Guidance v05r02,

Test Methods:

Emissions: ANSI C63.10-2013, KDB 558074 D01 DTS Measurement Guidance v05r02,

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

Abhijit Patibandla

Test Engineer

Date May 8, 2022

Suresh Kondapalli

Reviewer Signatory

Date May 8, 2022



Testing Cert #2742-01

US1109

4842D

Table of Contents

1	Executive Summary	7
1.1	Scope	7
1.2	Purpose	7
1.3	Summary of Test Results	7
1.4	Special Accessories	7
1.5	Equipment Modifications	7
2	Laboratory Information	8
2.1	Accreditations & Endorsements	8
2.1.1	US Federal Communications Commission	8
2.1.2	NIST / A2LA	8
2.1.3	Canada	8
2.1.4	Japan – VCCI	8
2.1.5	Acceptance by Mutual Recognition Arrangement	8
2.2	Test Facilities	9
2.2.1	Emission Test Facility	9
2.3	Measurement Uncertainty	9
2.3.1	Sample Calculation – radiated & conducted emissions	9
2.3.2	Measurement Uncertainty	10
2.4	Calibration Traceability	10
3	Product Information	11
3.1	Product Description	11
3.2	Equipment Configuration	11
3.3	Operating Mode	11
3.4	Unique Antenna Connector	12
3.4.1	Results	12
3.5	Duty Cycle	13
3.5.1	Results	13
4	Emissions	15
4.1	Output Power Requirements	15
4.1.1	Test Method	15
4.1.2	Results	16
4.2	Occupied Bandwidth	20
4.2.1	Test Method	20
4.2.2	Results	20
4.3	Peak Power Spectral Density	28
4.3.1	Test Method	28
4.3.2	Results	28
4.4	Out of Band Emissions	33
4.4.1	Test Method	33
4.4.2	Results	34

Table of Contents

4.5	Transmit Spurious Emissions	41
4.5.1	Test Methodology	41
4.5.2	Transmitter Spurious Emission Limit	42
4.5.3	Test Results	42
4.5.4	Sample Calculation	52
4.6	AC Conducted Emissions	53
4.6.1	Test Methodology	53
4.6.2	Test Results	53
5	<i>Test Equipment List</i>	57
5.1	Equipment List	57
6	<i>EMC Test Plan</i>	58
6.1	Introduction	58
6.2	Customer	58
6.3	Equipment Under Test (EUT)	59
6.4	Test Specifications	62

Index of Tables

Table 1: Summary of Test Results	7
Table 2: RF Output Power at the Antenna Port – Test Results	16
Table 3: Occupied Bandwidth – Test Results	21
Table 4: Peak Power Spectral Density – Test Results	29
Table 5: Out of Band Emissions – Test Results	34
Table 6: Transmit Spurious Emission at Band-Edge Requirements	43
Table 7: AC Conducted Emissions – Test Results	53
Table 8: Customer Information	58
Table 9: Technical Contact Information	58
Table 10: EUT Specifications	59
Table 11: Interface Specifications	60
Table 12: Supported Equipment	60
Table 13: Description of Sample used for Testing	60
Table 14: Description of Test Configuration used for Radiated Measurement.	60
Table 15: Final Test Mode for 2402 MHz to 2480MHz Band	61
Table 16: Test Specifications	62

1 Executive Summary

1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.247: 2021 and RSS 247: 2017 based on the results of testing performed on April 11, 2022 to May 6, 2022 on the USB Wireless Audio Transmitter Model Stealth600P-MAX-TX manufactured by Voyetra Turtle Beach, Inc. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report. The 2402 MHz to 2480 MHz frequency band is covered in this document.

1.3 Summary of Test Results

Table 1: Summary of Test Results

Test	Test Method ANSI C63.10:2013	Test Parameters	Measured Value	Result
Spurious Emission in Transmitted Mode	CFR47 15.209, CFR47 15.247 (d) RSS GEN Sect.8.9	Class B	-4.60 dB (Margin)	Complied
Restricted Bands of Operation	CFR47 15.205, RSS GEN Sect.8.10	Class B		Complied
AC Power Conducted Emission	CFR47 15.207, RSS-GEN Sect.8.8	Class B	-12.80 dB (Margin)	Complied
Occupied Bandwidth	CFR47 15.247 (a2), RSS GEN Sect.6.7, RSS 247 Sect. 5.2 (a)	≥ 500 kHz	1.038 MHz (99%) 0.715 MHz (DTS)	Complied
Maximum Output Power	CFR47 15.247 (b), RSS 247 Sect. 5.4 (d)	30 dBm w/ 6 dBi antenna	+4.86 dBm	Complied
Peak Power Spectral Density	CFR47 15.247 (e), RSS 247 Sect. 5.2 (b)	8 dBm/ 3 kHz	-16.67 dBm	Complied
Out of Band Emission	CFR47 15.247 (d), RSS 247 Sect.5.5	-30 dB	-16.04 dB (Margin)	Complied

1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

1.5 Equipment Modifications

None.

2 Laboratory Information

2.1 Accreditations & Endorsements

2.1.1 US Federal Communications Commission



Bureau Veritas Consumer Products Services, Inc. at 775 Montague Expressway, Milpitas CA 95035 is recognized by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (Registration No. US1109). The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, 20, 22, 24, 25, 27, 90, 95, 97 and 101. The accreditation is updated every 3 years.

2.1.2 NIST / A2LA



Bureau Veritas Consumer Products Services, Inc is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:2017 and ISO 9002 (Lab Code 2742-01). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

2.1.3 Canada



Bureau Veritas Consumer Products Services, Inc. at the 775 Montague Expressway, Milpitas, CA 95035 address is accredited by Industry Canada for

performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by Industry Canada (File Number 4842D). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. Bureau Veritas Consumer Products Services, Inc. at 775 Montague Expressway, Milpitas, CA 95035 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for for Milpitas: A-0133

2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all Bureau Veritas Consumer Products Services, Inc. at 775 Montague Expressway, Milpitas, CA 95035 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member country.

2.2 Test Facilities

All of the test facilities are located at 775 Montague Expressway, Milpitas, California, 95035, USA.

2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 and 10 meters. The site is listed with the FCC and accredited by A2LA (Lab Code 2742-01). A report detailing this site can be obtained from Bureau Veritas Consumer Products Services, Inc.

2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1st Edition, 1995.

The Combined Standard Uncertainty is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dB μ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V/m}}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

2.3.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	0.15 MHz ~ 30 MHz	2.70 dB
Radiated emissions	9 kHz ~ 30 MHz	2.16 dB
	30 MHz ~ 1 GHz	3.60 dB
	1 GHz ~ 18 GHz	4.82 dB
	18 GHz ~ 40 GHz	5.00 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2017. Equipment calibration records are kept on file at the test facility.

3 Product Information

3.1 Product Description

The Stealth 600P Gen 2 MAX Wireless Gaming System consists of two main communication modules, the Stealth600P-MAX-RX (“Headset”) and the Stealth600P-MAX-TX (“Transmitter”). These two modules comprise a closed-loop wireless audio gaming system that utilize a proprietary 2.4 GHz communication technology to offer wireless streaming audio and chat/talkback capabilities. The devices are designed to operate with a PlayStation gaming console or PC-based system.

Additionally, the Stealth 600P Gen 2 MAX has three versions that are 100% identical electrically and mechanically except for the color of their exterior plastics. The three model color variations are standard Black, Arctic Camo and Midnight Red.

3.2 Equipment Configuration

A description of the equipment configuration is given in the Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of an EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.3 Operating Mode

A description of the operation mode is given in the Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.


The final operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.4 Unique Antenna Connector

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

3.4.1 Results

The Stealth600P-MAX-TX uses the permanently attached PCB trace antenna inside the device. See EUT Photo for details.



3.5 Duty Cycle

The Stealth600P-MAX-TX, SN: PP1 was measured.

3.5.1 Results

Mode	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Factor (dB)
1 Mbps	0.273	0.286	95.45	0.22
2 Mbps	0.234	0.255	91.76	0.37

Notes: EUT was configured and measured for the duty cycle at each data rate.




Figure 1: Duty Cycle at 1 Mbps




Figure 2: Duty Cycle at 2 Mbps

4 Emissions

Testing was performed in accordance with CFR 47 Part 15.247: 2021 and RSS 247: 2017. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in section 8 of the standard were used.

4.1 Output Power Requirements

The maximum output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.

The maximum output power and harmonics shall not exceed CFR47 Part 15.247 (b):2021 and RSS 247: 2017 Sect. 5.4 (d).


The maximum transmitted powers are

Band 2400-2483.5 MHz: 1 W

4.1.1 Test Method

The ANSI C63.10-2013 Section 11.9.2.2 conducted method was used to measure the channel power output. The preliminary investigation was performed at different data rate/ chain to determine the highest power output for each mode. The worst findings were conducted on 3 channels in each operating range per CFR47 Part 15.247(b): 2021 and RSS 247 Sect. 5.4 (d). This test was conducted on 3 channels of Sample, S/N PP #1. The worst mode result indicated below.

Test Setup:



Method AVGSA-2 of "KDB 558074 – DTS Measurement Guidance v05r02" applies since the EUT continuously transmits with duty cycle less than 98%. Sample detector was used.

4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 2: RF Output Power at the Antenna Port – Test Results

Test Date: April 11, 2022			Test By: Abhijit Patibandla		
Test Method: Conducted Measurements			Power Setting: Fixed at 4 dBm		
Antenna Type: Integrated PCB			Max. Antenna Gain: -2.16 dBi		
Operating Mode: Uncorrelated			Signal State: Modulated		
Ambient Temp.: 23 °C			Relative Humidity: 46%		
USB Wireless Audio Transmitter					
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]
1 Mbps Data Rate					
2402	+30.00	4.54	0.22	4.76	-25.24
2442	+30.00	4.25	0.22	4.47	-25.53
2480	+30.00	3.87	0.22	4.09	-25.91
2 Mbps Data Rate					
2402	+30.00	4.49	0.37	4.86	-25.14
2442	+30.00	4.20	0.37	4.57	-25.43
2480	+30.00	3.84	0.37	4.21	-25.79
Note: The USB Wireless Audio Transmitter transmitted at the duty cycle determined in Section 3.5.					




Figure 3: Maximum Transmitted Power, 2402 MHz at 1Mbps




Figure 4: Maximum Conducted Output Power at 2442 MHz at 1Mbps




Figure 5: Maximum Conducted Output Power at 2480 MHz at 1Mbps




Figure 6: Maximum Conducted Output Power at 2402 MHz at 2Mbps




Figure 7: Maximum Conducted Output Power at 2442 MHz at 2Mbps




Figure 8: Maximum Conducted Output Power at 2480 MHz at 2Mbps

4.2 Occupied Bandwidth

The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.

The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.


The minimum 6 dB bandwidth shall be at least 500 kHz.

The bandwidth shall be at least 500 kHz per Section CFR47 15.247(a2) 2021 and RSS 247 Sect.5.2 (a) 2017

4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth according to ANSI C63.10:2013 Section 11.8.1. The measurement was performed with modulation per CFR47 15.247(a) (2) 2021 and RSS 247 Sect. 5.2 (a) 2017. The preliminary investigation was performed to find the narrowest 6 dB bandwidth for each operational mode at different data rates. This worst finding was performed on 3 channels in each operating frequency range; 2400 MHz to 2483.5 MHz. This test was conducted on 3 channels in each mode of Sample S/N PP #1. The worst sample result indicated below.

Test Setup:



4.2.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 3: Occupied Bandwidth – Test Results

Test Date: April 11, 2022			Test By: Abhijit Patibandla		
Test Method: Conducted Measurements			Power Setting: Fixed at 4 dBm		
Antenna Type: Integrated PCB			Max. Antenna Gain: -2.16 dBi		
Operating Mode: Uncorrelated			Signal State: Modulated		
Ambient Temp.: 23 °C			Relative Humidity: 46%		
Bandwidth (MHz) for USB Wireless Audio Transmitter					
Frequency (MHz)	Rate (Mbps)	Limit (kHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Results
2402	1	500	0.724	1.040	Pass
2442	1	500	0.715	1.038	Pass
2480	1	500	0.721	1.039	Pass
2402	2	500	1.386	2.059	Pass
2442	2	500	1.373	2.056	Pass
2480	2	500	1.383	2.058	Pass
Note: The USB Wireless Audio Transmitter transmitted at the duty cycle determined in Section 3.5.					




Figure 9: DTS Bandwidth 2402 MHz at 1 Mbps




Figure 10: DTS Bandwidth 2442 MHz at 1 Mbps




Figure 11: DTS Bandwidth 2480 MHz at 1 Mbps




Figure 12: 99% Bandwidth 2402 MHz at 1Mbps




Figure 13: 99% Bandwidth 2442 MHz at 1Mbps




Figure 14: 99% Bandwidth 2480 MHz at 1Mbps



Figure 15: DTS Bandwidth 2402 MHz at 2 Mbps




Figure 16: DTS Bandwidth 2442 MHz at 2 Mbps




Figure 17: DTS Bandwidth 2480 MHz at 2 Mbps




Figure 18: 99% Bandwidth 2402 MHz at 2 Mbps




Figure 19: 99% Bandwidth 2442 MHz at 2 Mbps




Figure 20: 99% Bandwidth 2480 MHz at 2 Mbps


4.3 Peak Power Spectral Density

According to the CFR47 Part 15.247 (e) and RSS 247 Sect.5.2 (b), the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.1 Test Method

The conducted method was used to measure the channel power output per ANSI C63.10-2013 Section 11.10.3. The measurement was performed with modulation per CFR47 Part 15.247 (e) and RSS 247 Sect.5.2 (b). The pre-evaluation was performed to find the worst modes. The worst findings were conducted on 3 channels in each operating frequency range of 2400 MHz to 2483.5 MHz. This test was conducted on 3 channels of Sample SN PP #1. The worst sample result indicated below.

Test Setup:



4.3.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 4: Peak Power Spectral Density – Test Results

Test Date: April 11, 2022				Test By: Abhijit Patibandla		
Test Method: Conducted Measurements				Power Setting: Fixed at 4 dBm		
Antenna Type: Integrated PCB				Max. Antenna Gain: -2.16 dBi		
Operating Mode: Uncorrelated				Signal State: Modulated		
Ambient Temp.: 23 °C				Relative Humidity: 46%		
Peak Power Spectral Density						
Freq. (MHz)	Config.	Output [dBm]	CF [dB]	Max. PPSD [dBm]	Limit [dBm]	Margin [dB]
2402	1 Mbps	-1.66	-15.01	-16.67	8.00	-24.67
2442	1 Mbps	-2.13	-15.01	-17.14	8.00	-25.14
2480	1 Mbps	-2.47	-15.01	-17.48	8.00	-25.48
2402	2 Mbps	-4.11	-14.86	-18.97	8.00	-26.97
2442	2 Mbps	-4.51	-14.86	-19.37	8.00	-27.37
2480	2 Mbps	-5.18	-14.86	-20.04	8.00	-28.04
<p>Note: CF accounted for the measured RBW and duty cycle correction. The bandwidth ratio is $10 \cdot \log(3\text{kHz}/100\text{kHz})$ or -15.23 dB. Since the USB Wireless Audio Transmitter transmitted at 95.45% duty cycle at 1 Mbps and 91.76% duty cycle at 2 Mbps, the final correction factor is -15.01 dB and -14.86; respectively.</p>						




Figure 21: Maximum Power Spectral Density-2402 MHz at 1 Mbps




Figure 22: Maximum Power Spectral Density-2442 MHz at 1 Mbps




Figure 23: Maximum Power Spectral Density-2480 MHz at 1 Mbps




Figure 24: Maximum Power Spectral Density-2402 MHz at 2 Mbps




Figure 25: Maximum Power Spectral Density-2442 MHz at 2 Mbps




Figure 26: Maximum Power Spectral Density-2480 MHz at 2 Mbps

4.4 Out of Band Emissions


The setup was identical to RF output power measurement. Intentional radiators operating under the alternative provisions to the general emission limits, must be designed to ensure that the 20 dB or 30 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If the frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Since the transmitter complies with the conducted power limits base on the use of RMS averaging per CFR47 Part 15.247(b)(3), any frequency outside the band of 2400MHz to 2483.5MHz, the power output level must be below 30db from the in-band transmitting signal; CFR 47 Part 15.215, 15.247(d) and RSS-247 Sect.5.5..

4.4.1 Test Method

The conducted method was used to measure the out-of-band emission requirement. The measurement was performed with modulation per CFR47 15.247(4) (d) 2021 and RSS-247 Sect.5.5: 2017. This test was conducted on 3 channels of Sample S/N PP #1. The worst sample result indicated below.

Test Setup:



4.4.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 5: Out of Band Emissions – Test Results

Test Date: April 11, 2022		Test By: Abhijit Patibandla		
Test Method: Conducted Measurements		Power Setting: Fixed at 4 dBm		
Antenna Type: Integrated PCB		Max. Antenna Gain: -2.16 dBi		
Operating Mode: Uncorrelated		Signal State: Modulated		
Ambient Temp.: 23 °C		Relative Humidity: 46%		
Out of Band Results for USB Wireless Audio Transmitter				
Frequency (MHz)	Rate (Mbps)	Out of Band Level (dBm)	30 dBc Level (dBm)	Margin (dB)
2402	1	-43.39	-26.24	-17.15
2442	1	-44.64	-26.56	-18.08
2480	1	-45.12	-26.90	-18.22
2402	2	-44.53	-28.49	-16.04
2442	2	-47.00	-28.73	-18.27
2480	2	-45.35	-29.04	-16.31
<p>Note: dBc is defined as the level below the main carrier. The band-edge level must be lower than the 30 dBc level. The maximum out of band emission on each individual output is at least 30 dB below the maximum in-band PSD on that output. (*) The band-edge is compared to the highest -30 dBc level of the test mode.</p>				




Figure 27: Conducted Band Edge - 2402 MHz at 1 Mbps




Figure 28: Out of band Emission - 2402 MHz at 1 Mbps




Figure 29: Conducted Band Edge - 2442 MHz at 1 Mbps



Figure 30: Out of band Emission - 2442 MHz at 1 Mbps




Figure 31: Conducted Band Edge - 2480 MHz at 1 Mbps




Figure 32: Out of band Emission - 2480 MHz at 1 Mbps




Figure 33: Conducted Band Edge - 2402 MHz at 2 Mbps




Figure 34: Out of band Emission - 2402 MHz at 2 Mbps




Figure 35: Conducted Band Edge - 2442 MHz at 2 Mbps




Figure 36: Out of band Emission - 2442 MHz at 2 Mbps




Figure 37: Conducted Band Edge - 2480 MHz at 2 Mbps



Figure 38: Out of band Emission - 2480 MHz at 2 Mbps

4.5 Transmit Spurious Emissions

Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmit mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS-Gen Sect. 8.9.

4.5.1 Test Methodology

4.5.1.1 Preliminary Test

A test program that controls instrumentation and data logging was used to automate the preliminary RF emission test procedure. The frequency range of interest was divided into sub-ranges to yield a frequency resolution of approximately 120 kHz and provide a reading at each frequency for no more than 12° of turntable rotation. For each frequency sub-range the turntable was rotated 360° while peak emission data was recorded and plotted over the frequency range of interest in horizontal and vertical antenna polarization's.

Preliminary emission profile testing was performed inside the anechoic chamber. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm (<1 GHz) and 150cm (>1 GHz) above the floor. The EUT was positioned as shown in the setup photographs. The receiving antenna was placed at a distance of 3m at a fixed height of 1m. Measurement equipment was located outside of the chamber. A video camera was placed inside the chamber to view the EUT.

Pres-scans were performed to determine the worst case configuration for data rate.

4.5.1.2 Final Test

For each frequency measured, the peak emission was maximized by manipulating the receiving antenna from 1 to 4 meters above the ground plane and placing it at the position that produced the maximum signal strength reading. The turntable was then rotated through 360° while observing the peak signal and placing the EUT at the position that produced maximum radiation. The six highest emissions relative to the limit were measured unless such emissions were more than 20 dB below the limit. If less than six emissions are within 20 dB of the limit, than the noise level of the receiver is measured at frequencies where emissions are expected. Multiples of all oscillator and microprocessor frequencies were also checked.

Final testing was performed on an NSA compliant test site. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm (<1 GHz) and 150cm (>1 GHz) above the ground plane. The placement of EUT and cables were the same as for preliminary testing and is shown in the setup photographs.


The final scans performed on the worst axis, Y-Axis up, for three operating channels in each operating mode;

2402 MHz, 2442 MHz, and 2480 MHz

4.5.1.3 Deviations

None.

Test Setup:



4.5.2 Transmitter Spurious Emission Limit

The spurious emissions of the transmitter shall not exceed the values in CFR47 Part 15.205, 15.209: 2021 and RSS Gen Sect. 8.10: 2019.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F (kHz)	300
0.490-1.705	24000/F (kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

All harmonics and spurious emission which are outside of the restricted band shall be 20dB below the in-band emission.

4.5.3 Test Results

The final measurement data was taken under the worst case operating modes, configurations, and/or cable positions. It also reflects the results including any modifications and/or special accessories listed in Sections 1.4 and test plan.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 6: Transmit Spurious Emissions at Band-Edge Requirements

Test Date: May 5, 2022								Test By: Abhijit Patibandla						
Test Method: Radiated Measurements								Power Setting: Fixed at 4 dBm						
Antenna Type: Integrated PCB								Max. Antenna Gain: -2.16 dBi						
Operating Mode: Uncorrelated								Signal State: Modulated						
Ambient Temp.: 23 °C								Relative Humidity: 41%						
Band-Edge Results														
Antenna Polarity & Test Distance: Vertical and Horizontal at 3m														
No.	Frequency (MHz)	Pol (H/V)	Reading AV (dBuV/m)	Reading PK (dBuV/m)	Factor (dB)	Level AV (dBuV/m)	Level PK (dB(uV/m))	Limit AV (dBuV/m)	Limit PK (dBuV/m)	Margin AV (dB)	Margin PK (dB)	Hght (cm)	Angle (Deg)	Pass/Fail
1	2390.00	H	-0.80	13.00	35.00	34.20	48.00	54.00	74.00	-19.80	-26.00	106	189	Pass
2	2401.59	H	59.20	64.00	35.10	94.30	99.10	54.00	74.00			106	196	N/A*
3	2480.49	H	56.60	62.20	35.40	92.00	97.60	54.00	74.00			158	194	N/A*
4	2483.50	H	6.80	20.70	35.40	42.20	56.10	54.00	74.00	-11.80	-17.90	157	195	Pass
5	2390.00	V	-1.70	11.80	35.00	33.30	46.80	54.00	74.00	-20.70	-27.20	324	328	Pass
6	2402.49	V	54.40	60.00	35.10	89.50	95.10	54.00	74.00			100	11	N/A*
7	2479.45	V	51.10	57.50	35.40	86.50	92.90	54.00	74.00			325	158	N/A*
8	2483.50	V	3.80	17.90	35.40	39.20	53.30	54.00	74.00	-14.80	-20.70	148	158	Pass
<p>Note: The emissions were measured at the adjacent restricted band of the fundamental signal. All the band-edge measurements met the restricted band requirements of CFR47 15.205 Band-edge measurement plots use a wider span than 2 MHz to evaluate additional spectrum bands for in-band leakage and spurious emission. (*) Fundamental/ Inband emission. Emission level (dBuV/m) = Reading Value (dBuV) + Factor (dB) AF (dB/m) = Antenna Factor (dB/m) – Preamplifier Gain (dB). Margin value = Emission level – Limit value.</p>														




Figure 39: Band-edge-2402 MHz




Figure 40: Band-edge-2480 MHz


Radiated Emissions										Page 1 of 6	
EUT Name	USB Wireless Audio Transmitter					Date	05/05/2022				
EUT Model	Stealth600P-MAX-TX					Temp / Hum in	23°C / 40%rh				
EUT Serial	PP #2					Temp / Hum out	N/A				
EUT Config.	EUT on Vertical Position					Line AC / Freq	5.0 VDC				
Standard	CFR47 Part 15 Subpart C					RBW / VBW	120 kHz/ 300 kHz				
Dist/Ant Used	3m / JB6 & AL-130R					Performed by	Abhijit Patibandla				
Freq.	Raw	Corrd'	Level	Det.	Pol.	Hght.	Azt	Limit	Margin	Result	
MHz	dBuV/m	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB		
9 kHz to 1 GHz, Transmitted Data at 2402 MHz											
23.31	12.40	35.10	47.50	Pk	X-axis	100	338	69.50	-22.00	Pass	
27.94	10.20	34.90	45.10	Pk	X-axis	100	359	69.50	-24.40	Pass	
33.07	12.30	22.90	35.20	QP	V	112	136	40.00	-4.80	Pass	
48.33	22.50	12.90	35.40	QP	V	102	170	40.00	-4.60	Pass	
50.53	21.20	12.10	33.30	QP	V	106	2	40.00	-6.70	Pass	
95.86	22.50	14.60	37.10	QP	V	110	215	43.50	-6.40	Pass	
676.62	-9.20	25.10	15.90	QP	V	206	158	46.00	-30.10	Pass	
836.96	-8.60	27.50	18.90	QP	H	180	174	46.00	-27.10	Pass	
Spec Margin = Level - Limit, Level = Raw+ Cbl+ CF ± Uncertainty											
CF= Amp Gain + ANT Factor											
Combined Standard Uncertainty $u_c(y) = \pm 3.51$ dB Expanded Uncertainty $U = ku_c(y)$ $k = 2$ for 95% confidence											
Note: The worst case emission was observed on Channel 2402 MHz.											
There were no significant emissions observed from 9 kHz to 30 MHz.											

Radiated Emissions										Page 2 of 6
EUT Name		USB Wireless Audio Transmitter					Date		05/06/2022	
EUT Model		Stealth600P-MAX-TX					Temp / Hum in		23°C / 40%rh	
EUT Serial		PP #2					Temp / Hum out		N/A	
EUT Config.		EUT on Vertical Position					Line AC / Freq		5.0 VDC	
Standard		CFR47 Part 15 Subpart C					RBW / VBW		1 MHz / 3 MHz	
Dist/Ant Used		3m / 3117, 1m / SAS-574					Performed by		Abhijit Patibandla	
Freq	Raw	Corrd ⁷	Level	Det	Pol	Hght	Azt	Limit	Margin	Comment
MHz	dBuV/m	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB	
Transmitted Data at 2402 MHz										
4803.61	54.90	-11.60	43.30	Pk	H	250	149	74.00	-30.70	Harmonics
4803.61	49.20	-11.60	37.60	Ave	H	250	149	54.00	-16.40	Harmonics
9608.92	53.10	-1.90	51.20	Pk	H	213	337	74.00	-22.80	Harmonics
9608.92	46.40	-1.90	44.50	Ave	H	213	337	54.00	-9.50	Harmonics
4804.33	54.10	-11.60	42.50	Pk	V	190	167	74.00	-31.50	Harmonics
4804.33	47.10	-11.60	35.50	Ave	V	190	167	54.00	-18.50	Harmonics
7205.38	48.40	-6.50	41.90	Pk	V	169	166	74.00	-32.10	Harmonics
7205.38	38.00	-6.50	31.50	Ave	V	169	166	54.00	-22.50	Harmonics
9607.30	49.80	-1.90	47.90	Pk	V	116	257	74.00	-26.10	Harmonics
9607.30	42.30	-1.90	40.40	Ave	V	116	257	54.00	-13.60	Harmonics
Transmitted Data at 2442 MHz										
4883.54	52.40	-11.40	41.00	Ave	H	250	144	54.00	-13.00	Harmonics
4883.54	57.40	-11.40	46.00	Pk	H	250	144	74.00	-28.00	Harmonics
7325.86	26.30	-6.20	20.10	Pk	H	170	88	74.00	-53.90	Harmonics
7325.86	15.30	-6.20	9.10	Ave	H	170	88	54.00	-44.90	Harmonics
9769.27	26.40	-1.50	24.90	Pk	H	257	221	74.00	-49.10	Harmonics
9769.27	15.10	-1.50	13.60	Ave	H	257	221	54.00	-40.40	Harmonics
4884.26	57.70	-11.40	46.30	Pk	V	245	186	74.00	-27.70	Harmonics
4884.26	52.60	-11.40	41.20	Ave	V	245	186	54.00	-12.80	Harmonics
9769.02	48.20	-1.50	46.70	Pk	V	115	272	74.00	-27.30	Harmonics
9769.02	40.80	-1.50	39.30	Ave	V	115	272	54.00	-14.70	Harmonics
Transmitted Data at 2480 MHz										
4959.62	60.40	-11.40	49.00	Pk	H	147	129	74.00	-25.00	Harmonics
4959.62	55.20	-11.40	43.80	Ave	H	147	129	54.00	-10.20	Harmonics
9920.81	50.00	-1.30	48.70	Pk	H	100	0	74.00	-25.30	Harmonics
9920.81	43.70	-1.30	42.40	Ave	H	100	0	54.00	-11.60	Harmonics
4959.82	59.00	-11.40	47.60	Pk	V	116	152	74.00	-26.40	Harmonics
4959.82	53.60	-11.40	42.20	Ave	V	116	152	54.00	-11.80	Harmonics
9919.15	45.80	-1.30	44.50	Pk	V	192	358	74.00	-29.50	Harmonics
9919.15	36.20	-1.30	34.90	Ave	V	192	358	54.00	-19.10	Harmonics

Spec Margin = Level - Limit, Level = Raw+ Cbl+ CF \pm Uncertainty. CF= Amp Gain + ANT Factor
Combined Standard Uncertainty $u_c(y) = \pm 4.91\text{dB}$ Expanded Uncertainty $U = ku_c(y)$ $k = 2$ for 95% confidence
Notes: All emissions passed the spurious emission limit

Radiated Emissions

EUT Name	USB Wireless Audio Transmitter	Date	05/05/2022
EUT Model	Stealth600P-MAX-TX	Temp / Hum in	23°C / 40%rh
EUT Serial	PP #2	Temp / Hum out	N/A
EUT Config.	EUT on Vertical Position	Line AC / Freq	5.0 VDC
Standard	CFR47 Part 15 Subpart C	RBW / VBW	120 kHz / 300 kHz
Dist/Ant Used	3m / JB3 & AL-130R	Date	Abhijit Patibandla





Notes: None.

Radiated Emissions

EUT Name	USB Wireless Audio Transmitter	Date	05/06/2022
EUT Model	Stealth600P-MAX-TX	Temp / Hum in	23°C / 40%rh
EUT Serial	PP #2	Temp / Hum out	N/A
EUT Config.	EUT on Vertical Position	Line AC / Freq	5.0 VDC
Standard	CFR47 Part 15 Subpart C	RBW / VBW	1 MHz / 3 MHz
Dist/Ant Used	3m / 3117, 1m / SAS-574	Performed by	Abhijit Patibandla

Above 1 GHz Plots for Transmit Mode at 2402 MHz





Notes: There were no emissions observed from 18 GHz to 26 GHz.

Radiated Emissions

EUT Name	USB Wireless Audio Transmitter	Date	05/06/2022
EUT Model	Stealth600P-MAX-TX	Temp / Hum in	23°C / 40%rh
EUT Serial	PP #2	Temp / Hum out	N/A
EUT Config.	EUT on Vertical Position	Line AC / Freq	5.0 VDC
Standard	CFR47 Part 15 Subpart C	RBW / VBW	1 MHz / 3 MHz
Dist/Ant Used	3m / 3117, 1m / SAS-574	Performed by	Abhijit Patibandla

Above 1 GHz Plots for Transmit Mode at 2442 MHz





Notes: There were no emissions observed from 18 GHz to 26 GHz.

Radiated Emissions

EUT Name	USB Wireless Audio Transmitter	Date	05/06/2022
EUT Model	Stealth600P-MAX-TX	Temp / Hum in	23°C / 40%rh
EUT Serial	PP #2	Temp / Hum out	N/A
EUT Config.	EUT on Vertical Position	Line AC / Freq	5.0 VDC
Standard	CFR47 Part 15 Subpart C	RBW / VBW	1 MHz / 3 MHz
Dist/Ant Used	3m / 3117, 1m / SAS-574	Performed by	Abhijit Patibandla

Above 1 GHz Plots for Transmit Mode at 2480 MHz



Notes: There were no emissions observed from 18 GHz to 26 GHz.

4.5.4 Sample Calculation

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{FIM} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: FIM = Field Intensity Meter (dB μ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V/m}}{20}}$$

4.6 AC Conducted Emissions

Testing was performed in accordance with ANSI C63.10: 2013. These test methods are listed under the laboratory's A2LA Scope of Accreditation.

This test measures the levels emanating from the EUT's AC input port, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

The AC conducted emissions of equipment under test shall not exceed the values in CFR47 Part 15.207: 2021 and RSS Gen: 2019 Sect. 8.8.

4.6.1 Test Methodology

A test program that controls instrumentation and data logging was used to automate the AC Power Line Conducted emission test procedure. The frequency range of interest was divided into sub-ranges such as to yield a frequency resolution of 9 kHz. Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a set of 50 μ H / 50 Ω LISNs.

Testing is performed in Conducted Emission Station. The setup photographs clearly identify which site was used. The vertical ground plane used in the semi-anechoic chamber is a 2m x 2m solid aluminum frame and panel, and it is bonded to the horizontal ground plane.

In the case of tabletop equipment, the EUT is placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane and 40cm from a vertical ground reference plane. The rear of the EUT was positioned flush with the backside of the table and directly over the LISNs. The power and I/O cables were routed over the edge of the table and bundled approximately 40cm from the ground plane. Support equipment was powered from a separate LISN.

4.6.1.1 Deviations

There were no deviations from this test methodology.

4.6.2 Test Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 7: AC Conducted Emissions – Test Results

Test Conditions: Conducted Measurement		Test Date: April 17, 2022
Antenna Type: Integrated		Power Level: 4
AC Power: USB Host Computer		Configuration: Tabletop
Ambient Temperature: 23° C		Relative Humidity: 39% RH
Configuration	Frequency Range	Test Result
Line 1 (Hot)	0.15 to 30 MHz	Pass
Line 2 (Neutral)	0.15 to 30 MHz	Pass


Conducted Emissions					Page 1 of 3			
EUT Name	USB Wireless Audio Transmitter				Date	April 17, 2022		
EUT Model	Stealth600P-MAX-TX				Temp / Hum in	23° C / 39% rh		
EUT Serial	PP #2				Temp / Hum out	N/A		
EUT Config.	Integrated Antenna				Line AC / Freq	Host @ 110 Vac/60 Hz		
Standard	CFR47 Part 15.207				RBW / VBW	9 kHz / 30 kHz		
Lab/LISN	CE Station /EMCO 3816				Performed by	Abhijit Patibandla		
Frequency	Raw	Corrd'	Level	Detector	Line	Limit	Margin	Result
MHz	dBuV	dB	dBuV		Line	dBuV	dB	
0.159	42.00	9.60	51.60	QP	Line	65.50	-13.90	Pass
0.159	24.40	9.60	34.00	Ave	Line	55.50	-21.50	Pass
0.208	34.00	9.60	43.60	QP	Line	63.30	-19.70	Pass
0.208	15.80	9.60	25.40	Ave	Line	53.30	-27.90	Pass
0.211	34.10	9.60	43.70	QP	Line	63.20	-19.50	Pass
0.211	16.00	9.60	25.60	Ave	Line	53.20	-27.60	Pass
0.234	30.80	9.50	40.30	QP	Line	62.30	-22.00	Pass
0.234	12.40	9.50	21.90	Ave	Line	52.30	-30.40	Pass
0.508	22.60	9.40	32.00	QP	Line	56.00	-24.00	Pass
0.508	16.00	9.40	25.40	Ave	Line	46.00	-20.60	Pass
0.163	41.60	9.60	51.20	QP	Neutral	65.30	-14.10	Pass
0.163	23.00	9.60	32.60	Ave	Neutral	55.30	-22.70	Pass
0.164	41.30	9.60	50.90	QP	Neutral	65.30	-14.40	Pass
0.164	23.10	9.60	32.70	Ave	Neutral	55.30	-22.60	Pass
0.178	36.70	9.60	46.30	QP	Neutral	64.60	-18.30	Pass
0.178	16.30	9.60	25.90	Ave	Neutral	54.60	-28.70	Pass
0.184	41.90	9.60	51.50	QP	Neutral	64.30	-12.80	Pass
0.184	24.00	9.60	33.60	Ave	Neutral	54.30	-20.70	Pass
Spec Margin = QP./Ave. - Limit, ± Uncertainty								
Combined Standard Uncertainty $u_c(y) = \pm 3.51$ dB Expanded Uncertainty $U = ku_c(y)$ $k = 2$ for 95% confidence								
Notes: EUT was setup as table top equipment and transmitted at 2402 MHz								

Conducted Emissions

Page 2 of 3

EUT Name	USB Wireless Audio Transmitter	Date	April 17, 2022
EUT Model	Stealth600P-MAX-TX	Temp / Hum in	23° C / 39% rh
EUT Serial	PP #2	Temp / Hum out	N/A
EUT Config.	Integrated Antenna	Line AC	Host @ 110 Vac/60 Hz
Standard	CFR47 Part 15.207	RBW / VBW	9 kHz / 30 kHz
Lab/LISN	CE Station /EMCO 3816	Performed by	Abhijit Patibandla


150 kHz to 30 MHz Plot for Line 1 (Hot)



Notes: Meets FCC Class B limit.

Conducted Emissions		Page 3 of 3	
EUT Name	USB Wireless Audio Transmitter	Date	April 17, 2022
EUT Model	Stealth600P-MAX-TX	Temp / Hum in	23° C / 39% rh
EUT Serial	PP #2	Temp / Hum out	N/A
EUT Config.	Integrated Antenna	Line AC	Host @ 110 Vac/60 Hz
Standard	CFR47 Part 15.207	RBW / VBW	9 kHz / 30 kHz
Lab/LISN	CE Station /EMCO 3816	Performed by	Abhijit Patibandla

150 kHz to 30 MHz Plot for Line 2 (Neutral)



Notes: Meets FCC Class B limit.

5 Test Equipment List

5.1 Equipment List

Equipment	Manufacturer	Model #	Serial/Inst #	Last Cal mm/dd/yyyy	Next Cal mm/dd/yyyy
Loop Antenna	COM-POWER	AL-130R	10160080	02/07/2022	02/07/2023
Bilog Antenna	Sunol Sciences	JB6	A111717	09/04/2020	09/04/2022
Horn Ant. (1-18GHz)	ETS-Lindgren	3117	218554	04/21/2021	04/21/2023
Horn Ant. (18-40GHz)	A.H Systems, In.	SAS-574	579	08/05/2020	08/05/2022
Spectrum Analyzer	KEYSIGHT	N9010A	MY51440112	11/21/2021	11/21/2022
EMI Receiver	Rohde & Schwarz	ESW44	1328.4100K-101662-MH	09/22/2021	09/22/2022
Preamplifier	RF-Lambda	RAMP00M50GA	18040300055	05/07/2021	05/07/2022
Power Sensor	ETS Lindgren	7002-006	00159814	01/16/2022	01/16/2023
Humidity/ Baro/ Temp. Recorder	PCE Instruments	PCE-THB 40	Q907623	08/31/2021	08/31/2022
DC Power Source	Agilent	E3610A	MY40002494	02/25/2022	02/25/2023
Notch Filter	Micro-Tronics	BRM50702	NA	VBU	VBU

* Calibration of equipment past due for re-calibration will be performed expeditiously. If any equipment is found to be out of tolerance at that time, affected customers will be notified accordingly.

6 EMC Test Plan

6.1 Introduction

This section provides a description of the Equipment Under Test (EUT), configurations, operating conditions, and performance acceptance criteria. It is an overview of information provided by the manufacturer so that the test laboratory may perform the requested testing.

6.2 Customer

Table 8: Customer Information

Company Name	Voyetra Turtle Beach, Inc.
Address	44 South Broadway, 4th Floor
City, State, Zip	White Plains NY 10601
Country	USA

Table 9: Technical Contact Information

Name	Tim Blaney
E-mail	tim@commcepts.net
Phone	(530) 277-3482

6.3 Equipment Under Test (EUT)

Table 10: EUT Specifications

EUT Specification	
Package Dimensions	51.5 mm (2.0”) x 15 mm (0.6”) x 7.8 mm (0.3”)
Power Input	Input Voltage: 5.0 Vdc via Host USB port.
Environment	Indoor
Operating Temperature Range:	0 to 50 degrees C
Multiple Feeds:	<input type="checkbox"/> Yes and how many <input checked="" type="checkbox"/> No
Product Marketing Name (PMN)	Stealth600P-MAX-TX
Hardware Version Identification Number (HVIN)	600P-MAX-TX
Firmware Version Identification Number (FVIN)	4.14.15.1
Operating Mode	TestCommon Unit Test 1.0.4.8
Transmitter Frequency Band	2402 MHz to 2480 MHz
Max. Measured Power Output	+4.86 dBm
Power Setting @ Operating Channel	+4.0 dBm
Antenna Type	Integrated PCB (-2.16 dBi)
Modulation Type	<input type="checkbox"/> AM <input type="checkbox"/> FM <input type="checkbox"/> DSSS <input type="checkbox"/> OFDM <input checked="" type="checkbox"/> Other describe: GFSK
Date Rates	1 Mbps and 2 Mbps
TX/RX Chain (s)	1
Directional Gain Type	<input checked="" type="checkbox"/> Uncorrelated <input checked="" type="checkbox"/> No Beam-Forming <input type="checkbox"/> Other describe:
Type of Equipment	<input type="checkbox"/> Table Top <input type="checkbox"/> Wall-mount <input type="checkbox"/> Floor standing cabinet <input checked="" type="checkbox"/> Other describe: <i>Table Top Device's accessory</i>
Note: The Stealth600P-MAX-TX has three versions that are 100% identical electrically and mechanically except for the color of their exterior plastics. The three model color variations are standard Black, Artic Camo and Midnight Red.	

Table 11: Interface Specifications

Interface Type	Cabled with what type of cable?	Is the cable shielded?	Maximum potential length of the cable?	Metallic (M), Coax (C), Fiber (F), or Not Applicable?
USB	Terminated	<input checked="" type="checkbox"/> Yes	<input checked="" type="checkbox"/> Metric:0.6 m	<input checked="" type="checkbox"/> M

Table 12: Supported Equipment

Equipment	Manufacturer	Model	Serial	Used for
Laptop	Lenovo	T430	PB-8HBRR	Set test mode

Table 13: Description of Sample used for Testing

Device	Serial Number	Configuration	Used For
Stealth600P-MAX-TX	PP #2	Radiated Sample	Radiated Emissions, Conducted Emission.
Stealth600P-MAX-TX	PP #1	Conducted Sample	Output Power, Occupied Bandwidth, Conducted Spurious Emissions, Peak Power Spectral Density
Note: None			

Table 14: Description of Test Configuration used for Radiated Measurement.

Device	Antenna	Mode	Setup Description
Stealth600P-MAX-TX	Integrated	Transmit & Receive	Stealth 600P-MAX-TX positioned vertically, worst case.
Note: This is the final setup configuration used for testing.			

Table 15: Final Test Mode for 2402 MHz to 2480 MHz Band

Test	Stealth600P-MAX-TX
Occupied Bandwidth	2402, 2442, 2480 MHz @ 1 and 2 Mbps
Output Power	2402, 2442, 2480 MHz @ 1 and 2 Mbps
Peak Power Spectral Density	2402, 2442, 2480 MHz @ 1 and 2 Mbps
Out-of-Band (-30 dBr)	2402, 2442, 2480 MHz @ 1 and 2 Mbps
Band-Edge (Radiated)	2402, 2480 MHz @ 2 Mbps
Transmitted Spurious Emission	2402, 2442, 2480 MHz @ 1 Mbps
AC Conducted Emission	2402 MHz @ 1 Mbps
Note: EUT transmits at 95.45% duty cycle in 1 Mbps mode and 91.76% in 2 Mbps mode.	

6.4 Test Specifications

Table 16: Test Specifications

Emissions and Immunity	
Rules & Regulations / Standards	Requirement
CFR 47 Part 15.247: 2021	All
RSS 247 Issue 2, 2017	All

END OF REPORT