

# RF EXPOSURE REPORT

# **CERTIFICATE OF CONFORMITY**

FCC Rule Part: FCC Part 2 (Section 2.1093)

Report No.: MFBUUY-WTW-P24040386

FCC ID: XGB-HWBB0006

Product: Wireless Headset

Brand: TURTLE BEACH

Model No.: HWBB0006

Received Date: 2024/4/18

Test Date: 2024/5/10

Issued Date: 2024/5/27

Applicant: Voyetra Turtle Beach, Inc.

Address: 44 South Broadway, 4th Floor White Plains NY 10601 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan **Test Location:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration / 198487 / TW2021

**Designation Number:** 

Approved by:	Jeremy Lin	, Date:	2024/5/27	
	Jeremy Lin / Project Engineer			

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by: Annie Chang / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/ourbusiness/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/ourbusiness/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Report No.: MFBUUY-WTW-P24040386 Page No. 1 / 8 Report Format Version: 7.1.0 Reference No.: BUUY-WTW-P24040386



# **Table of Contents**

Relea	se Control Record	3
1	Certificate	4
2	Applicable RF Exposure Limit	5
3	Test Results	7
4	Conclusion	7
5	Information of the Testing Laboratories	8



# **Release Control Record**

Issue No.	Description	Date Issued
MFBUUY-WTW-P24040386	Original release.	2024/5/27

Report No.: MFBUUY-WTW-P24040386 Page No. 3 / 8 Report Format Version: 7.1.0 Reference No.: BUUY-WTW-P24040386



# 1 Certificate

**Product:** Wireless Headset

**Brand:** TURTLE BEACH

Test Model: HWBB0006

Sample Status: Engineering sample

**Applicant:** Voyetra Turtle Beach, Inc.

**Test Date:** 2024/5/10

FCC Rule Part: FCC Part 2 (Section 2.1093)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Report No.: MFBUUY-WTW-P24040386 Page No. 4 / 8 Report Format Version: 7.1.0 Reference No.: BUUY-WTW-P24040386



# 2 Applicable RF Exposure Limit

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

# (e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)	
	Limits For Gene	eral Population / Uncontrolle	ed Exposure		
0.3-1.34	614	1.63	(100)*	<30	
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	<30	
30-300	27.5	0.073	0.2	<30	
300-1,500			f/1500	<30	
1,500-100,000			1.0	<30	

f = frequency in MHz. \* = Plane-wave equivalent power density.

### Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)
	Limits For Gene	eral Population / Uncontrolle	ed Exposure	
0.3-3.0	614	1.63	*(100)	⊴6
3.0-30	1842/f	4.89/f	*(900/f²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6

f = frequency in MHz. \* = Plane-wave equivalent power density.

Report No.: MFBUUY-WTW-P24040386 Page No. 5 / 8 Report Format Version: 7.1.0 Reference No.: BUUY-WTW-P24040386



### SAR-based Exemption - §1.1307(b)(3)(i)(B)

➤ The SAR-based exemption formula of §1.1307(b)(3)(i)(B), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW). This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz.

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm)

When 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

#### Fixed RF sources operating in the same time-averaging period – §1.1307(b)(3)(ii)(B)

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluatedk term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

#### Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using <u>paragraph (b)(3)(i)(B)</u> of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

 $P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to <u>paragraph</u> (<u>b)(3)(i)(B)</u> of this section for fixed, mobile, or portable RF source *i*.  $ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Exposure  $Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

b = number of fixed, mobile, or portable RF sources claiming exemption using <u>paragraph (b)(3)(i)(C)</u> of this section for Threshold ERP, including existing exempt transmitters and those being added.

 $P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

 $ERP_j$  = the ERP of fixed, mobile, or portable RF source j.

 $Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Report No.: MFBUUY-WTW-P24040386 Page No. 6 / 8 Report Format Version: 7.1.0 Reference No.: BUUY-WTW-P24040386



# 3 Test Results

Environmental 25°C, 76% R	Tested By:	Dalen Dai
---------------------------	------------	-----------

### For Single RF Source

SAR-based Exemption							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result
GFSK	2402-2480	0.001503	3	0.001828	0.5	2.717	Pass
Bluetooth	2402-2480	2.183	0.5	1.493	0.5	2.717	Pass

#### Notes:

- 1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2. Calculate the ERP of GFSK from the radiated field strength:
  ERP (dBm) = Radiated field strength (dBuV/m) + 20 x Log(d) 104.77 2.15
  d is the measurement distance, in 3 m.
  ERP = 70 + 20 x Log(3) 104.77 2.15 = -27.38 dBm (0.001828 mW)
  Average Power = ERP (dBm) Antenna Gain (dBi) + 2.15 = -28.23 dBm (0.001503 mW)
- 3. The average power used is the max tune-up power (including tolerances).

# For Multiple RF Sources (Simultaneous Operations)

Multiple RF Sources (Simultaneous Operations)							
Exemption Evaluation							
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Limit Threshold (mW)	Ratio	Sum of Ratios	Limit of Ratios	Test Result
GFSK	2402-2480	0.001828	2.717	0.001	0.804	1	Pass
Bluetooth	2402-2480	2.183	2.717	0.803		1	Pass

# 4 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBUUY-WTW-P24040386 Page No. 7 / 8 Report Format Version: 7.1.0 Reference No.: BUUY-WTW-P24040386



# 5 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@bureauveritas.com">service.adt@bureauveritas.com</a>
Web Site: <a href="mailto:http://ee.bureauveritas.com.tw">http://ee.bureauveritas.com.tw</a>

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: MFBUUY-WTW-P24040386 Reference No.: BUUY-WTW-P24040386 Page No. 8 / 8 Report Format Version: 7.1.0