



TÜVRheinland®
Precisely Right.

RF Exposure Exhibit

EUT Name: USB Wireless Audio Transmitter

EUT Model: Ear Force Stealth 420X+ TX (TB300-2571-01)

CFR47 Part 2.1093

Prepared for:

Tim Blaney
Voyetra Turtle Beach Inc.
100 Summit Lake Drive, Suite 100
Valhalla, New York 10959, USA

Prepared by:

TUV Rheinland of North America
1279 Quarry Lane, Ste. A
Pleasanton, CA 94566
Tel: (929) 249-9123
Fax: (925) 249-9124
<http://www.tuv.com/>

Report/Issue Date: June 12, 2016

Report Number: 31661416.001

1.1 Maximum Permissible Exposure

1.1.1 Test Methodology

In this section, we try to prove the safety of radiation harmfulness to the human body for our product. The KDB 447498 D01 General RF Exposure Guidance is followed. The Gain of the antenna used in this calculation is declared by the manufacturer, and the maximum average power input to the antenna is measured. Using the general SAR test exclusion guidance in Section 4.3 of KDB 447498, we show the device meeting the SAR exclusion threshold.

1.1.2 FCC KDB 447498 D01 – General SAR Test Exclusion Guidance

The SAR exclusion threshold conditions are listed:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})} \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$$
 - ☐ $f(\text{GHz})$ is the RF channel transmit frequency in GHz
 - ☐ Power and distance are rounded to the nearest mW and mm before calculation¹⁷
 - ☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:¹⁸
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · ($f(\text{MHz})/150$)] mW, at 100 MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion, and as illustrated in Appendix C:¹⁹
 - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm
 - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

1.1.3 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

1.1.4 Classification

The antenna of the product, under normal use condition, is less than 20cm away from the body of the user. This device is classified as a **Portable Device**.

1.1.5 SAR Test Exclusion Threshold

Antenna Gain

The transmitting antenna was integrated. The highest antenna gain was -0.5 dBi.

SAR Exclusion Threshold Calculation

| Mode | Max. Power (dBm) | EIRP (dBm) | Min. Separation Distance (mm) | Cal. Excl. Threshold | 1-g SAR Limit | 10-g extremity SAR Limit | Result |
|--|------------------|------------|-------------------------------|----------------------|---------------|--------------------------|------------|
| Modulated | -0.33 | -0.83 | 5 | 0.2604 | ≤ 3.0 | ≤ 7.5 | Exempted * |
| Note: 1. Since EUT can operate at distance less than 50 mm, the minimum distance, 5 mm, was used for calculation per condition #1 of SAR Exclusion Threshold. 2. The maximum output power was taken from Table 3 of "Turtle Beach - Ear Force Stealth 420X+ TX - FCC 15.247 Report 31661416.001." 3. (*) The calculated threshold is less than 3.0; therefore, EUT is SAR exempted for head and body usage. | | | | | | | |