

Emissions Test Report

EUT Name: Wireless Audio Headset
Model No.: Ear Force Stealth 700X
CFR 47 Part 15.407 2017 and RSS 247: 2017

Prepared for:

Tim Blaney
Voyetra Turtle Beach, Inc.
100 Summit Lake Drive, Suite 100
Valhalla, New York 10595 USA
Tel: (530) 277-3482

Prepared by:

TUV Rheinland of North America, Inc.
1279 Quarry Lane
Pleasanton, CA 94566
Tel: (925) 249-9123
Fax: (925) 249-9124
<http://www.tuv.com/>

Report/Issue Date: October 12, 2017
Job # 0000150094
Report Number: 31763105.001

Revisions

Revision No.	Date MM/DD/YYYY	Reason for Change	Author
0	09/22/2017	Original Document	N/A
1	10/12/2017	Remove RF Exposure Information	J. Luong

Note: Latest revision report will replace all previous reports.

Statement of Compliance

Manufacturer: Voyetra Turtle Beach, Inc.
100 Summit Lake Drive, Suite 100
Valhalla, New York 10595 USA
(530) 277-3482

Requester / Applicant: Tim Blaney

Name of Equipment: Wireless Audio Headset
Model No. Ear Force Stealth 700X (TB300-2770-01)
Type of Equipment: Intentional Radiator
Application of Regulations: CFR 47 Part 15.407 2017 and RSS 247: 2017
Test Dates: May 22, 2017 to August 8, 2017

Guidance Documents:

Emissions: ANSI C63.10-2013, KDB 789033 D02 General UNII Test Procedures New Rules v01r04

Test Methods:

Emissions: ANSI C63.10-2013, KDB 789033 D02 General UNII Test Procedures New Rules v01r04

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report contains data that are not covered by A2LA accreditation. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.

Jeremy Luong October 12, 2017

Test Engineer Date

David Spencer October 12, 2017

Laboratory Signatory Date



Testing Cert #3331.02

US1131

2932M

Table of Contents

1	Executive Summary	7
1.1	Scope	7
1.2	Purpose	7
1.3	Summary of Test Results	8
1.4	Special Accessories	8
1.5	Equipment Modifications	8
2	Laboratory Information	9
2.1	Accreditations & Endorsements	9
2.1.1	US Federal Communications Commission	9
2.1.2	NIST / A2LA	9
2.1.3	Canada – Industry Canada	9
2.1.4	Japan – VCCI	9
2.1.5	Acceptance by Mutual Recognition Arrangement	9
2.2	Test Facilities	10
2.2.1	Emission Test Facility	10
2.2.2	Immunity Test Facility	10
2.3	Measurement Uncertainty	10
2.3.1	Sample Calculation – radiated & conducted emissions	11
2.3.2	Measurement Uncertainty	11
2.3.3	Measurement Uncertainty Immunity	12
2.4	Calibration Traceability	12
3	Product Information	13
3.1	Product Description	13
3.2	Equipment Configuration	13
3.3	Operating Mode	13
3.4	Unique Antenna Connector	14
3.4.1	Results	14
3.5	Duty Cycle	15
3.5.1	Results	15
4	Emissions	18
4.1	Output Power Requirements	18
4.1.1	Test Method	18
4.1.2	Results	19
4.2	Occupied Bandwidth	35
4.2.1	Test Method	35
4.2.2	Results	35
4.3	Power Spectral Density	50
4.3.1	Test Method	50
4.3.2	Results	50

Table of Contents

4.4	Undesirable Emission Limits	65
4.4.1	Test Method	65
4.4.2	Results	65
4.5	Transmitter Spurious Emissions	93
4.5.1	Test Methodology	93
4.5.2	Transmitter Spurious Emission Limit	94
4.5.3	Results	94
4.6	AC Conducted Emissions	156
4.6.1	Test Methodology	156
4.6.2	Test Results	156
4.7	Frequency Stability	161
4.7.1	Test Methodology	161
4.7.2	Manufacturer Declaration	161
4.7.3	Limit	162
4.7.4	Test results:	162
4.8	Voltage Variation	164
4.8.1	Test Methodology	164
4.8.2	Test results	164
5	Test Equipment List	166
5.1	Equipment List	166
6	EMC Test Plan	167
6.1	Introduction	167
6.2	Customer	167
6.3	Equipment Under Test (EUT)	168
6.4	Test Specifications	171

Index of Tables

Table 1: Summary of Test Results	8
Table 2: RF Output Power at the Antenna Port – Test Results per FCC	19
Table 3: RF Output Power at the Antenna Port – Test Results per RSS-247	21
Table 4: Occupied Bandwidth – Test Results.....	36
Table 5: Power Spectral Density – Test Results for 802.11a	51
Table 6: Power Spectral Density – Test Results for 802.11n HT20	52
Table 7: Undesired Emissions for 802.11a – Test Results	66
Table 8: Undesired Emissions for 802.11n HT20 – Test Results.....	67
Table 9: Transmit Spurious Emission at Band-Edge Requirements.....	95
Table 10: Transmit Spurious Emission at Band-Edge Requirements Continued.....	96
Table 11: Transmit Spurious Emission at Band-Edge Requirements Continued.....	97
Table 12: AC Conducted Emissions – Test Results.....	156
Table 13: Frequency Stability – Test Results	162
Table 14: Voltage Variation – Test Results.....	164
Table 15: Customer Information	167
Table 16: Technical Contact Information.....	167
Table 17: EUT Specifications	168
Table 18: Antenna Information	169
Table 19: EUT Channel Power Specifications	169
Table 20: Interface Specifications	170
Table 21: Supported Equipment	170
Table 22: Description of Sample used for Testing.....	170
Table 23: Description of Test Configuration used for Radiated Measurement.....	170
Table 24: Test Specifications	171

1 Executive Summary

1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.407 2017 and RSS 247: 2017 based on the results of testing performed on May 22, 2017 to August 8, 2017 on the Wireless Audio Headset Model Ear Force Stealth 700X manufactured by Voyetra Turtle Beach, Inc. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report. The 5180 MHz – 5320 MHz, 5500 MHz – 5700 MHz, and 5745 MHz – 5825 MHz frequency bands are covered in this document.

1.3 Summary of Test Results

Table 1: Summary of Test Results

Test	Test Method ANSI C63.10:2013	Test Parameters	Measured Value	Result
Duty Cycle	Information Only	N/A	100%	N/A
Spurious Emission in Transmitted Mode	CFR47 15.209, CFR47 15.407 (b) RSS-GEN Sect.8.9, RSS 247 Sect. 6.2.1.2	Class B	-7.80 dB Margin	Complied
Restricted Bands of Operation	CFR47 15.205, RSS GEN Sect.8.10	Class B		Complied
AC Power Conducted Emission	CFR47 15.207, RSS-GEN Sect.8.8	Class B	-8.24 dB Margin	Complied
Occupied Bandwidth	CFR47 15.407 (a) & (e), RSS GEN Sect.6.6, RSS-247 Sect.6.2.4.1	DTS \geq 500 kHz	99% BW: 16.83 MHz 26dB BW: 23.13 MHz DTS BW: 16.32 MHz	Complied
Maximum Output Power	CFR47 15.407 (a) RSS 247 Sect. 6.2	UNII1: 250mW UNII2a: 250mW UNII2c: 250mW UNII3: 1W	UNII1: 7.87dBm/ 6.12mW UNII2a: 7.95dBm/ 6.24mW UNII2c: 7.84dBm/ 6.08mW UNII3: 7.91dBm/ 6.18mW	Complied
Peak Power Spectral Density	CFR47 15.407 (a) RSS 247 Sect. 6.2 (UNII2a, UNII2c & UNII3)	< 11 dBm/MHz < 30 dBm/ 500 kHz	UNII1: -2.57 dBm/ MHz UNII2a: -2.30 dBm/ MHz UNII2c: -2.48 dBm/ MHz UNII3: -5.46 dBm/ 500kHz	Complied
	RSS 247 Sect.6.2.1.1	< 10 dBm/MHz (e.i.r.p)	UNII1: -2.57 dBm/ MHz	Complied
Conducted Emission – Antenna Port	CFR47 15.407 (b)(1) (2)(3) RSS 247 Sect.6.2.1 to 6.2.3	< -27 dBm/MHz	-10.22 dB Margin	Complied
	CFR47 15.407 (b)(4) RSS 247 Sect.6.2.4	Spectrum Mask	-2.37 dB Margin	Complied
Frequency Stability	CFR47 15.407 (g), RSS GEN Sect. 6.11	\pm 20 ppm	7.89 ppm	Complied
Voltage Variation	CFR47 15.31(e)	\pm 20 ppm	3.40 ppm	Complied

1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

1.5 Equipment Modifications

None

2 Laboratory Information

2.1 Accreditations & Endorsements

2.1.1 US Federal Communications Commission



TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 is recognized by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (US1131). The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, and 90. The accreditation is updated every 3 years.

2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:1999 and ISO 9002 (Lab Code Testing Cert #3331.02). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

2.1.3 Canada – Industry Canada



TUV Rheinland of North America at the 1279 Quarry Ln, Pleasanton, CA 94566 address is accredited by Industry Canada for performing testing services for the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by Industry Canada (File Number 2932M). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0268

2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member country.

2.2 Test Facilities

All of the test facilities are located at 1279 Quarry Lane, Pleasanton, California 94566, USA.

2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 and 5 meters. The site is listed with the FCC and accredited by A2LA (Lab Code Testing Cert #3331.02). A report detailing this site can be obtained from TUV Rheinland of North America.

2.2.2 Immunity Test Facility

ESD, EFT, Surge, PQF: These tests are performed in an environmentally controlled room with a 3.7 m x 4.8 m x 3.175 mm thick aluminum floor connected to PE ground.

For ESD testing, tabletop equipment is placed on an insulated mat with a surface resistivity of 10^9 Ohms/square on a 1.6 m x 0.8 m x 0.8 m high non-conductive table with a 3.175 mm aluminum top (Horizontal Coupling Plane). The HCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors. The Vertical Coupling Plane consists of an aluminum plate 50 cm x 50 cm x 3.175 mm thick. The VCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors.

For EFT, Surge, PQF, the HCP and VCP are removed.

RF Field Immunity testing is performed in a 7.3m x 4.3m x 4.1m anechoic chamber.

RF Conducted and Magnetic Field Immunity testing is performed on a 4.8m x 3.7m x 3.175mm thick aluminum ground plane.

All test areas allow a minimum distance of 1 meter from the EUT to walls or conducting objects.

2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1st Edition, 1995.

The Combined Standard Uncertainty is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\text{Field Strength (dB}\mu\text{V/m)} = \text{RAW} - \text{AMP} + \text{CBL} + \text{ACF}$$

Where: RAW = Measured level before correction (dB μ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu\text{V/m} = 10^{\frac{\text{dB}\mu\text{V} / \text{m}}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor–Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

$$25 \text{ dBuV/m} + 17.5 \text{ dB} - 20 \text{ dB} + 1.0 \text{ dB} = 23.5 \text{ dBuV/m}$$

2.3.2 Measurement Uncertainty

Per CISPR 16-4-2	U _{lab}	U _{cispr}
Radiated Disturbance @ 10 meters		
30 – 1,000 MHz	2.25 dB	4.51 dB
Radiated Disturbance @ 3 meters		
30 – 1,000 MHz	2.26 dB	4.52 dB
1 – 6 GHz	2.12 dB	4.25 dB
6 – 18 GHz	2.47 dB	4.93 dB
Conducted Disturbance @ Mains Terminals		
150 kHz – 30 MHz	1.09 dB	2.18 dB
Disturbance Power		
30 MHz – 300 MHz	3.92 dB	4.3 dB

Voltech PM6000A

The estimated combined standard uncertainty for harmonic current and flicker measurements is $\pm 5.0\%$.	Per CISPR 16-4-2 Methods
------------------------------------------------------------------------------------------------------------	--------------------------

2.3.3 Measurement Uncertainty Immunity

The estimated combined standard uncertainty for ESD immunity measurements is $\pm 8.2\%$.	Per IEC 61000-4-2
The estimated combined standard uncertainty for radiated immunity measurements is ± 4.10 dB.	Per IEC 61000-4-3
The estimated combined standard uncertainty for conducted immunity measurements with CDN is ± 3.66 dB	Per IEC 61000-4-6
The estimated combined standard uncertainty for power frequency magnetic field immunity is $\pm 2.9\%$.	Per IEC 61000-4-8

Thermo KeyTek EMC Pro

The estimated combined standard uncertainty for EFT fast transient immunity measurements is $\pm 2.6\%$.
The estimated combined standard uncertainty for surge immunity measurements is $\pm 2.6\%$.
The estimated combined standard uncertainty for voltage variation and interruption measurements is $\pm 1.74\%$.

Measurement Uncertainty – Radio Testing

The estimated combined standard uncertainty for frequency error measurements is ± 3.88 Hz
The estimated combined standard uncertainty for carrier power measurements is ± 1.59 dB.
The estimated combined standard uncertainty for adjacent channel power measurements is ± 1.47 dB.
The estimated combined standard uncertainty for modulation frequency response measurements is ± 0.46 dB.
The estimated combined standard uncertainty for transmitter conducted emission measurements is ± 4.01 dB

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2005. Equipment calibration records are kept on file at the test facility.

3 Product Information

3.1 Product Description

The Stealth 700X is a completely wireless Xbox One audio gaming headset. It wirelessly connects directly to the Xbox One console over either a 2.4 GHz or 5.0 GHz Wi-Fi link. The functionality in the headset consists of 50mm speaker drivers, a flip up non-removable microphone, microphone monitoring (adjustable via EFAH) and game/chat mix controls on the headset. Additional wireless functionality includes a Bluetooth radio that provides simultaneous connection to a Turtle Beach mobile application and device audio profile for communication with a mobile phone. Additionally, it has a ProSpecs alternative glasses relief ear pad design. With the Microsoft integrated radio module, this headset is also capable of working with compatible Windows PCs in the future.

3.2 Equipment Configuration

A description of the equipment configuration is given in the Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of an EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.3 Operating Mode

A description of the operation mode is given in the Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

The final operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.4 Unique Antenna Connector


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

3.4.1 Results

The Wireless Audio Headset uses a dual band Fractus chip antenna for operation in the 2.4 GHz and 5150 MHz to 5850 MHz bands. The chip antenna is integrated on the PCB. It has a peak gain of 1.8 dBi in the 2.4 GHz band and 4.9 dBi in the 5150 MHz to 5850 MHz band.

There is an additional antenna specification available in the submittal package.

7.0 mm x 3.0 mm x 2.0 mm (image larger than real size)



3.5 Duty Cycle

The Ear Force Stealth 700X, SN: PP1 was measured for the duty cycle

3.5.1 Results

Mode	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Factor (dB)
802.11a	100	0	100	0
802.11n HT20	100	0	100	0
Notes: EUT configured and measured for the duty cycle. All measurements use 100% duty cycle.				




Figure 1: Duty Cycle for 802.11a




Figure 2: Duty Cycle for 802.11n HT20

4 Emissions

Testing was performed in accordance with CFR 47 Part 15.407: 2017 and RSS 247: 2017. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in section 8 of the standard were used.

4.1 Output Power Requirements

The maximum output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.

The maximum transmitted power limits per CFR47 Part 15.407 and RSS-247 are

Part 15.407(a)(1)(iv) – Band 5150-5250 MHz: 250 mW.

Part 15.407(a)(2) – Band 5250-5350 MHz, 5470-5725 MHz: 250 mW or 11 dBm + 10Log B.

Part 15.407(a)(3) – Band 5725-5825 MHz: 1 W

RSS 247 Sect. 6.2.1.1 – Band 5150-5250 MHz (e.i.r.p.): 200 mW or 10 + 10Log(B)

RSS 247 Sect. 6.2.2.1 – Band 5250-5350 MHz, 5470-5725 MHz: 250 mW or 11 dBm + 10Log B

RSS 247 Sect. 6.2.2.1, 6.2.3.1 – Band 5250-5350 MHz, 5470-5725 MHz: 250 mW or 11 dBm + 10Log B.


RSS 247 Sect. 6.242.1 – Band 5725-5850 MHz: 1 W

Note: B is the 99% emission bandwidth.

4.1.1 Test Method

The ANSI C63.10-2013 Section 12.3.2.2 conducted method was used to measure the channel power output. The preliminary investigation was performed at different data rate/ chain to determine the highest power output for each mode. The worst findings were conducted on 3 channels in each operating range per CFR47 Part 15.407(a) and RSS 247 Sect. 6.2.1.1. The worst mode results indicated below.

Test Setup:



Method SA-1 of “KDB 789033 D02 – Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices” applies since the EUT continuously transmit; where duty cycle is greater than 98%. Sample detector was used.

4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 2: RF Output Power at the Antenna Port – Test Results per FCC

Test Conditions: Conducted Measurement			Date: July 17, 2017		
Antenna Type: Chip			Power Setting: See test plan.		
Antenna Gain: 4.9 dBi			Signal State: Modulated at 100%		
Ambient Temp.: 23 °C			Relative Humidity:38%		
802.11a at 6 Mbps (FCC Limit)					
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]
5180	23.98	7.65			-16.33
5200	23.98	7.79			-16.19
5240	23.98	7.62			-16.36
5260	23.98	7.64			-16.34
5300	23.98	7.58			-16.40
5320	23.98	7.81			-16.17
5500	23.98	7.84			-16.14
5580	23.98	7.76			-16.22
5700	23.98	7.61			-16.37
5745	30.00	7.63			-22.37
5785	30.00	7.91			-22.09
5825	30.00	7.85			-22.15
Note: The headset is a client device. Worst case condition was observed at 6 Mbps.					

802.11n HT20 at 6.5 Mbps (FCC Limit)					
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	Σ Power [dBm]	Margin [dB]
5180	23.98	7.70			-16.28
5200	23.98	7.60			-16.38
5240	23.98	7.87			-16.11
5260	23.98	7.56			-16.42
5300	23.98	7.95			-16.03
5320	23.98	7.68			-16.30
5500	23.98	7.73			-16.25
5580	23.98	7.63			-16.35
5700	23.98	7.51			-16.47
5745	30.00	7.61			-22.39
5785	30.00	7.82			-22.18
5825	30.00	7.73			-22.27
Note: The headset is a client device. Worst case condition was observed at 6.5 Mbps.					

Table 3: RF Output Power at the Antenna Port – Test Results per RSS-247

Test Conditions: Conducted Measurement			Date: July 17, 2017		
Antenna Type: Chip			Power Setting: See test plan.		
Antenna Gain: 4.9 dBi			Signal State: Modulated at 100%		
Ambient Temp.: 23 °C			Relative Humidity: 38%		
802.11a at 6 Mbps (RSS-247 Limit)					
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	Σ Power [dBm]	Margin [dB]
5180	18.10	7.65			-10.45
5200	18.10	7.79			-10.31
5240	18.10	7.62			-10.48
5260	23.98	7.64			-16.34
5300	23.98	7.58			-16.40
5320	23.98	7.81			-16.17
5500	23.98	7.84			-16.14
5580	23.98	7.76			-16.22
5700	23.98	7.61			-16.37
5745	30.00	7.63			-22.37
5785	30.00	7.91			-22.09
5825	30.00	7.85			-22.15
Note: The headset is a client device. Worst case condition was observed at 6 Mbps. For 5150 – 5250 MHz, RSS-247 Limit = 23 dBm – 4.9 dBi = 18.10 dBm					
802.11n HT20 at 6.5 Mbps (RSS-247 Limit)					
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	Σ Power [dBm]	Margin [dB]
5180	18.10	7.70			-10.40
5200	18.10	7.60			-10.50
5240	18.10	7.87			-10.23
5260	23.98	7.56			-16.42
5300	23.98	7.95			-16.03
5320	23.98	7.68			-16.30

5500	23.98	7.73			-16.25
5580	23.98	7.63			-16.35
5700	23.98	7.51			-16.47
5745	30.00	7.61			-22.39
5785	30.00	7.82			-22.18
5825	30.00	7.73			-22.27
Note: The headset is a client device. Worst case condition was observed at 6.5 Mbps. For 5150 – 5250 MHz, RSS-247 Limit = 23 dBm – 4.9 dBi = 18.10 dBm					




Figure 3: Conducted Output Power-5180 MHz-11a-6 Mbps




Figure 4: Conducted Output Power -5200 MHz-11a-6 Mbps




Figure 5: Conducted Output Power-5240 MHz-11a-6 Mbps




Figure 6: Conducted Output Power-5260 MHz-11a-6 Mbps




Figure 7: Conducted Output Power-5300 MHz-11a-6 Mbps




Figure 8: Conducted Output Power-5320 MHz-11a-6 Mbps




Figure 9: Conducted Output Power-5500 MHz-11a-6 Mbps




Figure 10: Conducted Output Power-5580 MHz-11a-6 Mbps




Figure 11: Conducted Output Power-5700 MHz-11a-6 Mbps




Figure 12: Conducted Output Power-5745 MHz-11a-6 Mbps




Figure 13: Conducted Output Power-5785 MHz-11a-6 Mbps




Figure 14: Conducted Output Power-5825 MHz-11a-6 Mbps




Figure 15: Conducted Output Power-5180 MHz-HT20-6.5 Mbps




Figure 16: Conducted Output Power -5200 MHz-HT20-6.5 Mbps




Figure 17: Conducted Output Power-5240 MHz-HT20-6.5 Mbps




Figure 18: Conducted Output Power-5260 MHz-HT20-6.5 Mbps




Figure 19: Conducted Output Power-5300 MHz-HT20-6.5 Mbps




Figure 20: Conducted Output Power-5320 MHz-HT20-6.5 Mbps




Figure 21: Conducted Output Power-5500 MHz-HT20-6.5 Mbps




Figure 22: Conducted Output Power-5580 MHz-HT20-6.5 Mbps




Figure 23: Conducted Output Power-5700 MHz-HT20-6.5 Mbps




Figure 24: Conducted Output Power-5745 MHz-HT20-6.5 Mbps




Figure 25: Conducted Output Power-5785 MHz-HT20-6.5 Mbps




Figure 26: Conducted Output Power-5825 MHz-HT20-6.5 Mbps

4.2 Occupied Bandwidth

The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.

The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.

The 26 dB bandwidth is defined the bandwidth of 26 dBr from highest transmitted level of the fundamental frequency.


The minimum 6 dB bandwidth shall be at least 500 kHz per Section CFR47 15.407(e) 2017 and RSS 247 Sect.6.2.4.1: 2017

There is no restriction limits for the bandwidth. The 26 dB bandwidth was used to determine the limit for maximum conducted output power per CFR47 Part 15.407(a).

4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth. The measurement was performed with modulation per CFR47 15.407(a) & (e), RSS Gen Sect.6.6 and RSS-247 Sect.6.2.4.1. The preliminary investigation was performed to find the narrowest 26 dB bandwidth for each operational mode at different data rates. This worst finding was performed on 3 channels in each operating frequency range. The worst results indicated below.

Test Setup:



4.2.2 Results

These occupied bandwidth measurements were taken for reference only.

Table 4: Occupied Bandwidth – Test Results

Test Conditions: Conducted Measurement			Date: July 17, 2017	
Antenna Type: Chip			Power Setting: See test plan.	
Antenna Gain: 4.9 dBi			Signal State: Modulated at 100%	
Ambient Temp.: 23 °C			Relative Humidity:38%	
Bandwidth (MHz) for 802.11a				
Frequency (MHz)	Limit (kHz)	99% BW	26 dB BW	Results
5180	NA	16.851	23.130	NA
5200	NA	16.847	23.760	NA
5240	NA	16.841	23.410	NA
5260	NA	16.840	23.600	NA
5300	NA	16.839	23.33	NA
5320	NA	16.835	23.130	NA
5500	NA	16.849	24.050	NA
5580	NA	16.866	23.890	NA
5700	NA	16.874	24.300	NA
Frequency (MHz)	Limit (kHz)	99% BW	6 dB BW	Results
5745	500	16.865	16.340	Pass
5785	500	16.854	16.320	Pass
5825	500	16.859	16.410	Pass
Note: The bandwidth was measured at 6 Mbps for 802.11a mode. The 99% bandwidth measurements are informative, and 26 dB bandwidths are used to determine the output power limits.				
Bandwidth (MHz) for 802.11n HT20				
Frequency (MHz)	Limit (kHz)	99% BW	26 dB BW	Results
5180	NA	17.936	23.890	NA
5200	NA	17.916	24.110	NA
5240	NA	17.923	24.220	NA
5260	NA	17.913	23.910	NA

5300	NA	17.914	24.340	NA
5320	NA	17.921	24.460	NA
5500	NA	17.937	24.210	NA
5580	NA	17.933	25.420	NA
5700	NA	17.933	25.080	NA
Frequency (MHz)	Limit (kHz)	99% BW	6 dB BW	Results
5745	500	17.954	17.480	Pass
5785	500	17.932	17.530	Pass
5825	500	17.939	17.490	Pass
Note: The bandwidth was observed at MCS0, 6.5 Mbps mode. The 99% bandwidth measurements are informative, and 26 dB bandwidths are used to determine the output power limits.				




Figure 27: Occupied Bandwidth-5180 MHz-11a




Figure 28: Occupied Bandwidth-5200 MHz-11a




Figure 29: Occupied Bandwidth-5240 MHz-11a




Figure 30: Occupied Bandwidth-5260 MHz-11a




Figure 31: Occupied Bandwidth-5300 MHz-11a




Figure 32: Occupied Bandwidth-5320 MHz-11a




Figure 33: Occupied Bandwidth-5500 MHz-11a




Figure 34: Occupied Bandwidth-5580 MHz-11a




Figure 35: Occupied Bandwidth-5700 MHz-11a




Figure 36: Occupied Bandwidth-5745 MHz-11a




Figure 37: Occupied Bandwidth-5785 MHz-11a




Figure 38: Occupied Bandwidth-5825 MHz-11a




Figure 39: Occupied Bandwidth-5180 MHz-HT20




Figure 40: Occupied Bandwidth-5200 MHz-HT20




Figure 41: Occupied Bandwidth-5240 MHz-HT20




Figure 42: Occupied Bandwidth-5260 MHz-HT20




Figure 43: Occupied Bandwidth-5300 MHz-HT20




Figure 44: Occupied Bandwidth-5320 MHz-HT20




Figure 45: Occupied Bandwidth-5500 MHz-HT20




Figure 46: Occupied Bandwidth-5580 MHz-HT20




Figure 47: Occupied Bandwidth-5700 MHz-HT20




Figure 48: Occupied Bandwidth-5745 MHz-HT20




Figure 49: Occupied Bandwidth-5785 MHz-HT20




Figure 50: Occupied Bandwidth-5825 MHz-HT20

4.3 Power Spectral Density

According to the CFR47 Part 15.407 (a) and RSS 247 Sect. 6.2, the spectral power density output of the antenna port shall be as followed listed below during any time interval of continuous transmission.

The power spectral density limits per CFR47 Part 15.407 (a):

Band 5150-5250 MHz, 5250-5350 MHz, and 5470-5725 MHz: 11 dBm in any 1 MHz band

Band 5725-5850 MHz: 30 dBm in any 500 kHz band.

The power spectral density limits per RSS-247 Section 6.2:

Band 5150-5250 MHz: 10 dBm in any 1 MHz band, E.I.R.P.


Band 5250-5350 MHz, and 5470-5725 MHz: 11 dBm in any 1 MHz band

Band 5725-5850 MHz: 30 dBm in any 500 kHz band

4.3.1 Test Method

The conducted method was used to measure the channel power output per ANSI C63.10-2013 Section 12.3.2.2. The measurement was performed with modulation per CFR47 Part 15.407 (a) and RSS 247 Sect. 6.2. The pre-evaluation was performed to find the worst modes. The worst findings were conducted on 3 channels in each operating frequency range. The worst sample result indicated below.

Test Setup:



4.3.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 5: Power Spectral Density – Test Results for 802.11a

Test Conditions: Conducted Measurement			Date: July 20, 2017		
Antenna Type: Chip			Power Setting: See test plan.		
Antenna Gain: 4.9 dBi			Signal State: Modulated at 100%, 6 Mbps		
Ambient Temp.: 23 °C			Relative Humidity:35%		
802.11a					
Freq. (MHz)	Output [dBm]	CF [dB]	Total PPD [dBm]	Limit [dBm]	Margin [dB]
5180	-2.82			11.00*	-13.82
5200	-2.70			11.00*	-13.70
5240	-2.77			11.00*	-13.77
5260	-2.79			11.00	-13.79
5300	-2.95			11.00	-13.95
5320	-2.81			11.00	-13.81
5500	-2.48			11.00	-13.48
5580	-2.76			11.00	-13.76
5700	-2.80			11.00	-13.80
5745	-2.45	-3.01	-5.46	30.00	-35.46
5785	-2.57	-3.01	-5.58	30.00	-35.58
5825	-2.49	-3.01	-5.50	30.00	-35.50
802.11a (RSS-247 Limit)					
5180	-2.82			5.10	-7.92
5200	-2.70			5.10	-7.80
5240	-2.77			5.10	-7.87
Note: (*) FCC limit only, 5150-5250 MHz. RSS-247 and CFR47 Part 15.407 have same PPD limit in 5250-5350 MHz, 5470-5725 MHz, and 5725-5850 MHz bands. CF accounted for the measured RBW; 10*log (500kHz/1000kHz) or -3.01 dB. RSS-247 Limit at 5150-5250 MHz is eirp; 10dBm - 4.9dBi = 5.1 dBm					

Table 6: Power Spectral Density – Test Results for 802.11n HT20

Test Conditions: Conducted Measurement			Date: July 20, 2017		
Antenna Type: Chip			Power Setting: See test plan.		
Antenna Gain: 4.9 dBi			Signal State: Modulated at 100%, 6.5 Mbps		
Ambient Temp.: 23 °C			Relative Humidity:35%		
802.11n HT20					
Freq. (MHz)	Output [dBm]	CF [dB]	Total PPD [dBm]	Limit [dBm]	Margin [dB]
5180	-3.09			11.00	-14.09
5200	-3.04			11.00	-14.04
5240	-2.57			11.00	-13.57
5260	-3.27			11.00	-14.27
5300	-2.30			11.00	-13.30
5320	-3.04			11.00	-14.04
5500	-2.87			11.00	-13.87
5580	-3.06			11.00	-14.06
5700	-3.18			11.00	-14.18
5745	-3.08	-3.01	-6.09	30.00	-36.09
5785	-2.63	-3.01	-5.64	30.00	-35.64
5825	-2.85	-3.01	-5.86	30.00	-35.86
802.11n HT20 (RSS-247 Limit)					
5180	-3.09			5.10	-8.19
5200	-3.04			5.10	-8.14
5240	-2.57			5.10	-7.67
Note: (*) FCC limit only, 5150-5250 MHz. RSS-247 and CFR47 Part 15.407 have same PPD limit in 5250-5350 MHz, 5470-5725 MHz, and 5725-5850 MHz bands. CF accounted for the measured RBW; 10*log (500kHz/1000kHz) or -3.01 dB. RSS-247 Limit at 5150-5250 MHz is eirp; 10dBm - 4.9dBi = 5.1 dBm					




Figure 51: FCC-PPSD-5 GHz-5180 MHz-11a-6 Mbps




Figure 52: FCC-PPSD-5 GHz-5200 MHz-11a-6 Mbps




Figure 53: FCC-PPSD-5 GHz-5240 MHz-11a-6 Mbps




Figure 54: FCC-PPSD-5 GHz-5260 MHz-11a-6 Mbps




Figure 55: FCC-PPSD-5 GHz-5300 MHz-11a-6 Mbps




Figure 56: FCC-PPSD-5 GHz-5320 MHz-11a-6 Mbps




Figure 57: FCC-PPSD-5 GHz-5500 MHz-11a-6 Mbps




Figure 58: FCC-PPSD-5 GHz-5580 MHz-11a-6 Mbps




Figure 59: FCC-PPSD-5 GHz-5700 MHz-11a-6 Mbps




Figure 60: FCC-PPSD-5 GHz-5745 MHz-11a-6 Mbps




Figure 61: FCC-PPSD-5 GHz-5785 MHz-11a-6 Mbps




Figure 62: FCC-PPSD-5 GHz-5825 MHz-11a-6 Mbps




Figure 63: FCC-PPSD-5 GHz-5180 MHz-HT20-6.5 Mbps




Figure 64: FCC-PPSD-5 GHz-5200 MHz-HT20-6.5 Mbps




Figure 65: FCC-PPSD-5 GHz-5240 MHz-HT20-6.5 Mbps




Figure 66: FCC-PPSD-5 GHz-5260 MHz-HT20-6.5 Mbps




Figure 67: FCC-PPSD-5 GHz-5300 MHz-HT20-6.5 Mbps




Figure 68: FCC-PPSD-5 GHz-5320 MHz-HT20-6.5 Mbps




Figure 69: FCC-PPSD-5 GHz-5500 MHz-HT20-6.5 Mbps




Figure 70: FCC-PPSD-5 GHz-5580 MHz-HT20-6.5 Mbps




Figure 71: FCC-PPSD-5 GHz-5700 MHz-HT20-6.5 Mbps




Figure 72: FCC-PPSD-5 GHz-5745 MHz-HT20-6.5 Mbps




Figure 73: FCC-PPSD-5 GHz-5785 MHz-HT20-6.5 Mbps




Figure 74: FCC-PPSD-5 GHz-5825 MHz-HT20-6.5 Mbps

4.4 Undesirable Emission Limits

CFR47 15.407 (b) and RSS 247 Sect.6.2.1.2, 6.2.2.2, and 6.2.3.2: The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.


For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

4.4.1 Test Method

The conducted method was used to measure the undesirable emission requirement. The measurement was performed with modulation. This test was conducted on 3 channels of Sample in each mode on Sample. The worst sample result indicated below.

Test Setup:



4.4.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 7: Undesired Emissions for 802.11a – Test Results

Test Conditions: Conducted Measurement				Date: July 20, 2017		
Antenna Type: Chip				Power Setting: See test plan.		
Antenna Gain: 4.9 dBi				Signal State: Modulated at 100%		
Ambient Temp.: 23° C				Relative Humidity: 35%		
Undesired Emissions for 802.11a						
Frequency	Level	Det.	Port	Limit	Margin	Comments
MHz	dBuV/m			cm	dB	
1732.60	-43.46	Pk	RF	-27.00	-16.46	11a, 5180MHz, 6.0Mbps
36963.70	-38.85	Pk	RF	-27.00	-11.85	11a, 5180MHz, 6.0Mbps
1738.60	-43.61	Pk	RF	-27.00	-16.61	11a, 5200MHz, 6.0Mbps
37217.60	-38.69	Pk	RF	-27.00	-11.69	11a, 5200MHz, 6.0Mbps
1743.60	-42.28	Pk	RF	-27.00	-15.28	11a, 5240MHz, 6.0Mbps
37026.70	-38.42	Pk	RF	-27.00	-11.42	11a, 5240MHz, 6.0Mbps
1755.60	-42.39	Pk	RF	-27.00	-15.39	11a, 5260MHz, 6.0Mbps
37012.70	-39.12	Pk	RF	-27.00	-12.12	11a, 5260MHz, 6.0Mbps
1761.60	-40.8	Pk	RF	-27.00	-13.80	11a, 5300MHz, 6.0Mbps
36394.80	-39.5	Pk	RF	-27.00	-12.50	11a, 5300MHz, 6.0Mbps
1773.60	-39.93	Pk	RF	-27.00	-12.93	11a, 5320MHz, 6.0Mbps
36969.70	-38.84	Pk	RF	-27.00	-11.84	11a, 5320MHz, 6.0Mbps
1837.60	-38.57	Pk	RF	-27.00	-11.57	11a, 5500MHz, 6.0Mbps
36438.80	-38.57	Pk	RF	-27.00	-11.57	11a, 5500MHz, 6.0Mbps
3720.20	-41.38	Pk	RF	-27.00	-14.38	11a, 5580MHz, 6.0Mbps
36043.90	-39.35	Pk	RF	-27.00	-12.35	11a, 5580MHz, 6.0Mbps
3800.10	-37.22	Pk	RF	-27.00	-10.22	11a, 5700MHz, 6.0Mbps
37018.70	-38.59	Pk	RF	-27.00	-11.59	11a, 5700MHz, 6.0Mbps
3830.10	-36.95	Pk	RF	-27.00	-9.95	11a, 5745MHz, 6.0Mbps
36595.80	-39.45	Pk	RF	-27.00	-12.45	11a, 5745MHz, 6.0Mbps
3856.10	-39.52	Pk	RF	-27.00	-12.52	11a, 5785MHz, 6.0Mbps
36980.70	-38.95	Pk	RF	-27.00	-11.95	11a, 5785MHz, 6.0Mbps
4846.90	-38.41	Pk	RF	-27.00	-11.41	11a, 5825MHz, 6.0Mbps
38810.30	-39.13	Pk	RF	-27.00	-12.13	11a, 5825MHz, 6.0Mbps
Note: 1. Worst case condition observed at 6.0 Mbps. 2. All out of band emissions are lower than the -27dBm level. 3. 99% OBW emission of 5240 MHz operating channel did not leak into 5250 MHz-5350 MHz band. See Fig. 123. 4. Emissions of UNII3 channels met the band-edge spectrum mask.						

Table 8: Undesired Emissions for 802.11n HT20 – Test Results

Test Conditions: Conducted Measurement				Date: July 17, 2017		
Antenna Type: Chip				Power Setting: See test plan.		
Antenna Gain: 4.9 dBi				Signal State: Modulated at 100%		
Ambient Temp.: 23° C				Relative Humidity: 35%		
Undesired Emissions for 802.11n HT20						
Frequency	Level	Det.	Port	Limit	Margin	Comments
MHz	dBuV/m			cm	dB	
1743.60	-42.46	Pk	RF	-27.00	-15.46	HT20, 5180MHz, 6.5Mbps
39821.00	-39.39	Pk	RF	-27.00	-12.39	HT20, 5180MHz, 6.5Mbps
1736.60	-42.31	Pk	RF	-27.00	-15.31	HT20, 5200MHz, 6.5Mbps
37012.70	-38.12	Pk	RF	-27.00	-11.12	HT20, 5200MHz, 6.5Mbps
1748.60	-41.60	Pk	RF	-27.00	-14.60	HT20, 5240MHz, 6.5Mbps
39740.10	-39.17	Pk	RF	-27.00	-12.17	HT20, 5240MHz, 6.5Mbps
1747.60	-42.39	Pk	RF	-27.00	-15.39	HT20, 5260MHz, 6.5Mbps
36990.70	-38.79	Pk	RF	-27.00	-11.79	HT20, 5260MHz, 6.5Mbps
1771.60	-40.26	Pk	RF	-27.00	-13.26	HT20, 5300MHz, 6.5Mbps
37129.70	-39.50	Pk	RF	-27.00	-12.50	HT20, 5300MHz, 6.5Mbps
1778.60	-39.99	Pk	RF	-27.00	-12.99	HT20, 5320MHz, 6.5Mbps
36529.80	-39.29	Pk	RF	-27.00	-12.29	HT20, 5320MHz, 6.5Mbps
1826.60	-37.99	Pk	RF	-27.00	-10.99	HT20, 5500MHz, 6.5Mbps
36707.70	-39.13	Pk	RF	-27.00	-12.13	HT20, 5500MHz, 6.5Mbps
3720.20	-42.07	Pk	RF	-27.00	-15.07	HT20, 5580MHz, 6.5Mbps
36806.70	-39.90	Pk	RF	-27.00	-12.90	HT20, 5580MHz, 6.5Mbps
3800.10	-38.14	Pk	RF	-27.00	-11.14	HT20, 5700MHz, 6.5Mbps
36606.80	-39.21	Pk	RF	-27.00	-12.21	HT20, 5700MHz, 6.5Mbps
3830.10	-37.65	Pk	RF	-27.00	-10.65	HT20, 5745MHz, 6.5Mbps
37194.60	-37.63	Pk	RF	-27.00	-10.63	HT20, 5745MHz, 6.5Mbps
3856.10	-37.75	Pk	RF	-27.00	-10.75	HT20, 5785MHz, 6.5Mbps
37012.70	-38.88	Pk	RF	-27.00	-11.88	HT20, 5785MHz, 6.5Mbps
3887.94	-33.39	Pk	RF	-27.00	-6.39	HT20, 5825MHz, 6.5Mbps
4846.29	-29.37	Pk	RF	-27.00	-2.37	HT20, 5825MHz, 6.5Mbps
Note: 1. Worst case condition observed at 6.5 Mbps. 2. All out of band emissions are lower than the -27dBm level. 3. 99% OBW emission of 5240 MHz operating channel did not leak into 5250 MHz-5350 MHz band. See Fig. 124. 4. Emissions of UNII3 channels met the band-edge spectrum mask.						




Figure 75: Measured Band-edge for 802.11a-6 Mbps at 5180 MHz




Figure 76: Undesirable Emission for 802.11a-6 Mbps at 5180 MHz




Figure 77: Measured Band-edge for 802.11a-6 Mbps at 5200 MHz




Figure 78: Undesirable Emission for 802.11a-6 Mbps at 5200 MHz




Figure 79: Measured In-Band Band-edge for 802.11a-6 Mbps at 5240 MHz




Figure 80: Measured In-Band Band-edge for 802.11a-6 Mbps at 5240 MHz




Figure 81: Measured Band-edge for HT20-MCS0 at 5180 MHz




Figure 82: Undesirable Emission for HT20-MCS0 at 5180 MHz




Figure 83: Measured In-Band Band-edge for HT20-MCS0 at 5200 MHz




Figure 84: Measured In-Band Band-edge for HT20-MCS0 at 5200 MHz




Figure 85: Measured Band-edge for HT20-MCS0 at 5240 MHz




Figure 86: Undesirable Emission for HT20-MCS0 at 5240 MHz




Figure 87: Measured Band-edge for 802.11a-6 Mbps at 5260 MHz




Figure 88: Undesirable Emission for 802.11a-6 Mbps at 5260 MHz




Figure 89: Measured Band-edge for 802.11a-6 Mbps at 5300 MHz




Figure 90: Undesirable Emission for 802.11a-6 Mbps at 5300 MHz




Figure 91: Measured In-Band Band-edge for 802.11a-6 Mbps at 5320 MHz




Figure 92: Measured In-Band Band-edge for 802.11a-6 Mbps at 5320 MHz




Figure 93: Measured Band-edge for HT20-MCS0 at 5260 MHz




Figure 94: Undesirable Emission for HT20-MCS0 at 5260 MHz




Figure 95: Measured In-Band Band-edge for HT20-MCS0 at 5300 MHz




Figure 96: Measured In-Band Band-edge for HT20-MCS0 at 5300 MHz




Figure 97: Measured Band-edge for HT20-MCS0 at 5320 MHz




Figure 98: Undesirable Emission for HT20-MCS0 at 5320 MHz




Figure 99: Measured Band-edge for 802.11a-6 Mbps at 5500 MHz




Figure 100: Undesirable Emission for 802.11a-6 Mbps at 5550 MHz




Figure 101: Measured Band-edge for 802.11a-6 Mbps at 5580 MHz




Figure 102: Undesirable Emission for 802.11a-6 Mbps at 5580 MHz




Figure 103: Measured In-Band Band-edge for 802.11a-6 Mbps at 5700 MHz




Figure 104: Measured In-Band Band-edge for 802.11a-6 Mbps at 5700 MHz




Figure 105: Measured Band-edge for HT20-MCS0 at 5500 MHz




Figure 106: Undesirable Emission for HT20-MCS0 at 5500 MHz




Figure 107: Measured In-Band Band-edge for HT20-MCS0 at 5580 MHz




Figure 108: Measured In-Band Band-edge for HT20-MCS0 at 5580 MHz




Figure 109: Measured Band-edge for HT20-MCS0 at 5700 MHz




Figure 110: Undesirable Emission for HT20-MCS0 at 5700 MHz




Figure 111: Measured Band-edge for 802.11a-6 Mbps at 5745 MHz




Figure 112: Undesirable Emission for 802.11a-6 Mbps at 5745 MHz




Figure 113: Measured Band-edge for 802.11a-6 Mbps at 5785 MHz




Figure 114: Undesirable Emission for 802.11a-6 Mbps at 5785 MHz




Figure 115: Measured In-Band Band-edge for 802.11a-6 Mbps at 5825 MHz




Figure 116: Measured In-Band Band-edge for 802.11a-6 Mbps at 5825 MHz




Figure 117: Measured Band-edge for HT20-MCS0 at 5745 MHz




Figure 118: Undesirable Emission for HT20-MCS0 at 5745 MHz




Figure 119: Measured In-Band Band-edge for HT20-MCS0 at 5785 MHz




Figure 120: Measured In-Band Band-edge for HT20-MCS0 at 5785 MHz




Figure 121: Measured Band-edge for HT20-MCS0 at 5825 MHz




Figure 122: Undesirable Emission for HT20-MCS0 at 5825 MHz




Figure 123: Measured Band-edge for 11a-6 Mbps at 5240 MHz




Figure 124: Measured Band-edge for HT20-MCS0 at 5240 MHz

Note: Since the 99% bandwidth emission did not cross over into the UNII2a band, DFS is not required for 5240 MHz operating channel.