

# Emissions Test Report

EUT Name:Wireless Audio HeadsetModel No.:Stealth 700X Gen 2CFR 47 Part 15.407 2020 and RSS 247:2017

Prepared for:

Voyetra Turtle Beach, Inc. 100 Summit Lake Drive, Suite 100 Valhalla, New York 10595 USA

Prepared by:

TUV Rheinland of North America, Inc. 1279 Quarry Lane Pleasanton, CA 94566 Tel: (925) 249-9123 Fax: (925) 249-9124 http://www.tuv.com/

Report/Issue Date:	October 1, 2020
Job #	234157363
Report Number:	32063007.001

# Revisions

Revision No.	Date MM/DD/YYYY	Reason for Change	Author
0	10/01/2020	Original Document	N/A

Note: Latest revision report will replace all previous reports.

# **Statement of Compliance**

Manufacturer: Requester / Applicant:	Voyetra Turtle Beach, Inc. 100 Summit Lake Drive, Suite 100 Valhalla, New York 10595 USA (530) 277-3482 Tim Blaney
Name of Equipment:	Wireless Audio Headset
Model No.	Stealth 700X Gen 2 (TB300-2780-01)
Type of Equipment:	Intentional Radiator
Application of Regulations:	CFR 47 Part 15.407 2020 and RSS 247: 2017
Test Dates:	May 14, 2020 to September 30, 2020

Guidance Documents:

Emissions: ANSI C63.10-2013, KDB 789033 D02 General UNII Test Procedures New Rules v02r01

### Test Methods:

Emissions: ANSI C63.10-2013, KDB 789033 D02 General UNII Test Procedures New Rules v02r01

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report contains data that are not covered by A2LA accreditation. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.



1 E	Executive Summary	7
1.1	Scope	7
1.2	Purpose	7
1.3	Summary of Test Results	8
1.4	Special Accessories	8
1.5	Equipment Modifications	8
2 L	Laboratory Information	9
<b>2.1</b> 2 2 2 2 2 2	Accreditations & Endorsements   2.1.1 US Federal Communications Commission   2.1.2 NIST / A2LA   2.1.3 Canada   2.1.4 Japan – VCCI   2.1.5 Acceptance by Mutual Recognition Arrangement	9 9 9 9 9 9 9 9 9
<b>2.2</b> 2 2	Test Facilities   2.2.1 Emission Test Facility   2.2.2 Immunity Test Facility	<b>10</b> 1010101010
<b>2.3</b> 2 2	Measurement Uncertainty	10 11 11
2.4	Calibration Traceability	12
3 F	Product Information	13
3.1	Product Description	13
3.2	Equipment Configuration	13
3.3	Operating Mode	13
<b>3.4</b> 3	Unique Antenna Connector	<b>14</b> 14
<b>3.5</b> 3	Duty Cycle     3.5.1   Results	<b>15</b> 15
4 E	Emissions	18
<b>4.1</b> 4 4	Output Power Requirements	18 18 19
<b>4.2</b> 4 4	Occupied Bandwidth   4.2.1 Test Method   4.2.2 Results	<b>35</b> 35 35
<b>4.3</b> 4 4	Power Spectral Density   4.3.1 Test Method   4.3.2 Results	<b>52</b> 52 52
<b>4.4</b> 4	Undesirable Emission Limits	<b>67</b>

4.4.2 F	Results	68
4.5 Tra	ansmitter Spurious Emissions	95
4.5.1 7	Test Methodology	95
4.5.2	Fransmitter Spurious Emission Limit	96
4.5.3 F	Results	96
4.6 AC	Conducted Emissions	167
4.6.1 7	Test Methodology	167
4.6.2	Sest Results	167
4.7 Fre	equency Stability	172
4.7.1 7	Fest Methodology	172
4.7.2 N	Manufacturer Declaration	172
4.7.3 I	imit	172
4.7.4	est results:	172
4.8 Vo	Itage Variation	175
4.8.1 7	Test Methodology	175
4.8.2 7	Cest results	175
5 Test Eq	uipment List	177
5.1 Eq	uipment List	177
6 <b>EMC T</b>	lest Plan	178
6.1 Int	roduction	178
6.2 Cu	stomer	178
6.3 Eq	uipment Under Test (EUT)	179
6.4 Tes	st Specifications	182

Table 1: Summary of Test Results	
Table 2: RF Output Power at the Antenna Port – Test Results per FCC	19
Table 3: RF Output Power at the Antenna Port – Test Results per RSS-247	21
Table 4: Occupied Bandwidth – Test Results	
Table 5: Power Spectral Density – Test Results for 802.11a.	53
Table 6: Power Spectral Density – Test Results for 802.11n HT20	54
Table 7: Undesired Emissions for 802.11a – Test Results	68
Table 8: Undesired Emissions for 802.11n HT20 – Test Results	69
Table 9: Transmit Spurious Emission at Band-Edge Requirements	97
Table 10: Transmit Spurious Emission at Band-Edge Requirements Continued	
Table 11: Transmit Spurious Emission at Band-Edge Requirements Continued	99
Table 12: AC Conducted Emissions – Test Results	167
Table 13: Frequency Stability – Test Results	173
Table 14: Voltage Variation – Test Results	175
Table 15: Customer Information	178
Table 16: Technical Contact Information	178
Table 17: EUT Specifications	179
Table 18: Antenna Information	179
Table 19: EUT Channel Power Specifications	
Table 20: Interface Specifications	
Table 21: Supported Equipment	
Table 22: Description of Sample used for Testing	
Table 23: Description of Test Configuration used for Radiated Measurement.	
Table 24: Test Specifications	

# 1 Executive Summary

# 1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.407 2020 and RSS 247: 2017 based on the results of testing performed on May 14, 2020 to September 30, 2020 on the Wireless Audio Headset Model Stealth 700X Gen 2 manufactured by Voyetra Turtle Beach, Inc. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

# 1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report. The 5180 MHz – 5320 MHz, 5500 MHz – 5700 MHz, and 5745 MHz – 5825 MHz frequency bands are covered in this document.

# 1.3 Summary of Test Results

Table 1:	Summary	of Tes	t Results
----------	---------	--------	-----------

Test	Test Method ANSI C63.10:2013	Test Parameters	Measured Value	Result
Duty Cycle	Information Only	N/A	100%	N/A
Spurious Emission in Transmitted Mode	CFR47 15.209, CFR47 15.407 (b) RSS-GEN Sect.8.9, RSS 247 Sect. 6.2.1.2	Class B	-1.72 dB Margin	Complied
Restricted Bands of Operation	CFR47 15.205, RSS GEN Sect.8.10	Class B		Complied
ACPower Conducted Emission	CFR47 15.207, RSS-GEN Sect.8.8	Class B	-17.06 dB Margin	Complied
Occupied Bandwidth	CFR47 15.407 (a) & (e), RSS GEN Sect.6.7, RSS-247 Sect.6.2.4.1	DTS ≥ 500 kHz	99% BW: 16.65 MHz 26dB BW: 22.12 MHz DTS BW: 16.49 MHz	Complied
Maximum Output Power	CFR47 15.407 (a) RSS 247 Sect. 6.2	UNII1: 250mW UNII2a: 250mW UNII2c: 250mW UNII3: 1W	UNII1: 5.44dBm/ 3.5mW UNII2a: 5.30dBm/ 3.4mW UNII2c: 5.25dBm/ 3.3mW UNII3: 5.27dBm/ 3.4mW	Complied
Power Spectral Density	CFR47 15.407 (a) RSS 247 Sect. 6.2 (UNII2a, UNII2c & UNII3)	< 11 dBm/MHz < 30 dBm/ 500 kHz	UNII1: -5.02 dBm/ MHz UNII2a: -5.38 dBm/ MHz UNII2c: -5.10 dBm/ MHz UNII3: -7.55 dBm/ 500kHz	Complied
	RSS 247 Sect.6.2.1.1	<10 dBm/MHz (e.i.r.p)	UNII1: -5.02 dBm/ MHz	Complied
Conducted Emission –	CFR47 15.407 (b)(1) (2)(3) RSS 247 Sect.6.2.1 to 6.2.3	<-27 dBm/MHz	-9.65 dB Margin	Complied
AntennaPort	CFR47 15.407 (b)(4) RSS 247 Sect.6.2.4	SpectrumMask	-9.76 dB Margin	Complied
Frequency Stability	CFR47 15.407 (g), RSS GEN Sect. 6.11	±20 ppm	5.42 ppm	Complied
Voltage Variation	CFR47 15.31(e) RSS-Gen Sect. 6.11	±20 ppm	3.87 ppm	Complied

# 1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

# 1.5 Equipment Modifications

None

#### Laboratory Information 2

#### Accreditations & Endorsements 2.1

#### 2.1.1 **US Federal Communications Commission**



TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 is recognized by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and accepted by the FCC (US1131). The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, and 90. The accreditation is updated every 3 years.

# 2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:2017 and ISO 9002 (Lab Code

Testing Cert #3331.02). The scope of laboratory accreditation includes emission and immunity testing. The accreditation is updated annually.

### 2.1.3 Canada



TUV Rheinland of North America at the 1279 Quarry Ln, Pleasanton, CA 94566 address is accredited by Industry Canada for performing testing services for

the general public on a fee basis. This laboratory test facilities have been fully described in reports submitted to and accepted by Industry Canada (File Number 2932M). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

# 2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from

Information Technology Equipment, and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0326

#### Acceptance by Mutual Recognition Arrangement 2.1.5



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member

country.

# 2.2 Test Facilities

All of the test facilities are located at 1279 Quarry Lane, Pleasanton, California 94566, USA.

# 2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 and 5 meters. The site is listed with the FCC and accredited by A2LA (Lab Code Testing Cert #3331.02). The 3/5-meter semi-anechoic chamber used to collect the radiated data has been verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 meters. The site is listed with the FCC and accredited by A2LA (Lab Code Testing Cert #3331.02). The 3/5-meter semi-anechoic chamber used to collect the radiated data has been verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2014, at a test distance of 3 meter and 5 meters. A report detailing this site can be obtained from TUV Rheinland of North America.

# 2.2.2 Immunity Test Facility

ESD, EFT, Surge, PQF: These tests are performed in an environmentally controlled room with a 3.7 m x 4.8 m x 3.175 mm thick aluminum floor connected to PE ground.

For ESD testing, tabletop equipment is placed on an insulated mat with a surface resistivity of  $10^9$  Ohms/square on a 1.6 m x 0.8 m x 0.8 m high non-conductive table with a 3.175 mm aluminum top (Horizontal Coupling Plane). The HCP is connected to the main ground plane via a low impedance ground strap through two 470-k $\Omega$  resistors. The Vertical Coupling Plane consists of an aluminum plate 50 cm x 50 cm x 3.175 mm thick. The VCP is connected to the main ground plane via a low impedance ground strap through two 470-k $\Omega$  resistors.

For EFT, Surge, PQF, the HCP and VCP are removed.

RF Field Immunity testing is performed in a 7.3m x 4.3m x 4.1m anechoic chamber.

RF Conducted and Magnetic Field Immunity testing is performed on a 4.8m x 3.7m x 3.175mm thick aluminum ground plane.

All test areas allow a minimum distance of 1 meter from the EUT to walls or conducting objects.

# 2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1<sup>st</sup> Edition, 1995.

*The Combined Standard Uncertainty* is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

# 2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

Field Strength  $(dB\mu V/m) = RAW - AMP + CBL + ACF$ 

Where:  $RAW = Measured level before correction (dB\mu V)$ 

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu V/m = 10^{\frac{dB\mu V/m}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor-Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

25 dBuV/m + 17.5 dB - 20 dB + 1.0 dB = 23.5 dBuV/m

### 2.3.2 Measurement Uncertainty

Per CISPR 16-4-2	Ulab	Ucispr
Radiated Disturbance @ 1	10 meters	
30 – 1,000 MHz	2.25 dB	4.51 dB
Radiated Disturbance @ 3	3 meters	
30 – 1,000 MHz	2.26 dB	4.52 dB
1 – 6 GHz	2.12 dB	4.25 dB
6 – 40 GHz	2.47 dB	4.93 dB
Conducted Disturbance	) Mains Terminals	
150 kHz – 30 MHz	1.09 dB	2.18 dB
Disturbance Power		
30 MHz- 300 MHz	3.92 dB	4.3 dB

#### Voltech PM6000A

The estimated combined standard uncertainty for harmonic current and flicker measurements is $\pm$	Per CISPR 16-4-2
5.0%.	Methods

### Measurement Uncertainty - EMC Immunity

The estimated combined standard uncertainty for ESD immunity measurements is $\pm$ 8.2%.	Per IEC 61000-4-2
The estimated combined standard uncertainty for radiated immunity measurements is $\pm 4.10$ dB.	Per IEC 61000-4-3
The estimated combined standard uncertainty for conducted immunity measurements with CDN is $\pm3.66~dB$	Per IEC 61000-4-6
The estimated combined standard uncertainty for power frequency magnetic field immunity is $\pm$ 2.9%.	Per IEC 61000-4-8
The estimated combined standard uncertainty for EFT fast transient immunity measurements is $\pm$ 2.6%.	Per IEC 61000-4-4
The estimated combined standard uncertainty for surge immunity measurements is $\pm 2.6\%$ .	Per IEC 61000-4-5
The estimated combined standard uncertainty for voltage variation and interruption measurements is $\pm 1.74\%$ .	Per IEC 61000-4-11

### Measurement Uncertainty – Radio Testing

The estimated combined standard uncertainty for frequency error measurements is $\pm 3.88$ Hz
The estimated combined standard uncertainty for carrier power measurements is $\pm 0.70$ dB.
The estimated combined standard uncertainty for adjacent channel power measurements is $\pm 1.47$ dB.
The estimated combined standard uncertainty for modulation frequency response measurements is $\pm 0.46$ dB.
The estimated combined standard uncertainty for transmitter conducted emission measurements is $\pm 2.06$ dB

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

### 2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Standard 17025:2017. Equipment calibration records are kept on file at the test facility.

# 3 **Product Information**

# 3.1 Product Description

The Stealth 700X Gen 2 is a completely wireless Xbox One audio gaming headset. It wirelessly connects directly to the Xbox One and future Xbox consoles over a 2.4 or 5.0 GHz Wi-Fi link. The headset also contains a Bluetooth radio for communication with other mobile devices. The functionality in the headset consists of 50mm speaker drivers, a flip up non-removable microphone, microphone monitoring and game/chat mix controls on the headset. Additionally, it has a ProSpecs alternative glasses relief ear pad design. With the Microsoft integrated radio module, this headset is also capable of working with compatible Windows PCs in the future.

# 3.2 Equipment Configuration

A description of the equipment configuration is given in the Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of an EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

# 3.3 Operating Mode

A description of the operation mode is given in the Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

The final operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

# 3.4 Unique Antenna Connector

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

# 3.4.1 Results

The Stealth 700X Gen 2 uses a dual band Unictron chip antenna for the 2.4 GHz and 5150 MHz to 5850 MHz bands. The chip antenna is integrated onto the PCB. It has a maximum peak gain of 3.3 dBi in the 2.4 GHz band and 3.7 dBi in the 5150 MHz to 5850 MHz bands.

There is an additional antenna specification available in the submittal package.



# 3.5 Duty Cycle

The Stealth 700X Gen 2, SN: PP1 was measured for the duty cycle

# 3.5.1 Results

Mode	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Factor (dB)			
802.11a	100	0	100	0			
802.11n HT20	100	0	100	0			
<b>Notes:</b> EUT configured and measured for the duty cycle. All measurements use 100% duty cycle.							

Agile	Agilent Spectrum Analyzer - Swept SA										
LXI	Т	RF PRES	EL 50Ω AC			SENSE:INT	AL	IGNAUTO		05:08:5	i4 PM Jul 13, 2020
Cer	nter	Freq 5	.50000000	<mark>)0 GHz</mark> וי	NO: Wide 🖵 Gain:Low	Trig: Free #Atten: 30	Run dB	Avg Type: I	Log-Pwr	TF	ACE 1 2 3 4 5 6 YPE WWWWWWW DET P N N N N N
10 d	B/div	Ref	10.00 dBm	l						Mkr1 -16	50.00 ms 5.61 dBm
LOG											
0.00					P	9	· · · · · · · · · · · · · · · · · · ·			P	
-10.0											
20.0	WHM	WMWWW	nt Manual	My why want had	1-14/1/white	Wilhymprifille	university	1444/white	will white the	happhphip	when white
-20.0		01							- 10 - A	in Cali	
-30.0	-										
-40.0	_										
-50.0											
-60.0											
-70.0	-										
-80.0											
Cen Res	Center 5.500000000 GHz Span 0 Hz										
MSG								STATUS	2000		(1001 pto)

Figure 1: Duty Cycle for 802.11a

Agile	Agilent Spectrum Analyzer - Swept SA										
LXI	Т	RF PRES	EL 50 Ω AC			SENSE:INT	AL	IGNAUTO	- i samo da 🕳 cina di	05:13:1	5 PM Jul 13, 2020
Cer	nter	Freq 5	.5000000	00 GHz	PNO: Wide 🕞 FGain:Low	) Trig: Free #Atten: 30	Run dB	Avg Type:	Log-Pwr	Th	ACE 123456 YPE WWWWWWW DET P NNNNN
10 d	B/div	Ref	10.00 dBm	ı						Mkr1 -17	50.00 ms /.37 dBm
LOG											
0.00	-					· · · · · · · · · · · · · · · · · · ·					
-10.0	_										
-20.0	mhn	Uniperal	MAN MITHING	my many many	h have here have	www.willing	wandhike	home hours	WWWWWW	Mar Manual Mark	NI-4-MIN
-30.0											
-40.0	-										
-50.0	-										
-60.0	-										
-70.0	-										
-80.0											
Cer Res	nter 5 BW	5.50000 100 kH	00000 GHz Iz Cycle-11a.pn	g> saved	#VB	W 100 kHz		STATUS	Sweep	o 100.0 ms	Span 0 Hz (1001 pts)

Figure 2: Duty Cycle for 802.11n HT20

# 4 Emissions

Testing was performed in accordance with CFR 47 Part 15.407: 2020 and RSS 247: 2017. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in section 8 of the standard were used.

# 4.1 Output Power Requirements

The maximum output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.

The maximum transmitted power limits per CFR47 Part 15.407 and RSS-247 are

Part 15.407(a)(1)(iv) – Band 5150-5250 MHz: 250 mW.

Part 15.407(a)(2) – Band 5250-5350 MHz, 5470-5725 MHz: 250 mW or 11 dBm + 10Log B.

Part 15.407(a)(3) - Band 5725-5825 MHz:1 W

*RSS* 247 Sect. 6.2.1.1 – Band 5150-5250 MHz (e.i.r.p.): 200 mW or 10 + 10Log(B)

RSS 247 Sect. 6.2.2.1 – Band 5250-5350 MHz, 5470-5725 MHz: 250 mW or 11 dBm + 10Log B

RSS 247 Sect. 6.2.2.1, 6.2.3.1 – Band 5250-5350 MHz, 5470-5725 MHz: 250 mW or 11 dBm + 10Log B.

RSS 247 Sect. 6.242.1 – Band 5725-5850 MHz: 1 W

Note: B is the 99% emission bandwidth.

# 4.1.1 Test Method

The ANSI C63.10-2013 Section 12.3.2.2 conducted method was used to measure the channel power output. The preliminary investigation was performed at different data rate/ chain to determine the highest power output for each mode. The worst findings were conducted on 3 channels in each operating range per CFR47 Part 15.407(a) and RSS 247 Sect. 6.2.1.1. The worst mode results indicated below.

Test Setup:



Method SA-1 of "KDB 789033 D02 – Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices" applies since the EUT continuously transmit; where duty cycle is greater than 98%. Sample detector was used.

# 4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Date: July 13, 2020			Tested By: Jeremy Luong				
Test Method:	Test Method: Conducted Measurements			Power Setting: See test plan.			
Antenna Typ	e: Chip		Antenna Gain: +	-3.7 dBi			
Operating M	ode: Uncorrelat	ed	Signal State: Mo	dulated at 100%			
Ambient Ten	<b>пр.:</b> 23 °С		Relative Humidi	ty: 38%			
		802.11a at 6	Mbps (FCC Limit)	)			
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]		
5180	23.98	5.44			-18.54		
5200	23.98	5.00			-18.98		
5240	23.98	5.17			-18.81		
5260	23.98	4.89			-19.09		
5300	23.98	5.07			-18.91		
5320	23.98	4.87			-19.11		
5500	23.98	5.25			-18.73		
5580	23.98	4.94			-19.04		
5700	23.98	5.08			-18.90		
5745	30.00	5.27			-24.73		
5785	30.00	5.17			-24.83		
5825	30.00	5.08			-24.92		
Note: The hea Worst	idset is a client o case was observ	levice. ved at 6 Mbps.					

Table 2: RF Output Power at the Antenna Port – Test Results per FCC

802.11n HT20 at 6.5 Mbps (FCC Limit)							
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]		
5180	23.98	5.17			-18.81		
5200	23.98	5.11			-18.87		
5240	23.98	5.35			-18.63		
5260	23.98	5.11			-18.87		
5300	23.98	5.30			-18.68		
5320	23.98	5.11			-18.87		
5500	23.98	4.98			-19.00		
5580	23.98	5.20			-18.78		
5700	23.98	4.90			-19.08		
5745	30.00	4.88			-25.12		
5785	30.00	5.07			-24.93		
5825	30.00	5.03			-24.97		
Note: The hea Worst of	ndset is a client of case was observ	levice. red at 6.5 Mbps.					

Table 3: RF Output Power at the Antenna Port – Test Results per RSS-247							
Date: July 13	, 2020		Tested By: Jeremy Luong				
Test Method:	Conducted Me	asurements	Power Setting	Power Setting: See test plan.			
Antenna Typ	e: Chip		Antenna Gain	1: +3.7 dBi			
Operating M	ode: Uncorrelate	ed	Signal State: ]	Modulated at 100%	/0		
Ambient Ten	<b>пр.:</b> 23 °С		Relative Hum	idity: 38%			
		802.11a at 6 Mbp	s (RSS-247 Lim	it)			
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]		
5180	19.30	5.44			-13.86		
5200	19.30	5.00			-14.30		
5240	19.30	5.17			-14.13		
5260	23.98	4.89			-19.09		
5300	23.98	5.07			-18.91		
5320	23.98	4.87			-19.11		
5500	23.98	5.25			-18.73		
5580	23.98	4.94			-19.04		
5700	23.98	5.08			-18.90		
5745	30.00	5.27			-24.73		
5785	30.00	5.17			-24.83		
5825	30.00	5.08			-24.92		
Note: The he Worst For 51	adset is a client case was observ 50 – 5250 MHz,	device. ved at 6 Mbps. , RSS-247 Limit =	23 dBm – 3.7 dE	Bi = 19.30 dBm			
1	802	.11n HT20 at 6.5	Mbps (RSS-247	Limit)			
(MHz)	[dBm]	[dBm]	[dB]	∑ Power [dBm]	Margin [dB]		
5180	19.30	5.17			-14.13		
5200	19.30	5.11			-14.19		
5240	19.30	5.35			-13.95		
5260	23.98	5.11			-18.87		
5300	23.98	5.30			-18.68		

5320	23.98	5.11			-18.87	
5500	23.98	4.98			-19.00	
5580	23.98	5.20			-18.78	
5700	23.98	4.90			-19.08	
5745	30.00	4.88			-25.12	
5785	30.00	5.07			-24.93	
5825	30.00	5.03			-24.97	
Note: The headset is a client device. Worst case was observed at 6.5 Mbps. For 5150 – 5250 MHz, RSS-247 Limit = 23 dBm – 3.7 dBi = 19.30 dBm						





Figure 3: Conducted Output Power-5180 MHz-802.11a-6 Mbps

Figure 4: Conducted Output Power -5200 MHz-802.11a-6 Mbps







Figure 6: Conducted Output Power-5260 MHz-802.11a-6 Mbps



Figure 7: Conducted Output Power-5300 MHz-802.11a-6 Mbps



Figure 8: Conducted Output Power-5320 MHz-802.11a-6 Mbps







Figure 10: Conducted Output Power-5580 MHz-802.11a-6 Mbps







Figure 12: Conducted Output Power-5745 MHz-802.11a-6 Mbps







Figure 14: Conducted Output Power-5825 MHz-802.11a-6 Mbps







Figure 16: Conducted Output Power -5200 MHz-802.11n HT20-6.5 Mbps







Figure 18: Conducted Output Power-5260 MHz-802.11n HT20-6.5 Mbps







Figure 20: Conducted Output Power-5320 MHz-802.11n HT20-6.5 Mbps







Figure 22: Conducted Output Power-5580 MHz-802.11n HT20-6.5 Mbps







Figure 24: Conducted Output Power-5745 MHz-802.11n HT20-6.5 Mbps







Figure 26: Conducted Output Power-5825 MHz-802.11n HT20-6.5 Mbps

# 4.2 Occupied Bandwidth

The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.

The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.

The 26 dB bandwidth is defined the bandwidth of 26 dBr from highest transmitted level of the fundamental frequency.

The minimum 6 dB bandwidth shall be at least 500 kHz per Section CFR47 15.407(e) 2017 and RSS 247 Sect.6.2.4.1: 2017

There is no restriction limits for the bandwidth. The 26 dB bandwidth was used to determine the limit for maximum conducted output power per CFR47 Part 15.407(a).

# 4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth. The measurement was performed with modulation per CFR47 15.407(a)&(e), RSS Gen Sect.6.7 and RSS-247 Sect.6.2.4.1. The preliminary investigation was performed to find the narrowest 26 dB bandwidth for each operational mode at different data rates. This worst finding was performed on 3 channels in each operating frequency range. The worst results indicated below.

Test Setup:



### 4.2.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 4:	Occupied Bandwidth – Test Results
----------	-----------------------------------

Date: July 13, 2020		Tested	Tested By: Jeremy Luong				
Test Method: Cond	ucted Measurements	Power	Power Setting: See test plan.				
Antenna Type: Chi	р	Anten	na Gain: +3.7 dBi				
<b>Operating Mode:</b> U	Incorrelated	Signal	State: Modulated at 100	%			
Ambient Temp.: 23	3 ℃	Relativ	ve Humidity: 34%				
	Band	width (MHz) for	802.11a				
Frequency (MHz)	Limit (kHz)	99% BW	26 dB BW	Results			
5180	NA	16.651	23.160	NA			
5200	NA	16.654	22.420	NA			
5240	NA	16.646	23.330	NA			
5260	NA	16.640	22.190	NA			
5300	NA	16.632	22.120	NA			
5320	NA	16.646	22.71	NA			
5500	NA	16.639	23.180	NA			
5580	NA	16.639	22.400	NA			
5700	NA	16.660	22.960	NA			
Frequency (MHz)	Limit (kHz)	99% BW	6 dB BW	Results			
5745	500	16.659	16.487	Pass			
5785	500	16.673	16.517	Pass			
5825	500	16.682	16.522	Pass			
Note: The bandwidth was measured at 6 Mbps for 802.11a mode. The 99% bandwidth measurements are informative and 26 dB bandwidths are used to determine the output power limits.							
Bandwidth (MHz) for 802.11n HT20							
Frequency (MHz)	Limit (kHz)	99% BW	26 dB BW	Results			
5180	NA	17.772	23.920	NA			
5200	NA	17.755	23.320	NA			
5240	NA	17.756	23.300	NA			

Report Number: 32063007.001 EUT: Wireless Audio Headset Model: Stealth 700X Gen 2 Date: October 1, 2020. EMC / Rev0 FCC ID: XGB-TB2780, IC: 3879-2780

5260	NA	17.762	23.380	NA		
5300	NA	17.769	23.600	NA		
5320	NA	17.746	23.670	NA		
5500	NA	17.764	23.610	NA		
5580	NA	17.776	24.190	NA		
5700	NA	17.773	23.600	NA		
Frequency (MHz)	Limit (kHz)	99% BW	6 dB BW	Results		
5745	500	17.772	17.682	Pass		
5785	500	17.786	17.712	Pass		
5825	500	17.800	17.697	Pass		
Note: The bandwidth was observed at MCS0, 6.5Mbps mode. The 99% bandwidth measurements are informative and 26 dB bandwidths are used to determine the output power limits.						







Figure 28: Occupied Bandwidth-5200 MHz-802.11a



Figure 30: Occupied Bandwidth-5260 MHz-802.11a



Figure 31: Occupied Bandwidth-5300 MHz-802.11a



Figure 32: Occupied Bandwidth-5320 MHz-802.11a