

Emissions Test Report

EUT Name: USB Wireless Audio Transmitter **Model No.:** Ear Force Stealth 450 TX CFR 47 Part 15.247:2015 and RSS 210:2010

Prepared for:

Voyetra Turtle Beach, Inc. 100 Summit Lake Drive, Suite 100 Valhalla, New York 10595 USA

Prepared by:

TUV Rheinland of North America, Inc. 1279 Quarry Lane Pleasanton, CA 94566 Tel: (925) 249-9123 Fax: (925) 249-9124 http://www.tuv.com/

Report/Issue Date:	June 8, 2015
Report Number:	31561425.001
Revision Number:	0
Project Number:	0000126477

Statement of Compliance

Manufacturer:	Voyetra Turtle Beach, Inc.
	100 Summit Lake Drive, Suite 100
	Valhalla, New York 10595 USA
Requester / Applicant:	Tim Blaney
	(530) 277-3482
Name of Equipment:	USB Wireless Audio Transmitter
Model No.	Ear Force Stealth 450 TX (TB300-6161-01)
<i>Type of Equipment:</i>	Intentional Radiator
Application of Regulations:	CFR 47 Part 15.247:2015 and RSS 210:2010
Test Dates:	March 15, 2015 to May 28, 2015

Guidance Documents:

Issue Date: June 8, 2015

Emissions: ANSI C63.10: 2009, KDB 558074 D01 DTS Measurement Guidance v03r01

Test Methods:

Emissions: ANSI C63.10: 2009, KDB 558074 D01 DTS Measurement Guidance v03r01

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report contains data that are not covered by A2LA accreditation. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.

Jeremy Luong	June 8, 2015	David	Spencer	June	e 8, 2015	
Test Engineer	Date	Labora	tory Signatory	Date	e	
		F©	I+I	Industry Canada	Industrie Canada	
ŗ	Festing Cert #3331.02	US5254	2	2932M-2	1	
Report Number	:: 31561425.001	ar Force Stealth /5	n TX			Page 2 of 54

FCCID: XGB-TB6161, IC: 3879A-6161

1 Executive Summary	
1.1 Scope	6
1.2 Purpose	6
1.3 Summary of Test Results	6
1.4 Special Accessories	7
1.5 Equipment Modifications	7
2 Laboratory Information	
2.1 Accreditations & Endorsements	8
2.1.1 US Federal Communications Commission	8
2.1.2 NIST / A2LA 2.1.3 Canada – Industry Canada	
2.1.4 Japan – VCCI	8
2.1.5 Acceptance by Mutual Recognition Arrangement	9
2.2 Test Facilities	9
2.2.1 Emission Test Facility	9
2.2.2 Immunity Test Facility	9
2.3 Measurement Uncertainty	
2.3.1 Sample Calculation – radiated & conducted emissions 2.3.2 Measurement Uncertainties	
2.4 Calibration Traceability	
3 Product Information	
3.1 Product Description	
3.2 Fauinment Configuration	12
3.3 Operating Mode	
3.4 Unique Antenna Connector	
1 Emissions	11
4.1 Output Power Requirements	14
4.1.2 Results	
4.2 Occupied Bandwidth	19
4.2.1 Test Method	
4.2.2 Results	20
4.3 Out-of-Band Emissions	
4.3.1 Test Method	
4.3.2 Test Result	
4.4 Peak Power Spectral Density	
4.4.1 1 est Method 4.4.2 Results	
4.5 Maximum Permissible Exposure	

4	4.5.1	Test Methodology	
4	4.5.2	RF Exposure Limit	32
4	4.5.3	EUT Operating Condition	32
4	4.5.4	Classification	
4	4.5.5	Test Results	
4	4.5.6	Sample Calculation	
4.6		Transmitter Spurious Emissions	
4	1.6.1	Test Methodology	
4	1.6.2	Transmitter Spurious Emission Limit	
4	1.6.3	Test Results	
4	1.6.4	Sample Calculation	47
17		AC Conducted Emissions	18
/	171	Test Methodology	40 //8
-	172	Test Results	
-	+./.2		+0
5 7	Fest	Equipment List	49
5.1		Equipment List	49
6		C Test Dlan	50
0 1			50
6.1		Introduction	50
6.2		Customer	50
63		Fauinment Under Test (FUT)	51
0.5			
6.4		Test Specifications	54

Table 1: Summary of Test Results	6
Table 2: Summary of Uncertainties	11
Table 3: RF Output Power at the Antenna Port – Test Results	15
Table 4: Occupied Bandwidth – Test Results	20
Table 5: Out of Band Emissions – Test Results	24
Table 6: Peak Power Spectral Density – Test Results	29
Table 7: Transmit Spurious Emission at Band-Edge Requirements	
Table 8: Customer Information	
Table 9: Technical Contact Information	
Table 10: EUT Specifications	51
Table 11: Interface Specifications	
Table 12: Supported Equipment	
Table 13: Description of Sample used for Testing	
Table 14: Description of Test Configuration used for Radiated Measurement.	
Table 15: Final Test Mode for 2403.35 MHz to 2477.35MHz Band	53
Table 16: Test Specifications	54

1 Executive Summary

1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.247:2015 and RSS 210:2010 based on the results of testing performed on March 15, 2015 through May 28, 2015 on the USB Wireless Audio Transmitter Model Ear Force Stealth 450 TX manufactured by Voyetra Turtle Beach, Inc.. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

1.3 Summary of Test Results

Test	Test MethodTestANSI C63.4: 2009 / ANSI C64.10:2009Parame		Test MethodTest ParametersMeasured Value		Measured Value	Result
Spurious Emission in Transmitted Mode	CFR47 15.209, RSS-GEN Sect.7.2.3	Class B	-10.93 dB	Complied		
Restricted Bands of Operation	CFR47 15.205, RSS-210 Sect.2.6	Class B	(Margin)	Complied		
AC Power Conducted Emission	CFR47 15.207, RSS-GEN Sect.7.2.2	Class B	NA	Complied		
Occupied Bandwidth	CFR47 15.247 (a2), RSS GEN Sect.4.4.1	\geq 500 kHz	1.640 MHz	Complied		
Maximum Transmitted Power	CFR47 15.247 (b3), RSS-210 Sect. A.8.4	30 dBm w/ 6 dBi antenna	0.76 dBm	Complied		
Peak Power Spectral Density	CFR47 15.247 (e), RSS-210 Sect. A.8.2	8 dBm/ 3 kHz	-26.33 dBm	Complied		
Band Edge Measurement	CFR47 15.247 (d), RSS-210 Sect. A.8.5	-30 dBr	-10.01 dB (Margin)	Complied		
RF Exposure for General Population	CFR47 15.247 (i), 2.1091	1.0 mW/cm^2	0.0000002 mW/cm ²	Complied		

Table 1: Summary of Test Results

1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

1.5 Equipment Modifications

None.

2 Laboratory Information

2.1 Accreditations & Endorsements

2.1.1 US Federal Communications Commission



TUV Rheinland of North America at 1279 Quarry Lane, Ste. A., Pleasanton, CA 94566, is accredited by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and

accepted by the FCC. The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, and 90. The accreditation is updated every 3 years.

2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:1999 and ISO 9002 (Lab Code US5254). The scope of laboratory accreditation includes

emission and immunity testing. The accreditation is updated annually.

2.1.3 Canada – Industry Canada



TUV Rheinland of North America at the 1279 Quarry Ln, Pleasanton, CA 94566 address is accredited by Industry Canada for performing testing services for the general public on a fee basis. This laboratory test facilities have been

fully described in reports submitted to and accepted by Industry Canada (File Number 2932M). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment,

and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0031

VCCI Registration No. for Santa Clara: A-0032

2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member country.

2.2 Test Facilities

All of the test facilities are located at 1279 Quarry Lane, Ste. A, Pleasanton, California 94566, USA. The 2305 Mission College, Santa Clara, 95054, USA location is considered a Pleasanton annex.

2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2009, at a test distance of 3 and 5 meters. The site is listed with the FCC and accredited by A2LA (Lab Code US5254). The 3/5-meter semi-anechoic chamber used to collect the radiated data has been verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2009, at a test distance of 3 meters. A report detailing this site can be obtained from TUV Rheinland of North America.

2.2.2 Immunity Test Facility

ESD, EFT, Surge, PQF: These tests are performed in an environmentally controlled room with a 3.7 m x 4.8 m x 3.175 mm thick aluminum floor connected to PE ground.

For ESD testing, tabletop equipment is placed on an insulated mat with a surface resistivity of 10^9 Ohms/square on a 1.6 m x 0.8 m x 0.8 m high non-conductive table with a 3.175 mm aluminum top (Horizontal Coupling Plane). The HCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors. The Vertical Coupling Plane consists of an aluminum plate 50 cm x 50 cm x 3.175 mm thick. The VCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors.

For EFT, Surge, PQF, the HCP and VCP are removed.

RF Field Immunity testing is performed in a 7.3m x 4.3m x 4.1m anechoic chamber.

RF Conducted and Magnetic Field Immunity testing is performed on a 4.8m x 3.7m x 3.175mm thick aluminum ground plane.

All test areas allow a minimum distance of 1 meter from the EUT to walls or conducting objects.

2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1st Edition, 1995.

The Combined Standard Uncertainty is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

The Expanded Uncertainty defines an interval about the result of a measurement that may be expected to encompass a large fraction of the distribution of values that could reasonably be attributed to the measurand. The fraction may be viewed as the coverage probability or level of confidence of the interval.

2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

Field Strength $(dB\mu V/m) = RAW - AMP + CBL + ACF$

Where: RAW = Measured level before correction (dB μ V)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu V/m = 10^{\frac{dB\mu V/m}{20}}$$
 Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor-Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

25 dBuV/m + 17.5 dB - 20 dB + 1.0 dB = 23.5 dBuV/m

2.3.2 Measurement Uncertainties

 Table 2: Summary of Uncertainties

	U _{lab}	U _{cispr}			
Radiated Disturbance					
30 MHz – 25,000 MHz	3.2 dB	5.2 dB			
Conducted Disturbance @ Mains Terminals					
150 kHz – 30 MHz	2.4 dB	3.6 dB			
Disturbance Power					
30 MHz – 300 MHz	3.92 dB	4.5 dB			

Note: U_{lab} is the calculated Combined Standard Uncertainty

 U_{cispr} is the measurement uncertainty requirement per CISPR 16.

Measurement Uncertainty Immunity

The estimated combined standard uncertainty for ESD immunity measurements is $\pm 4.1\%$.

The estimated combined standard uncertainty for radiated immunity measurements is ± 2.7 dB.

The estimated combined standard uncertainty for conducted immunity measurements is \pm 1.4dB.

The estimated combined standard uncertainty for damped oscillatory wave immunity measurements is \pm 8.8%.

The estimated combined standard uncertainty for harmonic current and flicker measurements is $\pm 0.45\%$.

Measurement Uncertainty – Radio Testing

The estimated combined standard uncertainty for frequency error measurements is \pm 3.88 Hz
The estimated combined standard uncertainty for carrier power measurements is \pm 1.59 dB.
The estimated combined standard uncertainty for adjacent channel power measurements is \pm 1.47 dB.
The estimated combined standard uncertainty for modulation frequency response measurements is \pm 0.46 dB.
The estimated combined standard uncertainty for transmitter conducted emission measurements is $\pm 4.01 \text{ dB}$

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

2.4 Calibration Traceability

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Guide 17025:2005.

3 Product Information

3.1 Product Description

The Ear Force Stealth 450 Wireless Gaming System consists of two main communication modules, the Stealth 450 RX ("Headset") and the Stealth 450 TX ("Transmitter"). These two modules comprise a closed-loop wireless audio gaming system that utilize a proprietary 2.4 GHz communication technology to offer wireless streaming audio and chat/talkback capabilities.

3.2 Equipment Configuration

A description of the equipment configuration is given in Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of a EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.3 Operating Mode

A description of the operation mode is given in Test Plan Section. In the case of a EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

The final operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.4 Unique Antenna Connector

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

3.4.1 Results

The Ear Force Stealth 450 TX uses the permanently attached PCB trace antennas inside the device. See EUT Photo for details.



4 Emissions

Testing was performed in accordance with CFR 47 Part 15.247:2015 and RSS 210 Annex 8:2010. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in ANSI C63.10: 2009 were used.

4.1 Output Power Requirements

The maximum peak output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.

The maximum output power and harmonics shall not exceed CFR47 Part 15.247 (b3):2015 and RSS-210 A.8.4: 2010

The maximum transmitted power is +30 dBm or 1 Watt.

4.1.1 Test Method

The conducted method was used to measure the channel power output according to ANSI C63.10:2009 Section 6.10.3.1. The measurement was performed with modulation per CFR47 Part15.247 (b3):2015 and RSS-210 A.8.4: 2010. This test was conducted on 3 channels of Sample, S/N PP #1. The worst mode result indicated below.

Test Setup:



Method AVGSA-1 of "KDB 558074 – DTS Measurement Guidance v03r01" applies since the Ear Force Stealth 450 TX continuously transmits with duty cycle greater than 98%. Sample detector was used.

4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Test Conditions: Conducted Measurement Date: May 28, 2015					
Antenna Tyj	Antenna Type: Integrated Power Setting: 0 dBm				
Antenna Gai	Antenna Gain: -0.5 dBi Signal State: Modulated at 100%				
Ambient Ter	пр.: 23 °С		Relative	e Humidity:30%	
USB Wireless Audio Transmitter					
Frequency (MHz)	Limit [dBm]	OutputDuty Cycle \sum PowerMargin $[dBm]$ $[dB]$ $[dBm]$ $[dB]$			
2403.35	+30.00	0.76			-29.24
2441.35	+30.00	0.35			-29.65
2477.35	+30.00	-0.37			-30.37
Note: The USB Wireless Audio Transmitter transmitted at 100% duty cycle.					

Table 3: RF Output Power at the Antenna Port – Test Results



Figure 1: Maximum Conducted Output Power at 2403.35MHz - Transmitter



Figure 2: Maximum Conducted Output Power at 2441.35MHz - Transmitter



Figure 3: Maximum Conducted Output Power at 2477.35MHz - Transmitter

4.2 Occupied Bandwidth

The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.

The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.

The 6dB bandwidth is defined the bandwidth of 6dBr from highest transmitted level of the fundamental frequency.

The bandwidth shall be at least 500 kHz per Section CFR47 15.247(a2) 2015 and RSS Gen Sect. 4.4.1: 2010.

4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth according to ANSI C63.10:2009 Section 6.9.1. The measurement was performed with modulation per CFR47 15.247(a2) 2015 and RSS Gen Sect. 4.4.1:2010. This test was conducted on 3 channels in each mode of Sample S/N PP #1. The worst sample result indicated below.

Test Setup:



4.2.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Test Conditions: Con	Test Conditions: Conducted MeasurementDate: March 12, 2015					
Antenna Type: IntegratedPower Setting: 0 dBm						
Antenna Gain: -0.5 dl	Antenna Gain: -0.5 dBi Signal State: Modulated at 100%					
Ambient Temp.: 23 °	С	Relative Hu	midity: 31%			
	Bandwidth (MHz) for USB Wireless Audio Transmitter					
Frequency (MHz)	Limit (kHz)	Limit (kHz)99% Bandwidth6 dB BandwidthResults				
2403.35	500	1.914	1.640	Pass		
2441.35	500	1.916	1.659	Pass		
2477.35	500 1.916 1.673 Pass					
Note: The bandwidth was measured at 100% duty cycle						



Figure 4: Bandwidth- Transmitter -2403.35MHz



Figure 5: Bandwidth- Transmitter -2441.35MHz



Figure 6: Bandwidth-Transmitter -2477.35MHz

4.3 Out-of-Band Emissions

The setup was identical to RF output power measurement. Intentional radiators operating under the alternative provisions to the general emission limits, must be designed to ensure that the 20 dB or 30 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If the frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Since the transmitter complies with the conducted power limits base on the use of RMS averaging per CFR47 Part 15.247(b)(3), any frequency outside the band of 2400MHz to 2483.5MHz, the power output level must be below 30db from the in-band transmitting signal; CFR 47 Part 15.215, 15.247(d) and RSS-210 A8.5

4.3.1 Test Method

The conducted method was used to measure the out-of-band emission requirement. The measurement was performed with modulation per CFR47 15.247(4)(d) 2015 and *RSS-210 A8.5: 2010*. This test was conducted on 3 channels of Sample S/N PP #1. The worst sample result indicated below.

Test Setup:



4.3.2 Test Result

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Test Conditions: Conducted	l Measurement	Date: March 12, 2015					
Antenna Type: Integrated		Power Setting: See test pla	an				
Antenna Gain: -0.5 dBiSignal State: Modulated at 100%							
Ambient Temp.: 23 °CRelative Humidity:31%							
Out of Band Results for USB Wireless Audio Transmitter							
Operating Channel	Out of Band Level (dBm)	30 dBr Level (dBm)	Margin (dB)				
2403.35 MHz	-32.89	-43.64	-10.75				
2441.35 MHz	-33.37	-43.38	-10.01				
2477.35 MHz	-33.01	-43.65	-10.64				
Note: The band-edge level m	ust lower than the 30dBr lev	vel.					
The maximum out of band emission on each individual output put is at least 30 dB below the maximum in-band PSD on that output.							
(*) The band-edge is c	ompared to the highest -30d	Br level of the test mode.					

Table 5:	Out of	Band	Emissions	- Test	Results
----------	--------	------	-----------	--------	---------

Agilent Spect	rum Analyzer - S	wept SA						
KIRLS	RF 50	Ω AC	SENSE:I	NT	ALIGN AUTO		11:59:01 AM Mar	13, 201
Center F	req 2.4033	850000 GHz PN IFG	l0: Fast ↔ Tri ain:Low Att	g:FreeRun :en:30 dB	#Avg Type Avg Hold:	e: RMS 100/100	TRACE 1 2 TYPE MW DET P N	345 1000
0 dB/div	Ref Offset 2 Ref 22.20	2.2 dB I dBm				N	/lkr4 2.400 80 -36.726 (GH dBr
12.2								
1 20				<u>1</u>				
				X				
.00								
7.0								
27.8							-3	\$2.89 d
37.8				man her				
47.8			July	* VWW				
57.8	"holo alles of the second		all the second		Selected to the first of the second	- and and an and a second second	an weeks many particular and the	- -
67.8								
enter 2. Res BW	40335 GHz 100 kHz		#VBW 30	0 kHz		Swe	Span 150.0 ep 14.4 ms (100) MH 0 pt
KR MODE T	RC SCL	× 2.403.27 GHz	7 -2.893 dBm	FUNCTION	FUNCTION WIDTH	F	UNCTION VALUE	
2 N (f	2.400 00 GHz	-37.766 dBm					
3 N 4 N	1 f 1 f	2.483 50 GHz 2.400 80 GHz	dBm -36.726 dBm					
5								
7								
9								
10								
12								

Figure 7: Conducted Band Edge at 2403.35MHz-Transmitter



Figure 8: Out of band Emission-2403.35MHz-Transmitter

	RF 50 :	Ω AC	SENSE:INT		ALIGNAUTO	12:	01:34 PM Mar 13, 201
	req 2.4413	50000 GHz Pt IFG	IO: Fast ↔ Trig: I ain:Low Atter	Free Run 1: 30 dB	#Avg Type: RMS Avg Hold: 100/100		TRACE 1 2 3 4 5 TYPE MWWWW DET P N N N N
) dB/div	Ref Offset 2 Ref 22.20	2 dB dBm				Mkr4 2.	442 85 GH: 38.713 dBn
12.2							
2.20				<u>1</u>			
.80				Ă			
7.8							
27.8				4			-33.37 dB
37.8			N	V 4.			
17.8		2	AC	- VMu		<u>3</u>	
7.8 	we wanted and the second	prostor when the production of the	raded and argent		Man Berneth Construction of the second se	water war	arat and states
57.8							
						Sn	an 150.0 MH
enter 2. Res BW	44135 GHz 100 kHz		#VBW 300	kHz		Sweep 14.4	ms (1000 pts
enter 2. Res BW REMODE 1 N 2 N	44135 GHz 100 kHz	× 2.441 88 GHz 2.400 00 GHz	#VBW 300	KHZ Function fun	ICTION WIDTH	Sweep 14.4	ms (1000 pts
enter 2. Res BW 1 N 2 N 3 N	44135 GHz 100 kHz f f f	× 2.441 88 GHz 2.400 00 GHz 2.483 50 GHz 2.442 85 GHz	#VBW 300 Y -3.369 dBm -58.880 dBm -57.052 dBm -38.713 dBm	KHZ FUNCTION FUN	CTION WIDTH	Sweep 14.4	ms (1000 pts
enter 2. Res BW 1 N 2 N 3 N 4 N 5	44135 GHz 100 kHz RC SCL f f f f	X 2.441 88 GHz 2.400 00 GHz 2.483 50 GHz 2.442 85 GHz	#VBW 300 -3.369 dBm -58.880 dBm -57.052 dBm -38.713 dBm	KHZ FUNCTION FUN	CTION WIDTH	Sweep 14.4 FUNCTION VALU	ms (1000 pts
enter 2. Res BW 1 N 2 N 3 N 4 N 5 6	44135 GHz 100 kHz 6 Sci 1 f 1 f 1 f	8 2.441 88 GHz 2.400 00 GHz 2.483 50 GHz 2.442 85 GHz	#VBW 300 -3.369 dBm -58.880 dBm -57.052 dBm -38.713 dBm	KHZ FUNCTION FUN	ICTION WIDTH	Sweep 14.4 FUNCTION VALU	ms (1000 pts
enter 2. Res BW 1 N 2 N 3 N 4 N 5 6 7 8 9	44135 GHz 100 kHz 60 SGU 1 f 1 f 1 f 1 f	X 2.441 88 GHz 2.400 00 GHz 2.483 50 GHz 2.442 85 GHz	#VBW 300 3.369 dBm 58.880 dBm 57.052 dBm -38.713 dBm	KHZ FUNCTION FUN	ICTION WIDTH	Sweep 14.4 FUNCTION VALU	ms (1000 pts
enter 2. Res BW 1 N 2 N 3 N 4 N 5 6 7 8 9 9 0 1	44135 GHz 100 kHz 1 f 1 f 1 f 1 f	X 2.441 88 GHz 2.400 00 GHz 2.483 50 GHz 2.442 85 GHz	#VBW 300 3.369 dBm 58.880 dBm 57.052 dBm -38.713 dBm	KHZ FUNCTION FUN	ICTION WIDTH	Sweep 14.4	ms (1000 pts

Figure 9: Conducted Band Edge-2441.35MHz-Transmitter



Figure 10: Out of band Emission-2441.35MHz-Transmitter



Figure 11: Conducted Band Edge-2477.35MHz-Transmitter



Figure 12: Out of band Emission-2477.35MHz-Transmitter

4.4 Peak Power Spectral Density

According to the CFR47 Part 15.247 (e) and RSS-210 (A8.2), the spectral power density output of the antenna port shall be less than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.4.1 Test Method

The conducted method was used to measure the channel power output per ANSI C63.10:2009 Section 6.11.2. The measurement was performed with modulation per CFR47 Part 15.247 (e) and RSS-210 (A8.2). This test was conducted on 3 channels of Sample SN PP #1. The worst sample result indicated below.

Test Setup:



4.4.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 6: Peak Power Spectral Density – Test Results

Test Conditi	ons: Conducted]	Measurement	Date: March	Date: March 12, 2015					
Antenna Tyj	pe: Integrated		Power Setti	Power Setting: See test plan					
Antenna Gain: -0.5 dB Signal State: Modulated at 100%									
Ambient Ter	mp.: 23 °C		Relative Hu	umidity:31%					
Peak Power Spectral Density									
Freq. (MHz)	Config.	Output [dBm]	CF [dB]	Max. PPSD [dBm]	Limit [dBm]	Margin [dB]			
2403.35	Transmitter	-11.10	-15.23	-26.33	8.00	-34.33			
2441.35	Transmitter	-11.59	-15.23	-26.82	8.00	-34.82			
2477.35	35 Transmitter -12.40 -15.23 -27.63 8.00 -35.63								
Note: CF was The bas USB W	Note: CF was accounted for the measured RBW. The bandwidth ratio is 10*log (3kHz/100kHz) or -15.23 dB. USB Wireless Audio Transmitter transmitted at 100% duty cycle								







Figure 14: Maximum Power Spectral Density-2441.35MHz- Transmitter

LUV Rheinland 1279 Quarry Lane, Ste. A, Pleasanton, CA 95466 Tel: (925) 249-9123, Fax: (925) 249-9124



Figure 15: Maximum Power Spectral Density-2477.35MHz- Transmitter

4.5 Maximum Permissible Exposure

4.5.1 Test Methodology

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Semi-Anechoic Chamber, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an overprediction for near field power density. We will take that as the worst case to specify the safety range.

4.5.2 **RF Exposure Limit**

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm2)	Average Time (minutes)					
(A)Limits For Occupational / Control Exposures									
300 - 1500			F/300	6					
1500 - 100,000			5	6					
(B)Limits For General Population / Uncontrolled Exposure									
300 - 1500			F/1500	6					
1500 - 100,000			1.0	30					

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

F = Frequency in MHz

4.5.3 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

4.5.4 Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in user's manual. So, this device is classified as a **Mobile Device**.

4.5.5 Test Results

4.5.5.1 Antenna Gain

The transmitting antenna was integrated. The maximum antenna gain for the highest observed power was -0.5 dBi or 0.89 (numeric).

4.5.5.2 Output Power into Antenna & RF Exposure value at distance 20cm:

Calculations for this report are based on highest power measurement.

Limit for MPE (from FCC part 1.1310 Table1) is 1.0 mW/cm²

The highest measured power is 0.76 dBm or 0.001191mW.

Using the Friss transmission formula, the EIRP is Pout*G, and R is 20cm.

 $Pd = (0.001191*0.891) / (1600\pi) = 0.0000002 \text{ mW/cm2}$, which is 0.9999998 mW/cm2 below to the limit.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

4.5.6 Sample Calculation

The Friss transmission formula: $Pd = (Pout^{*}G) / (4^{*}\pi^{*}R^{2})$

Where;

Pd = power density in mW/cm² Pout = output power to antenna in mW G = gain of antenna in linear scale $\pi \approx 3.1416$ R = distance between observation point and center of the radiator in cm

Ref. : David K. Cheng, Field and Wave Electromagnetics, Second Edition, Page 640, Eq. (11-133).

4.6 Transmitter Spurious Emissions

Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmitting mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS-210 Sect. A.8.5

4.6.1 Test Methodology

4.6.1.1 Preliminary Test

A test program that controls instrumentation and data logging was used to automate the preliminary RF emission test procedure. The frequency range of interest was divided into sub-ranges to yield a frequency resolution of approximately 120 kHz and provide a reading at each frequency for no more than 12° of turntable rotation. For each frequency sub-range the turntable was rotated 360° while peak emission data was recorded and plotted over the frequency range of interest in horizontal and vertical antenna polarization's.

Preliminary emission profile testing was performed inside the anechoic chamber. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm above the floor. The EUT was positioned as shown in the setup photographs. The receiving antenna was placed at a distance of 3m at a fixed height of 1m. Measurement equipment was located outside of the chamber. A video camera was placed inside the chamber to view the EUT.

4.6.1.2 Final Test

For each frequency measured, the peak emission was maximized by manipulating the receiving antenna from 1 to 4 meters above the ground plane and placing it at the position that produced the maximum signal strength reading. The turntable was then rotated through 360° while observing the peak signal and placing the EUT at the position that produced maximum radiation. The six highest emissions relative to the limit were measured unless such emissions were more than 20 dB below the limit. If less than six emissions are within 20 dB of the limit, than the noise level of the receiver is measured at frequencies where emissions are expected. Multiples of all oscillator and microprocessor frequencies were also checked.

Final testing was performed on an NSA compliant test site. The EUT was placed on a 1.0m x 1.5m nonconductive table 80cm above the ground plane. The placement of EUT and cables were the same as for preliminary testing and is shown in the setup photographs.

The final scans performed on the worst axis, Y-Axis up, for three operating channels in each operating mode;

2403.35MHz, 2441.35MHz, and 2477.35MHz

4.6.1.3 Deviations

None.

4.6.2 Transmitter Spurious Emission Limit

The spurious emissions of the transmitter shall not exceed the values in CFR47 Part 15.205, 15.209: 2015 and RSS-210 A1.1.2 2010.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

All harmonics and spurious emission which are outside of the restricted band shall be 20dB below the inband emission.

4.6.3 Test Results

The final measurement data was taken under the worst case operating modes, configurations, and/or cable positions. It also reflects the results including any modifications and/or special accessories listed in Sections 1.4 and Test Plan.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Antenna Type: Integrated Power Setting: 0 dBm Max. Antenna Gain: -0.5 dBi Signal State: Modulated at 100% Ambient Temp.: 23 °C Relative Humidity:31% Edge Edge Freq. Mode Edge Freq. Pol. Ant. Table Det. Level Limit Ma MHz MHz V/H cm Deg. Pk/Avg dBuV/m dBuV/m d	Test Condi	Test Conditions: Radiated Measurement, Normal Temperature and Voltage only									
Signal State: Modulated at 100% Relative Humidity:31% Ambient Temp.: 23 °C Relative Humidity:31% Center Edge Freq. Mode Fedge Pol. Ant. Table Level Limit Mate MHz MHz V/H cm Deg. Pk/Avg dBuV/m dBuV/m d	Antenna Type: Integrated Power Setting: 0 dBm										
Relative Humidity:31% Relative Humidity:31% Band-Edge Results Center Edge Freq. Mode Freq. Pol. Ant. Table Det. Level Limit Mar. MHz MHz V/H cm Deg. Pk/Avg dBuV/m dBuV/m d	Max. Antenna Gain: -0.5 dBi Signal State: Modulated at 100%										
Band-Edge Results Center Edge Edge Det. Level Limit Material Freq. Mode Freq. Pol. Ant. Table Det. Level Limit Material MHz MHz V/H cm Deg. Pk/Avg dBuV/m dBuV/m	Ambient Temp.: 23 °CRelative Humidity:31%										
Center Edge Edge Image: Freq. Freq. Pol. Ant. Table Det. Level Limit Mage MHz MHz V/H cm Deg. Pk/Avg dBuV/m dBuV/m d	Band-Edge Results										
MHz V/H cm Deg. Pk/Avg dBuV/m dBuV/m d	Center Freq.	Mode	Edge Freq.	Pol.	Ant.	Table	Det.	Level	Limit	Margin	
	MHz		MHz	V/H	cm	Deg.	Pk/Avg	dBuV/m	dBuV/m	dB	
2403.35 Transmitter 2390.00 V 336 253 Pk 59.46 74.00 -1	2403.35	Transmitter	2390.00	v	336	253	Pk	59.46	74.00	-14.54	
2403.35 Transmitter 2390.00 V 336 253 Ave 39.34 54.00 -1	2403.35	Transmitter	2390.00	v	336	253	Ave	39.34	54.00	-14.66	
2403.35 Transmitter 2390.00 H 223 201 Pk 57.56 74.00 -1	2403.35	Transmitter	2390.00	Н	223	201	Pk	57.56	74.00	-16.44	
2403.35 Transmitter 2390.00 H 223 201 Ave 39.86 54.00 -1	2403.35	Transmitter	2390.00	Н	223	201	Ave	39.86	54.00	-14.14	
2477.35 Transmitter 2483.50 H 262 213 Pk 52.49 74.00 -2	2477.35	Transmitter	2483.50	Н	262	213	Pk	52.49	74.00	-21.51	
2477.35 Transmitter 2483.50 H 262 213 Ave 42.86 54.00 -1	2477.35	Transmitter	2483.50	Н	262	213	Ave	42.86	54.00	-11.14	
2477.35 Transmitter 2483.50 V 321 263 Pk 52.45 74.00 -2	2477.35	Transmitter	2483.50	v	321	263	Pk	52.45	74.00	-21.55	
2477.35 Transmitter 2483.50 V 321 263 Ave 41.28 54.00 -1	2477.35	Transmitter	2483.50	v	321	263	Ave	41.28	54.00	-12.72	

LUV Rheinland 1279 Quarry Lane, Ste. A, Pleasanton, CA 95466 Tel: (925) 249-9123, Fax: (925) 249-9124







Figure 21: Bandedge-2477.35 MHz-H-Ave



Figure 23: Bandedge-2477.35 MHz-V-Ave

Report Number: 31561425.001 EUT: USB Wireless Audio Transmitter Model: Ear Force Stealth 450 TX Issue Date: June 8, 2015

SOP 1 F	SOP 1 Radiated Emissions								ing #	31561425.	001 Page	1 of 6
EUT Nam	e	USB	Wireles	ss Audio T	ransmitter			Date	е	Ma	arch 13, 20)15
EUT Mod	EUT Model Ear Force Stealth 450 TX							Ten	1p / Ηι	$1 \text{ m in } \overline{23^\circ}$	°C / 33%rh	า
EUT Serial PP #2							Ten	າp / Hເ	um out N//	4		
EUT Config. Transmitter up right							Line	• AC /	Freq 5.0) VDC		
Standard	0	CFR [,]	47 Part	15 Subpa	art C			RB\	N/VB	W 120	0 kHz/ 300) kHz
Dist/Ant I	Used	3m /	JB3					Per	forme	dbv Jer	remv Luon	a
Freq	Ra	W	Chl	AF	Level	Det	Pol	Hoht	Azt	Limit	Margin	Result
MHz	dBuy	V/m	dB	dB	dBuV/m	Det.	H/V	cm	deg	dBuV/m	dB	itosuit
Transmitted Data at 2441.35MHz												
						a 2 ata						
52.81	40.	41	2.80	-24.61	18.60	QP	V	272	100	40.00	-21.40	Pass
66.58	40.	62	2.91	-24.34	19.19	QP	v	250	62	40.00	-20.81	Pass
68.99	42.	82	2.92	-24.21	21.52	QP	v	105	296	40.00	-18.48	Pass
72.01	50.	25	2.94	-24.12	29.07	QP	v	148	326	40.00	-10.93	Pass
77.43	43.	13	2.98	-24.36	21.75	QP	v	181	142	40.00	-18.25	Pass
84.03	45.	73	3.02	-25.02	23.72	QP	V	144	260	40.00	-16.28	Pass
Spec Marg CF= Amp (in = Le Gain +	vel - L ANT F	imit, Le Factor	evel = Raw	+ Cbl+ CF ±	Uncerta	ainty					
Combined S	tandard	Unce	rtainty U _c	$(y) = \pm 3.2 \text{ c}$	JB Expande	d Uncert	ainty U	$= ku_c(y)$	<i>k</i> = 1	2 for 95% con	fidence	
Note: The	worst	case	was obs	served at	Channel 24	41.35	MHz.					
The	broadk	band	at 30MF	Iz is not r	adio related	d.						

SOP 1 Ra	diated I	Emissi	ons				Track	ing #	315614	25.001 Pa	ge 2 of 6
EUT Name	USB	Wirele	ss Audio	Transmitt	er		Dat	е		May 15, 2	015
EUT Model	Ear I	Force S	tealth 45	0 T X			Ten	np / Hu	um in	23°C / 32%	%rh
EUT Serial PP #2							Ten	np / Hu	um out	N/A	
EUT Config. Transmitter up right							Line	e AC /	Freq	5.0 VDC	
Standard CFR47 Part 15 Subpart C						RB\	N / VB	W	1MHz / 3N	ЛНz	
Dist/Ant Us	ed 3m /	DRH-1	18, 1m /	RA42-K-F	-4B-C		Per	forme	d by	Jeremy Lu	iong
Freq	Raw	Cbl	AF	Level	Det	Pol	Hght	Azt	Limit	Margin	Comment
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB	
Transmitted Data at 2403.35MHz											
7210.17	47.60	2.30	-11.70	38.20	Ave	Н	201	368	54.00	-15.80	Harmonics
4808.25	53.80	1.90	-16.10	39.60	Ave	V	162	60	54.00	-14.40	Harmonics
9615.80	43.10	2.70	-7.90	37.90	Ave	V	122	160	54.00	-16.10	Harmonics
				Transmi	tted Data at	2441	.35MH	Z			
9764.53	46.50	2.70	-8.30	40.90	Ave	Н	128	210	54.00	-13.10	Harmonics
				Transmi	tted Data at	t 2477	.35MH	Z			
4954.18	50.87	1.87	-15.72	37.02	Ave	V	121	76	54.00	-16.98	Harmonics
9910.44	46.32	2.70	-7.94	41.08	Ave	V	155	306	54.00	-12.92	Spurious
Spec Margin : CF= Amp Gai	= Level - I in + ANT I	_imit, L Factor	evel = Rav	w+ Cbl+ C	F ± Uncertair	nty					
Combined Stan	idard Unce	rtainty U	$(y) = \pm 3.2$	dB Expar	nded Uncertair	nty \overline{U} =	= ku _c (y)	<i>k</i> = 2	2 for 95%	confidence	
Notes: All	emission	s passe	ed the sp	urious err	nission limit.						







Report Number: 31561425.001 EUT: USB Wireless Audio Transmitter Model: Ear Force Stealth 450 TX Issue Date: June 8, 2015





4.6.4 Sample Calculation

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

Field Strength $(dB\mu V/m) = FIM - AMP + CBL + ACF$

Where: FIM = Field Intensity Meter ($dB\mu V$)

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu V/m = 10^{\frac{dB\mu V/m}{20}}$$

4.7 AC Conducted Emissions

Testing was performed in accordance with ANSI C63.4: 2009. These test methods are listed under the laboratory's A2LA Scope of Accreditation.

This test measures the levels emanating from the EUT's AC input port, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

The AC conducted emissions of equipment under test shall not exceed the values in CFR47 Part 15.207: 2015 and RSS-210: 2010.

4.7.1 Test Methodology

A test program that controls instrumentation and data logging was used to automate the AC Power Line Conducted emission test procedure. The frequency range of interest was divided into sub-ranges such as to yield a frequency resolution of 9 kHz. Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a set of 50μ H / 50Ω LISNs.

Testing is either performed in 5m Chamber. The setup photographs clearly identify which site was used. The vertical ground plane used in the semi-anechoic chamber is a 2m x 2m solid aluminum frame and panel, and it is bonded to the horizontal ground plane.

In the case of tabletop equipment, the EUT is placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane and 40cm from a vertical ground reference plane. The rear of the EUT was positioned flush with the backside of the table and directly over the LISNs. The power and I/O cables were routed over the edge of the table and bundled approximately 40cm from the ground plane. Support equipment was powered from a separate LISN.

4.7.1.1 Deviations

There were no deviations from this test methodology.

4.7.2 Test Results

This test is not required since EUT is powered by 5 VDC via USB port on host platform.

5 Test Equipment List

5.1 Equipment List

Equipment	Manufacturer	Model #	Serial/Inst #	Last Cal mm/dd/yyyy	Next Cal mm/dd/yyyy
Bilog Antenna	Sunol Sciences	JB3	A061907	07/08/2014	07/08/2016
Horn Antenna	Sunol Sciences	DRH-118	A040806	02/10/2015	02/10/2016
Antenna (18-26GHz)	СМТ	RA42-K-F-4B-C	020131-004	07/24/2014	07/24/2015
Spectrum Analyzer	Rohde & Schwarz	FSL6	100169	01/13/2015	01/13/2016
Spectrum Analyzer	Agilent	N9038A	MY51210195	01/12/2015	01/12/2016
Spectrum Analyzer	Agilent	N9030A	MY51380689	01/19/2015	01/19/2016
Spectrum Analyzer	Rohde Schwarz	ESIB	832427/002	01/13/2015	01/13/2016
Spectrum Analyzer	Rohde Schwarz	FSV40	1321.3008K40	11/01/2015	11/01/2016
Amplifier	Sonoma Instruments	310	213221	09/30/2014	09/30/2015
Amplifier	Miteq	TTA1800-30-4G	1842452	01/13/2015	01/13/2016
Amplifier	Rohde & Schwarz	TS-PR26	100011	07/24/2014	07/24/2016
Amplifier	Rohde & Schwarz	TS-PR40	100012	02/21/2015	02/21/2016
Power Meter	Agilent	E4418B	MY45103902	01/15/2015	01/15/2016
Power Sensor	Hewlett Packard	8482A	US37295801	01/15/2015	01/15/2016
Thermometer	Fluke	5211	96480032	06/28/2014	06/28/2015
Thermo Chamber	Espec	BTZ-133	0613436	03/16/2015	03/16/2016
DC Power Supply	Agilent	E3634A	MY400004331	01/12/2015	01/12/2016
Notch Filter	Micro-Tronics	BRM50716	003	01/30/2015	01/30/2016
Signal Generator	Anritsu	MG3694A	42803	01/13/2015	01/13/2016
Signal Generator	Rohde & Schwarz	SMF100A	1167.0000K02	10/14/2014	10/14/2015
Signal Generator	Rohde & Schwarz	SMBV100A	1407.6004K02	12/04/2014	12/04/2015
Power Sensors	Rohde & Schwarz	OSP120	1520.9010.02	12/19/2014	12/14/2015

6 EMC Test Plan

6.1 Introduction

This section provides a description of the Equipment Under Test (EUT), configurations, operating conditions, and performance acceptance criteria. It is an overview of information provided by the manufacturer so that the test laboratory may perform the requested testing.

6.2 Customer

Table 8: Customer Int	formation
-----------------------	-----------

Company Name	Voyetra Turtle Beach, Inc.		
Address	100 Summit Lake Drive, Suite 100		
City, State, Zip	Valhalla, New York 10595		
Country	USA		

Table 9: Technical Contact Information

Name	Tim Blaney	
E-mail	tim@commcepts.net	
Phone	(530) 277-3482	

6.3 Equipment Under Test (EUT)

Table 10: EUT Specifications

EUT Specification				
Package Dimensions	69.85mm (2.75") x 25.4mm (1.0") x 9.5mm (0.375")			
Power Input	Transmitter Input Voltage: 5.0 Vdc (Host Computer)			
Environment	Indoor			
Operating Temperature Range:	0 to 50 degrees C			
Multiple Feeds:	☐ Yes and how many ⊠ No			
Hardware Version	PP			
Part Number	N/A			
RF Software Version	VMI Test Software V0.5			
Operating Mode	VMI RF Protocol			
Transmitter Frequency Band	2403.35 GHz to 2477.35 GHz			
Max. Ouput Power	0.76 dBm			
Power Setting @ Operating Channel	0 dBm			
Antenna Type	PCB Attached on board			
Modulation Type	AM FM DSSS OFDM			
Date Rate	11 kbps			
TX/RX Chain (s)	1			
Antenna Gain	2 antennas; Ant1 = Ant2 = -0.5 dBi			
Directional Gain Type	Uncorrelated No Beam-Forming Other describe:			
Type of Equipment	☐ Table Top ☐ Wall-mount ☐ Floor standing cabinet			
Note: Aux 0 is the default antenn	ia output.			

 Table 11: Interface Specifications

Interface Type	Cabled with what type of cable?	Is the cable shielded?	Maximum potential length of the cable?	Metallic (M), Coax (C), Fiber (F), or Not Applicable?
USB	Terminated	🛛 Yes	Metric:3m	\boxtimes M

Table 12: Supported Equipment

Equipment	Manufacturer	Model	Serial	Used for
Laptop	Dell Computer	D630	28353268189	Set test mode

Table 13: Description of Sample used for Testing

Device	Serial Number	Configuration	Used For
Ear Force Stealth 450 TX	PP #2	Radiated Sample	Radiated Emissions.
Ear Force Stealth 450 TX	PP #1	Conducted Sample	Output Power, Occupied Bandwidth, Conducted Spurious Emissions, Peak Power Spectral Density
Note: None			

Table 14: Description of Test Configuration used for Radiated Measurement.

Device	Antenna	Mode	Setup Description
Ear Force Stealth 450 TX	Integrated	Transmit & Receive	Ear Force Stealth 450 TX positioned vertically, Worst Case.
Note: The final setup configuration used for testing.			

Test	Ear Force Stealth 400 RX	
Occupied Bandwidth	2403.35, 2441.35, 2477.35 MHz @ 11 kbps	
Output Power	2403.35, 2441.35, 2477.35 MHz @ 11 kbps	
Peak Power Spectral Density	2403.35, 2441.35, 2477.35 MHz @ 11 kbps	
Out-of-Band (-30 dBr)	2403.35, 2441.35, 2477.35 MHz @ 11 kbps	
Band-Edge (Radiated)	2403.35, 2477.35 MHz @ 11 kbps	
Transmitted Spurious Emission	2403.35, 2441.35, 2477.35 MHz @ 11 kbps	
AC Conducted Emission	NA	
Note: EUT transmits at 100% duty cycle.		

Table 15: Final Test Mode for 2403.35 MHz to 2477.35MHz Band

6.4 Test Specifications

Testing requirements

Table 16: Test Specifications

Emissions and Immunity		
Standard	Requirement	
CFR 47 Part 15.247: 2015	All	
RSS-210 Iss. 8 2010	All	