

FCC & IC REPORT

(LTE)

Applicant: COPPERNIC
Address of Applicant: 185 avenue Archimede, 13857 Aix en Provence, FRANCE
Equipment Under Test (EUT)
Product Name: C-One² LF AGRIDENT
Model No.: C-One
Trade mark: COPPERNIC
FCC ID: XGK-C-ONE-LF-AGR
Canada IC: 8402A-CONELFAGR
Applicable standards: FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22 Subpart H
FCC CFR Title 47 Part 27 Subpart M
RSS-Gen Issue 5, March 2019 Amendment 1
RSS-132 Issue 3, January 2013
RSS-199 Issue 3, December 2016
Date of sample receipt: 11 Nov., 2019
Date of Test: 12 Nov., 2019 to 02 Apr., 2020
Date of report issued: 02 Apr., 2020
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful, and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2. Version

Version No.	Date	Description
00	11 Mar., 2020	Original
01	02 Apr., 2020	Update Band edge emission test, Update IC ID number
02	03 Apr., 2020	Update page 58, 59

Tested by:

Carey Chen

Test Engineer

Date:

02 Apr., 2020

Reviewed by:

Winner Zhang

Project Engineer

Date:

02 Apr., 2020

3. Contents

Page

1.	COVER PAGE	1
2.	VERSION	2
3.	CONTENTS	3
4.	TEST SUMMARY	4
5.	GENERAL INFORMATION	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T	5
5.3	TEST ENVIRONMENT AND MODE	8
5.4	DESCRIPTION OF SUPPORT UNITS	8
5.5	MEASUREMENT UNCERTAINTY	8
5.6	RELATED SUBMITTAL(S) / GRANT (S)	8
5.7	LABORATORY FACILITY	8
5.8	LABORATORY LOCATION	8
5.9	TEST INSTRUMENTS LIST	9
6.	TEST RESULTS	10
6.1	CONDUCTED OUTPUT POWER, ERP AND EIRP	10
6.2	PEAK-TO-AVERAGE RATIO	15
6.3	OCCUPY BANDWIDTH	18
6.4	OUT OF BAND EMISSION AT ANTENNA TERMINALS	37
6.5	FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	54
6.6	FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT	60
6.7	FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT	63
7	TEST SETUP PHOTO	65
8	EUT CONSTRUCTIONAL DETAILS	66

4. Test Summary

Test Items	Section		Result
	FCC	IC	
RF Exposure (SAR)	Part 1.1307 Part 2.1093	RSS-102	Passed (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 27.50 (h)(2)	RSS-Gen Section 6.12 RSS-132 section 5.4 RSS-199 section 4.4	Pass
Peak-to-Average Ratio	Part 27.50(d)(5)	RSS-132 section 5.4 RSS-199 section 4.4	Pass
Modulation Characteristics	Part 2.1047	RSS-132 section 5.2 RSS-199 section 4.1	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917(b) Part 27.53(m)	RSS Gen section 6.6	Pass
Out of band emission at antenna terminals	Part 2.1051 Part 22.917(a) Part 27.53(m)	RSS-Gen section 6.13 RSS-132 section 5.5 RSS-199 section 4.5	Pass
Field strength of spurious radiation	Part 2.1053 Part 22.917(a) Part 27.53(m)	RSS-Gen section 6.13 RSS-132 section 5.5 RSS-199 section 4.5	Pass
Frequency stability vs. temperature	Part 22.355 Part 27.54 Part 2.1055(a)(1)(b)	RSS-Gen section 6.11 RSS-132 section 5.3 RSS-199 section 4.3	Pass
Frequency stability vs. voltage	Part 22.355 Part 27.54 Part 2.1055(d)(2)	RSS-Gen section 6.11 RSS-132 section 5.3 RSS-199 section 4.3	Pass
Pass: The EUT complies with the essential requirements in the standard.			

5. General Information

5.1 Client Information

Applicant:	COPPERNIC
Address:	185 avenue Archimede, 13857 Aix en Provence, FRANCE
Manufacturer:	ASKEY COMPUTER Corp.
Address:	10 F, N°119, JIANKANG RD., ZHONGHE DIST., New Tapei City, TAIWAN

5.2 General Description of E.U.T.

Product Name:	C-One ² LF AGRIDENT
Model No.:	C-One
Operation Frequency range:	LTE Band 5: 824MHz-849MHz, RX: 869MHz-894MHz LTE Band 7: TX: 2500MHz-2570MHz, RX: 2620MHz-2690MHz
Modulation type:	QPSK, 16QAM
Antenna type:	Internal Antenna
Antenna gain:	LTE Band 5: -5.07dBi LTE Band 7: 2.32dBi
Power supply:	Rechargeable Li-ion Battery DC3.7V-3300mAh
AC adapter:	Model: SYS1561-1105-1 Input: AC100-240V, 50/60Hz, 1A Output: DC 5.35V, 2A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency List:

LTE Band 5 (1.4MHz)		LTE Band 5 (3MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
20407	824.70	20415	825.50
20408	824.80	20416	825.60
....			
20524	836.40	20524	836.40
20525	836.50	20525	836.50
20526	836.60	20526	836.60
...	...	...	...
20642	848.20	20634	847.40
20643	848.30	20635	847.50
LTE Band 5 (5MHz)		LTE Band 5 (10MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
20425	826.50	20450	829.00
20426	826.60	20451	829.10
....			
20524	836.40	20524	836.40
20525	836.50	20525	836.50
20526	836.60	20526	836.60
...	...	...	...
20624	846.40	20599	839.90
20625	846.50	20600	844.00

LTE Band 7 (5MHz)		LTE Band 7 (10MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
20775	2502.50	20800	2505.00
20776	2502.60	20801	2502.10
....			
21099	2534.90	21099	2534.90
21100	2535.00	21100	2535.00
21101	2535.20	21101	2535.20
...	...	...	...
21424	2567.40	21399	2564.90
21425	2567.50	21400	2565.00
LTE Band 7 (15MHz)		LTE Band 7 (20MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
20825	2507.50	20850	2510.00
20826	2507.60	20851	2510.10
....			
21099	2534.90	21099	2534.90
21100	2535.00	21100	2535.00
21101	2535.20	21101	2535.20
...	...	...	...
21374	2562.40	21349	2559.90
21375	2562.50	21350	2560.00

Regards to the operating frequency range, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channels as below:

LTE Band 5 (1.4MHz)			LTE Band 5 (3MHz)		
Channel:		Frequency (MHz)	Channel		Frequency (MHz)
Lowest channel	20407	824.70	Lowest channel	20415	825.50
Middle channel	20525	836.50	Middle channel	20525	836.50
Highest channel	20643	848.30	Highest channel	20635	847.50
LTE Band 5 (5MHz)			LTE Band 5 (10MHz)		
Channel		Frequency (MHz)	Channel		Frequency (MHz)
Lowest channel	20425	826.50	Lowest channel	20450	829.00
Middle channel	20525	836.50	Middle channel	20525	836.50
Highest channel	20625	846.50	Highest channel	20600	844.00

LTE Band 7 (5MHz)			LTE Band 7 (10MHz)		
Channel		Frequency (MHz)	Channel		Frequency (MHz)
Lowest channel	20775	2502.50	Lowest channel	20800	2505.00
Middle channel	21100	2535.00	Middle channel	21100	2535.00
Highest channel	21425	2567.50	Highest channel	21400	2565.00
LTE Band 7 (15MHz)			LTE Band 7 (20MHz)		
Channel		Frequency (MHz)	Channel		Frequency (MHz)
Lowest channel	20825	2507.50	Lowest channel	20850	2510.00
Middle channel	21100	2535.00	Middle channel	21100	2535.00
Highest channel	21375	2562.50	Highest channel	21350	2560.00

5.3 Test environment and mode

Operating Environment:	
Temperature:	Normal: 15°C ~ 35°C, Extreme: -30°C ~ +50°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar
Voltage:	Nominal: 3.7Vdc, Extreme: Low 3.5Vdc, High 4.2Vdc
Test mode:	
LTE QPSK mode	Keep the EUT communication with simulated station in QPSK mode
LTE 16-QAM mode	Keep the EUT communication with simulated station in 16-QAM mode
Remark: The EUT has been tested under continuous transmitting mode. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes with power adaptor, earphone and Data cable. Just the worst case position (H mode) shown in report.	

5.4 Description of Support Units

Test Equipment	Manufacturer	Model No.	Serial No.
Simulated Station	Anritsu	MT8820C	6201026545

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location


Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.9 Test Instruments list

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020
Biconical Antenna	SCHWARZBECK	VUBA9117	359	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2018	11-17-2019
				11-18-2019	11-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020
				03-18-2020	03-17-2021
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020
Spectrum Analyzer	Agilent	N9020A	MY50510123	11-18-2018	11-17-2019
				11-18-2019	11-17-2020
Signal Generator	Rohde & Schwarz	SMX	835454/016	03-18-2019	03-17-2020
Signal Generator	R&S	SMR20	1008100050	03-18-2019	03-17-2020
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020
DC Power Supply	XinNuoEr	WYK-10020K	1409050110020	09-25-2019	09-24-2020
Temperature Humidity Chamber	HengPu	HPGDS-500	20140828008	11-01-2019	10-31-2020
Simulated Station	Rohde & Schwarz	CMW500	140493	07-22-2019	07-21-2020

6. Test results

6.1 Conducted Output Power, ERP and EIRP

Test Requirement:	Part 22.913(a)(2), Part 27.50 (h)(2) RSS-132 section 5.4, RSS-199 section 4.4
Test Method:	ANSI/TIA-603-D 2010
Limit:	FCC: LTE Band 5: 7W, LTE Band 7: 2W, IC: LTE Band 5: 11.5W, LTE Band 7: 2W,
Test Setup:	 The diagram illustrates the test setup. On the left is a blue 'System simulator' with a screen and two ports. A line connects it to a black 'ATT' (attenuator) block. Another line connects the 'ATT' to a black 'EUT' (Equipment Under Test) device on the right.
Test Procedure:	The transmitter output was connected to a calibrated attenuator, the other end of which was connected to the CMW500. Transmitter output power was read off in dBm.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20407	20525	20643
					824.7MHz	836.5MHz	848.3MHz
5	1.4	QPSK	1	0	24.03	24.23	24.14
			1	2	24.08	24.40	24.36
			1	5	24.25	24.39	24.33
			3	0	23.35	23.44	23.32
			3	1	23.28	23.39	23.45
			3	2	23.30	23.57	23.41
			6	0	23.18	23.28	23.26
		Antenna Gain(dBi):				-5.07	
		Max. ERP for FCC (dBm):				17.18	
		ERP Limit for FCC (dBm):				38.45	
		Max. EIRP for IC (dBm):				19.33	
		EIRP Limit for IC (dBm):				40.61	
		16QAM	1	0	22.26	23.05	22.80
			1	2	22.24	22.70	22.37
			1	5	22.07	22.87	22.48
			3	0	22.20	21.77	22.19
			3	1	22.67	22.52	22.21
			3	2	22.44	22.27	22.02
			6	0	22.23	22.09	22.06
		Antenna Gain(dBi):				-5.07	
		Max. ERP for FCC (dBm):				15.83	
		ERP Limit for FCC (dBm):				38.45	
		Max. EIRP for IC (dBm):				17.98	
		EIRP Limit for IC (dBm):				40.61	

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20415	20525	20635
					825.5MHz	836.5MHz	847.50MHz
5	3	QPSK	1	0	24.26	24.30	24.14
			1	7	24.36	24.28	24.24
			1	14	24.35	24.30	24.31
			8	0	23.32	23.33	23.28
			8	4	23.35	23.38	23.33
			8	7	23.28	23.32	23.25
			15	0	23.26	23.30	23.29
		Antenna Gain(dBi):				-5.07	
		Max. ERP for FCC (dBm):				17.14	
		ERP Limit for FCC (dBm):				38.45	
		Max. EIRP for IC (dBm):				19.29	
		EIRP Limit for IC (dBm):				40.61	
		16QAM	1	0	23.02	22.76	22.61
			1	7	23.06	22.96	22.82
			1	14	22.58	22.70	22.75
			8	0	22.19	22.22	22.25
			8	4	22.18	22.16	22.56
			8	7	22.35	22.24	22.25
			15	0	22.28	22.32	22.52
		Antenna Gain(dBi):				-5.07	
		Max. ERP for FCC (dBm):				15.84	
		ERP Limit for FCC (dBm):				38.45	
		Max. EIRP for IC (dBm):				17.99	
		EIRP Limit for IC (dBm):				40.61	

Note: EIRP (dBm) = Average power (dBm) + Antenna Gain (dBi).
ERP (dBm) = EIRP (dBm) - 2.15 (dB).


LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)			
					20425	20525	20625	
					826.5MHz	836.5MHz	846.5MHz	
5	5	QPSK	1	0	24.16	24.10	24.28	
			1	12	24.26	24.22	24.07	
			1	24	23.92	23.31	24.22	
			12	0	23.36	23.36	23.20	
			12	6	23.31	23.34	23.29	
			12	11	23.26	23.30	23.27	
			25	0	23.33	23.26	23.27	
		Antenna Gain(dBi):				-5.07		
		Max. ERP for FCC (dBm):				17.06		
		ERP Limit for FCC (dBm):				38.45		
		Max. EIRP for IC (dBm):				19.21		
		EIRP Limit for IC (dBm):				40.61		
		16QAM	1	0	22.82	23.04	22.47	
			1	12	22.91	23.16	23.01	
			1	24	22.37	22.76	22.48	
			12	0	22.09	22.01	22.13	
			12	6	22.23	22.26	22.32	
			12	11	22.14	22.10	22.04	
			25	0	22.26	22.34	22.27	
		Antenna Gain(dBi):				-5.07		
		Max. ERP for FCC (dBm):				15.94		
		ERP Limit for FCC (dBm):				38.45		
		Max. EIRP for IC (dBm):				18.09		
		EIRP Limit for IC (dBm):				40.61		
LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)			
					20450	20525	20600	
					829.0MHz	836.5MHz	844.0MHz	
5	10	QPSK	1	0	24.13	24.29	24.37	
			1	24	24.30	24.39	24.51	
			1	49	24.17	24.18	24.31	
			25	0	23.42	23.34	23.31	
			25	12	23.31	23.38	23.32	
			25	24	23.39	23.33	23.28	
			50	0	23.30	23.42	23.34	
		Antenna Gain(dBi):				-5.07		
		Max. ERP for FCC (dBm):				17.29		
		ERP Limit for FCC (dBm):				38.45		
		Max. EIRP for IC (dBm):				19.44		
		EIRP Limit for IC (dBm):				40.61		
		16QAM	1	0	22.65	22.78	22.86	
			1	24	22.35	22.63	22.62	
			1	49	22.34	22.33	22.59	
			25	0	22.37	22.33	22.39	
			25	12	22.31	22.42	22.35	
			25	24	22.36	22.24	22.30	
			50	0	22.28	22.32	22.24	
		Antenna Gain(dBi):				-5.07		
		Max. ERP for FCC (dBm):				15.64		
		ERP Limit for FCC (dBm):				38.45		
		Max. EIRP for IC (dBm):				17.79		
		EIRP Limit for IC (dBm):				40.61		
Note: EIRP (dBm) = Average power (dBm) + Antenna Gain (dBi). ERP (dBm) = EIRP (dBm) - 2.15 (dB).								

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)			
					20775	21100	21425	
					2502.5MHz	2535.0MHz	2567.5MHz	
7	5	QPSK	1	0	23.63	24.10	23.95	
			1	12	23.83	23.93	24.27	
			1	24	23.78	23.85	23.98	
			12	0	22.86	22.94	23.17	
			12	6	22.85	23.03	23.18	
			12	11	22.85	22.92	23.18	
			25	0	22.87	22.95	23.16	
		Antenna Gain (dBi):				2.32		
		Max. EIRP (dBm):				26.59		
		EIRP Limit (dBm):				33.00		
		16QAM	1	0	22.21	22.31	22.65	
			1	12	22.35	22.30	22.73	
			1	24	22.11	22.12	22.67	
			12	0	21.60	21.75	21.91	
			12	6	21.41	22.03	21.86	
			12	11	21.66	21.71	22.26	
			25	0	21.73	21.83	22.07	
Antenna Gain (dBi):				2.32				
Max. EIRP (dBm):				25.05				
EIRP Limit (dBm):				33.00				
LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)			
					20800	21100	21400	
					2505.0MHz	2535.0MHz	2565.0MHz	
7	10	QPSK	1	0	23.98	24.18	24.07	
			1	24	24.14	24.10	24.24	
			1	49	24.00	23.97	24.26	
			25	0	22.95	23.00	23.18	
			25	12	23.00	23.11	23.24	
			25	24	22.98	23.03	23.33	
			50	0	23.03	23.09	23.25	
		Antenna Gain (dBi):				2.32		
		Max. EIRP (dBm):				26.58		
		EIRP Limit (dBm):				33.00		
		16QAM	1	0	22.64	22.53	22.88	
			1	24	22.79	22.75	22.79	
			1	49	22.52	22.19	22.95	
			25	0	22.19	22.02	22.21	
			25	12	21.98	22.09	22.18	
			25	24	22.01	21.98	22.25	
			50	0	22.02	22.06	22.31	
Antenna Gain (dBi):				2.32				
Max. EIRP (dBm):				25.27				
EIRP Limit (dBm):				33.00				
Note: EIRP (dBm) = Average power (dBm) + Antenna Gain (dBi).								

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)			
					20825	21100	21375	
					2507.5MHz	2535.0MHz	2562.5MHz	
7	15	QPSK	1	0	24.08	24.16	24.11	
			1	37	24.35	24.29	24.08	
			1	74	24.32	24.03	24.41	
			36	0	23.10	23.08	23.08	
			36	16	23.09	23.07	23.16	
			36	35	23.13	23.14	23.26	
			75	0	23.13	23.07	23.20	
		Antenna Gain (dBi):				2.32		
		Max. EIRP (dBm):				26.73		
		EIRP Limit (dBm):				33.00		
		16QAM	1	0	23.00	22.55	23.18	
			1	37	23.39	22.46	22.97	
			1	74	22.90	22.07	22.68	
			36	0	22.06	21.86	21.95	
			36	16	22.05	22.07	22.20	
			36	35	22.10	22.03	22.32	
			75	0	22.15	22.14	22.05	
Antenna Gain (dBi):				2.32				
Max. EIRP (dBm):				25.71				
EIRP Limit (dBm):				33.00				
LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)			
					20850	21100	21350	
					2510.0MHz	2535.0MHz	2560.0MHz	
7	20	QPSK	1	0	23.85	24.11	24.06	
			1	49	24.21	24.12	23.89	
			1	99	24.17	23.94	24.26	
			50	0	23.09	23.20	23.07	
			50	24	23.13	23.09	23.15	
			50	49	23.18	23.15	23.24	
			100	0	23.14	23.10	23.18	
		Antenna Gain (dBi):				2.32		
		Max. EIRP (dBm):				26.58		
		EIRP Limit (dBm):				33.00		
		16QAM	1	0	22.26	22.52	22.83	
			1	49	22.66	22.74	23.23	
			1	99	22.42	22.73	23.33	
			50	0	22.09	22.08	21.96	
			50	24	22.16	22.06	22.03	
			50	49	22.13	22.03	22.12	
			100	0	21.99	21.99	22.05	
Antenna Gain (dBi):				2.32				
Max. EIRP (dBm):				25.65				
EIRP Limit (dBm):				33.00				
Note: EIRP (dBm) = Average power (dBm) + Antenna Gain (dBi).								

Note: EIRP (dBm) = Average power (dBm) + Antenna Gain (dBi).


6.2 Peak-to-Average Ratio

Test Requirement:	Part 27.50(d)(5) RSS-132 section 5.4, RSS-199 section 4.4
Test Method:	ANSI/TIA-603-D 2010
Limit:	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
Test Setup:	 The diagram illustrates the test setup. On the left, there are two blue rectangular units: the top one is labeled 'System simulator' and the bottom one is labeled 'Spectrum Analyzer'. Both have a single output port. These two ports are connected to a single input port of a white rectangular unit labeled 'Splitter'. The 'Splitter' has two output ports. One output port is connected to a black rectangular unit labeled 'ATT' (Attenuator). The other output port is connected to a black rectangular unit labeled 'EUT' (Equipment Under Test).
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 Set the CCDF option in spectrum analyzer, $RBW \geq OBW$, 3 Set the EUT working in highest power level, measured and recorded the 0.1% as PAPR level. 4 Repeat step 1~3 at other frequency and modulations.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data (Worst case):

Bandwidth	Modulation	RB Size	RB Offset	PAPR
LTE Band 5 (Middle Channel)				
10MHz	QPSK	50	0	5.19
	16QAM	50	0	6.26
LTE Band 7 (Middle Channel)				
20MHz	QPSK	100	0	4.90
	16QAM	100	0	5.94

Test plots as below:



6.3 Occupy Bandwidth

Test Requirement:	Part 22.917(b), Part 27.53(m), RSS-GEN section 6.6
Test Method:	RSS-GEN section 6.6, ANSI/TIA-603-D 2010
Test Setup:	 The diagram illustrates the test setup. On the left, there are two blue rectangular units: the top one is labeled 'System simulator' and the bottom one is labeled 'Spectrum Analyzer'. Both have a single output port. These two ports are connected to a single input port of a white rectangular unit labeled 'Splitter'. The 'Splitter' has two output ports. One output port is connected to a black rectangular unit labeled 'ATT' (Attenuator). The other output port is connected to a black rectangular unit labeled 'EUT' (Equipment Under Test).
Test Procedure:	1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer 2. RBW was set to about 1% ~ 5% of emission BW, VBW= 3 times RBW. 3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:

TE Band 5					
Bandwidth	Channel	Frequency (MHz)	Modulation	99% OBW (kHz)	-26dBcEBW (kHz)
1.4MHz	20407	824.7	16QAM	1098	1302
			QPSK	1104	1296
	20525	836.5	16QAM	1098	1284
			QPSK	1104	1302
	20643	848.3	16QAM	1098	1302
			QPSK	1098	1296
3MHz	20415	825.5	16QAM	2724	3048
			QPSK	2736	3060
	20525	836.50	16QAM	2724	3036
			QPSK	2736	3060
	20635	847.50	16QAM	2724	3048
			QPSK	2748	3072
5MHz	20425	826.50	16QAM	4480	4940
			QPSK	4500	5020
	20525	836.50	16QAM	4500	4940
			QPSK	4520	4980
	20625	846.50	16QAM	4480	4920
			QPSK	4480	4960
10MHz	20450	829.00	16QAM	9080	10080
			QPSK	9080	10280
	20525	836.50	16QAM	9040	10200
			QPSK	9080	10200
	20600	844.00	16QAM	9040	10120
			QPSK	9040	10200


LTE Band 7					
Bandwidth	Channel	Frequency (MHz)	Modulation	99% OBW (kHz)	-26dBcEBW (kHz)
5MHz	20775	2502.5	16QAM	4500	4940
			QPSK	4500	4980
	21100	2535.0	16QAM	4480	4980
			QPSK	4520	4980
	21425	2567.5	16QAM	4500	4940
			QPSK	4500	5020
10MHz	20800	2505.0	16QAM	9080	10160
			QPSK	9040	10120
	21100	2535.0	16QAM	9080	10200
			QPSK	9080	10200
	21400	2565.0	16QAM	9080	10280
			QPSK	9040	10160
15MHz	20825	2507.5	16QAM	13500	14820
			QPSK	13500	14880
	21100	2535.0	16QAM	13500	14700
			QPSK	13500	14820
	21375	2562.5	16QAM	13500	14880
			QPSK	13500	14880
20MHz	20850	2510.0	16QAM	17840	19280
			QPSK	18000	19600
	21100	2535.0	16QAM	17840	19360
			QPSK	17920	19360
	21350	2560.0	16QAM	17920	19520
			QPSK	18080	19440

Test plot as follows:
LTE Band 5 part:

LTE Band 5: 99% Occupy bandwidth
BW: 1.4MHz




Date: 29.NOV.2019 14:58:04




Date: 29.NOV.2019 14:56:55

Lowest channel




Date: 29.NOV.2019 14:55:06




Date: 29.NOV.2019 14:53:59

Middle channel




Date: 29.NOV.2019 15:00:02




Date: 29.NOV.2019 14:58:34

Highest channel

LTE Band 5: 99% Occupy bandwidth
BW: 3MHz




Date: 29.NOV.2019 15:02:59




Date: 29.NOV.2019 15:01:34

Lowest channel




Date: 29.NOV.2019 15:05:31




Date: 29.NOV.2019 15:05:21

Middle channel




Date: 29.NOV.2019 15:07:24




Date: 29.NOV.2019 15:07:15

Highest channel

LTE Band 5: 99% Occupy bandwidth
BW: 5MHz




Date: 29.NOV.2019 15:09:32




Date: 29.NOV.2019 15:09:22

Lowest channel




Date: 29.NOV.2019 15:11:29




Date: 29.NOV.2019 15:10:32

Middle channel




Date: 29.NOV.2019 15:13:03




Date: 29.NOV.2019 15:12:48

Highest channel

LTE Band 5: 99% Occupy bandwidth
BW: 10MHz




Date: 29.NOV.2019 15:15:39




Date: 29.NOV.2019 15:15:31

Lowest channel




Date: 29.NOV.2019 15:16:22




Date: 29.NOV.2019 15:16:34

Middle channel



Date: 29.NOV.2019 15:17:28




Date: 29.NOV.2019 15:17:19

Highest channel


LTE Band 5: -26dBc bandwidth
BW: 1.4MHz

16QAM



Date: 29.NOV.2019 14:57:46


QPSK



Date: 29.NOV.2019 14:57:11


Lowest channel

16QAM



Date: 29.NOV.2019 14:54:28


QPSK



Date: 29.NOV.2019 14:54:18


Middle channel

16QAM



Date: 29.NOV.2019 14:59:21


QPSK




Date: 29.NOV.2019 14:59:07

Highest channel

LTE Band 5: -26dBc bandwidth BW: 3MHz




Date: 29.NOV.2019 15:03:24




Date: 29.NOV.2019 15:01:49

Lowest channel




Date: 29.NOV.2019 15:05:46




Date: 29.NOV.2019 15:05:09

Middle channel



Date: 29.NOV.2019 15:07:41




Date: 29.NOV.2019 15:07:04

Highest channel


LTE Band 5: -26dBc bandwidth
BW: 5MHz

16QAM



Date: 29.NOV.2019 15:09:49


QPSK



Date: 29.NOV.2019 15:09:05


Lowest channel

16QAM



Date: 29.NOV.2019 15:11:47


QPSK



Date: 29.NOV.2019 15:10:21


Middle channel

16QAM



Date: 29.NOV.2019 15:13:14

QPSK




Date: 29.NOV.2019 15:12:32

Highest channel


LTE Band 5: -26dBc bandwidth
BW: 10MHz

16QAM



Date: 29.NOV.2019 15:15:49


QPSK



Date: 29.NOV.2019 15:15:12


Lowest channel

16QAM



Date: 29.NOV.2019 15:16:12


QPSK



Date: 29.NOV.2019 15:16:46


Middle channel

16QAM



Date: 29.NOV.2019 15:17:45

QPSK




Date: 29.NOV.2019 15:17:09


Highest channel

LTE-Band 7 part:

LTE Band 7: 99% Occupy bandwidth BW: 5MHz




Date: 29.NOV.2019 14:33:27




Date: 29.NOV.2019 14:33:18

Lowest channel




Date: 29.NOV.2019 14:32:18




Date: 29.NOV.2019 14:31:46

Middle channel




Date: 29.NOV.2019 14:34:26




Date: 29.NOV.2019 14:34:15

Highest channel

LTE Band 7: 99% Occupancy bandwidth BW: 10MHz




Date: 29.NOV.2019 14:27:41




Date: 29.NOV.2019 14:27:26

Lowest channel




Date: 29.NOV.2019 14:28:45




Date: 29.NOV.2019 14:28:36

Middle channel



Date: 29.NOV.2019 14:30:09




Date: 29.NOV.2019 14:29:53

Highest channel


LTE Band 7: 99% Occupancy bandwidth BW: 15MHz

16QAM



Date: 29.NOV.2019 14:23:04


QPSK



Date: 29.NOV.2019 14:22:56


Lowest channel

16QAM



Date: 29.NOV.2019 14:21:15


QPSK



Date: 29.NOV.2019 14:21:00


Middle channel

16QAM



Date: 29.NOV.2019 14:24:19

QPSK




Date: 29.NOV.2019 14:24:07

Highest channel


LTE Band 7: 99% Occupancy bandwidth BW: 20MHz

16QAM



Date: 29.NOV.2019 14:19:11


QPSK



Date: 29.NOV.2019 14:18:48


Lowest channel

16QAM



Date: 29.NOV.2019 14:14:41


QPSK



Date: 29.NOV.2019 14:14:24


Middle channel

16QAM



Date: 29.NOV.2019 14:12:45

QPSK




Date: 29.NOV.2019 14:12:36

Highest channel


LTE Band 7: -26dBc bandwidth
BW: 5MHz

16QAM



Date: 29.NOV.2019 14:33:39


QPSK



Date: 29.NOV.2019 14:33:05


Lowest channel

16QAM



Date: 29.NOV.2019 14:32:42


QPSK



Date: 29.NOV.2019 14:31:32


Middle channel

16QAM



Date: 29.NOV.2019 14:34:43

QPSK




Date: 29.NOV.2019 14:34:04

Highest channel


LTE Band 7: -26dBc bandwidth BW: 10MHz

16QAM



Date: 29.NOV.2019 14:27:56


QPSK



Date: 29.NOV.2019 14:26:57


Lowest channel

16QAM



Date: 29.NOV.2019 14:29:11


QPSK



Date: 29.NOV.2019 14:28:23


Middle channel

16QAM



Date: 29.NOV.2019 14:30:29

QPSK




Date: 29.NOV.2019 14:29:39

Highest channel


LTE Band 7: -26dBc bandwidth
BW: 15MHz

16QAM



Date: 29.NOV.2019 14:23:18


QPSK



Date: 29.NOV.2019 14:22:43


Lowest channel

16QAM



Date: 29.NOV.2019 14:22:00


QPSK



Date: 29.NOV.2019 14:21:43


Middle channel

16QAM



Date: 29.NOV.2019 14:24:36

QPSK




Date: 29.NOV.2019 14:23:55

Highest channel


LTE Band 7: -26dBc bandwidth BW: 20MHz

16QAM



Date: 29.NOV.2019 14:15:38


QPSK



Date: 29.NOV.2019 14:15:30


Lowest channel

16QAM



Date: 29.NOV.2019 14:14:59


QPSK



Date: 29.NOV.2019 14:13:56


Middle channel

16QAM



Date: 29.NOV.2019 14:13:10


QPSK



Date: 29.NOV.2019 14:13:23


Highest channel

6.4 Out of band emission at antenna terminals

Test Requirement:	Part 22.917(b), Part 27.53(m) RSS-132 section 5.5, , RSS-199 section 4.5
Test Method:	RSS-GEN section 6.13, ANSI/TIA-603-D 2010
Limit:	LTE Band 5: The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB (-13 dBm). LTE Band 7: For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.
Test Setup:	
Test Procedure:	1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation. 2 The resolution bandwidth of the spectrum analyzer was set at 100 kHz when below 1GHz, 1MHz when above 1 GHz; sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic. 3 For the out of band: Set the RBW=100 kHz, VBW=300 kHz when below 1 GHz, RBW =1 MHz, VBW=3 MHz when above 1 GHz, Start=30MHz, Stop= 10th harmonic. 4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	Pre-scan all RB Size and offset, and found the RB Size and offset of worst case, so the report shows only the worst case test data.


Test plots as follows (Conducted spurious emission) (worst case):
LTE Band 5 part:

LTE Band 5: 16 QAM & RB Size 1 BW: 1.4MHz Lowest channel



Date: 29.NOV.2019 13:03:43


30MHz~1GHz



Date: 29.NOV.2019 13:40:07


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 13:03:17


30MHz~1GHz



Date: 29.NOV.2019 13:39:44


1GHz~25GHz

High channel



Date: 29.NOV.2019 13:04:14

30MHz~1GHz




Date: 29.NOV.2019 13:40:51

1GHz~25GHz


LTE Band 5: QPSK & RB Size 1

BW: 1.4MHz
Lowest channel



Date: 29.NOV.2019 13:59:41


30MHz~1GHz



Date: 29.NOV.2019 13:40:20


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 13:59:10


30MHz~1GHz



Date: 29.NOV.2019 13:39:27


1GHz~25GHz

High channel



Date: 29.NOV.2019 14:00:06


30MHz~1GHz



Date: 29.NOV.2019 13:41:05


1GHz~25GHz

LTE Band 5: 16 QAM & RB Size 1 BW: 10MHz Lowest channel



Date: 29.NOV.2019 13:11:26


30MHz~1GHz



Date: 29.NOV.2019 13:43:00


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 13:11:00


30MHz~1GHz



Date: 29.NOV.2019 13:42:08


1GHz~25GHz

High channel



Date: 29.NOV.2019 13:12:06


30MHz~1GHz



Date: 29.NOV.2019 13:43:46


1GHz~25GHz

LTE Band 5: QPSK & RB Size 1 BW: 10MHz Lowest channel



Date: 29.NOV.2019 13:58:34


30MHz~1GHz



Date: 29.NOV.2019 13:43:16


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 13:58:05


30MHz~1GHz



Date: 29.NOV.2019 13:42:32


1GHz~25GHz

High channel



Date: 29.NOV.2019 13:57:14

30MHz~1GHz




Date: 29.NOV.2019 13:44:00

1GHz~25GHz


LTE Band 7 part:

LTE Band 7: 16 QAM & RB Size 1 BW: 5MHz Lowest channel



Date: 29.NOV.2019 13:17:42


30MHz~1GHz



Date: 29.NOV.2019 13:35:05


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 13:17:20


30MHz~1GHz



Date: 29.NOV.2019 13:32:37


1GHz~25GHz

High channel



Date: 29.NOV.2019 13:18:01

30MHz~1GHz




Date: 29.NOV.2019 13:36:19

1GHz~25GHz

LTE Band 7: QPSK & RB Size 1


BW: 5MHz

Lowest channel



Date: 29.NOV.2019 14:02:49


30MHz~1GHz



Date: 29.NOV.2019 13:35:22


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 14:02:28


30MHz~1GHz



Date: 29.NOV.2019 13:32:07


1GHz~25GHz

High channel



Date: 29.NOV.2019 14:03:07


30MHz~1GHz



Date: 29.NOV.2019 13:35:54


1GHz~25GHz

LTE Band 7: 16 QAM & RB Size 1 BW: 20MHz Lowest channel



Date: 29.NOV.2019 13:20:39


30MHz~1GHz



Date: 29.NOV.2019 13:30:12


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 13:19:12


30MHz~1GHz



Date: 29.NOV.2019 13:29:38


1GHz~25GHz

High channel



Date: 29.NOV.2019 13:21:01


30MHz~1GHz



Date: 29.NOV.2019 13:27:34


1GHz~25GHz

LTE Band 7: QPSK & RB Size 1 BW: 20MHz Lowest channel



Date: 29.NOV.2019 14:03:54


30MHz~1GHz



Date: 29.NOV.2019 13:30:30


1GHz~25GHz

Middle channel



Date: 29.NOV.2019 14:03:38


30MHz~1GHz



Date: 29.NOV.2019 13:29:18


1GHz~25GHz

High channel




Date: 29.NOV.2019 14:04:09

30MHz~1GHz




Date: 29.NOV.2019 13:28:18

1GHz~25GHz

Band edge emission:**LTE Band 5 part:****LTE Band 5, BW: 1.4MHz
16QAM & RB Size 1**


Date: 2.APR.2020 07:56:48

Lowest channel




Date: 2.APR.2020 07:57:12

Highest channel

16QAM & RB Size 6


Date: 29.NOV.2019 10:44:58

Lowest channel




Date: 29.NOV.2019 10:45:47

Highest channel

LTE Band 5, BW: 1.4MHz
QPSK & RB Size 1

Date: 2.APR.2020 07:56:43


Lowest channel



Date: 2.APR.2020 07:57:06


Highest channel

QPSK & RB Size 6




Date: 29.NOV.2019 10:44:46

Lowest channel




Date: 29.NOV.2019 10:45:36

Highest channel

LTE Band 5, BW: 10MHz
16QAM & RB Size 1

Date: 2.APR.2020 08:04:48


Lowest channel



Date: 2.APR.2020 08:04:19


Highest channel

16QAM & RB Size 50




Date: 29.NOV.2019 10:40:59

Lowest channel




Date: 29.NOV.2019 10:40:07

Highest channel

LTE Band 5, BW: 10MHz
QPSK & RB Size 1

Date: 2.APR.2020 08:04:44


Lowest channel



Date: 2.APR.2020 08:04:15


Highest channel

QPSK & RB Size 50



Date: 29.NOV.2019 10:40:47


Lowest channel



Date: 29.NOV.2019 10:39:54


Highest channel

LTE Band 7 part:

LTE Band 7, BW: 5MHz
16QAM & RB Size 1

Date: 2.APR.2020 08:06:10


Lowest channel



Date: 2.APR.2020 08:06:40


Highest channel

16QAM & RB Size 25




Date: 2.APR.2020 08:16:54

Lowest channel




Date: 2.APR.2020 08:16:01

Highest channel

LTE Band 7, BW: 5MHz
QPSK & RB Size 1

Date: 2.APR.2020 08:06:03


Lowest channel



Date: 2.APR.2020 08:06:34


Highest channel

QPSK & RB Size 25




Date: 2.APR.2020 08:16:39

Lowest channel




Date: 2.APR.2020 08:16:09

Highest channel

LTE Band 7, BW: 20MHz
16QAM & RB Size 1

Date: 2.APR.2020 08:07:54


Lowest channel



Date: 2.APR.2020 08:07:20


Highest channel

16QAM & RB Size 100




Date: 29.NOV.2019 10:51:47

Lowest channel




Date: 29.NOV.2019 10:52:26

Highest channel

LTE Band 7, BW: 20MHz
QPSK & RB Size 1

Date: 2.APR.2020 08:07:48


Lowest channel



Date: 2.APR.2020 08:07:15


Highest channel

QPSK & RB Size 100



Date: 21.NOV.2019 15:12:14



Lowest channel



Date: 21.NOV.2019 15:11:39

Highest channel

6.5 Field strength of spurious radiation measurement

Test Requirement:	Part 22.917(b), Part 27.53(m), RSS-132 section 5.5, RSS-199 section 4.5
Test Method:	RSS-GEN section 6.13, ANSI/TIA-603-D 2010
Limit:	LTE Band 5: The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB (-13 dBm). LTE Band 7: For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.
Test setup:	Below 1GHz  Above 1GHz 
Test Procedure:	1. The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer. 2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations. 3. The frequency range up to tenth harmonic was investigated for each

	of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method. 4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency. $\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}$
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details.
Test results:	Passed

Measurement Data:

LTE Band 5 part:

1.4MHz(RB size 1 & RB offset 0) for QPSK							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1649.40	-60.47	9.58	0.22	-51.11	-13.00	-38.11	Vertical
2474.10	-54.80	10.79	0.29	-44.29	-13.00	-31.29	Vertical
3298.80	-62.64	12.14	0.37	-50.87	-13.00	-37.87	Vertical
1649.40	-56.94	9.58	0.22	-47.58	-13.00	-34.58	Horizontal
2474.10	-55.96	10.79	0.29	-45.45	-13.00	-32.45	Horizontal
3298.80	-62.71	12.14	0.37	-50.94	-13.00	-37.94	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1673.30	-59.99	9.62	0.25	-50.62	-13.00	-37.62	Vertical
2509.50	-54.40	10.83	0.32	-43.88	-13.00	-30.88	Vertical
3346.00	-62.25	12.23	0.40	-50.42	-13.00	-37.42	Vertical
1673.30	-57.10	9.62	0.25	-47.73	-13.00	-34.73	Horizontal
2509.50	-56.29	10.83	0.32	-45.77	-13.00	-32.77	Horizontal
3346.00	-63.27	12.23	0.40	-51.44	-13.00	-38.44	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1696.60	-60.07	9.66	0.26	-50.66	-13.00	-37.66	Vertical
2544.90	-54.01	10.88	0.34	-43.47	-13.00	-30.47	Vertical
3393.20	-62.26	12.32	0.41	-50.34	-13.00	-37.34	Vertical
1696.60	-57.05	9.66	0.26	-47.64	-13.00	-34.64	Horizontal
2544.90	-56.46	10.88	0.34	-45.92	-13.00	-32.92	Horizontal
3393.20	-63.78	12.32	0.41	-51.86	-13.00	-38.86	Horizontal
Remark:							
1. The emission levels of below 1 GHz are very lower than the limit and not show in test report.							


10MHz(RB size 1 & RB offset 0) for QPSK							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1658.00	-60.56	9.58	0.22	-51.20	-13.00	-38.20	Vertical
2487.00	-55.26	10.79	0.29	-44.75	-13.00	-31.75	Vertical
3316.00	-62.21	12.14	0.37	-50.44	-13.00	-37.44	Vertical
1658.00	-56.40	9.58	0.22	-47.04	-13.00	-34.04	Horizontal
2487.00	-56.76	10.79	0.29	-46.25	-13.00	-33.25	Horizontal
3316.00	-63.62	12.14	0.37	-51.85	-13.00	-38.85	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1673.30	-60.23	9.62	0.25	-50.86	-13.00	-37.86	Vertical
2509.50	-54.86	10.83	0.32	-44.34	-13.00	-31.34	Vertical
3346.00	-62.30	12.23	0.40	-50.47	-13.00	-37.47	Vertical
1673.30	-56.88	9.62	0.25	-47.51	-13.00	-34.51	Horizontal
2509.50	-56.71	10.83	0.32	-46.19	-13.00	-33.19	Horizontal
3346.00	-63.73	12.23	0.40	-51.90	-13.00	-38.90	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
1688.00	-59.98	9.66	0.26	-50.57	-13.00	-37.57	Vertical
2532.00	-54.50	10.88	0.34	-43.96	-13.00	-30.96	Vertical
3376.00	-62.51	12.32	0.41	-50.59	-13.00	-37.59	Vertical
1688.00	-56.80	9.66	0.26	-47.39	-13.00	-34.39	Horizontal
2532.00	-56.57	10.88	0.34	-46.03	-13.00	-33.03	Horizontal
3376.00	-63.56	12.32	0.41	-51.64	-13.00	-38.64	Horizontal
Remark:							
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.							

LTE Band 7 part:

5MHz(RB size 1 & RB offset 0) for QPSK							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
5005.00	-51.02	12.61	0.64	-39.05	-25.00	-14.05	Vertical
7507.50	-48.65	11.17	0.96	-38.44	-25.00	-13.44	Vertical
10010.00	-45.01	11.62	1.12	-34.51	-25.00	-9.51	Vertical
5005.00	-53.95	12.61	0.64	-41.98	-25.00	-16.98	Horizontal
7507.50	-49.31	11.17	0.96	-39.10	-25.00	-14.10	Horizontal
10010.00	-45.79	11.62	1.12	-35.29	-25.00	-10.29	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
5070.00	-51.12	12.62	0.65	-39.15	-25.00	-14.15	Vertical
7605.00	-48.84	11.20	0.98	-38.62	-25.00	-13.62	Vertical
10140.00	-45.22	11.64	1.14	-34.72	-25.00	-9.72	Vertical
5070.00	-53.76	12.62	0.65	-41.79	-25.00	-16.79	Horizontal
7605.00	-49.49	11.20	0.98	-39.27	-25.00	-14.27	Horizontal
10140.00	-46.14	11.64	1.14	-35.64	-25.00	-10.64	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
5135.00	-51.28	12.64	0.66	-39.30	-25.00	-14.30	Vertical
7702.50	-48.87	11.21	0.92	-38.58	-25.00	-13.58	Vertical
10270.00	-45.49	11.66	1.18	-35.01	-25.00	-10.01	Vertical
5135.00	-54.05	12.64	0.66	-42.07	-25.00	-17.07	Horizontal
7702.50	-49.76	11.21	0.92	-39.47	-25.00	-14.47	Horizontal
10270.00	-46.59	11.66	1.18	-36.11	-25.00	-11.11	Horizontal
Remark:							
3. The emission levels of below 1 GHz are very lower than the limit and not show in test report.							

20MHz(RB size 1 & RB offset 0) for QPSK							
Lowest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
5020.00	-50.76	12.61	0.65	-38.80	-25.00	-13.80	Vertical
7530.00	-48.97	11.19	0.97	-38.75	-25.00	-13.75	Vertical
10040.00	-45.07	11.63	1.13	-34.57	-25.00	-9.57	Vertical
5020.00	-53.74	12.61	0.65	-41.78	-25.00	-16.78	Horizontal
7530.00	-49.47	11.19	0.97	-39.25	-25.00	-14.25	Horizontal
10040.00	-45.59	11.63	1.13	-35.09	-25.00	-10.09	Horizontal
Middle channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
5070.00	-51.21	12.62	0.65	-39.24	-25.00	-14.24	Vertical
7605.00	-49.33	11.20	0.98	-39.11	-25.00	-14.11	Vertical
10140.00	-44.91	11.64	1.14	-34.41	-25.00	-9.41	Vertical
5070.00	-53.82	12.62	0.65	-41.85	-25.00	-16.85	Horizontal
7605.00	-49.60	11.20	0.98	-39.38	-25.00	-14.38	Horizontal
10140.00	-45.63	11.64	1.14	-35.13	-25.00	-10.13	Horizontal
Highest channel							
Frequency (MHz)	Level at antenna terminals (dBm)	Substitute antenna gain (dBi)	Cable Loss (dBi)	Spurious Emission level (dBm)	Limit Line (dBm)	Over Limit (dBm)	Polarization
5120.00	-51.09	12.64	0.66	-39.11	-25.00	-14.11	Vertical
7680.00	-49.33	11.21	0.92	-39.04	-25.00	-14.04	Vertical
10240.00	-45.38	11.66	1.18	-34.90	-25.00	-9.90	Vertical
5120.00	-53.89	12.64	0.66	-41.91	-25.00	-16.91	Horizontal
7680.00	-49.92	11.21	0.92	-39.63	-25.00	-14.63	Horizontal
10240.00	-45.76	11.66	1.18	-35.28	-25.00	-10.28	Horizontal
Remark:							
4. The emission levels of below 1 GHz are very lower than the limit and not show in test report.							

6.6 Frequency stability V.S. Temperature measurement

Test Requirement:	Part 22.355, Part 27.54, Part 2.1055(a)(1)(b) RSS-132 section 5.3, RSS-199 section 4.3
Test Method:	RSS-GEN section 6.11, ANSI/TIA-603-D 2010
Limit:	$\pm 2.5\text{ppm}$
Test setup:	
Test procedure:	1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data (worst case):


LTE Band 5 part:

Reference Frequency: LTE Band 5 (10MHz) Middle channel=20525 channel=836.50MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
QPSK					
3.70	-30	186	0.222355	±2.5	Pass
	-20	177	0.211596		
	-10	169	0.202032		
	0	160	0.191273		
	10	140	0.167364		
	20	152	0.181710		
	30	133	0.158996		
	40	121	0.144650		
	50	110	0.131500		
16QAM					
3.70	-30	180	0.215182	±2.5	Pass
	-20	173	0.206814		
	-10	165	0.197250		
	0	158	0.188882		
	10	150	0.179319		
	20	129	0.154214		
	30	134	0.160191		
	40	140	0.167364		
	50	109	0.130305		
Note: Only the worst case shown in the report.					

LTE Band 7 part:

Reference Frequency: LTE Band 7 (10MHz) Middle channel=21100 Frequency=2535.00MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
QPSK					
3.70	-30	173	0.068245	±2.5	Pass
	-20	160	0.063116		
	-10	151	0.059566		
	0	146	0.057594		
	10	140	0.055227		
	20	135	0.053254		
	30	129	0.050888		
	40	120	0.047337		
	50	112	0.044181		
16QAM					
3.70	-30	170	0.067061	±2.5	Pass
	-20	160	0.063116		
	-10	154	0.060750		
	0	146	0.057594		
	10	139	0.054832		
	20	132	0.052071		
	30	124	0.048915		
	40	116	0.045759		
	50	108	0.042604		
Note: Only the worst case shown in the report.					

6.7 Frequency stability V.S. Voltage measurement

Test Requirement:	Part 22.355, Part 27.54, Part 2.1055(d)(2) RSS-132 section 5.3, RSS-199 section 4.3
Test Method:	RSS-GEN section 6.11, ANSI/TIA-603-D 2010
Limit:	$\pm 2.5\text{ppm}$
Test setup:	 The diagram illustrates the test setup. On the left, there are two blue rectangular blocks labeled 'SS' (Signal Source) and 'SA' (Spectrum Analyzer). They are connected to a central grey block labeled 'Divider'. The output of the 'Divider' is connected to a black rectangular block labeled 'EUT' (Equipment Under Test) inside a blue-bordered box labeled 'Temperature & Humidity Chamber'. Below the chamber, there is a grey block labeled 'Power Source' with two green terminals. Red lines connect the 'Power Source' to the 'EUT'.
Test procedure:	1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. 3. Reduce the input voltage to specify extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data (worst case):

LTE Band 5 part:

Reference Frequency: LTE Band 5(10MHz) Middle channel=20525 channel=836.50MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
QPSK					
25	4.2	98	0.117155	±2.5	Pass
	3.7	80	0.095637		
	3.5	74	0.088464		
16QAM					
25	4.2	90	0.107591	±2.5	Pass
	3.7	80	0.095637		
	3.5	69	0.082487		
Note: Only the worst case shown in the report.					

LTE Band 7 part:

Reference Frequency: LTE Band 7(10MHz) Middle channel=21100 Frequency=2535.00MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
QPSK					
25	4.2	83	0.032742	±2.5	Pass
	3.7	76	0.029980		
	3.5	65	0.025641		
16QAM					
25	4.2	80	0.031558	±2.5	Pass
	3.7	70	0.027613		
	3.5	58	0.022880		
Note: Only the worst case shown in the report.					

7 Test Setup Photo

Radiated Spurious Emission
Below 1GHz



Above 1GHz



8 EUT Constructional Details

Reference to the test report No. CCISE191107101.

-----End of report-----