

	-2.00"-	
	VOLVO	
CUSTOMER ASSIGNED ———		
PART NUMBER CUSTOMER ASSIGNED	53351 yywwdxxx	SEE NOTE 6
Supplier number	MADE IN <country></country>	SEE NOTE 7
	P1TSQ22734Tyywwdsxaff	CUSTOMER SUPPLIE CONTENT SEE NOTE 8
	MODEL: SCU	
	FCC ID: XGS-SCU IC ID: 11881A-SCU	
	CE IP67	
	TANMSN: 601VOLxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx	SEE NOTE 9
	DO NOT OPEN, NO SERVICEABLE	
	COMPONENTS INSIDE	
	THE LABEL ARTWORK SHOWN IN THIS VIEW IS FOR REFERENCE ONLY	

(FIXED VALUE)

(EXAMPLE ONLY)

VIEW A-A

REVISIONS					
REV	ECO	DESCRIPTION	DATE	APPROVAL	
Α	5600	INITIAL RELEASE	26-JUL-21	M. RODGERS	

NOTES:

- 1. REFERENCE BOM FOR SPECIFIC LABEL STOCK. PRINTABLE GLOSSY METALLIZED POLLESTER PERMANENT LABEL MATERIAL. SUBSTITUTE WITH ORBCOMM APPROVAL ONLY.
- 2. USE BRADY UL RECOMMENDED B-434 LABELS AND RIBBONS. SUBSTITUTE WITH ORBCOMM APPROVAL ONLY.
- 3. LABEL MUST MEET THE FOLLOWING REQUIREMENTS:
- UL STANDARD: UL969
- UL FILE NO: MH17154.
- 4. PARTS TO BE MANUFACTURED IN COMPLIANCE WITH THE MOST CURRENT ROHS & REACH DIRECTIVE. ROHS & REACH DECLARATION MUST BE SUBMITTED WITH FIRST ARTICLE INSPECTION SAMPLES, AND RESUBMITTED WHENEVER NEW CHANGES TO THE DIRECTIVES ARE ISSUED.
- 5. REFERENCE THE LATEST REVISION OF THE MASTER ARTWORK, ATTACHED TO THE DIGITAL VARIANT PART NUMBER RECORD.
- 1. LABEL CONTENT MUST BE PRINTED EXACTLY AS SHOWN IN THE ARTWORK
- 2. LOCATION, STYLE AND SIZE OF ALL TEXT, GRAPHICS AND BARCODES MUST BE DUPLICATED EXACTLY.
 3. ANY DEVIATION FROM THE ARTWORK MUST BE APPROVED BY ORBCOMM ENGINEERING.
- 6. USING THE FONT SIZE AND LOCATION SPECIFIED IN THE ARTWORK, PRINT THE UNIT SERIAL NUMBER USING THE FORMAT "YYWWDXXX" WHERE "YY" IS THE LAST TWO NUMBERS OF THE CURRENT YEAR, "WW" IS THE WEEK OF THE CURRENT YEAR, "D" IS THE DAY OF THE CURRENT WEEK (MONDAY = 1, ETC) AND "XXX" IS THE RUNNING NUMBER, STARTING AT 001 EACH WEEK.
- 7. USING THE FONT SIZE AND LOCATION SPECIFIED, REPACE "<COUNTRY>" WITH COUNTRY OF MANUFACTURE.
- 8. IN BAR CODE 128 FORMAT ADD "P17508273#Tyywwdxxx#", WHERE "yyxxdxxx" MATCHES THE UNIT SERIAL NUMBER PER NOTE 6. HUMAN READABLE VERSÍÓN OF THIS SAME TEXT TO BE LOCATED CENTERED UNDER THE BARCODE AS SHOWN.
- 9. IN TEXT FORMAT ADD THE COMPLETE SATELLITE IDENTIFICATION NUMBER AS FOLLOWS: ADD THE COMPLETE 18 CHARACTER OG2 TAN+M\$N NUMBER SCANNED FROM THE SATELLITE MODEM, UNIT CARD, OR A LOOK-UP TABLE. TAN I =6-CHARACTERS, MSN FIELD =12-CHARACTERS. TAN +MSN STRING MUST BE LISTED IN THIS ORDER WITH TAN NUMBER FIRST & NO SPACES OR DASHES SEPARATING THE NUMBERS. SEE EXAMPLE VIEW A-A.

