



东莞市超威电子有限公司
Chaowei Electronics CO.,LTD

规格书

客 户：
品 名：2.4/5.8G WIFI Antenna
料 号：CW-TG2458G48-113IPEX80B
客户料号：
送样日期：2023.07.25

客户确认			供应厂商	
工程部	品保部	采购部	核准	送样人
			赵 2023.07.25 亚军	梁泳婷

地址：东莞市长安镇厦岗沙区祥隆路8号

TEL：0769-85644081


E-mail:zhaojack1@163.com

http://chaowei2000.1688.com

RoHS

Compatible

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



东莞市超威电子有限公司

产品名称 2.4/5.8G WIFI Antenna
 产品料号 CW-TG2458G48-113IPEX80B

缩放比例 NONE 单位 MM

核准人 审核人 制图人

赵军 冯大想 汪明



尺寸公差
 x. ±1.0
 x.x ±0.5
 x.xx ±0.1
 x° ±1°

REV.

A

4	CW-RSTG-01	Heat shrinkable casing	Ø3*L30mm	1
3	CW-TG24-5.2T	Copper pipe	Brass Tin plating	2
2	CW-XC-113-B	Coaxial Cable 1.13	OD:1.13MM Black	1
1	CW-IPEX-01	i-pex-l	CU Gold plating	1
NO	Part Number	Name	Material	Qt'y

1 2 3 4 5 6 7 8

Index:

- 1. Reliability Testing**
- 2. Specification**
- 3. S Parameter Test Data**
- 4. Antenna Radiation Pattern**




1. Reliability Testing

Test Item	Procedure	Requirement
1. Visual inspection and Dimension Check	Applicable methods using x5 magnification	follow specification
2. Rapid Changing of Temperature	-40°C (30minutes) to 80°C (30minutes); 24 cycles	After 2 hours recovery: 1. no visible damage 2. bandwidth tolerance < ±5%
3. Damp Heat	24 hours at 60°C; 90 ~ 95% RH	After 2 hours recovery: 1. no visible damage 2. bandwidth tolerance < ±5%
4. Endurance	24 hours at 80°C	After 2 hours recovery: 1. no visible damage 2. bandwidth tolerance < ±5%
5. Connector Pull Strength Test	>= 1.0 Kg	Hold 2~3S: 1. no visible damage 2. bandwidth tolerance < ±5%

2. Specification


GPS Antenna	
4G Antenna	
Working Frequency	2.4G(2400-2500MHz) 5G(5150-5850MHz)
VS.W.R	<2.0
Gain	4dBi
Polarization	Vertical
Impedance	50 Ohm
Material of Plastic	Brass
Connector Type	I-PEX

























3. S.W.R. Testing Result



4. Antenna Radiation Pattern

Frequency ID	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
Frequency (MHz)	2400.0	2450.0	2500.0	5150.0	5200.0	5250.0	5300.0	5350.0	5400.0	5450.0	5500.0	5550.0	5600.0	5650.0	5700.0	5750.0	5800.0	5850.0	5900.0	5950.0
Efficiency (dBi)	-1.64	-1.29	-1.03	-1.17	-1.48	-1.00	-1.57	-1.16	-0.98	-0.35	-1.14	-1.15	-1.74	-0.97	-1.70	-0.57	-1.84	-1.40	-2.15	-1.93
Gain (dBi)	2.81	3.67	3.06	3.11	2.43	3.13	2.93	2.54	3.29	3.88	3.34	2.75	1.99	3.28	2.46	3.42	2.26	2.52	2.20	3.11
Efficiency (%)	68.56	74.33	78.94	76.39	71.09	79.46	69.68	76.58	79.88	92.22	76.86	76.72	66.93	79.98	67.67	87.64	65.53	72.45	61.02	64.10
Directivity (dB)	4.45	4.96	4.09	4.27	3.91	4.13	4.50	3.70	4.27	4.23	4.48	3.90	3.73	4.25	4.15	3.99	4.09	3.92	4.34	5.04
Peak Gain Position (Theta)	112.00	110.00	108.00	110.00	110.00	107.00	108.00	107.00	104.00	106.00	101.00	106.00	106.00	104.00	105.00	102.00	102.00	132.00	22.00	22.00
Peak Gain Position (Phi)	90.00	90.00	90.00	180.00	180.00	360.00	180.00	180.00	360.00	180.00	30.00	360.00	300.00	360.00	300.00	360.00	360.00	270.00	150.00	150.00
Efficiency ThetaPol (%)	61.18	68.55	74.54	74.58	69.57	77.76	68.41	74.53	77.32	89.74	74.45	74.41	64.24	76.55	64.35	82.88	61.42	68.02	56.11	59.74
Efficiency PhiPol (%)	7.38	5.78	4.40	1.81	1.52	1.70	1.27	2.05	2.56	2.47	2.41	2.32	2.68	3.43	3.32	4.76	4.11	4.42	4.91	4.37
Upper Hem. Efficiency (%)	21.64	24.49	26.29	25.48	24.47	27.30	24.25	26.76	26.77	29.11	22.88	21.76	17.93	19.79	16.68	19.96	14.62	16.70	14.27	16.58
Lower Hem. Efficiency (%)	46.92	49.84	52.65	50.92	46.62	52.15	45.42	49.82	53.12	63.10	53.97	54.96	48.99	60.19	50.99	67.68	50.91	55.74	46.75	47.52
Eff 15deg (dBi)																				
Gain 15deg (dBi)																				
Eff 15deg (%)																				
Eff 30deg (dBi)																				
Gain 30deg (dBi)																				
Eff 30deg (%)																				
Empty																				





5. Testing Equipment Specification:

Antenna Anechoic Chamber Dimension: 7x3 x3 m

Quiet Zone: 600mm @1 GHz

Isolation: >100dB @ 1 MHz ~ 10 GHz

Testing Equipment: Agilent E5071C

Received Antenna: 0.4 ~ 6.0 GHz for Gain Calibration

Double Ridged Horn Antenna

