



**FCC CFR47 PART 15 SUBPART C
INDUSTRY CANADA RSS-210 ISSUE 7**

CERTIFICATION TEST REPORT

FOR

EBOOK READER WITH WWAN, WLAN AND USB PORTS

MODEL NUMBER: BNRZ100-01

**FCC ID: XHHBNRZ100-1
IC: 8961A-BNRZ10001**

REPORT NUMBER: 10U13105-1

ISSUE DATE: JUNE 10, 2010

Prepared for
BARNES AND NOBLE
400 HAMILTON AVENUE
PALO ALTO, CA 94301, U.S.A.

Prepared by
COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP[®]

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	06/10/10	Initial Issue	T. Chan

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	6
4.2. <i>SAMPLE CALCULATION.....</i>	6
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	6
5. EQUIPMENT UNDER TEST	7
5.1. <i>DESCRIPTION OF EUT.....</i>	7
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	7
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS.....</i>	7
5.4. <i>SOFTWARE AND FIRMWARE.....</i>	7
5.5. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
5.6. <i>DESCRIPTION OF TEST SETUP.....</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. ANTENNA PORT TEST RESULTS	11
7.1. <i>802.11b MODE IN THE 2.4 GHz BAND.....</i>	11
7.1.1. 6 dB BANDWIDTH	11
7.1.2. 99% BANDWIDTH	15
7.1.3. OUTPUT POWER	19
7.1.4. AVERAGE POWER	20
7.1.5. POWER SPECTRAL DENSITY	21
7.1.6. CONDUCTED SPURIOUS EMISSIONS.....	25
7.2. <i>802.11g MODE IN THE 2.4 GHz BAND.....</i>	29
7.2.1. 6 dB BANDWIDTH	29
7.2.2. 99% BANDWIDTH	32
7.2.3. OUTPUT POWER	35
7.2.4. AVERAGE POWER	36
7.2.5. POWER SPECTRAL DENSITY	37
7.2.6. CONDUCTED SPURIOUS EMISSIONS.....	40
8. RADIATED TEST RESULTS	44
8.1. <i>LIMITS AND PROCEDURE</i>	44
8.2. <i>TRANSMITTER ABOVE 1 GHz</i>	45
8.2.1. TRANSMITTER ABOVE 1 GHz FOR 802.11b MODE IN THE 2.4 GHz BAND ..	45
8.2.2. TRANSMITTER ABOVE 1 GHz FOR 802.11g MODE IN THE 2.4 GHz BAND ..	50
8.3. <i>RECEIVER ABOVE 1 GHz</i>	55

8.4. WORST-CASE BELOW 1 GHz.....	56
9. AC POWER LINE CONDUCTED EMISSIONS	59
10. MAXIMUM PERMISSIBLE EXPOSURE	63
11. SETUP PHOTOS	66

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: BARNES AND NOBLE
400 Hamilton Avenue.
PALO ALTO, CA 94301, U.S.A.

EUT DESCRIPTION: EBOOK READER WITH WWAN, WLAN AND USB PORTS

MODEL: BNRZ100-01

SERIAL NUMBER: 1001150000270042

DATE TESTED: MARCH 30 - APRIL 13, 2010

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass
INDUSTRY CANADA RSS-210 Issue 7 Annex 8	Pass
INDUSTRY CANADA RSS-GEN Issue 2	Pass

Compliance Certification Services, Inc. (CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For CCS By:



THU CHAN
EMC MANAGER
COMPLIANCE CERTIFICATION SERVICES

Tested By:



CHIN PANG
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 2, and RSS-210 Issue 7.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is an eBook reader device with WWAN, WLAN and USB ports. The radio module is manufactured by Marvel.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2462	802.11b	17.55	56.89
2412 - 2462	802.11g	20.70	117.49

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a chip antenna, with a maximum gain of 1.30 dBi.

5.4. SOFTWARE AND FIRMWARE

The EUT driver software installed during testing was Usbnet driver and bumin1 tool v0.12

The test utility software used during testing was telnet 192.168.0.17.

5.5. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined as the channel with the highest output power.

802.11b Mode (20 MHz BW operation): 11 Mbps, CCK.

802.11g Mode (20 MHz BW operation): 54 Mbps, OFDM.

The EUT is a portable device that has three orientations; therefore X, Y and Z orientations have been investigated. The worst case was found to be Z orientation.

For radiated emissions below 1 GHz the worst-case configuration is determined to be the mode and channel with the highest output power.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	Dell	Latitude D620	NA	Doc
AC Adapter	Dell	PA-1650-08D3	CN-ODF263-71615-72M-2925	Doc


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	US 115V	Un-shielded	2m	NA
2	DC	1	DC	Un-shielded	1m	NA
3	USB	1	EUT	Un-shielded	2m	NA

TEST SETUP

The EUT is installed in a host laptop computer during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01178	08/31/10
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	07/14/10
Antenna, Horn, 18 GHz	EMCO	3115	C00872	07/29/10
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00885	07/06/10
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	8/4/2010
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	08/04/10
Peak Power Meter	Boonton	4541	C01186	03/01/11
Peak Power Sensor	Boonton	57318	N/A	02/24/11

7. ANTENNA PORT TEST RESULTS

7.1. 802.11b MODE IN THE 2.4 GHz BAND

7.1.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.


TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.


RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	9.58	0.5
Middle	2437	9.58	0.5
High	2462	9.58	0.5

6 dB BANDWIDTH







7.1.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.


TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.


RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	13.438
Middle	2437	13.871
High	2462	13.757

99% BANDWIDTH







7.1.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

IC RSS-210 A8.4

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

Channel	Frequency (MHz)	Power meter Reading (dBm)	Attenuator and Cable Offset (dB)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	6.18	11	17.18	30	-12.82
Middle	2437	6.55	11	17.55	30	-12.45
High	2462	5.68	11	16.68	30	-13.32

7.1.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Power (dBm)
Low	2412	15.13
Middle	2437	15.18
High	2462	14.56

7.1.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

IC RSS-210 A8.2 (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


TEST PROCEDURE


Output power was measured based on the use of a peak measurement, therefore the power spectral density was measured using PSD Option 1 in accordance with FCC document "Measurement of Digital Transmission Systems Operating under Section 15.247", March 23, 2005.


RESULTS

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-9.38	8	-17.38
Middle	2437	-9.38	8	-17.38
High	2462	-9.53	8	-17.53

POWER SPECTRAL DENSITY







7.1.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.



The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS



SPURIOUS EMISSIONS, LOW CHANNEL



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



7.2. 802.11g MODE IN THE 2.4 GHz BAND

7.2.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.



TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2412	16.5	0.5
Middle	2437	16.5	0.5
High	2462	16.5	0.5

6dB BANDWIDTH





7.2.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.



TEST PROCEDURE


The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	16.3906
Middle	2437	16.4180
High	2462	16.4132

99% BANDWIDTH





7.2.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

IC RSS-210 A8.4

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

Channel	Frequency (MHz)	Power Meter PK Reading (dBm)	Attenuator and Cable Offset (dB)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	9.70	11	20.70	30	-9.30
Middle	2437	9.64	11	20.64	30	-9.36
High	2462	9.51	11	20.51	30	-9.49

7.2.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 11.0 dB (including 10 dB pad and .5 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	Power (dBm)
Low	2412	13.27
Middle	2437	13.46
High	2462	13.62

7.2.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

IC RSS-210 A8.2 (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.



TEST PROCEDURE


Output power was measured based on the use of a peak measurement, therefore the power spectral density was measured using PSD Option 1 in accordance with FCC document "Measurement of Digital Transmission Systems Operating under Section 15.247", March 23, 2005.

RESULTS

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-13.11	8	-21.11
Middle	2437	-13.19	8	-21.19
High	2462	-13.86	8	-21.86

POWER SPECTRAL DENSITY





7.2.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

IC RSS-210 A8.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.



The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS



SPURIOUS EMISSIONS, LOW CHANNEL



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



8. RADIATED TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-210 Clause 2.6 (Transmitter)

IC RSS-GEN Clause 6 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.



The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



8.2. TRANSMITTER ABOVE 1 GHz

8.2.1. TRANSMITTER ABOVE 1 GHz FOR 802.11b MODE IN THE 2.4 GHz BAND



RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS



High Frequency Measurement Compliance Certification Services, Fremont 5m Chamber															
Company:	Barnes & Noble														
Project #:	10U13105														
Date:	04/07/10														
Test Engineer:	Thanh Nguyen														
Configuration:	EUT at worst position(upward)														
Mode:	Transmit b mode														
Test Equipment:															
Horn 1-18GHz		Pre-amplifier 1-26GHz		Pre-amplifier 26-40GHz		Horn > 18GHz		Limit							
T60; S/N: 2238 @3m		T145 Agilent 3008A0050						FCC 15.209							
Hi Frequency Cables															
3' cable 22807700			12' cable 22807600			20' cable 22807500			HPF		Reject Filter		Peak Measurements RBW=VBW=1MHz		
3' cable 22807700			12' cable 22807600			20' cable 22807500							Average Measurements RBW=1MHz , VBW=10Hz		
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
High Channel															
4.924	3.0	39.8	28.6	32.7	5.9	-34.9	0.0	0.0	43.5	32.3	74	54	-30.5	-21.7	V
7.386	3.0	38.7	27.5	35.6	7.3	-34.6	0.0	0.0	46.9	35.7	74	54	-27.1	-18.3	Noise floor
4.924	3.0	39.6	28.5	32.7	5.9	-34.9	0.0	0.0	43.3	32.2	74	54	-30.7	-21.8	H
7.386	3.0	38.6	27.4	35.6	7.3	-34.6	0.0	0.0	46.8	35.7	74	54	-27.2	-18.3	Noise floor
Mid channel															
4.874	3.0	39.5	28.5	32.7	5.8	-34.9	0.0	0.0	43.1	32.2	74	54	-30.9	-21.8	H
7.311	3.0	39.5	27.2	35.5	7.3	-34.7	0.0	0.0	47.5	35.3	74	54	-26.5	-18.7	Noise floor
4.874	3.0	39.8	28.6	32.7	5.8	-34.9	0.0	0.0	43.4	32.2	74	54	-30.6	-21.8	V
7.311	3.0	39.7	27.5	35.5	7.3	-34.7	0.0	0.0	47.8	35.5	74	54	-26.2	-18.5	Noise floor
Low Channel															
4.824	3.0	39.8	28.6	32.7	5.8	-34.8	0.0	0.0	43.5	32.2	74	54	-30.5	-21.8	V
7.236	3.0	38.4	27.5	35.4	7.2	-34.7	0.0	0.0	46.3	35.5	74	54	-27.7	-18.5	Noise floor
4.824	3.0	39.7	28.5	32.7	5.8	-34.8	0.0	0.0	43.4	32.1	74	54	-30.6	-21.9	V
7.236	3.0	38.7	27.4	35.4	7.2	-34.7	0.0	0.0	46.6	35.3	74	54	-27.4	-18.7	Noise floor
Rev. 07.22.09															
f	Measurement Frequency			Amp	Preamp Gain						Avg Lim	Average Field Strength Limit			
Dist	Distance to Antenna			D Corr	Distance Correct to 3 meters						Pk Lim	Peak Field Strength Limit			
Read	Analyzer Reading			Avg	Average Field Strength @ 3 m						Avg Mar	Margin vs. Average Limit			
AF	Antenna Factor			Peak	Calculated Peak Field Strength						Pk Mar	Margin vs. Peak Limit			
CL	Cable Loss			HPF	High Pass Filter										

8.2.2. TRANSMITTER ABOVE 1 GHz FOR 802.11g MODE IN THE 2.4 GHz BAND



RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)



HARMONICS AND SPURIOUS EMISSIONS


High Frequency Measurement Compliance Certification Services, Fremont 5m Chamber																																																																																																																																																																																																																																																																																																																																																	
<p>Company: Barnes & Noble Project #: 10U13105 Date: 04/06/10 Test Engineer: Thanh Nguyen Configuration: EUT at worst position(upward) Mode: Transmut g mode</p> <p><u>Test Equipment:</u></p> <table border="1"> <tr> <td>Horn 1-18GHz</td> <td>Pre-amplifier 1-26GHz</td> <td>Pre-amplifier 26-40GHz</td> <td colspan="4">Horn > 18GHz</td> <td>Limit</td> </tr> <tr> <td>T60; S/N: 2238 @3m</td> <td>T145 Agilent 3008A005</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>25.95</td> </tr> <tr> <td colspan="7">Hi Frequency Cables</td> <td></td> </tr> <tr> <td>3' cable 22807700</td> <td>12' cable 22807600</td> <td>20' cable 22807500</td> <td>HPF</td> <td>Reject Filter</td> <td colspan="3">Peak Measurements RBW=VBW=1MHz</td> </tr> <tr> <td>3' cable 22807700</td> <td>12' cable 22807600</td> <td>20' cable 22807500</td> <td></td> <td></td> <td colspan="3">Average Measurements RBW=1MHz ; VBW=10Hz</td> </tr> </table> <table border="1"> <thead> <tr> <th>f GHz</th> <th>Dist (m)</th> <th>Read Pk dBuV</th> <th>Read Avg. dBuV</th> <th>AF dB/m</th> <th>CL dB</th> <th>Amp dB</th> <th>D Corr dB</th> <th>Fltr dB</th> <th>Peak dBuV/m</th> <th>Avg dBuV/m</th> <th>Pk Lim dBuV/m</th> <th>Avg Lim dBuV/m</th> <th>Pk Mar dB</th> <th>Avg Mar dB</th> <th>Notes (V/H)</th> </tr> </thead> <tbody> <tr> <td colspan="15">High Channel</td> </tr> <tr> <td>4.924</td> <td>3.0</td> <td>39.8</td> <td>26.0</td> <td>32.7</td> <td>5.9</td> <td>-34.9</td> <td>0.0</td> <td>0.0</td> <td>43.5</td> <td>29.8</td> <td>74</td> <td>54</td> <td>-30.5</td> <td>-24.2</td> <td>V</td> </tr> <tr> <td>7.386</td> <td>3.0</td> <td>38.3</td> <td>24.9</td> <td>35.6</td> <td>7.3</td> <td>-34.6</td> <td>0.0</td> <td>0.0</td> <td>46.5</td> <td>33.1</td> <td>74</td> <td>54</td> <td>-27.5</td> <td>-20.9</td> <td>Noise floor</td> </tr> <tr> <td>4.924</td> <td>3.0</td> <td>39.1</td> <td>25.9</td> <td>32.7</td> <td>5.9</td> <td>-34.9</td> <td>0.0</td> <td>0.0</td> <td>42.9</td> <td>29.7</td> <td>74</td> <td>54</td> <td>-31.1</td> <td>-24.3</td> <td>H</td> </tr> <tr> <td>7.386</td> <td>3.0</td> <td>39.8</td> <td>24.9</td> <td>35.6</td> <td>7.3</td> <td>-34.6</td> <td>0.0</td> <td>0.0</td> <td>48.0</td> <td>33.1</td> <td>74</td> <td>54</td> <td>-26.0</td> <td>-20.9</td> <td>Noise floor</td> </tr> <tr> <td colspan="15">Mid channel</td> </tr> <tr> <td>4.874</td> <td>3.0</td> <td>39.7</td> <td>25.6</td> <td>32.7</td> <td>5.8</td> <td>-34.9</td> <td>0.0</td> <td>0.0</td> <td>43.4</td> <td>29.3</td> <td>74</td> <td>54</td> <td>-30.6</td> <td>-24.7</td> <td>H</td> </tr> <tr> <td>7.311</td> <td>3.0</td> <td>39.3</td> <td>26.1</td> <td>35.5</td> <td>7.3</td> <td>-34.7</td> <td>0.0</td> <td>0.0</td> <td>47.3</td> <td>34.2</td> <td>74</td> <td>54</td> <td>-26.7</td> <td>-19.8</td> <td>Noise floor</td> </tr> <tr> <td>4.874</td> <td>3.0</td> <td>39.8</td> <td>25.7</td> <td>32.7</td> <td>5.8</td> <td>-34.9</td> <td>0.0</td> <td>0.0</td> <td>43.4</td> <td>29.4</td> <td>74</td> <td>54</td> <td>-30.6</td> <td>-24.6</td> <td>V</td> </tr> <tr> <td>7.311</td> <td>3.0</td> <td>39.5</td> <td>26.1</td> <td>35.5</td> <td>7.3</td> <td>-34.7</td> <td>0.0</td> <td>0.0</td> <td>47.5</td> <td>34.2</td> <td>74</td> <td>54</td> <td>-26.5</td> <td>-19.8</td> <td>Noise floor</td> </tr> <tr> <td colspan="15">Low Channel</td> </tr> <tr> <td>4.824</td> <td>3.0</td> <td>39.5</td> <td>26.0</td> <td>32.7</td> <td>5.8</td> <td>-34.8</td> <td>0.0</td> <td>0.0</td> <td>43.1</td> <td>29.6</td> <td>74</td> <td>54</td> <td>-30.9</td> <td>-24.4</td> <td>V</td> </tr> <tr> <td>7.236</td> <td>3.0</td> <td>38.4</td> <td>25.0</td> <td>35.4</td> <td>7.2</td> <td>-34.7</td> <td>0.0</td> <td>0.0</td> <td>46.3</td> <td>32.9</td> <td>74</td> <td>54</td> <td>-27.7</td> <td>-21.1</td> <td>Noise floor</td> </tr> <tr> <td>4.824</td> <td>3.0</td> <td>38.7</td> <td>24.9</td> <td>32.7</td> <td>5.8</td> <td>-34.8</td> <td>0.0</td> <td>0.0</td> <td>42.3</td> <td>28.5</td> <td>74</td> <td>54</td> <td>-31.7</td> <td>-25.5</td> <td>V</td> </tr> <tr> <td>7.236</td> <td>3.0</td> <td>38.1</td> <td>25.4</td> <td>35.4</td> <td>7.2</td> <td>-34.7</td> <td>0.0</td> <td>0.0</td> <td>46.1</td> <td>33.3</td> <td>74</td> <td>54</td> <td>-27.9</td> <td>-20.7</td> <td>Noise floor</td> </tr> </tbody> </table> <p>Rev. 07.22.09</p> <table border="1"> <tr> <td>f</td> <td>Measurement Frequency</td> <td>Amp</td> <td>Preamp Gain</td> <td>Avg Lim</td> <td>Average Field Strength Limit</td> </tr> <tr> <td>Dist</td> <td>Distance to Antenna</td> <td>D Corr</td> <td>Distance Correct to 3 meters</td> <td>Pk Lim</td> <td>Peak Field Strength Limit</td> </tr> <tr> <td>Read</td> <td>Analyzer Reading</td> <td>Avg</td> <td>Average Field Strength @ 3 m</td> <td>Avg Mar</td> <td>Margin vs. Average Limit</td> </tr> <tr> <td>AF</td> <td>Antenna Factor</td> <td>Peak</td> <td>Calculated Peak Field Strength</td> <td>Pk Mar</td> <td>Margin vs. Peak Limit</td> </tr> <tr> <td>CL</td> <td>Cable Loss</td> <td>HPF</td> <td>High Pass Filter</td> <td></td> <td></td> </tr> </table>															Horn 1-18GHz	Pre-amplifier 1-26GHz	Pre-amplifier 26-40GHz	Horn > 18GHz				Limit	T60; S/N: 2238 @3m	T145 Agilent 3008A005						25.95	Hi Frequency Cables								3' cable 22807700	12' cable 22807600	20' cable 22807500	HPF	Reject Filter	Peak Measurements RBW=VBW=1MHz			3' cable 22807700	12' cable 22807600	20' cable 22807500			Average Measurements RBW=1MHz ; VBW=10Hz			f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)	High Channel															4.924	3.0	39.8	26.0	32.7	5.9	-34.9	0.0	0.0	43.5	29.8	74	54	-30.5	-24.2	V	7.386	3.0	38.3	24.9	35.6	7.3	-34.6	0.0	0.0	46.5	33.1	74	54	-27.5	-20.9	Noise floor	4.924	3.0	39.1	25.9	32.7	5.9	-34.9	0.0	0.0	42.9	29.7	74	54	-31.1	-24.3	H	7.386	3.0	39.8	24.9	35.6	7.3	-34.6	0.0	0.0	48.0	33.1	74	54	-26.0	-20.9	Noise floor	Mid channel															4.874	3.0	39.7	25.6	32.7	5.8	-34.9	0.0	0.0	43.4	29.3	74	54	-30.6	-24.7	H	7.311	3.0	39.3	26.1	35.5	7.3	-34.7	0.0	0.0	47.3	34.2	74	54	-26.7	-19.8	Noise floor	4.874	3.0	39.8	25.7	32.7	5.8	-34.9	0.0	0.0	43.4	29.4	74	54	-30.6	-24.6	V	7.311	3.0	39.5	26.1	35.5	7.3	-34.7	0.0	0.0	47.5	34.2	74	54	-26.5	-19.8	Noise floor	Low Channel															4.824	3.0	39.5	26.0	32.7	5.8	-34.8	0.0	0.0	43.1	29.6	74	54	-30.9	-24.4	V	7.236	3.0	38.4	25.0	35.4	7.2	-34.7	0.0	0.0	46.3	32.9	74	54	-27.7	-21.1	Noise floor	4.824	3.0	38.7	24.9	32.7	5.8	-34.8	0.0	0.0	42.3	28.5	74	54	-31.7	-25.5	V	7.236	3.0	38.1	25.4	35.4	7.2	-34.7	0.0	0.0	46.1	33.3	74	54	-27.9	-20.7	Noise floor	f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit	Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit	Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit	AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit	CL	Cable Loss	HPF	High Pass Filter		
Horn 1-18GHz	Pre-amplifier 1-26GHz	Pre-amplifier 26-40GHz	Horn > 18GHz				Limit																																																																																																																																																																																																																																																																																																																																										
T60; S/N: 2238 @3m	T145 Agilent 3008A005						25.95																																																																																																																																																																																																																																																																																																																																										
Hi Frequency Cables																																																																																																																																																																																																																																																																																																																																																	
3' cable 22807700	12' cable 22807600	20' cable 22807500	HPF	Reject Filter	Peak Measurements RBW=VBW=1MHz																																																																																																																																																																																																																																																																																																																																												
3' cable 22807700	12' cable 22807600	20' cable 22807500			Average Measurements RBW=1MHz ; VBW=10Hz																																																																																																																																																																																																																																																																																																																																												
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)																																																																																																																																																																																																																																																																																																																																		
High Channel																																																																																																																																																																																																																																																																																																																																																	
4.924	3.0	39.8	26.0	32.7	5.9	-34.9	0.0	0.0	43.5	29.8	74	54	-30.5	-24.2	V																																																																																																																																																																																																																																																																																																																																		
7.386	3.0	38.3	24.9	35.6	7.3	-34.6	0.0	0.0	46.5	33.1	74	54	-27.5	-20.9	Noise floor																																																																																																																																																																																																																																																																																																																																		
4.924	3.0	39.1	25.9	32.7	5.9	-34.9	0.0	0.0	42.9	29.7	74	54	-31.1	-24.3	H																																																																																																																																																																																																																																																																																																																																		
7.386	3.0	39.8	24.9	35.6	7.3	-34.6	0.0	0.0	48.0	33.1	74	54	-26.0	-20.9	Noise floor																																																																																																																																																																																																																																																																																																																																		
Mid channel																																																																																																																																																																																																																																																																																																																																																	
4.874	3.0	39.7	25.6	32.7	5.8	-34.9	0.0	0.0	43.4	29.3	74	54	-30.6	-24.7	H																																																																																																																																																																																																																																																																																																																																		
7.311	3.0	39.3	26.1	35.5	7.3	-34.7	0.0	0.0	47.3	34.2	74	54	-26.7	-19.8	Noise floor																																																																																																																																																																																																																																																																																																																																		
4.874	3.0	39.8	25.7	32.7	5.8	-34.9	0.0	0.0	43.4	29.4	74	54	-30.6	-24.6	V																																																																																																																																																																																																																																																																																																																																		
7.311	3.0	39.5	26.1	35.5	7.3	-34.7	0.0	0.0	47.5	34.2	74	54	-26.5	-19.8	Noise floor																																																																																																																																																																																																																																																																																																																																		
Low Channel																																																																																																																																																																																																																																																																																																																																																	
4.824	3.0	39.5	26.0	32.7	5.8	-34.8	0.0	0.0	43.1	29.6	74	54	-30.9	-24.4	V																																																																																																																																																																																																																																																																																																																																		
7.236	3.0	38.4	25.0	35.4	7.2	-34.7	0.0	0.0	46.3	32.9	74	54	-27.7	-21.1	Noise floor																																																																																																																																																																																																																																																																																																																																		
4.824	3.0	38.7	24.9	32.7	5.8	-34.8	0.0	0.0	42.3	28.5	74	54	-31.7	-25.5	V																																																																																																																																																																																																																																																																																																																																		
7.236	3.0	38.1	25.4	35.4	7.2	-34.7	0.0	0.0	46.1	33.3	74	54	-27.9	-20.7	Noise floor																																																																																																																																																																																																																																																																																																																																		
f	Measurement Frequency	Amp	Preamp Gain	Avg Lim	Average Field Strength Limit																																																																																																																																																																																																																																																																																																																																												
Dist	Distance to Antenna	D Corr	Distance Correct to 3 meters	Pk Lim	Peak Field Strength Limit																																																																																																																																																																																																																																																																																																																																												
Read	Analyzer Reading	Avg	Average Field Strength @ 3 m	Avg Mar	Margin vs. Average Limit																																																																																																																																																																																																																																																																																																																																												
AF	Antenna Factor	Peak	Calculated Peak Field Strength	Pk Mar	Margin vs. Peak Limit																																																																																																																																																																																																																																																																																																																																												
CL	Cable Loss	HPF	High Pass Filter																																																																																																																																																																																																																																																																																																																																														

8.3. RECEIVER ABOVE 1 GHz


Note: No emissions were found within above 1GHz of 20dB below the system noise floor.

8.4. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



VERTICAL& HORIZONTAL DATA

30-1000MHz Frequency Measurement Compliance Certification Services, Fremont 5m Chamber													
Test Engr:	Thanh Nguyen												
Date:	04/06/10												
Project #:	10U13105												
Company:	Barnes & Noble												
EUT Description:	eBook reader with WWAN, WLAN and USB port												
EUT M/N:	TBD												
Test Target:	FCC 12.247												
Mode Oper:	TX (Worst Case)												
f	Measurement Frequency	Amp	Preamp Gain							Margin	Margin vs. Limit		
Dist	Distance to Antenna	D	Corr	Distance Correct to 3 meters									
Read	Analyzer Reading	Filter		Filter Insert Loss									
AF	Antenna Factor	Corr.		Calculated Field Strength									
CL	Cable Loss	Limit		Field Strength Limit									
f MHz	Dist (m)	Read dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Filter dB	Corr. dBuV/m	Limit dBuV/m	Margin dB	Ant. Pol. V/H	Det. P/A/QP	Notes
266.050	3.0	42.0	12.3	1.5	28.8	0.0	0.0	26.9	46.0	-19.1	H	P	
399.015	3.0	41.6	15.0	1.9	29.3	0.0	0.0	29.3	46.0	-16.7	H	P	
531.981	3.0	39.0	17.3	2.2	29.7	0.0	0.0	28.8	46.0	-17.2	H	P	
610.464	3.0	38.4	18.4	2.4	29.6	0.0	0.0	29.5	46.0	-16.5	H	P	
798.032	3.0	35.4	21.0	2.8	29.2	0.0	0.0	30.0	46.0	-16.0	H	P	
35.280	3.0	45.2	17.8	0.5	29.6	0.0	0.0	33.9	40.0	-6.1	V	P	
72.002	3.0	47.1	8.1	0.7	29.6	0.0	0.0	26.3	40.0	-13.7	V	P	
399.015	3.0	44.7	15.0	1.9	29.3	0.0	0.0	32.3	46.0	-13.7	V	P	
531.981	3.0	44.6	17.3	2.2	29.7	0.0	0.0	34.4	46.0	-11.6	V	P	
797.912	3.0	38.3	21.0	2.8	29.2	0.0	0.0	32.9	46.0	-13.1	V	P	
Rev. 1.27.09													
Note: No other emissions were detected above the system noise floor.													

9. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.

TEST PROCEDURE


ANSI C63.4

RESULTS


6 WORST EMISSIONS

CONDUCTED EMISSIONS DATA (115VAC 60Hz)										
Freq. (MHz)	Reading			Closs (dB)	Limit	EN_B		Margin		Remark
	PK (dBuV)	QP (dBuV)	AV (dBuV)			QP	AV	QP (dB)	AV (dB)	
0.22	55.16	--	34.60	0.00	62.74	52.74	-7.58	-18.14	L1	
0.62	45.65	--	29.23	0.00	56.00	46.00	-10.35	-16.77	L1	
3.64	46.54	--	36.01	0.00	56.00	46.00	-9.46	-9.99	L1	
0.17	55.18	--	40.70	0.00	65.21	55.21	-10.03	-14.51	L2	
1.78	42.53	--	38.77	0.00	56.00	46.00	-13.47	-7.23	L2	
3.58	48.45	--	371.17	0.00	56.00	46.00	-7.55	325.17	L2	
6 Worst Data										

LINE 1 RESULTS



LINE 2 RESULTS



10. MAXIMUM PERMISSIBLE EXPOSURE

FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 5
Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m ²)	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/f	2.19/f		6
10–30	28	2.19/f		6
30–300	28	0.073	2*	6
300–1 500	$1.585f^{0.5}$	$0.0042f^{0.5}$	$f/150$	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	$616\,000/f^{1.2}$
150 000–300 000	$0.158f^{0.5}$	$4.21 \times 10^{-4}f^{0.5}$	$6.67 \times 10^{-5}f$	$616\,000/f^{1.2}$

* Power density limit is applicable at frequencies greater than 100 MHz.

Notes: 1. Frequency, f , is in MHz.
2. A power density of 10 W/m² is equivalent to 1 mW/cm².
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μ T) or 12.57 milligauss (mG).

EQUATIONS

Power density is given by:

$$S = \text{EIRP} / (4 * \pi * D^2)$$

where

S = Power density in W/m²

EIRP = Equivalent Isotropic Radiated Power in W

D = Separation distance in m

Power density in units of W/m² is converted to units of mW/cm² by dividing by 10.

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \pi * S))$$

where

D = Separation distance in m

EIRP = Equivalent Isotropic Radiated Power in W

S = Power density in W/m²

For multiple colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the Power * Gain product (in linear units) of each transmitter.

$$\text{Total EIRP} = (P1 * G1) + (P2 * G2) + \dots + (Pn * Gn)$$

where

Px = Power of transmitter x

Gx = Numeric gain of antenna x

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

LIMITS

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm²

From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m²

RESULTS

Band	Mode	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	IC Power Density (W/m ²)	FCC Power Density (mW/cm ²)
2.4 GHz	WLAN	0.20	20.70	1.30	0.32	0.032