



FCC CFR47 PART 22H AND 24E
INDUSTRY CANADA RSS-132 ISSUE 2
INDUSTRY CANADA RSS-133 ISSUE 5

CERTIFICATION TEST REPORT
FOR

EBOOK READER WITH WWAN, WLAN AND USB PORTS

MODEL NUMBER: BNRZ100-01

FCC ID: XHHBNRZ100-1
IC: 8961A-BNRZ10001

REPORT NUMBER: 10U13105-3, Revision A
ISSUE DATE: JULY 16, 2010

Prepared for
BARNES AND NOBLE
400 HAMILTON AVENUE
PALO ALTO, CA 94301, U.S.A.

Prepared by
COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP[®]

NVLAP LAB CODE 200065-0

Revision History

Rev.	Date	Revisions	Revised By
--	06/10/10	Initial Issue	T. Chan
A	07/16/10	Removed HSUPA Section	T. Chan

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	5
4.2. <i>SAMPLE CALCULATION</i>	5
4.3. <i>MEASUREMENT UNCERTAINTY</i>	5
5. EQUIPMENT UNDER TEST	6
5.1. <i>DESCRIPTION OF EUT</i>	6
5.2. <i>MAXIMUM OUTPUT POWER</i>	6
5.3. <i>SOFTWARE AND FIRMWARE</i>	6
5.4. <i>WORST-CASE CONFIGURATION AND MODE</i>	7
5.5. <i>DESCRIPTION OF TEST SETUP</i>	8
6. TEST AND MEASUREMENT EQUIPMENT	11
7. RF POWER OUTPUT VERIFICATION	12
7.1. <i>RF POWER OUTPUT FOR GSM MODE</i>	15
7.2. <i>RF POWER OUTPUT FOR UMTS REL99</i>	16
7.3. <i>RF POWER OUTPUT FOR UMTS Rel 6 HSDPA</i>	17
8. CONDUCTED TEST RESULTS	18
8.1. <i>OCCUPIED BANDWIDTH</i>	18
8.2. <i>BAND EDGE</i>	31
8.3. <i>OUT OF BAND EMISSIONS</i>	48
8.4. <i>FREQUENCY STABILITY</i>	73
9. RADIATED TEST RESULTS	79
9.1. <i>RADIATED POWER (ERP & EIRP)</i>	79
9.2. <i>FIELD STRENGTH OF SPURIOUS RADIATION</i>	85
9.3. <i>RECEIVER SPURIOUS EMISSIONS</i>	94
9.4. <i>POWER LINE CONDUCTED EMISSION</i>	98
10. SETUP PHOTOS	101

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: BARNES AND NOBLE
400 HAMILTON AVENUE
PALO ALTO, CA 94301, U.S.A.

EUT DESCRIPTION: EBOOK READER WITH WWAN, WLAN AND USB PORTS

MODEL: BNRZ100-01

SERIAL NUMBER: 1001150000050048

DATE TESTED: APRIL 04-09, 2010

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 22 SUBPART H AND 24 SUBPART E	Pass
INDUSTRY CANADA RSS-132 Issue 2 and RSS-133 Issue 5	Pass

Compliance Certification Services, Inc. (CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For CCS By:



THU CHAN
EMC MANAGER
COMPLIANCE CERTIFICATION SERVICES

Tested By:



CHIN PANG
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with TIA-603-C, FCC CFR 47 Part 2, FCC CFR 47 Part 22, FCC CFR Part 24, RSS-132 Issue 2, and RSS-133 Issue 5.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

$$36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is an eBook Reader with WWAN, WiFi and USB ports device.

The radio module is manufactured by Sierra Wireless.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum conducted and ERP / EIRP output powers as follows:

Part 22 Cellular Band

Frequency range (MHz)	Modulation	Conducted		ERP	
		dBm	mW	dBm	mW
824.2 – 848.80	GPRS	32.33	1710.0	32.50	1778.3
824.2 – 848.80	EGPRS	30.83	1210.6	29.90	977.2
826.4 – 846.6	UMTS, REL99	27.13	516.4	25.70	371.5
826.4 – 846.6	UMTS, HSDPA	27.00	501.2	25.20	331.1

Part 24 PCS Band

Frequency range (MHz)	Modulation	Conducted		EIRP	
		dBm	mW	dBm	mW
1850.20 – 1909.8	GPRS	29.30	851.1	29.90	977.2
1850.20 – 1909.8	EGPRS	29.22	835.6	29.40	871.0
1852.4 – 1907.6	UMTS, REL99	25.97	395.4	28.00	631.0
1852.4 – 1907.6	UMTS, HSDPA	26.32	428.5	27.70	588.8

5.3. SOFTWARE AND FIRMWARE

The EUT is linked with Agilent 8969 Communications Test Set.

5.4. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined as the channel with the highest output power.

Based on the investigation results, the highest peak power and enhanced data rate is the worst-case scenario for all measurements.

Worst case modes:

- Cellular & PCS bands for GSM
 - GPRS (GSMK)
 - EGPRS (8PSK)
- Band V & Band II for UMTS (WCDMA)
 - Rel 99
 - Rel 6 HSDPA Subtest 2

For the fundamental investigation, since the EUT is a portable device that has three orientations; therefore X, Y and Z orientations have been investigated, also with AC/DC adapter, and the worst case was found to be at Z orientation for Cell band and X position for PCS band with AC/DC adapter.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Made in China	BNRP5-850	D947	DoC

I/O CABLES (CONDUCTED TEST)

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	US 115V	Un-shielded	2m	NA
2	DC	1	DC	Un-shielded	1m	NA
2	RF in/out	1	Spectrum	Un-shielded	1m	NA
3	RFIn/Out	1	Communications Test Set	Un-shielded	1.2m	NA
4	Antenna Port	1	EUT	Un-shielded	0.1m	NA


I/O CABLES (RADIATED TEST)

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	US 115V	Un-shielded	2m	NA
2	DC	1	DC	Un-shielded	1m	NA
3	RF In/Out	1	Horn	Un-shielded	1.5m	NA


TEST SETUP

The EUT is a stand alone device. A link is established between the EUT and the Agilent communications test set.

SETUP DIAGRAM FOR CONDUCTED TESTS



SETUP DIAGRAM FOR RADIATED TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	08/04/10
Antenna, Bilog, 2 GHz	Sunol Sciences	JB1	C01011	07/14/10
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01178	08/31/10
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	08/04/10
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00778	07/06/10
Temperature / Humidity Chamber	Thermotron	SE 600-10-10	C00930	04/07/11
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	01/07/12
Peak Power Meter	Agilent / HP	E4416A	C00963	12/04/11
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	05/06/11
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	11/06/10
Highpass Filter, 1.5 GHz	Micro-Tronics	HPM13193	N02688	CNR
Highpass Filter, 2.7 GHz	Micro-Tronics	HPM13194	N02686	CNR
Communications Test Set	Agilent / HP	E5515C	GB46160222	02/27/11
Directional Coupler, 4.2 GHz, 40 dB	A-R	DC7144A	C00983	CNR

7. RF POWER OUTPUT VERIFICATION

PROCEDURE USED TO ESTABLISH TEST SIGNAL

GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/900/1800/1900

Press Connection control to choose the different menus

Press RESET > choose all to reset all settings

Connection Press Signal Off to turn off the signal and change settings

Network Support > GSM+GPRS or GSM+EGPRS

Main Service > Packet Data

Service selection > Test Mode A – Auto Slot Config. off

MS Signal Press Slot Config bottom on the right twice to select and change the number of time slots and power setting

> Slot configuration > Uplink/Gamma

> 33 dBm for GPRS 850/900

> 27 dBm for EGPRS 850/900

> 30 dBm for GPRS1800/1900

> 26 dBm for EGPRS1800/1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel

Frequency Offset > + 0 Hz

Mode > BCCH and TCH

BCCH Level > -85 dBm (May need to adjust if link is not stable)

BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off

P0> 4 dB

Slot Config > Unchanged (if already set under MS Signal)

TCH > choose desired test channel

Hopping > Off

Main Timeslot > 3 (Default)

Network Coding Scheme > CS4 (GPRS) and MCS9 (EGPRS)

Bit Stream > 2E9-1PSR Bit Pattern

AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input

Connection Press Signal On to turn on the signal and change settings

WCDMA + HSDPA Procedure

The following settings were used to configure the Radio Communication Tester,

- Connection
 - Dedicated Chan (CS): RMC
 - Band Select:
 - Band VI for US Cell Band
 - Band II for US PCS Band
 - Band I for 2100MHz band
- Network
 - Requested UE Data
 - Authentication: Off
 - Security: Off
 - IMEI: ON
 - RLC Reestablish: Off
- BS Signal
 - Node –B Setting
 - RF Channel Downlink
 - Band VI: 4357 / 4407 / 4458
 - Band II: 9662 / 9800 / 9938
 - Band I: 10562 / 10700 / 10838
 - Circuit Switched
 - RMC Setting
 - Reference Channel Type: 12.2Kbps
 - Test Mode: Loop Mode 1 RLC TM
 - Channel Data Source DTCH: All One
 - Signaling RAB Setting
 - SRB Cell DCH: 13.6 Kbps
 - HSDPA HS-DSCH
 - Fixed Reference Channel
 - H-Set Selection: H-Set 1 QPSK
- UE Signal
 - Analyzer Setting
 - RF Channel Uplink:
 - Band VI: 4132 / 4182 / 4233
 - Band II: 9262 / 9400 / 9538
 - Band I: 9612 / 9750 / 9888
 - UE power Control
 - Max Allowed UE Power: 25

RULE PART(S)

FCC: §2.1046
IC: RSS-132, 4.4; RSS-133, 6.4

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a Communications Test Set and configured to operate at maximum power in a call. The peak power was measured using the spectrum analyzer at three equally spaced operating frequencies for each band. The RBW was set to 300 KHz for the GSM and EDGE measurements and 5 MHz for the UMTS (WCDMA) measurements.

MODES TESTED

- GSM – GSM/GPRS (GSMK) & EGPRS (8PSK) modes.
- UMTS (W-CDMA) - Rel 99, Rel 6 HSDPA

RESULTS

7.1. RF POWER OUTPUT FOR GSM MODE

GPRS (GMSK) - Coding scheme: CS4

Band	Ch	Frequency	Conducted output power (dBm)			
			Average		Peak	
			1 slot	2 slot	1 slot	2 slot
GSM850	128	824.2	32.15	31.95	32.33	32.10
	190	836.6	32.15	31.91	32.27	32.05
	251	848.8	32.05	31.80	32.10	31.85
GSM1900	512	1850.2	28.39	28.22	28.90	28.76
	661	1880	28.68	28.51	29.30	29.07
	810	1909.8	28.76	28.61	29.25	29.10

EGPRS (8PSK) - Coding scheme: MCS9

Band	Ch	Frequency	Conducted output power (dBm)			
			Average		Peak	
			1 slot	2 slot	1 slot	2 slot
GSM850	128	824.2	27.26	27.18	30.83	30.53
	190	836.6	27.21	27.15	30.72	30.60
	251	848.8	27.30	27.17	30.77	30.54
GSM1900	512	1850.2	25.45	25.40	29.00	28.93
	661	1880	25.50	25.28	29.10	29.05
	810	1909.8	25.70	25.60	29.22	29.18

7.2. RF POWER OUTPUT FOR UMTS REL99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 V7.5.0 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

	Mode	Rel99
	Subtest	-
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	HSDPA FRC	Not Applicable
	HSUPA Test	Not Applicable
	Power Control Algorithm	Algorithm2
	β_c	Not Applicable
	β_d	Not Applicable
	β_{ec}	Not Applicable
	β_c/β_d	8/15
	β_{hs}	Not Applicable
	β_{ed}	Not Applicable

REL 99

Band	UL Ch	DL Ch	Frequency	Conducted output power (dBm)	
				Average	Peak
UMTS850 (Band V)	4132	4357	826.4	23.04	27.13
	4180	4405	836.0	22.75	26.13
	4230	4455	846.0	22.96	26.39
UMTS1900 (Band II)	9262	9662	1852.4	22.4	25.97
	9400	9800	1880	22.19	25.88
	9538	9938	1907.6	22.56	25.67

7.3. RF POWER OUTPUT FOR UMTS Rel 6 HSDPA

The following Sub-Tests were completed according to the test requirements outlined in section 5.2A of the 3GPP TS34.121-1 V7.5.0 specification. All TX RMS and Peak power requirements for Power Class 3 were met according to table 5.2AA.5 and achieved through the outlined test procedure in section 5.2AA.4.2. A summary of these settings are illustrated below:

	Mode	Rel6 HSDPA	Rel6 HSDPA	Rel6 HSDPA	Rel6 HSDPA
	Subtest	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	HSUPA Test	Not Applicable			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_{ec}	-	-	-	-
	β_c/β_d	2/15	12/15	15/8	15/4
HSDPA Specific Settings	β_{hs}	4/15	24/15	30/15	30/15
	β_{ed}	Not Applicable			
	DACK	8			
	DNAK	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
CQI Repetition Factor (Table 5.2B.4)		2			
$A_{hs} = \beta_{hs}/\beta_c$		30/15			

Result

REL 6 HSDPA

Band	Subtest	UL Ch	DL Ch	Frequency	Conducted output power (dBm)	
					Average	Peak
UMTS850 (Band V)	1	4132	4357	826.4	23.00	26.60
		4180	4405	836.0	22.22	26.41
		4230	4455	846.0	22.45	26.41
	2*	4132	4357	826.4	23.25	27.00
		4180	4405	836.0	22.18	26.17
		4230	4455	846.0	22.33	26.35
	3	4132	4357	826.4	22.85	26.59
		4180	4405	836.0	22.20	26.01
		4230	4455	846.0	22.35	26.53
	4	4132	4357	826.4	22.72	26.58
		4180	4405	836.0	21.87	26.57
		4230	4455	846.0	22.04	26.87
UMTS1900 (Band II)	1	9262	9662	1852.4	22.33	25.57
		9400	9800	1880.0	22.30	26.22
		9538	9938	1907.6	22.51	25.10
	2*	9262	9662	1852.4	22.32	26.32
		9400	9800	1880.0	22.12	25.28
		9538	9938	1907.6	22.35	26.13
	3	9262	9662	1852.4	22.05	25.47
		9400	9800	1880.0	21.90	25.84
		9538	9938	1907.6	22.12	25.32
	4	9262	9662	1852.4	21.84	25.64
		9400	9800	1880.0	21.60	25.70
		9538	9938	1907.6	21.76	25.38

8. CONDUCTED TEST RESULTS

8.1. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049
IC: RSS-Gen, 4.6

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

MODES TESTED

- GSM - GSM (GSMK) & EGPRS (8PSK),
- UMTS (W-CDMA) - Rel 99, Rel 6 HSDPA Subtest 2



RESULTS


Band	Mode	Channel	f (MHz)	99% BW (kHz)	-26dB BW (kHz)
Cellular	GPRS	128	824.2	252.5094	310.838
		190	836.6	249.2059	304.738
		251	848.8	241.8986	310.642
	EGPRS	128	824.2	235.5266	275.786
		190	836.6	240.5685	291.520
		251	848.8	244.4805	285.830
PCS	GPRS	512	1850.2	252.9103	300.585
		661	1880.0	243.1867	302.784
		810	1909.8	240.2898	306.488
	EGPRS	512	1850.2	248.5690	295.075
		661	1880.0	246.3173	296.369
		810	1909.8	242.8424	284.905

Band	Mode	Channel	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
UMTS Band V	Rel 99	4132	826.4	4.1823	4.643
		4180	836.6	4.2234	4.574
		4230	846.6	4.1690	4.576
	HSDPA Rel 6 Subtest 2	4132	826.4	4.1679	4.560
		4180	836.6	4.2318	4.585
		4230	846.6	4.1838	4.645
UMTS Band II	Rel 99	9262	1852.4	4.1954	4.613
		9400	1880.0	4.2214	4.589
		9538	1907.6	4.2113	4.602
	HSDPA Rel 6 Subtest 2	9262	1852.4	4.1655	4.635
		9400	1880.0	4.2279	4.625
		9538	1907.6	4.1567	4.596


GPRS850 BAND



99% and 26dB Bandwidth








EGPRS850 BAND








UMTS REL99 Cellular Band








UMTS HSDPA Cellular Band








GPRS1900 PCS Band








EGPRS1900 PCS Band








UMTS REL99 PCS Band





UMTS HSDPA PCS Band





8.2. BAND EDGE

RULE PART(S)

FCC: §22.359, 24.238
IC: RSS-132, 4.5; RSS-133, 6.5

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

The transmitter output was connected to a Agilent 8960 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

For each band edge measurement:

- Set the spectrum analyzer span to include the block edge frequency (824, 848, 1850, 1910MHz)
- Set a marker to point the corresponding band edge frequency in each test case.
- Set display line at -13 dBm
- Set resolution bandwidth to at least 1% of emission bandwidth.

MODES TESTED


- GSM - GSM (GSMK) & EGPRS (8PSK),
- UMTS (W-CDMA) - Rel 99, Rel 6 HSDPA Subtest 2

RESULTS


See the following pages.

GPRS850

Low Channel Band Edge




High Channel Band Edge




EGPRS850


Low Channel Band Edge




High Channel Band Edge



UMTS, REL99 Low Channel Band Edge




High Channel Band Edge




UMTS, HSDPA CELL

Low Channel Band Edge




High Channel Band Edge




GPRS1900

Low Channel Band Edge




High Channel Band Edge




EGPRS1900

Low Channel Band Edge




High Channel Band Edge




UMTS, REL99 PCS BAND

Low Channel Band Edge




High Channel Band Edge




UMTS HSDPA PCS BAND

Low Channel Band Edge



High Channel Band Edge



8.3. OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238
IC: RSS-132, 4.5; RSS-133, 6.5

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

For each out of band emissions measurement:

- Set display line at -13 dBm
- Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.


MODES TESTED


- GSM - GSM (GSMK) & EGPRS (8PSK),
- UMTS (W-CDMA) - Rel 99, Rel 6 HSDPA Subtest 2


RESULTS

See the following pages.


GPRS Mode (Cellular Band)










EGPRS Mode (Cellular Band)










UMTS REL99 CELL BAND










UMTS HSDPA Mode (Cellular Band)










GPRS Mode (PCS Band)










EGPRS Mode (PCS Band)










UMTS REL99 PCS BAND









UMTS HSDPA Mode (PCS Band)







8.4. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235
IC: RSS-132, 4.3; RSS-133, 6.3

LIMITS

§22.355 & RSS-132 4.3 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

RSS-133 6.3 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE

Frequency Stability vs Temperature:

The EUT is place inside a temperature chamber. The temperature is set to 20°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until +50°C is reached. Reference power supply voltage for these tests is 3.7 Vdc.

Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case). The test voltages are 3.7 to 4.26. Vdc.

MODES TESTED

- GSM - GSM (GSMK) & EGPRS (8PSK),
- UMTS (W-CDMA) - Rel 99

RESULTS

See the following pages.

GPRS Mode (Cellular Band)

Reference Frequency: Cellular Mid Channel 835.999979MHz @ 20°C				
Limit: to stay +- 2.5 ppm = 2090.000 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	835.999944	0.042	2.5
3.70	40	835.999954	0.030	2.5
3.70	30	835.999958	0.025	2.5
3.70	20	835.999979	0	2.5
3.70	10	836.000005	-0.031	2.5
3.70	0	835.999956	0.028	2.5
3.70	-10	835.999940	0.047	2.5
3.70	-20	835.999989	-0.012	2.5
3.70	-30	835.999994	-0.018	2.5

Reference Frequency: Cellular Mid Channel 835.999979MHz @ 20°C				
Limit: to stay +- 2.5 ppm = 2090.000 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.40	20	835.999970	0	2.5
4.26	20	835.999973	-0.004	2.5
3.3 (end point voltage)	20	835.999969	0.001	2.5

EGPRS Mode (Cellular Band)

Reference Frequency: Cellular Mid Channel 836.599958MHz @ 20°C				
Limit: to stay +- 2.5 ppm = 2091.500 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	836.599950	0.010	2.5
3.70	40	836.599952	0.007	2.5
3.70	30	836.599953	0.006	2.5
3.70	20	836.599958	0	2.5
3.70	10	836.599997	-0.047	2.5
3.70	0	836.600001	-0.051	2.5
3.70	-10	836.599956	0.002	2.5
3.70	-20	836.599977	-0.023	2.5
3.70	-30	836.600003	-0.054	2.5

Reference Frequency: Cellular Mid Channel 836.599958MHz @ 20°C				
Limit: to stay +- 2.5 ppm = 2091.500 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.40	20	836.599985	0	2.5
4.26	20	836.599945	0.048	2.5
3.3 (end point voltage)	20	836.599981	0.005	2.5

UMTS Rel 99 Mode (Cellular Band)

Reference Frequency: Cellular Mid Channel 836.399981MHz @ 20°C Limit: to stay +- 2.5 ppm = 2091.000 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	836.400000	-0.023	2.5
3.70	40	836.400001	-0.024	2.5
3.70	30	836.399998	-0.020	2.5
3.70	20	836.399981	0	2.5
3.70	10	836.399997	-0.019	2.5
3.70	0	836.399972	0.011	2.5
3.70	-10	836.399975	0.007	2.5
3.70	-20	836.399984	-0.004	2.5
3.70	-30	836.399999	-0.022	2.5

Reference Frequency: Cellular Mid Channel 836.399981MHz @ 20°C Limit: to stay +- 2.5 ppm = 2091.000 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.40	20	836.399999	0	2.5
4.26	20	836.400001	-0.002	2.5
3.3 (end point voltage)	20	836.399997	0.002	2.5

GPRS Mode (PCS Band)

Reference Frequency: PCS Mid Channel 1879.999950MHz @ 20°C				
Limit: within the authorized block or +/- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	1879.999932	0.010	2.5
3.70	40	1879.999925	0.013	2.5
3.70	30	1879.999936	0.007	2.5
3.70	20	1879.999950	0	2.5
3.70	10	1879.999940	0.005	2.5
3.70	0	1879.999929	0.011	2.5
3.70	-10	1879.999935	0.008	2.5
3.70	-20	1879.999969	-0.010	2.5
3.70	-30	1879.999975	-0.013	2.5

Reference Frequency: PCS Mid Channel 1879.999950MHz @ 20°C				
Limit: within the authorized block or +/- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.40	20	1879.999961	0	2.5
4.26	20	1879.999967	-0.003	2.5
3.3 (end point voltage)	20	1879.999956	0.003	2.5

EGPRS Mode (PCS Band)

Reference Frequency: PCS Mid Channel 1879.999975MHz @ 20°C				
Limit: within the authorized block or +- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	1879.999908	0.036	2.5
3.70	40	1879.999912	0.034	2.5
3.70	30	1879.999925	0.027	2.5
3.70	20	1879.999975	0	2.5
3.70	10	1879.999996	-0.011	2.5
3.70	0	1879.999993	-0.010	2.5
3.70	-10	1879.999907	0.036	2.5
3.70	-20	1879.999925	0.027	2.5
3.70	-30	1880.000007	-0.017	2.5

Reference Frequency: PCS Mid Channel 1879.999975MHz @ 20°C				
Limit: within the authorized block or +- 2.5 ppm = 4700.000 Hz				
Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.40	20	1879.999948	0	2.5
4.26	20	1879.999956	-0.004	2.5
3.30 (end point voltage)	20	1879.999935	0.007	2.5

UMTS Rel 99 Mode (PCS Band)

Reference Frequency: PCS Mid Channel 1879.999970MHz @ 20°C Limit: to stay +- 2.5 ppm = 4700.000 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.70	50	1880.000003	-0.018	2.5
3.70	40	1880.000008	-0.020	2.5
3.70	30	1879.999998	-0.015	2.5
3.70	20	1879.999970	0	2.5
3.70	10	1879.999964	0.003	2.5
3.70	0	1879.999960	0.005	2.5
3.70	-10	1879.999956	0.007	2.5
3.70	-20	1879.999958	0.006	2.5
3.70	-30	1879.999965	0.003	2.5

Reference Frequency: PCS Mid Channel 1879.999970MHz @ 20°C Limit: to stay +- 2.5 ppm = 4700.000 Hz				
DC Power Supply (Vdc)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
3.40	20	1879.999958	0.000	2.5
4.26	20	1880.000001	-0.023	2.5
3.3(end point voltage)	20	1879.999952	0.003	2.5

9. RADIATED TEST RESULTS

9.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232
IC: RSS-132; 4.4, RSS-133, 6.4

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) & RSS-133 § 6.4 - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

RSS-132 4.4, SRSP503 5.1.3 - The maximum ERP shall be 11.5 Watts for mobile stations.

TEST PROCEDURE

ANSI / TIA / EIA 603C
RSS-132; RSS-133

MODES TESTED

- GSM - GSM (GSMK) & EGPRS (8PSK),
- UMTS (W-CDMA) - Rel 99, Rel 6 HSDPA Subtest 2

RESULTS for Cellular Band (ERP)

Mode	Channel	f (MHz)	ERP	
			dBm	mW
GPRS	128	824.20	32.50	1778.28
	190	836.60	31.40	1380.38
	251	848.80	31.70	1479.11
EGPRS	128	824.20	29.80	954.99
	190	836.60	29.90	977.24
	251	848.80	28.70	741.31

Mode	Channel	f (MHz)	ERP	
			dBm	mW
Rel 99	4132	826.40	25.20	331.13
	4180	836.00	25.40	346.74
	4230	846.60	25.70	371.54
HSDPA (Subtest 1)	4132	826.40	24.90	309.03
	4180	836.60	25.20	331.13
	4230	846.60	25.00	316.23

RESULTS for PCS Band (EIRP)

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
GPRS	512	1850.20	28.00	630.96
	661	1880.00	29.90	977.24
	810	1909.80	28.70	741.31
EGPRS	512	1850.20	29.20	831.76
	661	1880.00	29.00	794.33
	810	1909.80	29.40	870.96

Mode	Channel	f (MHz)	EIRP	
			dBm	mW
Rel 99	9262	1852.40	27.30	537.03
	9400	1880.00	28.00	630.96
	9538	1907.60	27.80	602.56
HSDPA (Subtest 1)	9262	1852.40	27.70	588.84
	9400	1880.00	27.00	501.19
	9538	1907.60	27.60	575.44

ERP for GPRS Mode (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber A

Company: BARNES AND NOBLE
Project #: 10U13105
Date: 4/1/2010
Test Engineer: MENGISTU MEKURIA
Configuration: EUT and AC Adapter
Mode: TX, GPRS CELL BAND

Test Equipment:

Receiving: Sunol T122, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.

f MHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch							
824.20	-2.2	V	34.8	32.5	38.5	-5.9	
824.20	-10.2	H	30.5	20.3	38.5	-18.1	
Mid Ch							
836.60	-1.7	V	33.1	31.4	38.5	-7.1	
836.60	-8.9	H	31.2	22.3	38.5	-16.1	
High Ch							
848.80	-0.5	V	32.1	31.7	38.5	-6.8	
848.80	-9.2	H	31.2	22.0	38.5	-16.4	

Rev. 1.24.7

ERP for EGPRS Mode (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber A

Company: BARNES AND NOBLE
Project #: 10U13105
Date: 4/1/2010
Test Engineer: MENGISTU MEKURIA
Configuration: EUT and AC Adapter
Mode: TX, EGPRS CELL BAND

Test Equipment:

Receiving: Sunol T122, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.

f MHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch							
824.20	-5.0	V	34.8	29.8	38.5	-8.7	
824.20	-11.5	H	30.5	19.0	38.5	-19.4	
Mid Ch							
836.60	-3.2	V	33.1	29.9	38.5	-8.5	
836.60	-10.1	H	31.2	21.1	38.5	-17.3	
High Ch							
848.80	-3.4	V	32.1	28.7	38.5	-9.7	
848.80	-11.2	H	31.2	20.0	38.5	-18.5	

Rev. 1.24.7

ERP for UMTS Rel 99 Mode (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B

Company: Barnes and Noble
Project #: 10U13105
Date: 4/2/2010
Test Engineer: Chin Pang
Configuration: EUT and AC adapter
Mode: TX, WCDMA850+Rel 99

Test Equipment:

Receiving: Sunol T130, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.

f MHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch							
826.40	-7.4	V	32.6	25.2	38.5	-13.3	
826.40	-13.5	H	30.4	16.9	38.5	-21.6	
Mid Ch							
836.40	-7.3	V	32.7	25.4	38.5	-13.1	
836.40	-13.9	H	30.7	16.8	38.5	-21.6	
High Ch							
846.60	-7.0	V	32.7	25.7	38.5	-12.8	
846.60	-14.3	H	30.7	16.4	38.5	-22.0	

Rev. 1.24.7

ERP for UMTS Rel 6 HSDPA Mode (Cellular Band)

High Frequency Substitution Measurement Compliance Certification Services Chamber B

Company: Barnes and Noble
Project #: 10U13105
Date: 4/2/2010
Test Engineer: Chin Pang
Configuration: EUT and AC Adapter
Mode: TX, WCDMA850+HSDPA

Test Equipment:

Receiving: Sunol T130, and 3m Chamber N-type Cable (Setup this one for testing EUT)
Substitution: Dipole S/N: 00022117, 6ft SMA Cable (SN # 208947003) Warehouse.

f MHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch							
826.40	-7.7	V	32.6	24.9	38.5	-13.6	
826.40	-13.7	H	30.4	16.7	38.5	-21.8	
Mid Ch							
836.40	-7.5	V	32.7	25.2	38.5	-13.3	
836.40	-14.1	H	30.7	16.6	38.5	-21.8	
High Ch							
846.60	-7.7	V	32.7	25.0	38.5	-13.5	
846.60	-14.5	H	30.7	16.2	38.5	-22.2	

Rev. 1.24.7

EIRP for GPRS Mode (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B							
Company:Barnes and noble Project #:10U13105 Date: 4/2/2010 Test Engineer: Chin Pang Configuration:EUT and AC Adapter Mode:TX GPRS1900							
<u>Test Equipment:</u> Receiving: Horn T59, and Chamber B SMA Cables Substitution: Horn T72 Substitution, 6ft SMA Cable (208947003) Warehouse							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch							
1.850	-12.2	V	40.2	28.0	33.0	-5.0	
1.850	-16.5	H	39.5	23.0	33.0	-10.0	
Mid Ch							
1.880	-10.4	V	40.3	29.9	33.0	-3.2	
1.880	-16.1	H	40.1	24.0	33.0	-9.0	
High Ch							
1.910	-11.5	V	40.2	28.7	33.0	-4.3	
1.910	-16.0	H	40.1	24.1	33.0	-8.9	

Rev. 1.24.7

EIRP for EGPRS Mode (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B							
Company:Barnes and noble Project #:10U13105 Date: 4/2/2010 Test Engineer: Chin Pang Configuration:EUT and AC Adapter Mode:TX EGPRS1900							
<u>Test Equipment:</u> Receiving: Horn T59, and Chamber B SMA Cables Substitution: Horn T72 Substitution, 6ft SMA Cable (208947003) Warehouse							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch							
1.850	-11.0	V	40.2	29.2	33.0	-3.8	
1.850	-15.2	H	39.5	24.3	33.0	-8.7	
Mid Ch							
1.880	-11.3	V	40.3	29.0	33.0	-4.1	
1.880	-16.5	H	40.1	23.6	33.0	-9.4	
High Ch							
1.910	-10.8	V	40.2	29.4	33.0	-3.6	
1.910	-13.3	H	40.1	26.8	33.0	-6.2	

Rev. 1.24.7

EIRP for UMTS Rel 99 Mode (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B							
Company:Barnes and noble Project #:10U13105 Date: 4/2/2010 Test Engineer: Chin Pang Configuration:EUT and AC Adapter Mode:TX, WCDMA 1900, Rel 99							
<u>Test Equipment:</u> Receiving: Horn T59, and Chamber B SMA Cables Substitution: Horn T72 Substitution, 6ft SMA Cable (208947003) Warehouse							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch							
1.852	-16.5	V	40.2	23.7	33.0	9.3	
1.852	-12.2	H	39.5	27.3	33.0	5.7	
Mid Ch							
1.880	-17.0	V	40.3	23.3	33.0	9.8	
1.880	-12.1	H	40.1	28.0	33.0	5.0	
High Ch							
1.908	-17.0	V	40.2	23.2	33.0	9.8	
1.908	-12.3	H	40.1	27.8	33.0	5.2	

Rev. 1.24.7

EIRP for UMTS Rel 6 HSDPA Mode (PCS Band)

High Frequency Fundamental Measurement Compliance Certification Services Chamber B							
Company:Barnes and noble Project #:10U13105 Date: 4/2/2010 Test Engineer: Chin Pang Configuration:EUT Mode:TX, WCDMA 1900, HSDPA							
<u>Test Equipment:</u> Receiving: Horn T59, and Chamber B SMA Cables Substitution: Horn T72 Substitution, 6ft SMA Cable (208947003) Warehouse							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Path Loss (dBm)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch							
1.852	-12.5	V	40.2	27.7	33.0	5.3	
1.852	-16.4	H	39.5	23.1	33.0	9.9	
Mid Ch							
1.880	-13.3	V	40.3	27.0	33.0	6.1	
1.880	-16.8	H	40.1	23.3	33.0	9.7	
High Ch							
1.908	-12.6	V	40.2	27.6	33.0	5.4	
1.908	-16.0	H	40.1	24.1	33.0	8.9	

Rev. 1.24.7

9.2. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238
IC: RSS-132, 4.5; RSS-233, 6.5

LIMIT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

TEST PROCEDURE

For Cellular equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For PCS equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

MODES TESTED

- GSM - GSM (GSMK) & EGPRS (8PSK),
- UMTS (W-CDMA) - Rel 99, Rel 6 HSDPA Subtest 2

RESULTS

See the following pages.

GPRS Mode (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:	Barn& Noble									
Project #:	10U13105									
Date:	3/30/2010									
Test Engineer:	Thanh Nguyen									
Configuration:	EUT WITH AC/DC Adapter									
Mode:	TX, CELL GPRS MODE									
Chamber	Pre-amplifier		Filter		Limit					
5m Chamber B	T145 8449B		Filter 1		TX Part 22					
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch 824.2MHz										
1.648	-46.8	H	3.0	37.2	35.5	1.0	-46.3	-13.0	-33.3	
2.473	-46.9	H	3.0	39.8	35.4	1.0	-43.6	-13.0	-30.6	
4.121	-64.4	H	3.0	46.7	35.2	1.0	-54.1	-13.0	-41.1	
1.648	-46.2	V	3.0	36.8	35.5	1.0	-46.1	-13.0	-33.1	
2.473	-46.1	V	3.0	41.7	35.4	1.0	-40.9	-13.0	-27.9	
4.121	-58.1	V	3.0	46.1	35.2	1.0	-48.3	-13.0	-35.3	
Mid Ch 836.6MHz										
1.674	-33.6	H	3.0	37.5	35.5	1.0	-32.8	-13.0	-19.8	
2.510	-39.5	H	3.0	39.9	35.4	1.0	-36.1	-13.0	-23.1	
4.184	-64.8	H	3.0	46.8	35.2	1.0	-54.4	-13.0	-41.4	
1.674	-37.7	V	3.0	37.1	35.5	1.0	-37.2	-13.0	-24.2	
2.510	-39.1	V	3.0	41.8	35.4	1.0	-33.8	-13.0	-20.8	
4.184	-64.1	V	3.0	46.3	35.2	1.0	-54.2	-13.0	-41.2	
High Ch 848.8 MHz										
1.698	-40.5	H	3.0	37.7	35.5	1.0	-39.5	-13.0	-26.5	
2.546	-40.1	H	3.0	40.1	35.4	1.0	-36.6	-13.0	-23.6	
4.255	-59.2	H	3.0	47.0	35.2	1.0	-48.5	-13.0	-35.5	
1.698	-50.5	V	3.0	37.4	35.5	1.0	-49.7	-13.0	-36.7	
2.546	-37.6	V	3.0	42.0	35.4	1.0	-32.2	-13.0	-19.2	
4.244	-65.8	V	3.0	46.5	35.2	1.0	-55.7	-13.0	-42.7	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

EGPRS Mode (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement																																																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">Company:</td> <td colspan="10">Barn& Noble</td> </tr> <tr> <td>Project #:</td> <td colspan="10">10U13105</td> </tr> <tr> <td>Date:</td> <td colspan="10">3/30/2010</td> </tr> <tr> <td>Test Engineer:</td> <td colspan="10">Thanh Nguyen</td> </tr> <tr> <td>Configuration:</td> <td colspan="10">EUT WITH AC/DC Adapter</td> </tr> <tr> <td>Mode:</td> <td colspan="10">TX, CELL EGPRS MODE</td> </tr> </table>											Company:	Barn& Noble										Project #:	10U13105										Date:	3/30/2010										Test Engineer:	Thanh Nguyen										Configuration:	EUT WITH AC/DC Adapter										Mode:	TX, CELL EGPRS MODE									
Company:	Barn& Noble																																																																											
Project #:	10U13105																																																																											
Date:	3/30/2010																																																																											
Test Engineer:	Thanh Nguyen																																																																											
Configuration:	EUT WITH AC/DC Adapter																																																																											
Mode:	TX, CELL EGPRS MODE																																																																											
Chamber			Pre-amplifier			Filter			Limit																																																																			
5m Chamber B			T145 8449B			Filter 1			TX Part 22																																																																			
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes																																																																		
Low Ch 824.2MHz																																																																												
1.648	-46.8	H	3.0	37.2	35.5	1.0	-46.3	-13.0	-33.3																																																																			
2.473	-46.9	H	3.0	39.8	35.4	1.0	-43.6	-13.0	-30.6																																																																			
4.121	-65.8	H	3.0	46.7	35.2	1.0	-55.5	-13.0	-42.5																																																																			
1.648	-46.2	V	3.0	36.8	35.5	1.0	-46.1	-13.0	-33.1																																																																			
2.473	-46.1	V	3.0	41.7	35.4	1.0	-40.9	-13.0	-27.9																																																																			
4.121	-55.1	V	3.0	46.1	35.2	1.0	-45.3	-13.0	-32.3																																																																			
Mid Ch 836.6MHz																																																																												
1.674	-33.6	H	3.0	37.5	35.5	1.0	-32.8	-13.0	-19.8																																																																			
2.510	-39.5	H	3.0	39.9	35.4	1.0	-36.1	-13.0	-23.1																																																																			
4.184	-58.3	H	3.0	46.8	35.2	1.0	-47.9	-13.0	-34.9																																																																			
1.674	-37.7	V	3.0	37.1	35.5	1.0	-37.2	-13.0	-24.2																																																																			
2.510	-39.1	V	3.0	41.8	35.4	1.0	-33.8	-13.0	-20.8																																																																			
4.184	-62.7	V	3.0	46.3	35.2	1.0	-52.8	-13.0	-39.8																																																																			
High Ch 848.8 MHz																																																																												
1.698	-40.5	H	3.0	37.7	35.5	1.0	-39.5	-13.0	-26.5																																																																			
2.546	-40.1	H	3.0	40.1	35.4	1.0	-36.6	-13.0	-23.6																																																																			
4.255	-57.3	H	3.0	47.0	35.2	1.0	-46.7	-13.0	-33.7																																																																			
1.698	-50.5	V	3.0	37.4	35.5	1.0	-49.7	-13.0	-36.7																																																																			
2.546	-37.6	V	3.0	42.0	35.4	1.0	-32.2	-13.0	-19.2																																																																			
4.244	-57.8	V	3.0	46.5	35.2	1.0	-47.8	-13.0	-34.8																																																																			

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UMTS REL 99 Mode (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:Barnes and Noble Project #:10U13105 Date:4/5/2010 Test Engineer:Chin Pang Configuration:EUT and AC Adapter Mode:TX, WCDMA850 Rel 99										
Chamber			Pre-amplifier		Filter		Limit			
5m Chamber A	T144 8449B	Filter 1	TX Part 22							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch										
1.65	-52.1	H	3.0	36.6	38.1	1.0	-52.7	-13.0	-39.7	
2.48	-58.8	H	3.0	40.0	37.5	1.0	-55.3	-13.0	-42.3	
1.65	-52.5	V	3.0	36.9	38.1	1.0	-52.8	-13.0	-39.8	
2.48	-60.0	V	3.0	41.7	37.5	1.0	-54.7	-13.0	-41.7	
Mid Ch										
1.67	-52.4	H	3.0	36.8	38.1	1.0	-52.7	-13.0	-39.7	
2.51	-56.4	H	3.0	40.1	37.5	1.0	-52.7	-13.0	-39.7	
1.67	-51.8	V	3.0	37.1	38.1	1.0	-51.8	-13.0	-38.8	
2.51	-56.0	V	3.0	41.8	37.5	1.0	-50.6	-13.0	-37.6	
High Ch										
1.69	-48.5	H	3.0	37.0	38.1	1.0	-48.6	-13.0	-35.6	
2.54	-57.1	H	3.0	40.3	37.5	1.0	-53.2	-13.0	-40.2	
1.69	-52.9	V	3.0	37.3	38.1	1.0	-52.7	-13.0	-39.7	
2.54	-60.3	V	3.0	41.9	37.5	1.0	-54.8	-13.0	-41.8	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

UMTS HSDPA (Cellular Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:Barnes and Noble Project #:10U13105 Date:4/5/2010 Test Engineer:Chin Pang Configuration:EUT and AC Adapter Mode:TX, WCDMA850 HSDPA										
Chamber			Pre-amplifier		Filter		Limit			
5m Chamber B	T145 8449B	Filter 1	TX Part 22							
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch										
1.65	-47.6	H	3.0	37.3	35.5	1.0	-44.9	-13.0	-31.9	
2.48	-61.5	H	3.0	39.8	35.4	1.0	-56.1	-13.0	-43.1	
1.65	-49.5	V	3.0	36.8	35.5	1.0	-47.2	-13.0	-34.2	
2.48	-62.0	V	3.0	41.7	35.4	1.0	-54.7	-13.0	-41.7	
Mid Ch										
1.67	-52.8	H	3.0	37.5	35.5	1.0	-49.9	-13.0	-36.9	
2.51	-60.0	H	3.0	39.9	35.4	1.0	-54.5	-13.0	-41.5	
1.67	-53.1	V	3.0	37.1	35.5	1.0	-50.5	-13.0	-37.5	
2.51	-63.2	V	3.0	41.8	35.4	1.0	-55.8	-13.0	-42.8	
High Ch										
1.69	-53.0	H	3.0	37.7	35.5	1.0	-49.9	-13.0	-36.9	
2.54	-61.5	H	3.0	40.1	35.4	1.0	-55.8	-13.0	-42.8	
1.69	-53.1	V	3.0	37.4	35.5	1.0	-50.2	-13.0	-37.2	
2.54	-63.4	V	3.0	41.9	35.4	1.0	-55.9	-13.0	-42.9	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

GPRS Mode (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:		Barnes& Noble 10U13105 3/31/2010 Thanh Nguyen EUT and AC Adapter TX, GPRS1900								
Chamber			Pre-amplifier			Filter			Limit	
5m Chamber B			T145 8449B			Filter 1			TX Part 24	
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch										
3.704	-59.3	H	3.0	45.3	35.4	1.0	-48.3	-13.0	-35.3	
5.551	-60.6	H	3.0	50.0	35.4	1.0	-45.0	-13.0	-32.0	
3.704	-55.2	V	3.0	45.1	35.4	1.0	-44.4	-13.0	-31.4	
5.551	-57.7	V	3.0	49.2	35.4	1.0	-42.9	-13.0	-29.9	
Mid Ch										
3.760	-61.4	H	3.0	45.5	35.3	1.0	-50.2	-13.0	-37.2	
5.640	-60.3	H	3.0	50.2	35.4	1.0	-44.6	-13.0	-31.6	
3.760	-53.6	V	3.0	45.3	35.3	1.0	-42.7	-13.0	-29.7	
5.640	-60.6	V	3.0	49.3	35.4	1.0	-45.7	-13.0	-32.7	
High Ch										
3.820	-59.8	H	3.0	45.7	35.3	1.0	-48.4	-13.0	-35.4	
5.729	-61.6	H	3.0	50.3	35.4	1.0	-45.8	-13.0	-32.8	
3.820	-51.6	V	3.0	45.4	35.3	1.0	-40.4	-13.0	-27.4	
5.729	-59.2	V	3.0	49.4	35.4	1.0	-44.3	-13.0	-31.3	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

EGPRS Mode (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement											
Company:		Barnes& Noble									
Project #:		10U13105									
Date:		3/30/2010									
Test Engineer:		Thanh Nguyen									
Configuration:		EUT and AC Adapter									
Mode:		TX, EGPRS1900									
Chamber			Pre-amplifier			Filter			Limit		
5m Chamber B			T145 8449B			Filter 1			TX Part 24		
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes	
Low Ch											
3.704	-55.9	H	3.0	45.3	35.4	1.0	-44.9	-13.0	-31.9		
5.551	-56.8	H	3.0	50.0	35.4	1.0	-41.2	-13.0	-28.2		
3.704	-51.5	V	3.0	45.1	35.4	1.0	-40.7	-13.0	-27.7		
5.551	-56.6	V	3.0	49.2	35.4	1.0	-41.8	-13.0	-28.8		
Mid Ch											
3.760	-52.4	H	3.0	45.5	35.3	1.0	-41.2	-13.0	-28.2		
5.640	-60.3	H	3.0	50.2	35.4	1.0	-44.6	-13.0	-31.6		
3.760	-52.1	V	3.0	45.3	35.3	1.0	-41.2	-13.0	-28.2		
5.640	-57.3	V	3.0	49.3	35.4	1.0	-42.5	-13.0	-29.5		
High Ch											
3.820	-58.2	H	3.0	45.7	35.3	1.0	-46.7	-13.0	-33.7		
5.729	-62.9	H	3.0	50.3	35.4	1.0	-47.0	-13.0	-34.0		
3.820	-57.9	V	3.0	45.4	35.3	1.0	-46.8	-13.0	-33.8		
5.729	-64.8	V	3.0	49.4	35.4	1.0	-49.9	-13.0	-36.9		
Rev. 03.03.09											
Note: No other emissions were detected above the system noise floor.											

UMTS REL 99 Mode (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:Barnes and Noble Project #:10U13105 Date:4/5/2010 Test Engineer:Chin Pang Configuration:EUT and AC Adapter Mode:TX, WCDMA1900 Rel 99										
Chamber		Pre-amplifier		Filter		Limit				
5m Chamber A		T144 8449B		Filter 1		TX Part 24				
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch										
3.70	-58.8	H	3.0	45.0	36.8	1.0	-49.6	-13.0	-36.6	
5.56	-65.7	H	3.0	50.0	36.3	1.0	-51.0	-13.0	-38.0	
3.70	-62.5	V	3.0	44.9	36.8	1.0	-53.4	-13.0	-40.4	
5.56	-66.3	V	3.0	49.3	36.3	1.0	-52.3	-13.0	-39.3	
Mid Ch										
3.76	-62.0	H	3.0	45.2	36.8	1.0	-52.6	-13.0	-39.6	
5.64	-65.0	H	3.0	50.1	36.3	1.0	-50.2	-13.0	-37.2	
3.76	-63.5	V	3.0	45.1	36.8	1.0	-54.2	-13.0	-41.2	
5.64	-67.0	V	3.0	49.4	36.3	1.0	-52.9	-13.0	-39.9	
High Ch										
3.82	-60.7	H	3.0	45.3	36.7	1.0	-51.1	-13.0	-38.1	
5.72	-66.2	H	3.0	50.2	36.3	1.0	-51.3	-13.0	-38.3	
3.82	-62.6	V	3.0	45.2	36.7	1.0	-53.2	-13.0	-40.2	
5.72	-67.3	V	3.0	49.5	36.3	1.0	-53.1	-13.0	-40.1	

Rev. 03.03.09
Note: No other emissions were detected above the system noise floor.

UMTS HSDPA (PCS Band)

Compliance Certification Services Above 1GHz High Frequency Substitution Measurement										
Company:Barnes and Noble Project #:10U13105 Date:4/5/2010 Test Engineer:Chin Pang Configuration:EUT and AC Adapter Mode:TX, WCDMA1900 HSDPA										
Chamber		Pre-amplifier			Filter		Limit			
5m Chamber B		T145 8449B			Filter 1		TX Part 24			
f GHz	SA reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Path Loss (dB)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch										
3.70	-60.4	H	3.0	45.3	35.4	1.0	-49.4	-13.0	-36.4	
5.56	-66.3	H	3.0	50.0	35.4	1.0	-50.7	-13.0	-37.7	
3.70	-64.0	V	3.0	45.1	35.4	1.0	-53.2	-13.0	-40.2	
5.56	-67.0	V	3.0	49.2	35.4	1.0	-52.2	-13.0	-39.2	
Mid Ch										
3.76	-63.4	H	3.0	45.5	35.3	1.0	-52.2	-13.0	-39.2	
5.64	-65.8	H	3.0	50.2	35.4	1.0	-50.1	-13.0	-37.1	
3.76	-64.0	V	3.0	45.3	35.3	1.0	-53.1	-13.0	-40.1	
5.64	-67.1	V	3.0	49.3	35.4	1.0	-52.2	-13.0	-39.2	
High Ch										
3.82	-63.0	H	3.0	45.7	35.3	1.0	-51.6	-13.0	-38.6	
5.72	-66.5	H	3.0	50.3	35.4	1.0	-50.6	-13.0	-37.6	
3.82	-66.0	V	3.0	45.4	35.3	1.0	-54.9	-13.0	-41.9	
5.72	-66.1	V	3.0	49.4	35.4	1.0	-51.2	-13.0	-38.2	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.										

9.3. RECEIVER SPURIOUS EMISSIONS

LIMIT

RSS-Gen 7.2.2

Spurious Emission Limits for Receivers:


Spurious Frequency (MHz)	Field Strength (microvolts/m at 3 metres)
30-88	100
88-216	150
216-960	200
Above 960	500

TEST PROCEDURE


The search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (local oscillator frequency, intermediate frequency or carrier frequency), or 30 MHz, whichever is the higher, to at least 3 times the highest tunable and local oscillator frequencies.

RESULTS

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



SPURIOUS EMISSIONS ABOVE 1000 MHz (WORST-CASE CONFIGURATION)

Note: No emissions were detected above the system noise floor.

9.4. POWER LINE CONDUCTED EMISSION

LIMIT

RSS-Gen 7.2.2

Except when the requirements applicable to a given device state otherwise, for any licence-exempt radio communication device equipped to operate from the public utility AC power supply, either directly or indirectly, the radio frequency voltage that is conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in Table 2. The tighter limit applies at the frequency range boundaries.

Table 2 – AC Power Lines Conducted Emission Limits

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
		66 to 56 [*]
0.15-0.5		
0.5-5	56	46
5-30	60	50


^{*} Decreases with the logarithm of the frequency.

RESULTS

6 WORST EMISSIONS

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq. (MHz)	Reading			Closs (dB)	Limit QP	EN B AV	Margin		Remark L1 / L2
	PK (dBuV)	QP (dBuV)	AV (dBuV)				QP (dB)	AV (dB)	
0.43	45.88	--	25.18	0.00	57.33	47.33	-11.45	-22.15	L1
0.55	43.38	--	26.10	0.00	56.00	46.00	-12.62	-19.90	L1
1.37	35.43	--	20.38	0.00	56.00	46.00	-20.57	-25.62	L1
0.18	42.89	--	27.87	0.00	64.44	54.44	-21.55	-26.57	L2
0.36	43.67	--	29.50	0.00	58.71	48.71	-15.04	-19.21	L2
0.55	42.19	--	27.12	0.00	56.00	46.00	-13.81	-18.88	L2
6 Worst Data									

LINE 1 RESULTS




LINE 2 RESULTS



Compliance Certification Services
47173 Benicia Street
Fremont, CA 94538
Tel: (510) 771-1000
Fax: (510) 661-0888

Data#: 14 File#: LC 10U13105.EMI Date: 03-30-2010 Time: 14:00:20



(Line Conduction)

Trace: 12

Ref Trace:

Condition: CISPR CLASS-B
Test Operator: : Thanh Nguyen
Project #: : 10U13105
Company: : Barnes & Noble
EUT Description: : eBook Reader w/WWAN, WLAN and USB Port
Configuration: : EUT only
Mode: : Tx/Rx link to Base Station
Target: : FCC Class B
Voltage: : 115VAC 60Hz
: L2: Peak(Blue); Average (Green)