

Report No.: SEWM2306000190RG09

Rev.: 01 1 of 11 Page:

TEST REPORT

Application No: SEWM2306000190RG

Applicant: NetComm Wireless Pty Ltd

Address of Applicant: Level 5, 18-20 Orion Road, Lane Cove, NSW, Australia

Manufacturer: Casa Systems, Inc.

Address of Manufacturer: 100 Old River Road Andover, MA 01810

EUT Description: 5G Wi-Fi 6 Residential Gateway

Model No.: CFW-4222

Trade Mark:

casa systems

FCC ID: XIA-CFW4222A

Standards: 47 CFR Part 2.1091


FCC KDB 447498 D01 v06

Date of Receipt: 2022/11/01 Date of Issue: 2023/06/25

Test Result: PASS*

In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Well Wei Wireless Laboratory Manager



South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房南部 邮编: 215000

t (86-512) 62992980 t (86-512) 62992980

www.sgsgroup.com.cn



Report No.: SEWM2306000190RG09

Rev.: 01 Page: 2 of 11

Version

Revision Record								
Version	Chapter	Modifier	Remark					
01		2023/06/25		Original				

Prepared By	(Nick Hu) / Test Engineer				
Checked By	(Stone Gu) / Reviewer				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sps.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Felectronic Documents at http://www.sps.com/en/Terms-and-Conditions.frems-b-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document sadvised that information contained hereon reflects the Company's findings at the time of its intermiton only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. For one of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the Attention. To check the authenticity of testing /inspection report & certificate, please contact us at telephone; (86-755) 83071443, or email: CND Doccheck@sps.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 www.sgsgroup.com.cn t (86-512) 62992980



Report No.: SEWM2306000190RG09

Rev.: 01 3 of 11 Page:

Contents

1	Ver	sion	2
		neral Information	
		Client Information Test Facility	
		General Description of EUT	
3	RF	Exposure Evaluation	7
	3.1	RF Exposure Compliance Requirement	7
		.1 Limits	
		.2 Test Procedure	
	3.1.	.3 EUT RF Exposure Evaluation	8
	3.1.	.4 Exposure calculations for multiple sources	.11



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sps.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Felectronic Documents at http://www.sps.com/en/Terms-and-Conditions.frems-b-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document sadvised that information contained hereon reflects the Company's findings at the time of its intermiton only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. For one of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the Attention. To check the authenticity of testing /inspection report & certificate, please contact us at telephone; (86-755) 83071443, or email: CND Doccheck@sps.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国•苏州•中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 www.sgsgroup.com.cn t (86-512) 62992980



Report No.: SEWM2306000190RG09

Rev.: 01 Page: 4 of 11

2 General Information

2.1 Client Information

Applicant:	NetComm Wireless Pty Ltd
Address of Applicant:	Level 5, 18-20 Orion Road, Lane Cove,NSW, Australia
Manufacturer:	Casa Systems, Inc.
Address of Manufacturer:	100 Old River Road Andover, MA 01810

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC -Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327





Report No.: SEWM2306000190RG09

Rev.: 01 5 of 11 Page:

2.3 General Description of EUT

EUT Description:	5G Wi-Fi 6 Residential Gateway										
Model No.:	CFW-4222										
Trade Mark:	casa systems	casa systems									
Hardware Version:	V1.1	V1.1									
Software Version:	CFW4222-CS.NA	CFW4222-CS.NA									
Antenna Type:	PCB Antenna	PCB Antenna									
	LTE Band 2:	3.03dBi (Ant0)	LTE Band 4:	1.65dBi (Ant0)							
	LTE Band 5:	1.46dBi (Ant0)	LTE Band 7:	1.91dBi (Ant3)							
	LTE Band 12:	0.4dBi (Ant0)	LTE Band 13:	-0.07dBi (Ant0)							
	LTE Band 14:	0.63dBi (Ant0)	LTE Band 17:	1.64dBi (Ant0)							
	LTE Band 25:	3.03dBi (Ant0)	LTE Band 26:	1.46dBi (Ant0)							
	LTE Band 30:	2.84dBi (Ant3)	LTE Band 38:	2.46dBi (Ant0)							
	LTE Band 41:	2.51dBi (Ant0)	LTE Band 48:	2.94dBi (Ant0)							
	LTE Band 66:	2.26dBi (Ant0)	LTE Band 71:	-0.63dBi (Ant0)							
	LTE CA_2C:	3.03dBi (Ant0)	LTE CA_5B:	1.46dBi (Ant0)							
	LTE CA_7C:	1.91dBi (Ant3)	LTE CA_38C:	2.46dBi (Ant0)							
	LTE CA_41C:	2.51dBi (Ant0)	LTE CA_48C:	2.94dBi (Ant0)							
	LTE CA_66B:	2.26dBi (Ant0)	LTE CA_66C:	-0.63dBi (Ant0)							
Antenna Gain:	NR Band n2:	3.03dBi (Ant0)	NR Band n5:	1.46dBi (Ant0)							
	NR Band n7:	1.91dBi (Ant3)	NR Band n12:	0.4dBi (Ant0)							
	NR Band n13:	-0.07dBi (Ant0)	NR Band n14:	0.63dBi (Ant0)							
	NR Band n25:	3.03dBi (Ant0)	NR Band n26:	1.46dBi (Ant0)							
	NR Band n30:	2.8dBi (Ant3)	NR Band n38:	2.14dBi (Ant3)							
	TATA Dana 1150.	Z.OUDI (AIIIO)	NIT Dalid 1130.	2.14dBi (Ant0)							
	NR Band n41:	2.14dBi (Ant3) 2.14dBi (Ant0)	NR Band n48:	2.94dBi (Ant0)							
	NR Band n66:	2.26dBi (Ant0)	NR Band n70:	0.76dBi (Ant0)							
	NR Band n71:	-0.77dBi (Ant0)	NR Band n77:	3.33dBi (Ant0) 3.33dBi (Ant3)							
	NR Band n78:	2.94dBi (Ant0) 2.94dBi (Ant3)									
	BT/BLE:	4.08dBi (Ant1)	2.4G WIFI:	2.61dBi (Ant1)							



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditio

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980

t (86-512) 62992980 www.sgsgroup.com.cn



Report No.: SEWM2306000190RG09

Rev.: 01

		Page: 6 of 11					
			1.57dBi (Ant2)				
5150MHz to 5250MHz:	1.79dBi (Ant3) 1.63dBi (Ant4) 1.49dBi (Ant5) 1.44dBi (Ant6)	5250MHz to 5350MHz:	0.82dBi (Ant3) 1.25dBi (Ant4) 1.63dBi (Ant5) 1.04dBi (Ant6)				
5470MHz to 5725MHz:	2.05dBi (Ant3) 1.89dBi (Ant4) 1.64dBi (Ant5) 2.12dBi (Ant6)	5725MHz to 5850MHz:	2.14dBi (Ant3) 2.3dBi (Ant4) 2.33dBi (Ant5) 2.49dBi (Ant6)				
LTE CA: LTE UL CA_2C; LTE UL CA_5B; LTE UL CA_7C; LTE UL CA_38C; LTE UL CA_41C; LTE UL CA_48C; LTE UL CA_66B; LTE UL CA_66C;							
ENDC: DC_5A_n2A; DC_14A			_66A_n2A;				

DC_71A_n2A; DC_13A_n2A; DC_7A_n2A; DC_4A_n2A;

_13A_n5A; DC_2A_n5A; DC 12A n5A; DC 30A n5A; DC 66A n5A

DC_7A_n5A; DC_48A_n5A; DC_5A_n7A; DC_12A_n7A; DC_12A_n7A; DC_66A_n7A; DC_71A_n7A; DC_13A_n7A;

DC_2A_n7A; DC_4A_n7A;

DC_2A_n12A; DC_30A_n12A; DC_66A_n12A; DC_7A_n12A; DC_5A_n12A;

DC 48A n12A;

DC 2A n14A; DC 30A n14A; DC 66A n14A;

DC_66A_n25A; DC_12A_n25A; DC_48A_n25A; DC_7A_n25A; DC_71A_n25A;

DC_5A_n25A; DC_26A_n25A; DC_13A_n25A;

DC_2A_n30A; DC_5A_n30A; DC_12A_n30A; DC_14A_n30A; DC_66A_n30A DC 66A n38A; DC 2A n38A; DC 12A n38A; DC 4A n38A; DC 5A n38A;

DC_71A_n38A;

DC_2A_n41A; DC_66A_n41A; DC_25A_n41A; DC_26A_n41A; DC_5A_n41A;

DC 4A n41A DC 12A n41A; DC 71A n41A;

DC_2A_n48A; DC_5A_n48A; DC_13A_n48A; DC_66A_n48A;

DC_13A_n66A; DC_2A_n66A; DC_5A_n66A; DC_12A_n66A; DC_14A_n66A;

DC_30A_n66A; DC_71A_n66A; DC_48A_n66A; DC_7A_n66A;

DC_2A_n71A; DC_66A_n71A; DC_5A_n71A; DC_7A_n71A; DC_48A_n71A; DC_41A_n77A; DC_7A_n77A; DC_2A_n77A; DC_5A_n77A; DC_13A_n77A;

DC_66A_n77A; DC_12A_n77A; DC_14A_n77A; DC_30A_n77A; DC_25A_n77A;

DC_71A_n77A;

DC_7A_n78A; DC_38A_n78A; DC_5A_n78A; DC_66A_n78A; DC_2A_n78A;

12A n78A; DC 13A n78A; DC 41A n78A; DC 4A n78A; DC 71A n78A;

DC_26A_n78A; DC_25A_n78A

NR UL CA:

n2-n48; n2-n77; n2-n78; n2-n41; n5-n77; n5-n78; n7-n77; n7-n78; n12-n41; n12-n48; n12-n77; n12-n78; n14-n77; n25-n38; n25-n41; n25-n77; n25-n78; n30-n77; n38-n66; n41-n66; n41-n71; n48-n66; n48-n71; n66-n77; n66-n78; n71-n77; n71-n78;

The antenna gain are derived from the gain information report provided by the manufacturer.

Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditio

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国・苏州・中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000 t (86-512) 62992980 t (86-512) 62992980



Report No.: SEWM2306000190RG09

Rev.: 01 Page: 7 of 11

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm2)	Averaging time (minutes)							
(A) Limits for Occupational/Controlled Exposures											
0.3-3.0	614	1.63	*(100)	6							
3.0-30	1842/f	4.89/f	*(900/f2)	6							
30-300	61.4	0.163	1.0	6							
300-1500	/	1	f/300	6							
1500-100,000	/	1	5	6							
(B) Limits for General P	opulation/Uncontrolled	Exposure								
0.3-1.34	614	1.63	*(100)	30							
1.34-30	824/f	2.19/f	*(180/f2)	30							
30-300	27.5	0.073	0.2	30							
300-1500	/	1	f/1500	30							
1500-100,000	/	1	1.0	30							

F=frequency in MHz

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4* Pi * R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents as http://www.sgs.com/en/Terms-and-Conditions.formate-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this lest report refer only to the sample(s) tested and such sample(s) are retained for 50 days only.

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Fee Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 t (86-512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com

⁼Plane-wave equivalent power density



Report No.: SEWM2306000190RG09

Rev.: 01 Page: 8 of 11

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

3.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Max Conducte d Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusio n
LTE Band 2/LTE CA_2C	1850.7	3.03	25.00	28.03	33.00	0.1264	1.0000	8.00	12.01	8.00	Pass
LTE Band 4	1710.7	1.65	25.00	26.65	30.00	0.0920	1.0000	5.00	12.01	5.00	Pass
LTE Band 5/LTE CA_5B	824.7	1.46	25.00	24.31	38.45	0.0881	0.5498	15.60	9.41	9.41	Pass
LTE Band 7/LTE CA_7C	2502.5	1.91	25.00	26.91	33.00	0.0977	1.0000	8.00	12.01	8.00	Pass
LTE Band 12	699.7	0.40	25.00	23.25	34.77	0.0690	0.4665	11.92	8.70	8.70	Pass
LTE Band 13	779.5	-0.07	25.00	22.78	34.77	0.0619	0.5197	11.92	9.16	9.16	Pass
LTE Band 14	790.5	0.63	25.00	23.48	34.77	0.0727	0.5270	11.92	9.23	9.23	Pass
LTE Band 17	706.5	1.64	25.00	24.49	34.77	0.0918	0.4710	11.92	8.74	8.74	Pass
LTE Band 25	1850.7	3.03	25.00	28.03	33.00	0.1264	1.0000	8.00	12.01	8.00	Pass
LTE Band 26(814- 824)	814.7	1.46	25.00	24.31	NA	0.0881	0.5431	NA	9.36	9.36	Pass
LTE Band 26(824- 849)	824.7	1.46	25.00	24.31	38.45	0.0881	0.5498	15.60	9.41	9.41	Pass
LTE Band 30	2307.5	2.84	21.00	23.84	23.98	0.0482	1.0000	2.98	16.01	2.98	Pass
LTE Band 38/LTE CA_38C	2572.5	2.46	25.00	27.46	33.00	0.1108	1.0000	8.00	12.01	8.00	Pass
LTE Band 38/LTE CA_38C(PC2)	2572.5	2.46	28.00	30.46	33.00	0.2212	1.0000	5.00	9.01	5.00	Pass
LTE Band 41/LTE CA_41C	2498.5	2.51	25.00	27.51	33.00	0.1121	1.0000	8.00	12.01	8.00	Pass
LTE Band 41/LTE CA_41C(PC2)	2498.5	2.51	28.00	30.51	33.00	0.2237	1.0000	5.00	9.01	5.00	Pass
LTE Band 48/LTE CA_48C	3552.5	2.94	20.00	22.94	23.00	0.0391	1.0000	3.00	17.01	3.00	Pass
LTE Band 66/LTE CA_66B/LTE CA_66C	1710.7	2.26	25.00	27.26	30.00	0.1059	1.0000	5.00	12.01	5.00	Pass
LTE Band 71	665.5	-0.63	25.00	22.22	34.77	0.0544	0.4437	11.92	8.48	8.48	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions/Terms-and-Conditions-Terms-and-Cond



Report No.: SEWM2306000190RG09

Rev.: 01 9 of 11 Page:

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	MIMO Directional gain	Max Conducted Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusio n
NR Band n2	1852.5	3.03	NA	25.00	28.03	33.00	0.1264	1.0000	8.00	12.01	8.00	Pass
NR Band n5	826.5	1.46	NA	25.00	24.31	38.45	0.0881	0.5510	15.60	9.42	9.42	Pass
NR Band n7	2502.5	1.91	NA	25.00	26.91	33.00	0.0977	1.0000	8.00	12.01	8.00	Pass
NR Band n12	701.5	0.40	NA	25.00	23.25	34.77	0.0690	0.4677	11.92	8.71	8.71	Pass
NR Band n13	779.5	-0.07	NA	25.00	22.78	34.77	0.0619	0.5197	11.92	9.16	9.16	Pass
NR Band n14	790.5	0.63	NA	25.00	23.48	34.77	0.0727	0.5270	11.92	9.23	9.23	Pass
NR Band n25	1852.5	3.03	NA	25.00	28.03	33.00	0.1264	1.0000	8.00	12.01	8.00	Pass
NR Band n26(814- 824)	816.5	1.46	NA	25.00	24.31	NA	0.0881	0.5443	NA	9.37	9.37	Pass
NR Band n26(824- 849)	826.5	1.46	NA	25.00	24.31	38.45	0.0881	0.5510	15.60	9.42	9.42	Pass
NR Band n30	2307.5	2.80	NA	21.00	23.80	23.98	0.0477	1.0000	2.98	16.01	2.98	Pass
NR Band n38	2575.0	2.14	NA	25.00	27.14	33.00	0.1030	1.0000	8.00	12.01	8.00	Pass
NR Band n38(PC2/MIMO)	2575.0	2.14	2.14	28.00	30.14	33.00	0.2055	1.0000	5.00	9.01	5.00	Pass
NR Band n41	2506.0	2.14	NA	25.00	27.14	33.00	0.1030	1.0000	8.00	12.01	8.00	Pass
NR Band n41(PC1.5/MIMO)	2506.0	2.14	2.14	29.00	31.14	33.00	0.2587	1.0000	4.00	8.01	4.00	Pass
NR Band n48	3555.0	2.94	NA	20.00	22.94	23.00	0.0391	1.0000	3.00	17.01	3.00	Pass
NR Band n66	1712.5	2.26	NA	25.00	27.26	30.00	0.1059	1.0000	5.00	12.01	5.00	Pass
NR Band n70	1697.5	0.76	NA	25.00	25.76	30.00	0.0749	1.0000	5.00	12.01	5.00	Pass
NR Band n71	665.5	-0.77	NA	25.00	22.08	34.77	0.0527	0.4437	11.92	8.48	8.48	Pass
NR Band n77 (3450-3550)	3455.0	3.33	NA	25.00	28.33	30.00	0.1354	1.0000	5.00	12.01	5.00	Pass
NR Band n77 (3450- 3550)(PC1.5/MIMO)	3455.0	3.33	3.33	26.50	29.83	30.00	0.1913	1.0000	3.50	10.51	3.50	Pass
NR Band n77 (3700-3980)	3705.0	3.33	NA	25.00	28.33	30.00	0.1354	1.0000	5.00	12.01	5.00	Pass
NR Band n77 (3700- 3980)(PC1.5/MIMO)	3705.0	3.33	3.33	26.50	29.83	30.00	0.1913	1.0000	3.50	10.51	3.50	Pass
NR Band n78 (3450-3550)	3455.0	2.94	NA	25.00	27.94	30.00	0.1238	1.0000	5.00	12.01	5.00	Pass
NR Band n78 (3450- 3550)(PC1.5/MIMO)	3455.0	2.94	2.94	26.50	29.44	30.00	0.1749	1.0000	3.50	10.51	3.50	Pass
NR Band n78 (3700-3800)	3705.0	2.94	NA	25.00	27.94	30.00	0.1238	1.0000	5.00	12.01	5.00	Pass
NR Band n78 (3700- 3800)(PC1.5/MIMO)	3705.0	2.94	2.94	26.50	29.44	30.00	0.1749	1.0000	3.50	10.51	3.50	Pass
Bluetooth	2402.0	4.08	NA	14.00	18.08	30.00	0.0128	1.0000				Pass
2.4G WiFi	2412.0	2.61	2.61	20.00	22.61	30.00	0.0363	1.0000		NA		Pass
5G WiFi	5320.0	2.49	2.49	23.00	25.49	30.00	0.0704	1.0000				Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sps.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Felectronic Documents at http://www.sps.com/en/Terms-and-Conditions.frems-b-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document sadvised that information contained hereon reflects the Company's findings at the time of its intermiton only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. For one of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the Attention. To check the authenticity of testing /inspection report & certificate, please contact us at telephone; (86-755) 83071443, or email: CND Doccheck@sps.com

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国•苏州•中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980

t (86-512) 62992980 www.sgsgroup.com.cn



Report No.: SEWM2306000190RG09

Rev.: 01 10 of 11 Page:

Due to the EUT support NR ENDC and CA

Both LTE and NR/LTE band can transmit simultaneously, the formula of the calculated the MPE is:

$$\sum_{i=1}^{n} \frac{S_{E_{i}}(dutyfactor)}{MPE_{E_{i}}} < 1$$

NOTE The corresponding MEs must be expressed in terms of power density in the above summation Therefore, the worst-case(DC_5A_n12A) situation is 0.1602+0.1475=0.3077, which is less than "1", this confirmed that the device comply with MPE limit.





Report No.: SEWM2306000190RG09

Rev.: 01 Page: 11 of 11

3.1.4 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table(A) and Table(B). To comply with the MPE, the fraction of the MPE in terms of E2, H2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^{n} \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration	
1	WWAN + Bluetooth+ WiFi 2.4G+ WiFi 5G	

No.	Mode	Power Density (mW/cm²)	MPE Limit (mW/cm²)	Result Ratio	Total Ratio	Limit	Result
	NR Band n71	0.0527	0.4437	0.1188			
	Bluetooth	0.0128	1.0000	0.0128	0.0000		
1	WiFi 2.4G	0.0363	1.0000	0.0363	0.2383	1.00	Pass
	WiFi 5G	0.0704	1.0000	0.0704			

---End of Report---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Decument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgor falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained of 3 days only.

t (86-512) 62992980