



# FCC RADIO EXPOSURE TEST REPORT

FCC ID : XIA-NTC224  
Equipment : 4G LTE Cat 1 Industrial IoT Router  
Brand Name :  **NetCommWireless**  
Model Name : NTC-224  
Applicant : NetComm Wireless Limited  
18-20 Orion Road Lane Cove NSW 2066 Australia  
Manufacturer : NetComm Wireless Limited  
18-20 Orion Road Lane Cove NSW 2066 Australia  
Standard : 47 CFR Part 2.1091

The product was received on Sep. 20, 2018, and testing was started from Oct. 03, 2018 and completed on Oct. 22, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

  
Approved by: Cliff Chang

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report</b> .....	<b>3</b>
<b>Summary of Test Result</b> .....	<b>4</b>
<b>1 General Description</b> .....	<b>5</b>
1.1 EUT General Information .....	5
1.2 Testing Location .....	5
<b>2 RF Exposure Limit Introduction</b> .....	<b>6</b>
<b>3 Radio Frequency Radiation Exposure Evaluation</b> .....	<b>7</b>
3.1 Power Density Calculation .....	7
<b>Photographs of EUT v01</b>	



### History of this test report

Report No.	Version	Description	Issued Date
FA891425AA	01	Initial issue of report	Nov. 13, 2018



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3	-	Exposure evaluation	PASS	-

Reviewed by: Sam Chen

Report Producer: Wendy Pan



# 1 General Description

## 1.1 EUT General Information

RF General Information				
Evaluation Mode	Bandwidth (MHz)	TX Frequency (MHz)	RX Frequency (MHz)	Modulation Type
WCDMA Band 5	5	826.4 MHz ~ 846.6	871.4 MHz ~ 891.6	WCDMA: BPSK / QPSK HSDPA: 16QAM HSUPA: QPSK
WCDMA Band 2	5	1852.4 ~ 1907.6	1932.4 ~ 1987.6	
WCDMA Band 4	5	1712.4 ~ 1752.6	2112.4 ~ 2152.6	

## 1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.



## 2 RF Exposure Limit Introduction

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 3 Radio Frequency Radiation Exposure Evaluation

#### 3.1 Power Density Calculation

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
Band 5_WCDMA_5MHz	3.13	23.31	26.44	0.50	26.94	0.49431	20	0.09834	0.55093
Band 2_WCDMA_5MHz	3.42	22.01	25.43	0.50	25.93	0.39174	20	0.07793	1
Band 4_WCDMA_5MHz	3.28	22.18	25.46	0.50	25.96	0.39446	20	0.07847	1

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

**Conclusion:**

According to 47 CFR Part 2.1091, the RF exposure analysis concludes that the RF Exposure is compliant.

————THE END————