



RF Exposure Evaluation Report

APPLICANT : NetComm Wireless Limited
EQUIPMENT : Vodafone MachineLink 3G
BRAND NAME : NetComm Wireless
MODEL NAME : NWL-10
FCC ID : XIA-NWL10
FILING TYPE : Certification
STANDARD : OET Bulletin 65 Supplement C (Edition 01-01)

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with FCC OET Bulletin 65 Supplement C (Edition 01-01), and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



Table of Contents

1. ADMINISTRATION DATA 4
 1.1. Testing Laboratory 4
 1.2. Applicant 4
 1.3. Manufacturer 4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) 5
3. RF EXPOSURE LIMIT INTRODUCTION 6
4. CONDUCTED RF OUTPUT POWER (UNIT: DBM)..... 7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION 11



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA2N1433	Rev. 01	Initial issue of report	Jan. 02, 2013
FA2N1433	Rev. 02	Update report for revising HW and SW	Jan. 18, 2013
FA2N1433	Rev. 03	Update report for adding data in section 5	Jan. 24, 2013



1. Administration Data

1.1. Testing Laboratory

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978

1.2. Applicant

Company Name	NetComm Wireless Limited
Address	Level 2, 18-20 Orion Road Lane Cove, NSW Australia

1.3. Manufacturer

Company Name	NetComm Wireless Limited
Address	Level 2, 18-20 Orion Road Lane Cove, NSW Australia



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Vodafone MachineLink 3G
Brand Name	NetComm Wireless
Model Name	NWL-10
FCC ID	XIA-NWL10
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Antenna Type	PCB Antenna
HW Version	V1.1
SW Version	V1.10.16.2
Uplink Modulation	GPRS: GMSK EDGE: GMSK, 8PSK WCDMA (Rel 99): QPSK
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



3. RF Exposure Limit Introduction

The FCC categorizes the RF exposure limit based on the intended usage of the device and the user’s awareness and ability to exercise control over his or her exposure. This is a consumer product to be used in the home, hence this device was evaluated by mobile device with general population/uncontrolled exposure condition. The definition of these category are shown as follows:

▪ **Mobile Devices:**

A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitters' radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR 2.1091.

▪ **General Population/Uncontrolled Exposure:**

The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category and the general population/uncontrolled exposure limits apply to these devices.

Per OET Bulletin 65, the power density limit for General Population/Uncontrolled Exposure summary here:

Table: Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Power Density (S) (mW/cm ²)
0.3–1.34	*(100)
1.34–30	*(180/f ²)
30–300	0.2
300–1500	f/1500
1500–100,000	1.0

f = frequency in MHz

* = Plane-wave equivalent power density



4. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

Burst Average Power (dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS (GMSK, 1 Tx slot) – CS1	32.71	32.68	32.40	29.50	29.33	29.10
GPRS (GMSK, 2 Tx slots) – CS1	29.85	29.80	29.71	26.45	26.00	25.87
GPRS (GMSK, 3 Tx slots) – CS1	27.84	27.82	27.69	25.22	24.80	24.66
GPRS (GMSK, 4 Tx slots) – CS1	25.69	26.65	26.51	23.90	23.56	23.48
EDGE (GMSK, 1 Tx slot) – MCS1	32.64	32.62	32.41	29.48	29.28	29.02
EDGE (GMSK, 2 Tx slots) – MCS1	29.77	29.72	29.61	26.46	25.92	25.72
EDGE (GMSK, 3 Tx slots) – MCS1	27.71	27.66	27.55	25.20	24.74	24.61
EDGE (GMSK, 4 Tx slots) – MCS1	25.50	25.44	25.51	23.88	23.51	23.40
EDGE (8PSK, 1 Tx slot) – MCS5	26.81	26.70	26.51	25.56	25.11	24.85
EDGE (8PSK, 2 Tx slots) – MCS5	23.79	23.70	23.68	22.46	21.99	21.74
EDGE (8PSK, 3 Tx slots) – MCS5	22.24	22.15	22.10	21.22	20.79	20.59
EDGE (8PSK, 4 Tx slots) – MCS5	21.20	21.03	20.99	19.96	19.56	19.39
Frame-Average Power (dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS (GMSK, 1 Tx slot) – CS1	23.71	23.68	23.40	20.50	20.33	20.10
GPRS (GMSK, 2 Tx slots) – CS1	23.85	23.80	23.71	20.45	20.00	19.87
GPRS (GMSK, 3 Tx slots) – CS1	23.58	23.56	23.43	20.96	20.54	20.40
GPRS (GMSK, 4 Tx slots) – CS1	22.69	23.65	23.51	20.90	20.56	20.48
EDGE (GMSK, 1 Tx slot) – MCS1	23.64	23.62	23.41	20.48	20.28	20.02
EDGE (GMSK, 2 Tx slots) – MCS1	23.77	23.72	23.61	20.46	19.92	19.72
EDGE (GMSK, 3 Tx slots) – MCS1	23.45	23.40	23.29	20.94	20.48	20.35
EDGE (GMSK, 4 Tx slots) – MCS1	22.50	22.44	22.51	20.88	20.51	20.40
EDGE (8PSK, 1 Tx slot) – MCS5	17.81	17.70	17.51	16.56	16.11	15.85
EDGE (8PSK, 2 Tx slots) – MCS5	17.79	17.70	17.68	16.46	15.99	15.74
EDGE (8PSK, 3 Tx slots) – MCS5	17.98	17.89	17.84	16.96	16.53	16.33
EDGE (8PSK, 4 Tx slots) – MCS5	18.20	18.03	17.99	16.96	16.56	16.39
<p>Remark: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below: Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB</p>						

<WCDMA Conducted Power >

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

WCDMA Setup Configuration:

- a. The EUT was connected to Base Station referred to the drawing of Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting
 - i. Data rates: Varied from RMC 12.2Kbps
 - ii. RMC Test Loop = Loop Mode 1
 - iii. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

HSDPA Setup Configuration:

The EUT was connected to Base Station referred to the drawing of Setup Configuration.

- a. The RF path losses were compensated into the measurements.
- b. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- c. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d=12/15, \beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station referred to the drawing of Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCl
 - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d=12/15, \beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration



WCDMA Average Power (dBm)							
Band		WCDMA Band V			WCDMA Band II		
Channel		4132	4182	4233	9262	9400	9538
Frequency (MHz)		826.4	836.4	846.6	1852.4	1880.0	1907.6
3GPP Rel 99	RMC 12.2K	23.69	23.63	23.66	23.29	23.28	23.27
3GPP Rel 6	HSDPA Subtest-1	23.62	23.50	23.56	23.23	23.23	23.21
3GPP Rel 6	HSDPA Subtest-2	23.58	23.48	23.50	23.22	23.21	23.20
3GPP Rel 6	HSDPA Subtest-3	23.14	23.07	23.09	22.90	22.89	22.88
3GPP Rel 6	HSDPA Subtest-4	23.10	23.07	23.06	22.85	22.83	22.81
3GPP Rel 6	HSUPA Subtest-1	22.00	21.52	21.80	22.02	21.56	21.70
3GPP Rel 6	HSUPA Subtest-2	21.62	21.32	21.45	21.35	21.15	21.28
3GPP Rel 6	HSUPA Subtest-3	21.42	21.26	21.30	21.43	21.30	21.37
3GPP Rel 6	HSUPA Subtest-4	21.75	21.42	21.70	21.30	21.25	21.38
3GPP Rel 6	HSUPA Subtest-5	21.80	21.50	21.72	21.92	21.48	21.67



5. Radio Frequency Radiation Exposure Evaluation

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna (i.e., 20 cm for this product)

For this device, the calculation is as follows:

WWAN Operating frequency ≤ 1.5GHz

WWAN Main Antenna

Function	Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Source-Based Time-Average Power (dBm)	Source-Based Time-Average Power (mW)	Source-Based Time-Average EIRP (mW)	Source-Based Time-Average ERP (mW)	Calculated RF Exposure (mW/cm ²)	Limit (mW/cm ²)
GPRS 850 (1 Tx slot)	824.20	1.30	1.35	24.00	251.19	338.84	206.54	0.07	0.55
GPRS 850 (2 Tx slots)	824.20	1.30	1.35	24.00	251.19	338.84	206.54	0.07	0.55
GPRS 850 (3 Tx slots)	824.20	1.30	1.35	23.74	236.59	319.15	194.54	0.06	0.55
GPRS 850 (4 Tx slots)	836.40	1.30	1.35	24.00	251.19	338.84	206.54	0.07	0.56
WCDMA Band 5	826.40	1.30	1.35	24.00	251.19	338.84	206.54	0.07	0.55

Optional External WWAN Antenna

Function	Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Source-Based Time-Average Power (dBm)	Source-Based Time-Average Power (mW)	Source-Based Time-Average EIRP (mW)	Source-Based Time-Average ERP (mW)	Calculated RF Exposure (mW/cm ²)	Limit (mW/cm ²)
GPRS 850 (1 Tx slot)	824.20	3.92	2.47	24.00	251.19	619.44	377.57	0.12	0.55
GPRS 850 (2 Tx slots)	824.20	3.92	2.47	24.00	251.19	619.44	377.57	0.12	0.55
GPRS 850 (3 Tx slots)	824.20	3.92	2.47	23.74	236.59	583.45	355.63	0.12	0.55
GPRS 850 (4 Tx slots)	836.40	3.92	2.47	24.00	251.19	619.44	377.57	0.12	0.56
WCDMA Band 5	826.40	3.92	2.47	24.00	251.19	619.44	377.57	0.12	0.55

Note: The above optional external antenna spec was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



WWAN Operating frequency > 1.5GHz

WWAN Main Antenna

Function	Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Source-Based Time-Average Power (dBm)	Source-Based Time-Average Power (mW)	Source-Based Time-Average EIRP (mW)	Calculated RF Exposure (mW/cm ²)	Limit (mW/cm ²)
GPRS 1900 (1 Tx slot)	1850.20	2.00	1.58	21.00	125.89	199.53	0.04	1.00
GPRS 1900 (2 Tx slots)	1850.20	2.00	1.58	21.00	125.89	199.53	0.04	1.00
GPRS 1900 (3 Tx slots)	1850.20	2.00	1.58	21.74	149.28	236.59	0.05	1.00
GPRS 1900 (4 Tx slots)	1850.20	2.00	1.58	21.00	125.89	199.53	0.04	1.00
WCDMA Band 2	1852.40	2.00	1.58	24.00	251.19	398.11	0.08	1.00

Optional External WWAN Antenna

Function	Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Source-Based Time-Average Power (dBm)	Source-Based Time-Average Power (mW)	Source-Based Time-Average EIRP (mW)	Calculated RF Exposure (mW/cm ²)	Limit (mW/cm ²)
GPRS 1900 (1 Tx slot)	1850.20	2.50	1.78	21.00	125.89	223.87	0.04	1.00
GPRS 1900 (2 Tx slots)	1850.20	2.50	1.78	21.00	125.89	223.87	0.04	1.00
GPRS 1900 (3 Tx slots)	1850.20	2.50	1.78	21.74	149.28	265.46	0.05	1.00
GPRS 1900 (4 Tx slots)	1850.20	2.50	1.78	21.00	125.89	223.87	0.04	1.00
WCDMA Band 2	1852.40	2.50	1.78	24.00	251.19	446.68	0.09	1.00

Note: The above optional external antenna spec was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Conclusion:

Per part 2.1091(c), EUT source-based time-averaged ERP < 1.5W for RF operating frequency ≤ 1.5GHz, EUT source-based time-averaged EIRP < 3W for RF operating frequency > 1.5GHz, routine evaluation of MPE is not required; MPE calculation is sufficient to show compliance. The MPE calculation results indicate that the EUT complies with the RF exposure limit of FCC OET Bulletin 65 Supplement C (Edition 01-01).