

PRODUCT LABELING

FCC ID / IC number label

Terminal



Base



Note:

- No special tools are required to open the battery compartment.
- Device is shipped without batteries

For terminal:

EFT930G - xxxx0102

XXXXXXXXXX 



Serial N : AAJJPTxxxxxxxx







IMEI: 358758xxxxxxxx



Ratings: 5V $\bar{\bar{}}$ 1A

FCC ID: XKB-EFT930G contains FCC ID: VW3HILOC
IC: 2586D-EFT930G contains IC: 2599H-HILOC 

For base :


 IN	 OUT	COMØ		
---	--	------	---	--



ingenico BAS930P-1NT101






Bar-Code  **Bar-Code** 

AAJJJBXXXXXXXXX 2XXXXXXXXX



A utiliser uniquement avec l'alimentation fournie.
Use only with provided power supply.
Nur mit dem original netzteile verwenden.
Da utilizzare solo con alimentazione fornita.

 **Made in:**

XX  Ratings: 5V $\bar{\bar{}}$ 1A  FCC ID:XKB-BAS930P
US:IEOMM03BBAS930


				
---	---	---	---	--



ingenico BAS930P-NNN101

Bar-Code  **Bar-Code** 

AAJJJBXXXXXXXXX 2XXXXXXXXX

A utiliser uniquement avec l'alimentation fournie.
Use only with provided power supply.
Nur mit dem original netzteile verwenden.
Da utilizzare solo con alimentazione fornita.

 **Made in:**

XX  Ratings: 5V $\bar{\bar{}}$ 1A  FCC ID:XKB-BAS930P
US:IEOMM03BBAS930

Color:White RAL9010
Adhésive one side: permanent UL969 certified
Material:Vynil or Polyester,thickness 50 to 100 m UL969 certified

PRODUCT REFERENCE DEFINITION

EFT930G – wxyz0102

w: Magnetic Head type

- 1: ISO2 Reader (1 track)
- 2: ISO1 and ISO2 Reader (2 tracks)
- 3: ISO1, ISO2 and ISO3 Reader (3 tracks)
- 4: ISO2 and ISO3 Reader (2 tracks)

x: USB Port configuration

- N: No USB Port
- A: 1 x USB Type A only
- B: 1 x USB Type B only
- C: 1 x USB Type A and 1 x USB Type B

y: Extension Board Option

- N: With SDCARD and SAM3
- L: Without
- X: others memory card (SAM, SDCARD) configuration

z: Thermal Pinter Option

- H: High speed printer OK
- L: Low speed printer

0102: Hardware version

BAS930X – wxy101

X: Link Type

- N: Charger Only
- P: Infra Red

w: Serial link

- N: None
- 1: 1 serial link
- 2: 2 serial links

x: USB Port configuration

- N : No USB Port
- A: 1 x USB Type A only
- B: 1 x USB Type B only
- C: 1 x USB Type A and 1 x USB Type B

y: Network type

- N: None
- T: Telephone
- E: Ethernet

101: Hardware version