



TEST REPORT

N°: 838096-R1-E

JDE : 137851

Subject Electromagnetic compatibility and Radio spectrum Matters (ERM) tests according to standards: FCC CFR 47 Part 15, Subpart B et C RSS-210 Issue 8.1

Issued to INGENICO
Rovaltain TGV – Quartier de la Gare
9 Avenue de la gare
26958 VALENCE CEDEX 9

Apparatus under test

↳ Product **Lecteur RFID / RFID Reader**

↳ Trade mark **INGENICO**

↳ Manufacturer **INGENICO**

↳ Model under test **IUC160-01T3176A**

↳ Serial number **15232UN00000016**

↳ FCCID **XKB-IUC16XCL**

↳ ICID **2586D-IUC16XCL**

Test date Du 18 au 28 Septembre 2015 / From September 18th to 28th, 2015

Test location Moirans

IC Test site 6500A-1 & 6500A-3

Test performed by Jonathan PAUC / Jonathan SARTO

Composition of document 31 pages

Modification of the last version None

Document issued on November 2nd, 2015

Written by :
Jonathan PAUC
Tests operator

Approved by :

Anthony MERLIN

Technical manager



This document shall not be reproduced, except in full, without the written approval of the LCIE. This document contains results related only to the item tested. It does not imply the conformity of the whole production to the item tested. Unless otherwise specified; the decision of conformity takes into account the uncertainty of measures. This document does not anticipate any certification decision.

LCIE

33, av du Général Leclerc
BP 8
92266 Fontenay-aux-Roses cedex
France

Tél : +33 1 40 95 60 60
Fax : +33 1 40 95 86 56
contact@lcie.fr
www.lcie.fr

Société par Actions Simplifiée
au capital de 15 745 984 €
RCS Nanterre B 408 363 174
www.lcie.com



SUMMARY

1. TEST PROGRAM.....	3
2. SYSTEM TEST CONFIGURATION	4
3. CONDUCTED EMISSION DATA	6
4. RADIATED EMISSION DATA (15.209).....	8
5. FUNDAMENTAL FREQUENCY TOLERANCE (15.225E).....	15
6. BAND-EDGE COMPLIANCE §15.209	17
7. OCCUPIED BANDWIDTH	19
8. ANNEX 1 (GRAPHS).....	21
9. UNCERTAINTIES CHART.....	31



1. TEST PROGRAM

Standard:

- FCC Part 15, Subpart C
- ANSI C63.10 (2013)
- RSS-210 Issue 8.1 – Feb 2015
- RSS-Gen Issue 4 – Nov 2014

EMISSION TEST	LIMITS			RESULTS (Comments)
	Frequency	Quasi-peak value (dB μ V)	Average value (dB μ V)	
Limits for conducted disturbance at mains ports 150kHz-30MHz CFR 47 §15.207	150-500kHz	66 to 56	56 to 46	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
	0.5-5MHz	56	46	
	5-30MHz	60	50	
Radiated emissions 9kHz-30MHz CFR 47 §15.209 (a) CFR 47 §15.225 RSS-Gen §4.9	Measure at 300m 9kHz-490kHz : 67.6dB μ V/m /F(kHz)			<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
	Measure at 30m 490kHz-1.705MHz : 87.6dB μ V/m /F(kHz) 1.705MHz-30MHz : 29.5 dB μ V/m			
Radiated emissions 30MHz-2GHz* CFR 47 §15.209 (a) CFR 47 §15.225 RSS-Gen §4.9 <i>Highest frequency : 390MHz (Declaration of provider)</i>	Measure at 3m 30MHz-88MHz : 40 dB μ V/m 88MHz-216MHz : 43.5 dB μ V/m 216MHz-960MHz : 46.0 dB μ V/m Above 960MHz : 54.0 dB μ V/m			<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
Fundamental field strength limit CFR 47 §15.225 RSS-210 §A2.6	Operation within the band 13.110-14.010 MHz			<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
Fundamental frequency tolerance CFR 47 §15.225 RSS-210 §A2.6	Operation within the band 13.110-14.010 MHz			<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
Band edge compliance CFR 47 §15.225 RSS-210 §A2.6	Operation within the band 13.110-14.010 MHz			<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
Occupied bandwidth RSS-Gen §4.6.1	No limit			<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL <input type="checkbox"/> NA <input type="checkbox"/> NP
Receiver Spurious Emission** RSS-Gen §4.10	See RSS-Gen §4.10			<input type="checkbox"/> PASS <input type="checkbox"/> FAIL <input checked="" type="checkbox"/> NA <input type="checkbox"/> NP

*§15.33: The highest internal source of a testing device is defined like more the highest frequency generated or used in the testing device or on which the testing device works or agrees.

- If the highest frequency of the internal sources of the testing device is lower than 108 MHz, measurement must be only performed until 1GHz.
- If the highest frequency of the internal sources of the testing device ranges between 108 MHz and 500 MHz, measurement must be only performed until 2GHz.
- If the highest frequency of the internal sources of the testing device ranges between 500 MHz and 1 GHz, measurement must be only performed until 5GHz.

If the highest frequency of the internal sources of the testing device is above 1 GHz, measurement must be only performed until 5 times the highest frequency or 40 GHz, while taking smallest of both.

**Testing covered the receive mode, and receiver spurious emissions are considered to be the same as transmitter.

2. SYSTEM TEST CONFIGURATION

2.1. HARDWARE IDENTIFICATION (EUT AND AUXILIARIES):

Equipment under test (EUT):

IUC160-01T3176A

Serial Number: 15232UN00000016



Photography of EUT


Power supply:

During all the tests, EUT is supplied by V_{nom} : 5VDC
For measurement with different voltage, it will be presented in test method.

Name	Type	Rating	Reference / Sn	Comments
Supply1	<input type="checkbox"/> AC <input checked="" type="checkbox"/> DC <input type="checkbox"/> Battery USB From Laptop	5V – 500mA	-	-

Inputs/outputs - Cable					
Access	Type	Length used (m)	Declared <3m	Shielded	Under test
Access1	USB power supply	2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Access2	COM0 RS232	2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Access3	SAM2	/	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Access4	SAM1	/	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Access5	μSD Card – MMC	/	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Access6	Wake Up (2 Wires)	0.3	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

Auxiliary equipment used during test			
Type	Reference	Sn	Comments
Laptop LENOVO	8896-2FG	L3-B7463	



**Equipment information:**

RF module:	NC		
Frequency band:	[13.553–13.567] MHz		
Sub-band REC7003:	Annexe g(f)		
RF mode:	<input type="checkbox"/> Transmitter	<input checked="" type="checkbox"/> Transceiver	<input type="checkbox"/> Receiver <input type="checkbox"/> Standby
Product class § 7.1.4	<input checked="" type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3
Receiver classification § 4.1.1	<input type="checkbox"/> 1	<input checked="" type="checkbox"/> 2	<input type="checkbox"/> 3
Antenna type:	<input type="checkbox"/> External:		<input checked="" type="checkbox"/> Internal:
Antenna gain:	NC		
Extreme temperature range:	<input checked="" type="checkbox"/> Category I (General) -20°C to +55°C Performed at -30°C to +70°C	<input type="checkbox"/> Category II (Portable) -10°C to +55°C	<input type="checkbox"/> Category III (Indoor) +5°C to +35°C
Extreme test source voltage:	<input type="checkbox"/> ±10%:		<input checked="" type="checkbox"/> other: 5V – 5.5Vdc

NC : Not communicated by customer

2.2. EUT RUNNING MODE

Firmware / Software version of EUT: Appli : App_Cem.

A continuous reading process is performed between EUT and Contact less Card through RFID Protocol.
A continuous Writing/reading process is performed between SAM card & EUT / also between MMC & EUT.

2.3. EQUIPMENT MODIFICATIONS

None Modification:

2.4. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follow:

$$FS = RA + AF + CF - AG$$

Where
 FS = Field Strength
 RA = Receiver Amplitude
 AF = Antenna Factor
 CF = Cable Factor
 AG = Amplifier Gain

Assume a receiver reading of 52.5dB μ V is obtained. The antenna factor of 7.4 and a cable factor of 1.1 are added. The amplifier gain of 29dB is subtracted, giving a field strength of 32 dB μ V/m.

$$FS = 52.5 + 7.4 + 1.1 - 29 = 32 \text{ dB}\mu\text{V/m}$$

The 32 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32\text{dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m.}$$

2.5. CALIBRATION DATE

The calibration intervals are extended at 12+2 months. This extended interval is based on the fact that there is sufficient calibration data to statistically establish a trend or based on experience of use of the test equipment to assure good measurement results for a longer period



3. CONDUCTED EMISSION DATA

3.1. ENVIRONMENTAL CONDITIONS

Date of test	September 30 th , 2015
Test performed by	Jonathan SARTO
Atmospheric pressure (hPa)	1001
Relative humidity (%)	36
Ambient temperature (°C)	21

3.2. TEST SETUP

Mains terminals


The EUT and auxiliaries are set:

- 80cm above the ground on the non-conducting table (Table-top equipment)
- 10cm above the ground on isolating support (Floor standing equipment)

The distance between the EUT and the LISN is 80cm. The EUT is 40cm away for the vertical ground plane.

The EUT is powered by V_{nom} .

The EUT is powered through a LISN (measure). Auxiliaries are powered by another LISN.



Test setup



3.3. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
Cable + self	-	-	A5329578	07/15	07/16
Conducted emission comb generator	BARDET	-	A3169049	-	-
LISN	RHODE & SCHWARZ	ENV216	C2320123	02/15	02/16
Receiver 20Hz – 8GHz	ROHDE & SCHWARZ	ESU8	A2642019	04/15	04/16
Thermo-hygrometer (PM2)	OREGON	BAR916HG-G	B4206011	09/15	09/16
Transient limiter	RHODE & SCHWARZ	ESH3-Z2	A7122204	11/14	11/15

3.4. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION

None Divergence:

3.5. TEST RESULTS

Mains terminals:

Supply1

Measurements are performed on the phase (L1) and neutral (N) of the power line.

Results: (PEAK detection)

Graph identifier	Line	Comments
Emc# 1	Phase	- See annex 1
Emc# 2	Neutral	- See annex 1
Emc# 3	Phase	Dummy load See annex 1
Emc# 4	Neutral	Dummy load See annex 1

3.6. CONCLUSION

The sample of the equipment IUC160-01T3176A Sn: 15232UN00000016, tested in the configuration presented in this test report satisfies to requirements of class B limits of the standard FCC Part15C, for conducted emissions.



4. RADIATED EMISSION DATA (15.209)

4.1. ENVIRONMENTAL CONDITIONS

Date of test	: September 18 th , 2015	September 21 st , 2015
Test performed by	: J.PAUC	J.PAUC
Atmospheric pressure (hPa)	: 990	991
Relative humidity (%)	: 46	44
Ambient temperature (°C)	: 22	21

4.2. TEST SETUP

The installation of EUT is identical for pre-characterization measures in a 3 meters semi- anechoic chamber and for measures on the 10 meters Open site.


The EUT and auxiliaries are set:

- 80cm above the ground on the non-conducting table (Table-top equipment) - Below 1GHz
- 150cm above the ground on the non-conducting table (Table-top equipment) - Above 1GHz
- 10cm above the ground on isolating support (Floor standing equipment)


The EUT is powered by V_{nom} .




Test setup on OATS – Worst case



Test setup in anechoic chamber (Pos XY) – setup <1GHz



Test setup in anechoic chamber (Pos Z) – setup <1GHz



Test setup in anechoic chamber (Pos XY) – setup >1GHz



Test setup in anechoic chamber (Pos Z) – setup >1GHz



4.3. TEST METHOD

Pre-characterisation measurement: (9kHz – 2GHz)

A pre-scan of all the setup has been performed in a 3 meters semi-anechoic chamber for frequency from 30MHz to 2GHz. Test is performed in horizontal (H) and vertical (V) polarization, the loop antenna was rotated during the test for maximized the emission measurement. Continuous linear turntable azimuth search was performed with 360 degrees range. Measurement performed on all axis of EUT used in normal configuration.

The pre-characterization graphs are obtained in PEAK detection and PEAK/AVERAGE from 1GHz to 2GHz.

Characterization on 10 meters open site from 9kHz to 1GHz:

The product has been tested according to ANSI C63.10, FCC part 15 subpart C. Radiated Emissions were measured on an open area test site. A description of the facility is on file with the FCC. The product has been tested at a distance of **10 meters** from the antenna and compared to the FCC part 15 subpart C §15.225 limits in the frequency range 13.553MHz 13.567MHz. Measurement bandwidth was 9kHz below 30MHz and 120kHz from 30 MHz to 1GHz. Test is performed in horizontal (H) and vertical (V) polarization, the loop antenna was rotated during the test for maximized the emission measurement. The height antenna is varied from 1m to 4m. Continuous linear turntable azimuth search was performed with 360 degrees range. Measurement performed on all axis of EUT used in normal configuration. A summary of the worst case emissions found in all test configurations and modes is shown.

Frequency list has been created with anechoic chamber pre-scan results.

Characterization on 3 meters full anechoic chamber from 1GHz to 2GHz:

The product has been tested at a distance of **3 meters** from the antenna and compared to the FCC part 15 subpart B §15.109 limits and C §15.209 limits. Measurement bandwidth was 1MHz from 1GHz to 2GHz.

Test is performed in horizontal (H) and vertical (V) polarization. Continuous linear turntable azimuth search was performed with 360 degrees range. Measurement performed on all axis of EUT used in normal configuration. A summary of the worst case emissions found in all test configurations and modes is shown. The height antenna is

- On mast, varied from 1m to 4m
- Fixed and centered on the EUT (EUT smaller than the beamwidth of the measurement antenna, ANSI C63.10 §6.6.5)

Frequency list has been created with anechoic chamber pre-scan results.



4.4. TEST EQUIPMENT LIST

Anechoic chamber					
DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
Antenna Bi-log	CHASE	CBL6111A	C2040172	06/15	06/17
Cable Measure @3m	-	-	A5329038	08/14	10/15
Cable Measure @3m	-	-	A5329206	04/15	04/16
Semi-Anechoic chamber #3	SIEPEL	-	D3044017	-	-
Spectrum analyzer	ROHDE & SCHWARZ	FSV 30	A4060050	01/15	01/16
Thermo-hygrometer (C3)	OREGON	BAR206	B4204078	04/15	04/16
Turntable chamber (Cage#3)	ETS Lindgren	Model 2165	F2000371	-	-
Table	LCIE	-	F2000461	-	-
Horn Antenna	EMCO	3115	C2042029	09/14	09/15
Amplifier 1-6GHz	HEWLETT PACKARD	-	A7085016	10/14	10/15

OATS					
DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
Antenna Bi-log	CHASE	CBL6111A	C2040051	04/14	04/16
Antenna Loop	ELECTRO-METRICS	EM-6879	C2040052	10/13	10/15
Cable	SUCOFLEX	106G	A5329061	03/15	03/16
Cable (OATS)	-	-	A5329623	10/14	10/15
Radiated emission comb generator	BARDET	-	A3169050	-	-
OATS	-	-	F2000409	09/14	09/15
Receiver 20Hz – 8GHz	ROHDE & SCHWARZ	ESU8	A2642019	04/15	04/16
Receiver 20-1000MHz	ROHDE & SCHWARZ	ESVS30	A2642006	05/15	05/16
Thermo-hygrometer (PM2)	OREGON	BAR916HG-G	B4206011	07/15	07/16
Antenna mast (OATS)	LCIE	-	F2000288	-	-
Turntable / Mast controller (OATS)	ETS Lindgren	Model 2066	F2000372	-	-
Antenna mast (OATS)	ETS Lindgren	2071-2	F2000392	-	-
Turntable (OATS)	ETS Lindgren	Model 2187	F2000403	-	-
Table	LCIE	-	F2000438	-	-

4.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION

None Divergence:

4.6. TEST RESULTS

4.6.1. Pre-characterization at 3 meters [9kHz-30MHz]

See graph for 9kHz-30MHz band:

Graph identifier	Polarization	EUT position	Comments
Emr# 1	0°	Axis XY	See annex 1
Emr# 2	90°	Axis XY	See annex 1

4.6.2. Pre-characterization at 3 meters [30MHz-1GHz]

See graphs for 30MHz-1GHz:

Graph identifier	Polarization	EUT position	Comments
Emr# 3	Vertical & Horizontal	Axis XY	See annex 1
Emr# 4	Vertical & Horizontal	Axis Z	See annex 1



4.6.3. Pre-characterization at 3 meters [1GHz-2GHz]

See graphs for 1GHz-2GHz:

Graph identifier	Polarization	EUT position	Comments
Emr# 5	Vertical & Horizontal	Axis XY	See annex 1
Emr# 6	Vertical & Horizontal	Axis Z	See annex 1

4.6.4. Characterization on 10 meters open site below 30 MHz

Worst case final data result:

Frequency list has been created with semi-anechoic chamber pre-scan results. Measurements are performed using a QUASI-PEAK detection.

No	Frequency (MHz)	QPeak Limit (dB μ V/m) @ 30m	Qpeak (dB μ V/m) @ 30m	Margin (Mes-Lim) (dB)	Angle Table (deg)	Pol Ant.	Ht Ant. (cm)	Correc. Factor (dB)	Comments
1	13.56	84	40.4	-43.6	96	90	100	35.1	-
2	27.119	29.5	14	-15.5	90	90	100	45.0	-

Note: Measure have been done at 10m distance and corrected according to requirements of 15.209.e) ($M@30m = M@10m - 19.1dB$)

Limits Sub clause §15.225

Frequency (MHz)	Field strength (μ V/m)	Measurement distance (m)
13.553-13.567	15 848 84 dB μ V/m	30
13.410-13.553 13.567-13.710	334 50.5 dB μ V/m	30
13.110-13.410 13.710-14.010	106 40.5 dB μ V/m	30

See following chapter of this test report for band edge measurements.



4.6.5. Characterization on 10 meters open site from 30MHz to 1GHz

Worst case final data result:

Frequency list has been created with semi-anechoic chamber pre-scan results. Measurements are performed using a QUASI-PEAK detection.

No	Frequency (MHz)	Limit QPeak (dBµV/m)	Measure QPeak (dBµV/m)	Margin QPeak (dB)	Angle Table (°)	Pol. Ant.	Ht. Ant. (cm)	FC (dB)	Remark
1	39.826	40.0	36.9	-3.1	154	V	100	14.4	/
2	40.678	40.0	33.4	-6.6	162	V	100	13.9	/
3	41.526	40.0	38.0	-2.0	143	V	100	13.5	/
4	42.852	40.0	33.3	-6.7	139	V	322	12.8	/
5	47.999	40.0	32.8	-7.2	9	V	100	10.3	/
6	59.995	40.0	32.1	-7.9	221	V	230	7.6	/
7	67.786	40.0	35.3	-4.7	274	V	250	7.8	/
8	96.328	43.5	29.8	-13.7	194	V	200	11.3	/
9	116.224	43.5	27.8	-15.7	153	V	150	13.4	/
10	209.64	43.5	32.3	-11.2	31	H	400	11.8	/
11	290.28	46.0	41.6	-4.4	320	H	343	16.2	/
12	483.82	46.0	43.3	-2.7	140	H	230	21.5	/
13	628.96	46.0	34.9	-11.1	31	H	183	24.4	/
14	870.876	46.0	38.8	-7.2	360	V	211	28.3	/

Note: Measure have been done at 10m distance and corrected according to requirements of 15.209.e)
($M@3m = M@10m + 10.5dB$)

4.6.6. Characterization on 3meters anechoic chamber from 1GHz to 2GHz

Worst case final data result:

The frequency list is created from the results obtained during the pre-characterization in anechoic chamber. Measurements are performed using a PEAK and AVERAGE detection.

No	Frequency (MHz)	Limit Peak (dBµV/m)	Measure Peak (dBµV/m)	Margin Peak (dB)	Limit Average (dBµV/m)	Measure Average (dBµV/m)	Margin Average (dB)	Angle Table (°)	Pol. Ant.	Ht. Ant. (cm)	FC (dB)	Remark
1	1957.150	74.0	55.7	-18.3	54.0	48.8	-5.2	94	V	100	29.4	/
2	1660.800	74.0	48.6	-25.4	54.0	38.3	-15.7	87	V	100	28.3	/
3	1451.540	74.0	44.4	-29.6	54.0	33.4	-20.6	98	V	100	27.4	/

Note: Measures have been done at 3m distance.

4.7. CONCLUSION

The sample of the equipment IUC160-01T3176A Sn: 15232UN00000016, tested in the configuration presented in this test report satisfies to requirements of class B limits of the standard FCC Part15B and C, for radiated emissions.



5. FUNDAMENTAL FREQUENCY TOLERANCE (15.225E)

5.1. ENVIRONMENTAL CONDITIONS

Date of test : September 28th, 2015
Test performed by : J.PAUC
Atmospheric pressure (hPa) : 999
Relative humidity (%) : 41
Ambient temperature (°C) : 22

5.2. TEST SETUP

Frequency of carrier: 13.56 MHz
Upper limit: 13.561356 MHz
Lower limit: 13.558644 MHz
The equipment (IUC 160) is set in a climatic chamber. Measure is performed on one channel of RF module.



Test setup

5.3. TEST METHOD

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency when the temperature is varied from -20°C to $+50^{\circ}\text{C}$ at the nominal power voltage and the primary power voltage is varied from 5 to 5.5Vdc of the rated supply voltage at 20°C .



5.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
Antenna Loop	LCIE	-	-	-	-
Cable Measure	-	40G	A5329653	12/14	12/15
Multimeter - CEM	FLUKE	87	A1240251	06/15	06/16
Power supply DC 300W / 150V-6A	SODILEC	7SDLIN/GB AUTO 300	A7043036	-	-
Thermo-hygrometer (PM2)	OREGON	BAR916HG-G	B4206011	07/15	07/16
Spectrum Analyzer 9kHz - 6GHz	ROHDE & SCHWARZ	FSL6	A2642020	07/14	09/15
Cable	MICRO-COAX	-	A5329653	04/15	04/16
Climatic chamber	BIA CLIMATIC	CL 6-25	D1022117	12/13	12/15

5.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION

None Divergence: According to USB recommendation : Voltage range is set from 5V to 5.5Vdc

EUT doesn't work at a voltage below 5Vdc

5.6. TEST RESULTS

Voltage	Temperature			
	-30°C	-20°C	20°C	+70°C
Mains voltage: 5Vdc (V_{nom})				
Frequency Drift (MHz)	+ 0.000083	+ 0.000051	REF	- 0.000073
Carrier level (dBc)	+ 2.00	+ 1.5	REF	+ 2.60
Mains voltage: 5.5Vdc (V_{max})				
Frequency Drift (MHz)	+ 0.000083	+ 0.000051	+ 0.000000	- 0.000073
Carrier level (dBc)	+ 3.00	+ 1.50	+ 0.00	+ 2.60

Frequency drift measured is **83Hz** when the temperature is varied from -30°C to +70°C and voltage is varied.

5.1. CONCLUSION

The sample of the equipment IUC160-01T3176A Sn: 15232UN00000016, tested in the configuration presented in this test report satisfies to requirements of the standard FCC Part15C, for fundamental frequency tolerance.



6. BAND-EDGE COMPLIANCE §15.209

6.1. ENVIRONMENTAL CONDITIONS

Date of test : September 28th, 2015
Test performed by : J.PAUC
Atmospheric pressure (hPa) : 999
Relative humidity (%) : 41
Ambient temperature (°C) : 22

6.2. TEST SETUP

For measurement, the power level calibration of the spectrum analyzer is related to the field strength measured in chapter radiated emission data.



Test setup

6.3. TEST METHOD

Frequency band 13.110-14.010MHz

Following plots show radiated emission level in the frequency band 13.110-14.010MHz with a RBW of 9kHz and a quasi-peak detector. The graphs are obtained with a measuring receiver.

Frequency band 13.553-13.567MHz

Following plots show radiated emission level in the frequency band 13.55.-13.567MHz with a RBW of 1kHz. The graphs are obtained with a measuring receiver.




6.4. TEST EQUIPMENT LIST

DESCRIPTION	MANUFACTURER	MODEL	N° LCIE	Cal_Date	Cal_Due
Antenna Loop	LCIE	-	-	-	-
Cable Measure	-	40G	A5329653	12/14	12/15
Multimeter - CEM	FLUKE	87	A1240251	06/15	06/16
Power supply DC 300W / 150V-6A	SODILEC	7SDLIN/GB AUTO 300	A7043036	-	-
Thermo-hygrometer (PM2)	OREGON	BAR916HG-G	B4206011	07/15	07/16
Spectrum Analyzer 9kHz - 6GHz	ROHDE & SCHWARZ	FSL6	A2642020	07/14	09/15
Cable	-	MICRO-COAX	A5329653	04/15	04/16
Climatic chamber	BIA CLIMATIC	CL 6-25	D1022117	12/13	12/15

6.5. DIVERGENCE, ADDITION OR SUPPRESSION ON THE TEST SPECIFICATION

None Divergence:

6.6. TEST RESULTS




6.7. CONCLUSION

The sample of the equipment IUC160-01T3176A, Sn: 15232UN00000016, tested in the configuration presented in this test report satisfies to requirements of the standard FCC Part15C, for band-edge compliance.



8. ANNEX 1 (GRAPHS)

RADIATED EMISSIONS			
Graph name:	Emr#1	Test configuration:	
Limit:	FCC CFR47 Part15C	Pre-characterisation - (0°) - (Worst case)	
Class:			
Frequency range: [9kHz - 30MHz]			
Antenna polarization:	Horizontal	RBW :	100kHz
Azimuth:	0° - 360°	VBW :	300kHz




Frequency (MHz)	Peak Level (dBµV/m)
13.55862	80.46



RADIATED EMISSIONS

Graph name:	Emr#2	Test configuration:
Limit:	FCC CFR47 Part15C	Pre-characterisation - (90°) - (Worst case)
Class:		
Frequency range: [9kHz - 30MHz]		
Antenna polarization:	Horizontal	RBW : 100kHz
Azimuth:	0° - 360°	VBW : 300kHz

- FCC/FCC CFR47 Part15C - Classe: - Moyenne/3.0m/
- FCC/FCC CFR47 Part15C - Classe: - QCrête/3.0m/
- FCC/FCC CFR47 Part15C - Classe: - Crête/3.0m/
- Mes.Peak (Horizontale)
- Peak (Peak/LimQ-Peak) (Horizontale)




Frequency (MHz)	Peak Level (dBµV/m)
0.827595	54.61
13.55862	65.27



RADIATED EMISSIONS

Graph name:	Emr#3	Test configuration:
Limit:	FCC CFR47 Part15C	(H+V) - Pos XY
Class:		
Frequency range: [30MHz - 1GHz]		
Antenna polarization:	Horizontal & Vertical	RBW : 100kHz
Azimuth:	0° - 360°	VBW : 300kHz




Frequency (MHz)	Peak Level (dBµV/m)
39.826	46.1
40.676	53.77
41.509	57.32
47.969	35.65
60.022	30.58
67.791	26.35
96.759	40.22
290.28	31.88
403.16	37.79
854.76	39.06
887	38.42
306.4	33.19
338.68	35.05
370.92	38.28
467.68	34.58
483.84	34.55
499.96	33.71
628.96	36.43



RADIATED EMISSIONS

Graph name:	Emr#4	Test configuration:	
Limit:	FCC CFR47 Part15C	(H+V) - Pos Z	
Class:			
Frequency range: [30MHz - 1GHz]			
Antenna polarization:	Horizontal & Vertical	RBW :	100kHz
Azimuth:	0° - 360°	VBW :	300kHz




Frequency (MHz)	Peak Level (dBµV/m)
39.826	45.26
40.676	52.44
41.526	58.31
42.852	42.33
48.02	34.33
59.988	30.53
67.791	26.23
96.759	36.11
116.224	30.41
241.88	31.8
870.88	44.59
967.64	40.11
209.64	31.73
290.28	37.07
483.84	38.9
628.96	36.49
661.2	35.79



RADIATED EMISSIONS

Graph name:	Emr#5	Test configuration:
Limit:	FCC CFR47 Part15B	(H+V) – Pos XY
Class:	B	
Frequency range: [1GHz - 2GHz]		
Antenna polarization:	Horizontal & Vertical	RBW : 1MHz
Azimuth:	0° - 360°	VBW : 3MHz




Spurious emissions

Frequency (MHz)	Peak Level (dBµV/m)	Position
1956.6	55.89	Polarisation horizontale
1956.8	55.97	Polarisation verticale
1451.6	47.45	Polarisation verticale
1659.7	49.65	Polarisation verticale



RADIATED EMISSIONS

Graph name:	Emr#6	Test configuration:
Limit:	FCC CFR47 Part15B	(H+V) – Pos Z
Class:	B	
Frequency range: [1GHz - 2GHz]		
Antenna polarization:	Horizontal & Vertical	RBW : 1MHz
Azimuth:	0° - 360°	VBW : 3MHz




Spurious emissions

Frequency (MHz)	Peak Level (dBµV/m)	Position
1956.6	54.13	Polarisation horizontale
1956.8	53.02	Polarisation verticale
1451.6	46.67	Polarisation verticale
1659.7	48.41	Polarisation verticale



CONDUCTED EMISSIONS		
Graph name:	Emc#1	Test configuration:
Limit:	EN 55022	Phase
Class:	B	
Frequency range: [150kHz - 30MHz]		
Voltage / Frequency:	110VAC / 60Hz	RBW : 10kHz
Line:	Phase	VBW : 30kHz




Spurious emissions

Frequency (MHz)	Mes.Peak (dBµV)	Mes.QPeak (dBµV)	LimQP (dBµV)	Mes.QPeak-LimQP (dB)	Mes.Avg (dBµV)	LimAvg (dBµV)	Mes.Avg-LimAvg (dB)
0.15	65	61.93	66	-4.07	40.23	56	-15.77
5.124	36.5	30.98	60	-29.02	21.68	50	-28.32
13.56	69.23	58.02	60	-1.98	29.42	50	-20.58
13.704	47.19	36.84	60	-23.16	25.12	50	-24.88
27.12	50.17	37.79	60	-22.21	33.66	50	-16.34



CONDUCTED EMISSIONS		
Graph name:	Emc#2	Test configuration:
Limit:	EN 55022	Neutral
Class:	B	
Frequency range: [150kHz - 30MHz]		
Voltage / Frequency:	110VAC / 60Hz	RBW : 10kHz
Line:	Neutre	VBW : 30kHz




Frequency (MHz)	Mes.Peak (dBµV)	Mes.QPeak (dBµV)	LimQP (dBµV)	Mes.QPeak-LimQP (dB)	Mes.Avg (dBµV)	LimAvg (dBµV)	Mes.Avg-LimAvg (dB)
0.15	64.89	61.49	66	-4.51	39	56	-17
0.398	46.22	40.08	57.9	-17.82	29.71	47.9	-18.18
4.248	37.18	32.38	56	-23.62	22.74	46	-23.26
13.56 *	69.28	66.92	60	6.92	58.31	50	8.31
13.704	46.7	35.38	60	-24.62	27.52	50	-22.48

* : RFID carrier frequency



CONDUCTED EMISSIONS		
Graph name:	Emc#3	Test configuration:
Limit:	EN 55022	Phase – Dummy load
Class:	B	
Frequency range: [150kHz - 30MHz]		
Voltage / Frequency:	110VAC / 60Hz	RBW : 10kHz
Line:	Phase	VBW : 30kHz




Frequency (MHz)	Mes.Peak (dBµV)	Mes.QPeak (dBµV)	LimQP (dBµV)	Mes.QPeak-LimQP (dB)	Mes.Avg (dBµV)	LimAvg (dBµV)	Mes.Avg-LimAvg (dB)
0.15	63.17	60.94	66	-5.06	39.75	56	-16.25
13.56	50.66	47.37	60	-12.63	41.54	50	-8.46



CONDUCTED EMISSIONS

Graph name:	Emc#4	Test configuration:	
Limit:	EN 55022	Neutral – Dummy load	
Class:	B		
Frequency range: [150kHz - 30MHz]			
Voltage / Frequency:	110VAC / 60Hz	RBW :	10kHz
Line:	Neutral	VBW :	30kHz



Frequency (MHz)	Mes.Peak (dBµV)	Mes.QPeak (dBµV)	LimQP (dBµV)	Mes.QPeak-LimQP (dB)	Mes.Avg (dBµV)	LimAvg (dBµV)	Mes.Avg-LimAvg (dB)
0.15	64.04	60.95	66	-5.05	38.73	56	-17.27
0.47	46.38	40.73	56.51	-15.78	27.7	46.51	-18.82
1.24	37.57	33.44	56	-22.56	22.53	46	-23.47
13.56	51.85	47.79	60	-12.21	41.86	50	-8.14



9. UNCERTAINTIES CHART

Type de mesure / Kind of measurement	Incertitude élargie laboratoire / Wide uncertainty laboratory (k=2) ± x	Incertitude limite du CISPR / CISPR uncertainty limit ± y
Mesure des perturbations conduites en tension sur le réseau d'énergie <i>Measurement of conducted disturbances in voltage on the power port</i>	3.57 dB	3.6 dB
Mesure des perturbations conduites en tension sur le réseau de télécommunication <i>Measurement of conducted disturbances in voltage on the telecommunication port.</i>	3.28 dB	A l'étude / Under consid.
Mesure des perturbations discontinues conduites en tension <i>Measurement of discontinuous conducted disturbances in voltage</i>	3.47 dB	3.6 dB
Mesure des perturbations conduites en courant <i>Measurement of conducted disturbances in current</i>	2.90 dB	A l'étude / Under consid.
Mesure du champ électrique rayonné sur le site en espace libre de Moirans <i>Measurement of radiated electric field on the Moirans open area test site</i>	5.07 dB	5.2 dB

Les valeurs d'incertitudes calculées du laboratoire étant inférieures aux valeurs d'incertitudes limites établies par la norme, la conformité de l'échantillon est établie directement par les niveaux limites applicables. / The uncertainty values calculated by the laboratory are lower than limit uncertainty values defined by the standard. The conformity of the sample is directly established by the applicable limits values.