

Test at TX 5180 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	5.96	dBm	INFO
Ref. Frequency	---	---	5187.590	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 5180 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5171.2088	MHz	INFO
T2 99%	---	---	5188.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.96 4.79 30
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.63	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.63	dBm	na
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	--	23.48	9.63	dBm	na



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.84	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.84	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:10:41
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5180 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	5.88	dBm	INFO
Ref. Frequency	---	---	5182.400	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.88 4.79 25
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5150.000000	---	5171.2088	MHz	PASS
T2 99%	---	5250.000000	5188.9411	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.2	MHz	INFO
T1 26dB	5150.000000	---	5170.0000	MHz	PASS
T2 26dB	---	5250.000000	5190.2000	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

Message with SA scan ~

Test References

TC Start	27.10.2022 21:11:40
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_1
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:11:42
Message	set WLAN5Gx to n_HT20_U_NII_1, Frequency [MHz] 5200 ,

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:13:16
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5200 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.27	dBm	INFO
Ref. Frequency	---	---	5207.590	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.27 4.8 30
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	12.07	dBm	INFO
Peak Power	---	---	16.106456	mW	INFO
Frequency at Peak	---	---	5204.995	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-1

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:13:46
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F., E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5200 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.21	dBm	INFO
Ref. Frequency	---	---	5207.590	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 5200 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.24	MHz	INFO
T1 26dB	---	---	5189.9200	MHz	INFO
T2 26dB	---	---	5210.1600	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.21 4.8 30
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.83	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.83	dBm	PASS
Limit: 11 dBm + 10 log 20.24					
Max Output Power DC corrected	--	24.06	9.83	dBm	na



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.73	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.73	dBm/1MHz	PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:15:30
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	ISED RSS247 -
Test Method	
TC Version	0.0.1
My Description	ISED Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5200 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.29	dBm	INFO
Ref. Frequency	---	---	5192.610	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 5200 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5191.2088	MHz	INFO
T2 99%	---	---	5208.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.29 4.8 30
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.72	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.72	dBm	na
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	--	23.48	9.72	dBm	na



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.73	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.73	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:17:13
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5200 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.20	dBm	INFO
Ref. Frequency	---	---	5202.800	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.20 4.8 25
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5150.000000	---	5191.2088	MHz	PASS
T2 99%	---	5250.000000	5208.9411	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.2	MHz	INFO
T1 26dB	5150.000000	---	5189.9500	MHz	PASS
T2 26dB	---	5250.000000	5210.1500	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

Message with SA scan ~

Test References

TC Start	27.10.2022 21:18:12
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_1
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:18:13
Message	set WLAN5Gx to n_HT20_U_NII_1, Frequency [MHz] 5240

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:21:44
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5240 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.31	dBm	INFO
Ref. Frequency	---	---	5232.410	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.31 4.81 30
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	12.14	dBm	INFO
Peak Power	---	---	16.368165	mW	INFO
Frequency at Peak	---	---	5244.845	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-1

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:22:14
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F, E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5240 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.11	dBm	INFO
Ref. Frequency	---	---	5247.790	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 5240 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.2	MHz	INFO
T1 26dB	---	---	5229.9600	MHz	INFO
T2 26dB	---	---	5250.1600	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.11 4.81 30
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.97	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.97	dBm	PASS
Limit: 11 dBm + 10 log 20.2					
Max Output Power DC corrected	--	24.05	9.97	dBm	na



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.56	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.56	dBm/1MHz	PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:23:57
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	ISED RSS247 -
Test Method	
TC Version	0.0.1
My Description	ISED Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5240 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.36	dBm	INFO
Ref. Frequency	---	---	5242.200	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 5240 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5231.2088	MHz	INFO
T2 99%	---	---	5248.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.36 4.81 30
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.86	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.86	dBm	na
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	--	23.48	9.86	dBm	na



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-1 Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.56	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.56	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

Test References

TC Start	27.10.2022 21:25:41
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-1
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5240 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.09	dBm	INFO
Ref. Frequency	---	---	5242.600	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.09 4.81 25
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5150.000000	---	5231.2088	MHz	PASS
T2 99%	---	5250.000000	5248.9411	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.15	MHz	INFO
T1 26dB	5150.000000	---	5230.0000	MHz	PASS
T2 26dB	---	5250.000000	5250.1500	MHz	DFS required

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-1

Message with SA scan ~

Test References

TC Start	27.10.2022 21:26:33
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_2A
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:26:34
Message	set WLAN5Gx to n_HT20_U_NII_2A, Frequency [MHz] 5260 ,

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:28:44
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5260 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.15	dBm	INFO
Ref. Frequency	---	---	5258.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.15 4.81 30
Start [MHz] Stop [MHz]	5235.000 5285.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	12.25	dBm	INFO
Peak Power	---	---	16.78804	mW	INFO
Frequency at Peak	---	---	5264.795	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-2A

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:29:15
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F, E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5260 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.24	dBm	INFO
Ref. Frequency	---	---	5258.000	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A 5260 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.24	MHz	INFO
T1 26dB	---	---	5249.9200	MHz	INFO
T2 26dB	---	---	5270.1600	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.24 4.81 30
Start [MHz] Stop [MHz]	5240.000 5280.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.97	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.97	dBm	PASS
Limit: 11 dBm + 10 log 20.24					
Max Output Power DC corrected	--	24.06	9.97	dBm	PASS



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.57	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.57	dBm/1MHz	PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:30:58
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	ISED RSS247 -
Test Method	
TC Version	0.0.1
My Description	ISED Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5260 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.39	dBm	INFO
Ref. Frequency	---	---	5252.610	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A 5260 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5251.2088	MHz	INFO
T2 99%	---	---	5268.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.39 4.81 30
Start [MHz] Stop [MHz]	5240.000 5280.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.87	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.87	dBm	PASS
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	--	23.48	9.87	dBm	PASS



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.57	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.57	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:32:42
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5260 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.24	dBm	INFO
Ref. Frequency	---	---	5263.000	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.24 4.81 25
Start [MHz] Stop [MHz]	5235.000 5285.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5250.000000	---	5251.2088	MHz	PASS since U-NII-1 is supported
T2 99%	---	5350.000000	5268.9411	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.25	MHz	INFO
T1 26dB	5250.000000	---	5249.9500	MHz	PASS since U-NII-1 is supported
T2 26dB	---	5350.000000	5270.2000	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

Message with SA scan ~

Test References

TC Start	27.10.2022 21:33:35
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_2A
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:33:36
Message	set WLAN5Gx to n_HT20_U_NII_2A, Frequency [MHz] 5280 ,

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:34:42
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	True Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5280 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.35	dBm	INFO
Ref. Frequency	---	---	5272.610	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.35 4.82 30
Start [MHz] Stop [MHz]	5255.000 5305.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	12.25	dBm	INFO
Peak Power	---	---	16.78804	mW	INFO
Frequency at Peak	---	---	5284.995	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-2A

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:35:13
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F, E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	True Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5280 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.51	dBm	INFO
Ref. Frequency	---	---	5272.610	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A 5280 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.24	MHz	INFO
T1 26dB	---	---	5269.9600	MHz	INFO
T2 26dB	---	---	5290.2000	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.51 4.82 30
Start [MHz] Stop [MHz]	5260.000 5300.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	10.05	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	10.05	dBm	PASS
Limit: 11 dBm + 10 log 20.24					
Max Output Power DC corrected	--	24.06	10.05	dBm	PASS



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.54	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.54	dBm/1MHz	PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:36:57
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	ISED RSS247 -
Test Method	
TC Version	0.0.1
My Description	ISED Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	True Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5280 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.44	dBm	INFO
Ref. Frequency	---	---	5282.600	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A 5280 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5271.2088	MHz	INFO
T2 99%	---	---	5288.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.44 4.82 30
Start [MHz] Stop [MHz]	5260.000 5300.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	---	---	9.95	dBm	INFO
Duty Cycle Correction	---	---	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	9.95	dBm	PASS
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	---	23.48	9.95	dBm	PASS



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.54	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.54	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:38:41
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	True Freq [MHz] 5280
Frequency high to test	False Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5280 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.37	dBm	INFO
Ref. Frequency	---	---	5272.410	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.37 4.82 25
Start [MHz] Stop [MHz]	5255.000 5305.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5250.000000	---	5271.2088	MHz	PASS since U-NII-1 is supported
T2 99%	---	5350.000000	5288.9411	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.25	MHz	INFO
T1 26dB	5250.000000	---	5269.9500	MHz	PASS since U-NII-1 is supported
T2 26dB	---	5350.000000	5290.2000	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

Message with SA scan ~

Test References

TC Start	27.10.2022 21:39:34
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_2A
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:39:35
Message	set WLAN5Gx to n_HT20_U_NII_2A, Frequency [MHz] 5320

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:40:47
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	True Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5320 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.35	dBm	INFO
Ref. Frequency	---	---	5312.610	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.35 4.82 30
Start [MHz] Stop [MHz]	5295.000 5345.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	12.35	dBm	INFO
Peak Power	---	---	17.179084	mW	INFO
Frequency at Peak	---	---	5325.095	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-2A

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:41:18
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F, E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	True Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5320 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	--	--	6.13	dBm	INFO
Ref. Frequency	--	--	5327.790	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	--	--	1	--	INFO
Duty Cycle max	--	--	0	dB	INFO
Duty Cycle (Burst Ratio) min	--	--	1	--	INFO
Duty Cycle min	--	--	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A 5320 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	--	--	20.32	MHz	INFO
T1 26dB	--	--	5309.9200	MHz	INFO
T2 26dB	--	--	5330.2400	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.13 4.82 30
Start [MHz] Stop [MHz]	5300.000 5340.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.97	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.97	dBm	PASS
Limit: 11 dBm + 10 log 20.32					
Max Output Power DC corrected	--	24.08	9.97	dBm	PASS



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.5	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.5	dBm/1MHz	PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:43:03
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	ISED RSS247 -
Test Method	
TC Version	0.0.1
My Description	ISED Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	True Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5320 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	5.88	dBm	INFO
Ref. Frequency	---	---	5321.400	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A 5320 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5311.2088	MHz	INFO
T2 99%	---	---	5328.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.88 4.82 30
Start [MHz] Stop [MHz]	5300.000 5340.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	9.86	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	9.86	dBm	PASS
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	--	23.48	9.86	dBm	PASS



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2A Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-1.5	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-1.5	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

Test References

TC Start	27.10.2022 21:44:47
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-2A
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5260
Frequency mid to test	False Freq [MHz] 5280
Frequency high to test	True Freq [MHz] 5320
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5320 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	6.31	dBm	INFO
Ref. Frequency	---	---	5321.800	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.31 4.82 25
Start [MHz] Stop [MHz]	5295.000 5345.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5250.000000	---	5311.2088	MHz	PASS since U-NII-1 is supported
T2 99%	---	5350.000000	5328.9411	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.25	MHz	INFO
T1 26dB	5250.000000	---	5309.9500	MHz	PASS since U-NII-1 is supported
T2 26dB	---	5350.000000	5330.2000	MHz	PASS

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2A

Message with SA scan ~

Test References

TC Start	27.10.2022 21:45:40
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_2C
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:45:41
Message	set WLAN5Gx to n_HT20_U_NII_2C, Frequency [MHz] 5500 ,

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-2C

Test References

TC Start	27.10.2022 21:47:31
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-2C
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5500
Frequency mid to test	False Freq [MHz] 5600
Frequency high to test	False Freq [MHz] 5700
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5500 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	4.27	dBm	INFO
Ref. Frequency	---	---	5492.410	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.27 4.79 30
Start [MHz] Stop [MHz]	5475.000 5525.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	9.94	dBm	INFO
Peak Power	---	---	9.862795	mW	INFO
Frequency at Peak	---	---	5505.145	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-2C

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C

Test References

TC Start	27.10.2022 21:48:02
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F, E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2C
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5500
Frequency mid to test	False Freq [MHz] 5600
Frequency high to test	False Freq [MHz] 5700
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5500 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	4.34	dBm	INFO
Ref. Frequency	---	---	5496.800	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C 5500 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.28	MHz	INFO
T1 26dB	---	---	5489.9200	MHz	INFO
T2 26dB	---	---	5510.2000	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.34 4.79 30
Start [MHz] Stop [MHz]	5480.000 5520.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	7.84	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	7.84	dBm	PASS
Limit: 11 dBm + 10 log 20.28					
Max Output Power DC corrected	--	24.07	7.84	dBm	PASS



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-3.67	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-3.67	dBm/1MHz	PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C

Test References

TC Start	27.10.2022 21:49:47
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	ISED RSS247 -
Test Method	
TC Version	0.0.1
My Description	ISED Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2C
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5500
Frequency mid to test	False Freq [MHz] 5600
Frequency high to test	False Freq [MHz] 5700
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5500 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	4.15	dBm	INFO
Ref. Frequency	---	---	5497.200	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C 5500 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.702	MHz	INFO
T1 99%	---	---	5491.2088	MHz	INFO
T2 99%	---	---	5508.9111	MHz	INFO



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C_BW


Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.15 4.79 30
Start [MHz] Stop [MHz]	5480.000 5520.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	7.74	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	7.74	dBm	PASS
Limit: 11 dBm + 10 log 17.702					
Max Output Power DC corrected	--	23.48	7.74	dBm	PASS



ISED RSS247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C Max OP and PSD

Power Spectral Density

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power Spectral Density	--	--	-3.67	dBm/1MHz	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Power Spectral Density DC corrected	--	11	-3.67	dBm/1MHz	PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2C

Test References

TC Start	27.10.2022 21:51:31
Ambit Temp [°C] Humidity [rel%]	27.4 44
System Version	3.3.1.6
Test Specification	FCC 15.407, ISED RSS247 -
Test Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
TC Version	0.0.1
My Description	FCC 15.407 Bandwidths - WLAN5Gx n-HT20 mode U-NII-2C
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5500
Frequency mid to test	False Freq [MHz] 5600
Frequency high to test	False Freq [MHz] 5700
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5500 MHz

RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	4.03	dBm	INFO
Ref. Frequency	---	---	5492.610	MHz	INFO


READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.03 4.79 25
Start [MHz] Stop [MHz]	5475.000 5525.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	1 2500 1001 SWE

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 99%	---	---	17.732	MHz	INFO
T1 99%	5470.000000	---	5491.2088	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5508.9411	MHz	

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2C 99PCT

Plot: Bandwidth within Band




FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2C

RESULT


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.25	MHz	INFO
T1 26dB	5470.000000	---	5489.9500	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5510.2000	MHz	

Plot: Bandwidth only



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2C 26dB

Plot: Bandwidth within Band



FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB ~ WLAN5Gx n-HT20 mode U-NII-2C

Message with SA scan ~

Test References

TC Start	27.10.2022 21:52:24
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	-
Test Method	
TC Version	0.0.1
My Description	Message with SA Scan n_HT20_U_NII_2C
Add. Information	

Test Parameter

Switched Path	EUT - SignalingUnit - SpectrumAnalyzer
Message start	27.10.2022 21:52:26
Message	set WLAN5Gx to n_HT20_U_NII_2C, Frequency [MHz] 5600 ,

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Common 5Gx 6Gx # Peak output power 3MHz/3MHz ~ WLAN5Gx n-HT20 mode U-NII-2C

Test References

TC Start	27.10.2022 21:53:42
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	Common 5Gx 6Gx - none
Test Method	
TC Version	0.0.1
My Description	Peak OP 3MHz/3MHz - WLAN5Gx n-HT20 mode U-NII-2C
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5500
Frequency mid to test	True Freq [MHz] 5600
Frequency high to test	False Freq [MHz] 5700
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5600 MHz

RESULT: Reference Power cond.


Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	4.38	dBm	INFO
Ref. Frequency	---	---	5602.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.38 4.85 30
Start [MHz] Stop [MHz]	5575.000 5625.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: Time [ms] Count Points per Section Type	300 20 1001 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Peak Power	---	---	10.19	dBm	INFO
Peak Power	---	---	10.447202	mW	INFO
Frequency at Peak	---	---	5605.095	MHz	INFO



Common 5Gx 6Gx # Peak output power 3MHz-3MHz ~ WLAN5Gx n-HT20 mode U-NII-2C

FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C

Test References

TC Start	27.10.2022 21:54:13
Ambit Temp [°C] Humidity [rel%]	27.3 44
System Version	3.3.1.6
Test Specification	FCC 15.247 -
Test Method	KDB789033 D02, F, E.2.e.
TC Version	0.0.1
My Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx n-HT20 mode U-NII-2C
Add. Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	1
User Interaction	No
Device Class UNII_1	Client

Test Parameter

Technology to test	WLAN5Gx n-HT20 mode
Antenna Port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5500
Frequency mid to test	True Freq [MHz] 5600
Frequency high to test	False Freq [MHz] 5700
Auto Control enabled Power Supply Climatic Box	No No
Additional Path Loss [dB]	1.4
Switched Path	EUT - SignalingUnit - SpectrumAnalyzer

Test Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1321.3008K40/101353,3.70
Switch matrix,Rohde&Schwarz,OSP-B157W8PLUS,1527.1144.05 / 100837,2.10.0.23

Test at TX 5600 MHz


RESULT: Reference Power cond.

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Ref. Power 1MHz/1MHz cond.	---	---	4.38	dBm	INFO
Ref. Frequency	---	---	5592.410	MHz	INFO

Evaluation max. Duty Cycle

Duty Cycle evaluation

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
No enough Bursts detected, Duty Cycle Burst Ratio set to 1					
Duty Cycle (Burst Ratio) max	---	---	1	---	INFO
Duty Cycle max	---	---	0	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	1	---	INFO
Duty Cycle min	---	---	0	dB	INFO




FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C 5600 MHz - DutyCycle

Evaluation Bandwidth

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Bandwidth 26dB	---	---	20.28	MHz	INFO
T1 26dB	---	---	5589.9600	MHz	INFO
T2 26dB	---	---	5610.2400	MHz	INFO



FCC 15.247 # Max output power and psd ~ WLAN5Gx n-HT20 mode U-NII-2C_BW

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.38 4.85 30
Start [MHz] Stop [MHz]	5580.000 5620.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: Time [ms] Count Points per Section Type	53700 1 161 SWE

RESULT

Test Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max Output Power	--	--	8.02	dBm	INFO
Duty Cycle Correction	--	--	0	dB	INFO
Limit absolute					
Max Output Power DC corrected	--	24	8.02	dBm	PASS
Limit: 11 dBm + 10 log 20.28					
Max Output Power DC corrected	--	24.07	8.02	dBm	PASS