

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM170800828103

Page: 1 of 6

SAR Evaluation Report

Application No.: SZEM1708008281CR

Applicant: SAKAR INTERNATIONAL INC.

Address of Applicant: 195 Carter Drive, Edison NJ 08817, USA.

Manufacturer: same as applicant

Address of Manufacturer: same as applicant

Equipment Under Test (EUT):

EUT Name: 5 IN 1 BLUETOOTH FITNESS TRACKER

 Model No.:
 TYL-5402

 FCC ID:
 XKK-TYL-5402

 Standards:
 47 CFR Part 1.1307

47 CFR Part 2.1093

KDB447498D01 General RF Exposure Guidance v06

 Date of Receipt:
 2017-08-04

 Date of Test:
 2017-08-10

 Date of Issue:
 2017-08-17

Test Result : Pass*

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions/rerms-en-Countinos/terms-en-Co

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM170800828103

Page: 2 of 6

2 Version

Revision Record									
Version Chapter		Date	Modifier	Remark					
01		2017-08-17		Original					

Authorized for issue by:		
	Brix Chen	
	Bill Chen /Project Engineer	
	Eric Fu	
	Eric Fu /Reviewer	



Report No.: SZEM170800828103

Page: 3 of 6

3 Contents

		Page
1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	GENERAL INFORMATION	4
	4.1 GENERAL DESCRIPTION OF EUT	5
	4.3 TEST FACILITY	5
	4.5 ABNORMALITIES FROM STANDARD CONDITIONS 4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5 SAR EVALUATION		6
	5.1 RF Exposure Compliance Requirement	6
	5.1.2 Limits	6



Report No.: SZEM170800828103

Page: 4 of 6

4 General Information

4.1 General Description of EUT

Product Name:	5 IN 1 BLUETOOTH FITNESS TRACKER		
Model No.:	TYL-5402		
Frequency Range:	2402MHz to 2480MHz		
Bluetooth Version:	V4.0 Signal mode		
Modulation Type:	GFSK		
Number of Channels:	40		
Sample Type:	Portable production		
Antenna Type:	Ceramic		
Antenna Gain:	5.05dBi		
Power supply:	Rechargeable battery:DC 3.7V 130mAh 0.481Wh(Charge by USB) Test voltage:AC 120V 60Hz		
Cable:	USB cable:57cm unshielded		



Report No.: SZEM170800828103

Page: 5 of 6

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



Report No.: SZEM170800828103

Page: 6 of 6

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation 17

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max Conducted Peak Output Power is	-4.15	dBm on the lowest channel	2.48	GHz
-4.15 dBm logarithmic terms convert to numer				
According to the formula. calculate the test ex				
[(max. power of channel, including tune-up tole				
(min. test separation distance, mm)] · [√f(GHz)]				
General RF Exposure = (0.38 mW / 5 mm) x	√2.48	GHz = 0.12	(1)	
SAR requirement:				
S = 3.0			(2)	
(1) < (2)				
So the SAR report is not required.				