



BUREAU  
VERITAS

Test Report No.: RF140319N033



Test Lab  
Cert 2951.01

## TEST REPORT



Applicant	MEDIALINK PRODUCTS LLC
Address:	1951 OLD CUTHBERT RD., STE 301 CHERRY HILL, NJ 08034-1411

Manufacturer or Supplier	Tranwo Technology Corp.
Address:	No.236, Sec. 3, Huanbei Rd., Jubei City, Hsinchu County 30265, Taiwan
Product	Travel Wi-Fi Router
Brand Name	MEDIALINK
Model	MWN-TR150N
Additional Model & Model Difference	N/A
Date of tests	May 24, 2013 ~ Jun. 20, 2013

The tests have been carried out according to the requirements of the following standard:

**FCC Part 15, Subpart C (Section 15.247)**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Venless Long Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	  Date: Mar. 24, 2014

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



## **TABLE OF CONTENTS**

RELEASE CONTROL RECORD..... 4

1 SUMMARY OF TEST RESULTS ..... 5

2 MEASUREMENT UNCERTAINTY ..... 5

3 GENERAL INFORMATION..... 6

3.1 GENERAL DESCRIPTION OF EUT..... 6

3.2 DESCRIPTION OF TEST MODES..... 7

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST ..... 8

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 8

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....11

3.4 DESCRIPTION OF SUPPORT UNITS.....11

4 TEST TYPES AND RESULTS ..... 12

4.1 CONDUCTED EMISSION MEASUREMENT ..... 12

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT ..... 12

4.1.2 TEST INSTRUMENTS..... 12

4.1.3 TEST PROCEDURES ..... 13

4.1.4 DEVIATION FROM TEST STANDARD ..... 13

4.1.5 TEST SETUP..... 14

4.1.6 EUT OPERATING CONDITIONS ..... 14

4.1.7 TEST RESULTS ..... 15

4.2 RADIATED EMISSION MEASUREMENT ..... 17

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT ..... 17

4.2.2 TEST INSTRUMENTS..... 18

4.2.3 TEST PROCEDURES ..... 19

4.2.4 DEVIATION FROM TEST STANDARD ..... 19

4.2.5 TEST SETUP..... 20

4.2.6 EUT OPERATING CONDITIONS ..... 20

4.2.7 TEST RESULTS ..... 21

4.3 6DB BANDWIDTH MEASUREMENT..... 35

4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT ..... 35

4.3.2 TEST INSTRUMENTS..... 35

4.3.3 TEST PROCEDURE..... 35

4.3.4 DEVIATION FROM TEST STANDARD ..... 35

4.3.5 TEST SETUP..... 36

4.3.6 EUT OPERATING CONDITIONS ..... 36



4.3.7	TEST RESULTS .....	37
4.4	CONDUCTED OUTPUT POWER .....	38
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT .....	38
4.4.2	TEST SETUP .....	38
4.4.3	TEST INSTRUMENTS .....	38
4.4.4	TEST PROCEDURES .....	39
4.4.5	DEVIATION FROM TEST STANDARD .....	39
4.4.6	EUT OPERATING CONDITIONS .....	39
4.4.7	TEST RESULTS .....	40
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	41
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	41
4.5.2	TEST SETUP .....	41
4.5.3	TEST INSTRUMENTS .....	41
4.5.4	TEST PROCEDURE .....	41
4.5.5	DEVIATION FROM TEST STANDARD .....	41
4.5.6	EUT OPERATING CONDITION .....	41
4.5.7	TEST RESULTS .....	42
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	43
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT .....	43
4.6.2	TEST SETUP .....	43
4.6.3	TEST INSTRUMENTS .....	43
4.6.4	TEST PROCEDURE .....	43
4.6.5	DEVIATION FROM TEST STANDARD .....	44
4.6.6	EUT OPERATING CONDITION .....	44
4.6.7	TEST RESULTS .....	45
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	49
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	50



**BUREAU  
VERITAS**

Test Report No.: RF140319N033

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130523N031	Original release	Jun. 21, 2013
RF140319N033	Base on the original report RF130523N031 change the applicant, manufacturer, brand name, product name, model and FCC ID.	Mar. 24, 2014



# 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.93dB at 2.8244MHz
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.9dB at 2390MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

# 2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.94dB
Radiated emissions	30MHz ~ 1GMHz	3.64dB
	1GHz ~ 18GHz	2.2dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Travel Wi-Fi Router
<b>MODEL NO.</b>	MWN-TR150N
<b>FCC ID</b>	XKP-MWNTR150N
<b>NOMINAL VOLTAGE</b>	120Vac / 60Hz
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>OPERATING FREQUENCY</b>	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
<b>PEAK POWER</b>	14.72 dBm (Maximum)
<b>ANTENNA TYPE</b>	Wire antenna with 3.5 dBi gain
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	N/A

**NOTE:**

1. The EUT incorporates a SISO function without beam forming.details refer to the following table:

MODULATION MODE	TX FUNCTION	RX FUNCTION
802.11b	1TX	1RX
802.11g	1TX	1RX
802.11n (HT20)	1TX	1RX
802.11n (HT40)	1TX	1RX

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. This report is issued for changing the applicant, manufacturer, brand name, product name, model and FCC ID base on the original report RF130523N031.



### 3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		



### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	<b>Adapter mode with WIFI function</b>

Where **RE<1G**: Radiated Emission below 1GHz      **RE≥1G**: Radiated Emission above 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

#### **RADIATED EMISSION TEST (BELOW 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
-	802.11n HT40	1 to 11	11	OFDM	BPSK	6.0	X





**RADIATED EMISSION TEST (ABOVE 1GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
-	802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0	X
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	X
-	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5	X
-	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	13.5	X

**POWER LINE CONDUCTED EMISSION TEST:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n HT40	1 to 11	11	OFDM	BPSK	6.0



**BANDEDGE MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
-	802.11n HT40	3 to 9	3, 9	OFDM	BPSK	13.5

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n HT20	1 to 11	1,6, 11	OFDM	BPSK	6.5
-	802.11n HT40	3 to 9	3,6, 9	OFDM	BPSK	13.5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	25deg. C, 60%RH	120Vac, 60Hz	Yuqiang Yin
RE≥1G	25deg. C, 60%RH	120Vac, 60Hz	Yuqiang Yin
PLC	25deg. C, 60%RH	120Vac, 60Hz	Bin Wei
APCM	25deg. C, 60%RH	120Vac, 60Hz	Venless Long



### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

- FCC Part 15, Subpart C (15.247)**
- 558074 D01 DTS Meas Guidance**
- ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	E6420	9H12FS1	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line :Unshielded, Detachable,1.0m;DC Line: Unshielded, Undetachable, 2.0m RJ45 cable: Unshielded, Detachable,10 m

**NOTE:** All power cords of the above support units are non shielded (1.8m).



## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU 26	100005	May 14,13	May 13,14
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	May 14,13	May 13,14
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	May 14,13	May 13,14
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

2. The test was performed in Shielding Room 553.



#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



#### 4.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
  - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: 802.11g-CH1

PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.27512	10.44	35.21	24.44	45.65	34.88	60.96	50.96	-15.31	-16.08
2	1.08058	9.99	41.91	30.8	51.9	40.79	56	46	-4.1	-5.21
3	1.73339	9.93	39.06	28.32	48.99	38.25	56	46	-7.01	-7.75
4	<b>2.82444</b>	<b>9.91</b>	<b>41.47</b>	<b>32.16</b>	<b>51.38</b>	<b>42.07</b>	<b>56</b>	<b>46</b>	<b>-4.62</b>	<b>-3.93</b>
5	5.43632	9.95	38.14	19.44	48.09	29.39	60	50	-11.91	-20.61
6	8.09903	10.01	32.11	16.18	42.12	26.19	60	50	-17.88	-23.81

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>PHASE</b>	Neutral	<b>6dB BANDWIDTH</b>	9kHz
--------------	---------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.31422	10.47	29.54	16.17	40.01	26.64	59.86	49.86	-19.85	-23.22
2	0.3846	10.46	29.84	15.87	40.3	26.33	58.18	48.18	-17.88	-21.85
3	0.68204	10.13	27.14	14.58	37.27	24.71	56	46	-18.73	-21.29
4	1.0884	9.85	38.07	25.85	47.92	35.7	56	46	-8.08	-10.3
5	2.75015	9.7	40.61	27.19	50.31	36.89	56	46	-5.69	-9.11
6	5.73348	9.84	30.12	17.54	39.96	27.38	60	50	-20.04	-22.62

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.







## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



### 4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Agilent	E4446A	MY46180622	Apr. 24,13	Apr. 23,14
EMI Test Receiver	Rohde&Schwarz	ESVD	847398/003	May 14,13	May 13,14
Bilog Antenna	Teseq	CBL 6111D	27089	Jul. 27, 13	Jul. 26, 14
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	Oct. 18, 12	Oct. 17, 14
Pre-Amplifier (9kHz~1GHz)	SONOMA	310D	186955	Mar. 05,14	Mar. 04,15
Pre-Amplifier (100MHz-26.5GHz)	Agilent	8449B	3008A00409	May 14,13	May 13,14
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8 .8m	NSEMC006	Jun. 11, 13	Jun. 10, 14
Digital Multimeter	FLUKE	15B	A1220010D G	Oct. 30, 13	Oct. 29, 14
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA91702 42	Feb. 13,14	Feb. 12,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,13	Nov. 03,14
Loop antenna (9kHz~30MHz)	Daze	ZN30900A	0708	Dec. 05,13	Dec. 04,14
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.
  2. The test was performed in Dongguan Chamber 10m.
  3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.
  4. The FCC Site Registration No. is 502831.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation



#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



**4.2.7 TEST RESULTS**


**BELOW 1GHz WORST-CASE DATA: 802.11g- CH11**

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
<b>NO.</b>	<b>FREQ. (MHz)</b>	<b>EMISSION LEVEL (dBuV/m)</b>	<b>LIMIT (dBuV/m)</b>	<b>MARGIN (dB)</b>	<b>ANTENNA HEIGHT (m)</b>	<b>TABLE ANGLE (Degree)</b>	<b>RAW VALUE (dBuV)</b>	<b>CORRECTION FACTOR (dB/m)</b>
1	165.80	35.1 QP	43.5	-8.4	1.11 H	184	22.98	12.16
2	208.48	33.2 QP	43.5	-10.3	1.65 H	105	22.86	10.35
3	233.70	34.2 QP	46.0	-11.9	1.42 H	138	21.84	12.31
4	278.32	40.9 QP	46.0	-5.1	1.59 H	0	25.60	15.31
5	796.30	40.0 QP	46.0	-6.0	1.90 H	67	12.74	27.25
6	914.64	40.5 QP	46.0	-5.5	2.18 H	25	10.93	29.54

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.52	36.0 QP	40.0	-4.0	1.50 V	66	17.09	18.95
2	96.20	40.7 QP	43.5	-2.8	1.50 V	126	29.51	11.19
3	144.71	35.8 QP	43.5	-7.7	1.50 V	104	22.97	12.84
4	191.60	34.1 QP	43.5	-9.4	1.50 V	61	23.38	10.69
5	479.43	31.7 QP	46.0	-14.3	1.50 V	124	10.98	20.74
6	840.02	33.1 QP	46.0	-12.9	1.50 V	83	5.81	27.28

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz DATA

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.4 PK	74.0	-24.6	1.00 H	184	12.15	37.25
2	2390.00	37.6 AV	54.0	-16.4	1.00 H	184	0.35	37.25
3	*2412.00	98.9 PK			1.00 H	184	61.61	37.29
4	*2412.00	95.1 AV			1.00 H	184	57.84	37.29
5	4824.00	55.5 PK	74.0	-18.5	1.00 H	43	13.87	41.63
6	4824.00	51.7 AV	54.0	-2.3	1.00 H	43	10.07	41.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.3 PK	74.0	-22.7	1.00 V	106	14.05	37.25
2	2390.00	40.5 AV	54.0	-13.5	1.00 V	106	3.25	37.25
3	*2412.00	98.5 PK			1.00 V	106	61.21	37.29
4	*2412.00	94.3 AV			1.00 V	106	57.00	37.29
5	4824.00	61.1 PK	74.0	-12.9	1.55 V	225	19.47	41.63
6	4824.00	50.7 AV	54.0	-3.3	1.55 V	225	9.07	41.63

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	99.4 PK			1.00 H	154	62.07	37.33
2	*2437.00	96.2 AV			1.00 H	154	58.87	37.33
3	4874.00	55.4 PK	74.0	-18.6	1.00 H	92	13.71	41.69
4	4874.00	50.4 AV	54.0	-3.6	1.00 H	92	8.71	41.69
5	7311.00	55.3 PK	74.0	-18.7	1.08 H	286	9.51	45.79
6	7311.00	41.6 AV	54.0	-12.4	1.08 H	286	-4.19	45.79
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	101.0 PK			1.00 V	27	63.67	37.33
2	*2437.00	98.4 AV			1.00 V	27	61.07	37.33
3	4874.00	55.5 PK	74.0	-18.5	1.00 V	245	13.81	41.69
4	4874.00	51.3 AV	54.0	-2.7	1.00 V	245	9.61	41.69
5	7311.00	54.5 PK	74.0	-19.5	1.13 V	142	8.71	45.79
6	7311.00	42.0 AV	54.0	-12.0	1.13 V	142	-3.79	45.79

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.





EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.5 PK			1.00 H	155	62.13	37.37
2	*2462.00	96.2 AV			1.00 H	155	58.83	37.37
3	2483.50	50.5 PK	74.0	-23.5	1.00 H	155	13.09	37.41
4	2483.50	39.0 AV	54.0	-15.0	1.00 H	155	1.59	37.41
5	4924.00	51.0 PK	74.0	-23.0	1.00 H	98	9.24	41.76
6	4924.00	47.2 AV	54.0	-6.8	1.00 H	98	5.44	41.76
7	7386.00	54.7 PK	74.0	-19.3	1.14 H	290	8.89	45.81
8	7386.00	41.5 AV	54.0	-12.5	1.14 H	290	-4.31	45.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.5 PK			1.00 V	29	62.13	37.37
2	*2462.00	97.0 AV			1.00 V	29	59.63	37.37
3	2483.50	49.7 PK	74.0	-24.3	1.00 V	29	12.29	37.41
4	2483.50	39.3 AV	54.0	-14.7	1.00 V	29	1.89	37.41
5	4924.00	54.4 PK	74.0	-19.6	1.00 V	247	12.64	41.76
6	4924.00	49.6 AV	54.0	-4.4	1.00 V	247	7.84	41.76
7	7386.00	55.3 PK	74.0	-18.7	1.00 V	148	9.49	45.81
8	7386.00	42.3 AV	54.0	-11.7	1.00 V	148	-3.51	45.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.4 PK	74.0	-27.6	1.00 H	158	9.15	37.25
2	2390.00	34.7 AV	54.0	-19.3	1.00 H	158	-2.55	37.25
3	*2412.00	90.4 PK			1.00 H	158	53.11	37.29
4	*2412.00	79.7 AV			1.00 H	158	42.41	37.29
5	4824.00	50.9 PK	74.0	-23.1	1.18 H	100	9.27	41.63
6	4824.00	38.0 AV	54.0	-16.0	1.18 H	100	-3.63	41.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	48.6 PK	74.0	-25.4	1.00 V	30	11.35	37.25
2	2390.00	35.5 AV	54.0	-18.5	1.00 V	30	-1.75	37.25
3	*2412.00	92.9 PK			1.00 V	30	55.61	37.29
4	*2412.00	87.7 AV			1.00 V	30	50.41	37.29
5	4824.00	56.3 PK	74.0	-17.7	1.00 V	239	14.67	41.63
6	4824.00	42.1 AV	54.0	-11.9	1.00 V	239	0.47	41.63

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	91.9 PK			1.00 H	160	54.57	37.33
2	*2437.00	81.5 AV			1.00 H	160	44.17	37.33
3	4874.00	50.8 PK	74.0	-23.2	1.07 H	94	9.11	41.69
4	4874.00	37.9 AV	54.0	-16.1	1.07 H	94	-3.79	41.69
5	7311.00	54.1 PK	74.0	-19.9	1.16 H	287	8.31	45.79
6	7311.00	43.5 AV	54.0	-10.5	1.16 H	287	-2.29	45.79
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	91.9 PK			1.00 V	28	54.57	37.33
2	*2437.00	82.3 AV			1.00 V	28	44.97	37.33
3	4874.00	50.2 PK	74.0	-23.8	1.00 V	251	8.51	41.69
4	4874.00	36.8 AV	54.0	-17.2	1.00 V	251	-4.89	41.69
5	7311.00	53.9 PK	74.0	-20.1	1.02 V	143	8.11	45.79
6	7311.00	40.8 AV	54.0	-13.2	1.02 V	143	-4.99	45.79

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	89.6 PK			1.00 H	151	52.23	37.37
2	*2462.00	79.3 AV			1.00 H	151	41.93	37.37
3	2483.50	48.5 PK	74.0	-25.5	1.00 H	151	11.09	37.41
4	2483.50	33.9 AV	54.0	-20.1	1.00 H	151	-3.51	37.41
5	4924.00	49.3 PK	74.0	-24.7	1.00 H	103	7.54	41.76
6	4924.00	36.8 AV	54.0	-17.2	1.00 H	103	-4.96	41.76
7	7386.00	53.8 PK	74.0	-20.2	1.08 H	294	7.99	45.81
8	7386.00	41.3 AV	54.0	-12.7	1.08 H	294	-4.51	45.81
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	90.6 PK			1.00 V	34	53.23	37.37
2	*2462.00	80.7 AV			1.00 V	34	43.33	37.37
3	2483.50	47.3 PK	74.0	-26.7	1.00 V	34	9.89	37.41
4	2483.50	34.4 AV	54.0	-19.6	1.00 V	34	-3.01	37.41
5	4924.00	50.5 PK	74.0	-23.5	1.04 V	256	8.78	41.76
6	4924.00	37.9 AV	54.0	-16.1	1.04 V	256	-3.86	41.76
7	7386.00	54.4 PK	74.0	-19.6	1.14 V	152	8.59	45.81
8	7386.00	41.3 AV	54.0	-12.7	1.14 V	152	-4.51	45.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.6 PK	74.0	-2.4	1.00 H	155	34.35	37.25
2	<b>2390.00</b>	<b>52.1 AV</b>	<b>54.0</b>	<b>-1.9</b>	<b>1.00 H</b>	<b>155</b>	<b>14.85</b>	<b>37.25</b>
3	*2412.00	101.4 PK			1.00 H	155	64.11	37.29
4	*2412.00	93.4 AV			1.00 H	155	56.11	37.29
5	4824.00	52.0 PK	74.0	-22.0	1.00 H	96	10.37	41.63
6	4824.00	40.1 AV	54.0	-13.9	1.00 H	96	-1.53	41.63
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.9 PK	74.0	-3.1	1.00 V	23	33.65	37.25
2	2390.00	50.6 AV	54.0	-3.4	1.00 V	23	13.35	37.25
3	*2412.00	102.1 PK			1.00 V	23	64.81	37.29
4	*2412.00	91.2 AV			1.00 V	23	53.91	37.29
5	4824.00	55.6 PK	74.0	-18.4	1.00 V	251	13.97	41.63
6	4824.00	42.3 AV	54.0	-11.7	1.00 V	251	0.67	41.63

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* " : Fundamental frequency.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.5 PK			1.00 H	160	63.17	37.33
2	*2437.00	85.9 AV			1.00 H	160	48.57	37.33
3	4874.00	51.8 PK	74.0	-22.2	1.02 H	97	10.11	41.69
4	4874.00	39.7 AV	54.0	-14.3	1.02 H	97	-1.99	41.69
5	7331.00	53.0 PK	74.0	-21.0	1.18 H	282	7.20	45.80
6	7331.00	40.8 AV	54.0	-13.2	1.18 H	282	-5.00	45.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	100.2 PK			1.00 V	32	62.87	37.33
2	*2437.00	91.1 AV			1.00 V	32	53.77	37.33
3	4874.00	53.9 PK	74.0	-20.1	1.00 V	249	12.21	41.69
4	4874.00	40.5 AV	54.0	-13.5	1.00 V	249	-1.19	41.69
5	7311.00	53.9 PK	74.0	-20.1	1.05 V	143	8.11	45.79
6	7311.00	40.9 AV	54.0	-13.1	1.05 V	143	-4.89	45.79

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	99.6 PK			1.00 H	149	62.23	37.37
2	*2462.00	90.7 AV			1.00 H	149	53.33	37.37
3	2483.50	69.5 PK	74.0	-4.5	1.00 H	149	32.09	37.41
4	2483.50	48.4 AV	54.0	-5.6	1.00 H	149	10.99	37.41
5	4924.00	51.3 PK	74.0	-22.7	1.06 H	89	9.54	41.76
6	4924.00	38.7 AV	54.0	-15.3	1.06 H	89	-3.06	41.76
7	7386.00	53.8 PK	74.0	-20.2	1.12 H	285	7.99	45.81
8	7386.00	41.2 AV	54.0	-12.8	1.12 H	285	-4.61	45.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	100.2 PK			1.00 V	28	62.83	37.37
2	*2462.00	90.4 AV			1.00 V	28	53.03	37.37
3	2483.50	68.3 PK	74.0	-5.7	1.00 V	28	30.89	37.41
4	2483.50	47.1 AV	54.0	-6.9	1.00 V	28	9.69	37.41
5	4924.00	50.6 PK	74.0	-23.4	1.00 V	253	8.84	41.76
6	4924.00	37.8 AV	54.0	-16.2	1.00 V	253	-3.96	41.76
7	7386.00	54.2 PK	74.0	-19.8	1.09 V	148	8.39	45.81
8	7386.00	41.2 AV	54.0	-12.8	1.09 V	148	-4.61	45.81

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* " : Fundamental frequency.



802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.5 PK	74.0	-12.5	1.00 H	148	24.25	37.25
2	2390.00	45.2 AV	54.0	-8.8	1.00 H	148	7.95	37.25
3	*2422.00	91.2 PK			1.00 H	148	53.90	37.30
4	*2422.00	84.5 AV			1.00 H	148	47.20	37.30
5	4844.00	49.5 PK	74.0	-24.5	1.15 H	105	7.84	41.66
6	4844.00	37.1 AV	54.0	-16.9	1.15 H	105	-4.56	41.66
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.5 PK	74.0	-9.5	1.00 V	31	27.25	37.25
2	2390.00	47.8 AV	54.0	-6.2	1.00 V	31	10.55	37.25
3	*2422.00	93.4 PK			1.00 V	31	56.10	37.30
4	*2422.00	85.1 AV			1.00 V	31	47.80	37.30
5	4844.00	48.9 PK	74.0	-25.1	1.04 V	247	7.24	41.66
6	4844.00	36.5 AV	54.0	-17.5	1.04 V	247	-5.16	41.66

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* " : Fundamental frequency.





CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	91.3 PK			1.00 H	152	53.97	37.33
2	*2437.00	81.4 AV			1.00 H	152	44.07	37.33
3	4874.00	50.1 PK	74.0	-23.9	1.00 H	93	8.41	41.69
4	4874.00	38.5 AV	54.0	-15.5	1.00 H	93	-3.19	41.69
5	7311.00	53.4 PK	74.0	-20.6	1.17 H	283	7.61	45.79
6	7311.00	40.8 AV	54.0	-13.2	1.17 H	283	-4.99	45.79

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	92.0 PK			1.00 V	35	54.67	37.33
2	*2437.00	82.4 AV			1.00 V	35	45.07	37.33
3	4874.00	49.8 PK	74.0	-24.2	1.00 V	255	8.11	41.69
4	4874.00	38.4 AV	54.0	-15.6	1.00 V	255	-3.29	41.69
5	7311.00	52.9 PK	74.0	-21.1	1.03 V	140	7.11	45.79
6	7311.00	40.5 AV	54.0	-13.5	1.03 V	140	-5.29	45.79

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	90.8 PK			1.00 H	154	53.44	37.36
2	*2452.00	81.4 AV			1.00 H	154	44.04	37.36
3	2483.50	60.7 PK	74.0	-13.3	1.00 H	154	23.29	37.41
4	2483.50	43.2 AV	54.0	-10.8	1.00 H	154	5.79	37.41
5	4904.00	49.8 PK	74.0	-24.2	1.07 H	99	8.07	41.73
6	4904.00	37.9 AV	54.0	-16.1	1.07 H	99	-3.83	41.73
7	7356.00	53.8 PK	74.0	-20.2	1.08 H	279	8.00	45.80
8	7356.00	41.2 AV	54.0	-12.8	1.08 H	279	-4.60	45.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	91.4 PK			1.00 V	32	54.04	37.36
2	*2452.00	80.8 AV			1.00 V	32	43.44	37.36
3	2483.50	58.5 PK	74.0	-15.5	1.00 V	32	21.09	37.41
4	2483.50	42.1 AV	54.0	-11.9	1.00 V	32	4.69	37.41
5	4904.00	49.1 PK	74.0	-24.9	1.00 V	258	7.37	41.73
6	4904.00	36.7 AV	54.0	-17.3	1.00 V	258	-5.03	41.73
7	7356.00	54.4 PK	74.0	-19.6	1.20 V	139	8.60	45.80
8	7356.00	41.6 AV	54.0	-12.4	1.20 V	139	-4.20	45.80

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* " : Fundamental frequency.



### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer (9KHz-40GHz)	Agilent	E4446A	MY46180622	Apr. 24,13	Apr. 23,14
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 30,13	Oct. 29,14

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

2. The test was performed in Oven room

#### 4.3.3 TEST PROCEDURE


1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation.



#### 4.3.5 TEST SETUP



#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



### 4.3.7 TEST RESULTS

#### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	12.18	0.5	PASS
6	2437	12.18	0.5	PASS
11	2462	12.19	0.5	PASS

#### 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.48	0.5	PASS
6	2437	16.42	0.5	PASS
11	2462	16.43	0.5	PASS

#### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.53	0.5	PASS
6	2437	17.46	0.5	PASS
11	2462	17.56	0.5	PASS

#### 802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	36.00	0.5	PASS
6	2437	36.18	0.5	PASS
9	2452	36.10	0.5	PASS




#### 4.4 CONDUCTED OUTPUT POWER

##### 4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

##### 4.4.2 TEST SETUP



##### 4.4.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	Anritsu	ML2495A	1139001	Nov. 04,13	Nov. 03,14
Power Sensor	Anritsu	MA2411B	1126068	Nov. 04,13	Nov. 03,14

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA
2. The test was performed in Oven room



#### 4.4.4 TEST PROCEDURES

A power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 EUT OPERATING CONDITIONS

Same as item 4.3.6.



#### 4.4.7 TEST RESULTS

##### 802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	10.75	13.12	30	PASS
6	2437	10.44	12.84	30	PASS
11	2462	10.99	12.86	30	PASS

##### 802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	6.73	13.77	30	PASS
6	2437	6.42	13.84	30	PASS
11	2462	6.78	14.21	30	PASS

##### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PEAK POWER (dBm)	POWER LIMIT (dBm)	PASS/FAIL
1	2412	5.90	13.84	30	PASS
6	2437	6.24	14.32	30	PASS
11	2462	6.48	14.65	30	PASS

##### 802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PEAK POWER (dBm)	POWER LIMIT (dBm)	PASS/FAIL
3	2422	6.23	14.62	30	PASS
6	2437	6.20	14.56	30	PASS
9	2452	6.27	14.72	30	PASS






## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

1. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
2. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
3. Use the peak marker function to determine the maximum amplitude level.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6



### 4.5.7 TEST RESULTS

#### 802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-14.84	8	PASS
6	2437	-14.90	8	PASS
11	2462	-15.41	8	PASS

#### 802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-13.12	8	PASS
6	2437	-12.88	8	PASS
11	2462	-16.17	8	PASS

#### 802.11n (20MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-19.52	8	PASS
6	2437	-19.18	8	PASS
11	2462	-18.90	8	PASS

#### 802.11n (40MHz)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-22.20	8	PASS
6	2437	-25.86	8	PASS
9	2452	-22.15	8	PASS




## 4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

### 4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

### 4.6.4 TEST PROCEDURE

#### Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



### **Measurement Procedure –Unwanted Emission Level**

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

#### **4.6.5 DEVIATION FROM TEST STANDARD**

No deviation.

#### **4.6.6 EUT OPERATING CONDITION**

Same as item 4.3.6




BUREAU VERITAS

Test Report No.: RF140319N033

### 4.6.7 TEST RESULTS

#### 802.11b



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China


Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



BUREAU VERITAS

Test Report No.: RF140319N033

### 802.11g



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)





BUREAU VERITAS



Test Report No.: RF140319N033

### 802.11n (20MHz)



#### CH 1



#### CH 6



#### CH 11



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)





BUREAU VERITAS



Test Report No.: RF140319N033

### 802.11n (40MHz)



#### CH 3



#### CH 6



#### CH 9



Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)





**BUREAU  
VERITAS**

Test Report No.: RF140319N033

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



**BUREAU  
VERITAS**

Test Report No.: RF140319N033

## **6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**