



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

Application No. : LL223014(1)

Client : Activision Publishing, Inc.
3100 Ocean Park Blvd.,
Santa Monica, CA 90405,
United States

Sample Description : One (1) submitted sample(s) stated to be PS3 "Tony Hawk: Ride" Skateboard Controller of Model No. 83783.790

Radio Frequency : 2404.4MHz ~ 2479.2MHz Transceiver

Rating : 4 x 1.5V AA size batteries

No. of submitted sample : Three (3) piece(s)

Date Received : 2009-07-10.

Test Period : 2009-07-15 to 2009-07-17.

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-08 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 12.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart C.

Remark : The receiver within the transceiver is subject to verification procedure.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : 

Mr. Wong Lap-Pong, Andrew
Assistant Manager
Electrical Division

Page 1 of 12

FCC ID: XLU83783790

This document is issued subject to CMA Testing standard TEARMS AND CONDITIONS, and shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

Table of Contents

1	General Information.....	3
1.1	General Description	3
1.2	Location of the test site.....	4
1.3	List of measuring equipment	5
2	Description of the radiated emission test.....	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
2.3	Radiated Emission Measurement Data (Con't)	8
3	Description of the Line-conducted Test	9
3.1	Test Procedure	9
3.2	Test Result	9
3.3	Graph and Table of Conducted Emission Measurement Data.....	9
4	Photograph	10
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	10
4.2	Photographs of the External and Internal Configurations of the EUT	10
5	Supplementary document	11
5.1	Band Edges	11
5.2	Duty cycle	11
5.3	Transmission time.....	11
6	Appendices	12



TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

1 General Information

1.1 General Description

The equipment under test (EUT) is a transceiver for PS3 “Tony Hawk: Ride” Skateboard Controller. It operates at 2404.4MHz ~ 2479.2MHz and the oscillation of MCU is generated by a crystal. The EUT is powered by 4 x 1.5V AA size batteries. There are eleven buttons on the skateboard. When the skateboard is synchronized with the dongle unit, the player can play the TV games.

The antenna is permanently attached in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

- MAR105 and associated circuit act as a RF module.
- MTF0241_TX and associated circuit act as a main processor.
- PIC18F24J10 and associated circuit act as an IR module.

FCC ID: XLU83783790

Page 3 of 12

This document is issued subject to CMA Testing standard TEARMS AND CONDITIONS, and shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AL027798-001

Date : 2009-08-13

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID: XLU83783790

Page 4 of 12

This document is issued subject to CMA Testing standard TEARMS AND CONDITIONS, and shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
Spectrum Analyzer	R&S	FSP30	100628	2009-09-23
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-531	2010-05-19
Broadband Pre-Amplifier	Schwarzbeck	BBV9718	9718-119	2010-05-08



TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Both Average and Peak Detector data were measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

The frequencies from fundamental up to the tenth harmonics were investigated. The emissions which lower than the radiated ambience were not reported. Thus, those highest emissions were presented in next pages.

It was found that the EUT meet the FCC requirement.



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Skateboard: Transmitter Mode with Peak Detector

	Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V)	Transducer Factor (dB/m)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
First Channel	2405.024	V	97.8	-6.8	91.0	114.0	-23.0
	#4810.062	H	52.1	1.0	53.1	74.0	-20.9
	7212.010	H	40.5	9.9	50.4	74.0	-23.6
	9620.030	V	38.4	12.8	51.2	74.0	-22.8

Middle Channel	2441.504	V	98.7	-6.8	91.9	114.0	-22.1
	#4882.980	H	53.1	1.0	54.1	74.0	-19.9
	#7324.490	V	40.6	9.9	50.5	74.0	-23.5
	9765.952	V	35.5	12.8	48.3	74.0	-25.7

Last Channel	2478.824	V	99.8	-6.8	93.0	114.0	-21.0
	#4957.628	V	52.5	1.0	53.5	74.0	-20.5
	#7436.362	H	41.7	9.9	51.6	74.0	-22.4
	9915.176	V	37.1	12.8	49.9	74.0	-24.1

Remark: Transducer Factor = Antenna Factor + Cable Loss - Gain of Pre-Amplifier

FCC ID: XLU83783790

Page 7 of 12

This document is issued subject to CMA Testing standard TEARMS AND CONDITIONS, and shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AL027798-001 Date : 2009-08-13

2.3 Radiated Emission Measurement Data (Con't)

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Skateboard: Transmitter Mode with Average Detector

	Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V)	Transducer Factor (dB/m)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
First Channel	2405.024	V	97.2	-6.8	90.4	94.0	-3.6
	#4810.062	H	50.9	1.0	51.9	54.0	-2.1
	7212.010	H	36.5	9.9	46.4	54.0	-7.6
	9620.030	V	32.1	12.8	44.9	54.0	-9.1

Middle Channel	2441.504	V	97.8	-6.8	91.0	94.0	-3.0
	#4882.980	H	51.4	1.0	52.4	54.0	-1.6
	#7324.490	V	35.8	9.9	45.7	54.0	-8.3
	9765.952	V	28.1	12.8	40.9	54.0	-13.1

Last Channel	2478.824	V	99.5	-6.8	92.7	94.0	-1.3
	#4957.628	V	50.4	1.0	51.4	54.0	-2.6
	#7436.362	H	36.6	9.9	46.5	54.0	-7.5
	9915.176	V	30.8	12.8	43.6	54.0	-10.4

Remark: Transducer Factor = Antenna Factor + Cable Loss - Gain of Pre-Amplifier

FCC ID: XLU83783790

Page 8 of 12



TEST REPORT

Report No. : AL027798-001

Date : 2009-08-13

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AL027798-001

Date : 2009-08-13

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho6.jpg.



TEST REPORT

Report No. : AL027798-001

Date : 2009-08-13

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Band Edges

The plots saved in TestRpt2.pdf show the first and last channels are confined in the specific band. It also shows that the band edges met 15.249(d) requirements at 2.4GHz and 2.4835GHz.

5.2 Duty cycle

Not Applicable

5.3 Transmission time

Not Applicable

FCC ID: XLU83783790

Page 11 of 12



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AL027798-001

Date : 2009-08-13

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	3	pages
A4.	ID Label/Location	1	page
A5.	Band Edges Plot	2	pages
A6.	Block Diagram	1	page
A7.	Schematics Diagram	3	pages
A8.	User Manual	1	page
A9.	Operation Description	1	page

***** End of Report *****

FCC ID: XLU83783790

Page 12 of 12

This document is issued subject to CMA Testing standard TEARMS AND CONDITIONS, and shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>