



www.nemko.com

Report number: **254061-2TRFWL**

Equipment Under Test: TRU7P8PWE/AC-WS


Applicant: TEKO Telecom Srl
Via Meucci, 24/a
I-40024 Castel S. Pietro Terme (BO)

FCC ID: XM2-EP7P8P

Test specification:

Title 47-Telecommunication
Chapter I - Federal Communications Commission
Subchapter D – Safety and special radio services
Part 90, Subpart S – Private land mobile services

– **Subpart I – General technical standards**

Reviewed by:  2014/03/27
Signature Date
P. Barbieri, Wireless/EMC Specialist

Reviewed by:  2014/03/27
Signature Date
G. Curioni, Wireless/EMC Specialist


Nemko S.p.A. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko S.p.A. accepts no responsibility for damages, if any suffered by any third party as a result of decisions made or actions based on this report.

This report shall not be reproduced except in full without the written approval of the testing laboratory.

Table of contents

Section 1: Report summary	3
Section 2: Equipment under test	4
2.1 Identification of equipment under test (EUT)	4
2.2 Accessories and support equipment	5
2.3 EUT description	6
2.4 Technical specifications of the EUT	6
2.5 EUT setup diagram.....	7
2.6 Operation of the EUT during testing	8
2.7 Modifications incorporated in the EUT	8
Section 3: Test conditions	9
3.1 Deviations from laboratory tests procedures.....	9
3.2 Test conditions, power source and ambient temperatures.....	9
3.3 Measurement uncertainty	9
3.4 Test equipment.....	10
Section 4: Result summary	11
4.1 FCC Part 90: Test results	11
Appendix A: Test results	12
Clause 90.205, 90.219(e)(1) Output power	12
Clause 90.209, 90.210(g), 90.210(h), 90.691, 90.219(e)(4) Occupied bandwidth	14
Clause 90.209, 90.210(g), 90.210(h), 90.691, 90.219(e)(3) Spurious emissions at the antenna terminal	16
Clause 90.219(e)(3) Field strength of spurious radiation	19
Clause 90.213 Frequency stability.....	24
Clause 90.214 Transient Frequency behaviour	26
Clause 90.219(e)(2) Noise Figure	27
Clause 935210 D02v02 (D.3)(i) Intermodulation	28
Clause 935219 D02v02 (D.3)(l) Filter frequency response	30
Appendix B: Block diagrams of test set-ups	31
Appendix C: Photo of set-ups	32

	Section 1: Report summary
	Report Number: 254061-2
	Specification: FCC 90

Section 1: Report summary

This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Italy SpA.

Test specification:
 FCC Part 90 Private land mobile services
 Subpart I – General technical standards

Compliance status:	Complies
Exclusions:	None
Non-compliances:	None
Report release history:	Original release
Test location:	Nemko Italy S.p.A. Via Carroccio, 4 I-20853 Biassono (Italy)
Registration number:	481407 (10 m Semi anechoic chamber)

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contain in this report are within Nemko Italy's ISO/IEC 17025 accreditation.

Nemko Italy SpA. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Italy SpA. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report

Section 2: Equipment under test

2.1 Identification of equipment under test (EUT)

The following information identifies the EUT under test:

Type of equipment:	Remote Unit
Product marketing name:	Teko Telecom Srl
Model number:	TRU7P8PWE/AC-WS
Serial number:	130848001
Nemko sample number:	-----
FCC ID:	XM2-EP7P8P
Date of receipt:	2014-03-03

2.2 Accessories and support equipment

The following information identifies accessories used to exercise the EUT during testing:

No other FCC-ID equipment are used to exercise the EUT during testing

Item # 1

Type of equipment:	Master Unit - Subrack
Brand name:	Teko Telecom srl
Model name or number:	SUB-TRX-PSU
Serial number:	101083001
Nemko sample number:	-----
Connection port:	-----
Cable length and type:	-----

Item # 2

Type of equipment:	Master Unit – Management Module
Brand name:	Teko Telecom srl
Model name or number:	TSPV-R
Serial number:	081900043
Nemko sample number:	-----
Connection port:	LAN port
Cable length and type:	-----

Item # 3

Type of equipment:	Master Unit – Optical Module
Brand name:	Teko Telecom srl
Model name or number:	TTRU4W-S-M
Serial number:	110679007
Nemko sample number:	-----
Connection port:	DL/UL RF connector (to connect to the base station) Optical port (to connect to remote unit)
Cable length and type:	-----

Item # 4

Type of equipment:	Master Unit – Power Supply
Brand name:	Teko Telecom srl
Model name or number:	TPSU/AC
Serial number:	100012286
Nemko sample number:	-----
Connection port:	-----
Cable length and type:	-----

	Section 2: Equipment under test
	Report Number: 254061-2
	Specification: FCC 90

Section 2: Equipment under test, continued

2.3 EUT description

See confidential block diagram and operational description

2.4 Technical specifications of the EUT

Operating band:	Down Link: 851–862 MHz, Up Link: 806-817 MHz
Operating frequency:	Wideband
Modulation type:	iDEN, FM
Occupied bandwidth:	Standard
Emission designator:	iDEN: D7W FM: F3E (Voice)
RF Output	Down Link: 31dBm (1,25W) Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
Gain	Down Link: 36dB Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
Antenna data:	No antenna provided
Antenna type:	No antenna provided External Antenna (Equipment that has an external 50 Ω RF connector)
Power source	100-240 Vac

Section 2: Equipment under test, continued

2.5 EUT setup diagram

In this system, Remote Unit is the EUT. Master Unit includes only management module and optical module (to convert RF signal in optical signal in down link direction and viceversa optical signal in RF signal in up link direction). As described in “Operational description”, master unit is connected directly to base station, so the system doesn’t use another equipment (under another FCC ID) to exercise the EUT. Signal generator is linked directly to the RF connector of optical module in the Master Unit.


Test setup for output power, occupied bandwidth, spurious emissions:



Procedure


Connect the signal modulated generator to the input of the EUT, so that the EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT.

Test setup for intermodulation:



Procedure

Connect two signal modulated generators to the input of the EUT, so that the two input signals are same level. The EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT. At maximum drive level, for each modulation applies two tones for fulfill two tests (high-band edge and low-band-edge)

Test setup for Noise figure:**Procedure**

Connect the EUT with the spectrum analyzer as described in the picture below. Connect the “Output Noise Source” spectrum analyzer with the RF input connector of the Remote Unit. Connect the output RF connector with the spectrum analyzer. Between spectrum analyzer and Remote Unit use a “Noise Source” (Test probe), so the noise of reference is generated. Set the EUT at max gain.

2.6 Operation of the EUT during testing

In down-link direction, normal working at max gain with max RF power output

2.7 Modifications incorporated in the EUT

None

There were no modifications performed to the EUT during this assessment

Section 3: Test conditions

3.1 Deviations from laboratory tests procedures

No deviations were made from laboratory test procedures.

3.2 Test conditions, power source and ambient temperatures

Normal temperature, humidity and air pressure test conditions	Temperature: 15–30 °C Relative humidity: 30–60 % Air pressure: 860–1060 hPa When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.
Power supply range:	The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages $\pm 5\%$, for which the equipment was designed.

Section 3: Test conditions, continued

3.3 Measurement uncertainty

Nemko S.p.A. measurement uncertainty has been calculated using the standard CISPR 16-4-2 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modeling – Uncertainty in EMC measurements“. All calculations have been performed to provide a confidence level of 95 % and can be found in Nemko S.p.A. document WML1002.

3.4 Test equipment

Client's property:

Identification number	Description	Manufacturer model	s/n	Cal. Due
1a	Vector Signal Generator	Agilent N5182A MXG	MY48180714	May 2015
1b	Vector Signal Generator	Agilent E4438C ESG	MY45094485	Ago 2016
2a	Spectrum Analyzer	Agilent E4440A	US40420470	May 2015
2b	Spectrum Analyzer	Agilent E9020A MXA	MY48011812	Ago 2015
3	Network Analyzer	Agilent E5071B	MY42301133	Ago 2016
4	Climatic chamber	Angelantoni Hygros 600	7237	Nov 2014
5	Noise Source	Agilent 346B	4124A17612	Ago 2014

Property of Nemko Italy:

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle months	Next cal.
Trilog Broad Band Antenna 25-2000 MHz	Schwarzbeck	VULB 9168	VULB 9168-242	36	02/2015
Trilog Broad Band Antenna 25-8000 MHz	Schwarzbeck	VULB 9162	VULB 9162-25	36	05/2015
Antenna 1-18 GHz	Schwarzbeck	STLP 9148	STPL 9148-123	36	02/2015
Double ridge waveguide horn	RFspin	DRH40	061106A40		08/2016
Preamplifier 18-40 GHz	Miteq	JS44	1648665		09/2014
Broadband preamplifier 1-18 GHz	Schwarzbeck	BBV 9718	9718-137	36	09/2014
EMI receiver 20 Hz ÷ 8 GHz	R&S	ESU8	100202	12	02/2015
EMI receiver 20 Hz ÷ 3 GHz	R&S	ESCI	100888	12	08/2014
Hydraulic revolving platform	Nemko	RTPL 01	4.233		NCR
Turning-table	R&S	HCT	835 803/03		NCR
Antenna mast	R&S	HCM	836 529/05		NCR
Controller	R&S	HCC	836 620/7		NCR
Spectrum Analyzer 9kHz ÷ 40GHz	R&S	FSEK	848255/005		08/2014
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530		08/2014
Shielded room	Siemens	10m control room	1947		NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	70		NCR
Shielded Room	Siemens	3m semi-anechoic chamber	3		NCR
Motor controller	Emco	1051-25	9012-1559		NCR
Motor controller	Emco	1061-1.521	9012-1508		NCR
Antenna Tower	Emco	2071-2	9601-1940		NCR
Controller pole/table	Emco	2090	9511-1099		NCR
V-Network	Rohde & Schwarz	ESH2-Z5	872 460/041	12	09/2014

Note: N/A = Not applicable, NCR = No cal required, COU = Cal on use

Section 4: Result summary

4.1 FCC Part 90: Test results

The column headed 'Required' indicates whether the associated clauses were invoked for the apparatus under test. The following abbreviations are used:

N	No : not applicable / not relevant.
Y	Yes : Mandatory i.e. the apparatus shall conform to these tests.
N/T	Not Tested, mandatory but not assessed. (See report summary)

Part	Test method	Test description	Required	Result
§90.205 §90.219(e)(1)	§2.1047	Output power	Y	Pass
§90.209, §90.210(g), §90.210(h), §90.691, §90.219(e)(4)	§2.1049	Occupied bandwidth	Y	Pass
§90.209, §90.210(g), §90.210(h), §90.691, §90.219(e)(4)	§2.1051	Spurious Emissions at the antenna terminal	Y	Pass
§90.219(e)(3)	§2.1053	Field strength of spurious radiation	Y	Pass
§90.213	§2.1055	Frequency stability	N	N/A a)
§90.214	--	Transient Frequency Behaviour		
§90.219(e)(2)	--	Noise Figure	Y	Pass
935210 D02v02 (D.3)(i)	--	Intermodulation	Y	Pass
935210 D02v02 (D.3)(l)	--	Out of Band Rejection (Filter Frequency Response)	Y	Pass

Notes:

- a) NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)

	Appendix A: Test Result
	Report Number: 254061-2
	Specification: FCC 90

Appendix A: Test results

Clause 90.205, 90.219(e)(1) Output power

90.205
 Applicants for licenses must request and use no more power than the actual power necessary for satisfactory operation. Except where otherwise specifically provided for, the maximum power that will be authorized to applicants whose license applications for new stations are filed after August 18, 1995 is as follows in FCC Part 90.205 (a) through (r).

90.219(e)(1)
 The output power capability of a signal booster must be designed for deployments providing a radiated power not exceeding 5 Watts ERP for each retransmitted channel.

Test date: [2014-03-07](#)
 Test results: [Pass](#)



Special notes
 Conducted measurement were performed:
 - The power was measured using spectrum analyzer with RMS detector / average power meter.

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB

Only conducted measurement at antenna connector was possible, no antenna provided by manufacturer

Test data

Direction	Modulation	Frequency (MHz)	RF output channel Power (dBm)	RF output channel Power (W)	PAR (dB)
Down-link	iDEN (25 kHz)	856.5	31.10	1.29	3,22
Down-link	FM	856.5	31.01	1.26	---


Mod. iDEN

Mod. FM
Test result

$$G_{\max} \text{ antenna gain (dBi)} = 39 - 31.10 = 7.90 \text{ dBi}$$

$$\text{EIRP} = 31.10 + 7.90 = 39 \text{ dBm}$$

$$\text{ERP} = 39 - 2.14 = 36.86 \text{ dBm} = 4.85 \text{ W} < 5 \text{ W ERP}$$

	Appendix A: Test Result
	Report Number: 254061-2
	Specification: FCC 90

Clause 90.209, 90.210(g), 90.210(h), 90.219(e)(4), 90.691 Occupied bandwidth

90.219(e)(4)
 A signal booster must be designed such that all signals that it retransmits meet the following requirements:

- (i) The signals are retransmitted on the same channels as received. Minor departures from the exact provider or reference frequencies of the input signals are allowed, *provided that* the retransmitted signals meet the requirements of § 90.213.
- (ii) There is no change in the occupied bandwidth of the retransmitted signals.
- (iii) The retransmitted signals continue to meet the unwanted emissions limits of § 90.210 applicable to the corresponding received signals (assuming that these received signals meet the applicable unwanted emissions limits by a reasonable margin).

Test date: [2014-03-07](#)
 Test results: [Pass](#)

Test data
 Resolution bandwidth was set wider or equal than occupied bandwidth.

Clause 90.210, 90.210(g), 90.210(h), 90.219(e)(3), 90.691 Spurious emissions at the antenna terminal

§ 90.210(g)

Emission Mask G. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(2) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB

§ 90.210(h)

Emission Mask H. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(5) On any frequency removed from the center of the authorized bandwidth by more than 25 kHz: At least $43 + \log (P)$ dB.

§ 90.219(e)(3)

Spurious emissions from a signal booster must not exceed -13 dBm within any 100 kHz measurement bandwidth.

§ 90.691

Emission mask requirements for EA-based systems.

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

§ 2.1051 Measurements required: Spurious emissions at antenna terminals.

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in §2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

Test date: [2014-03-07](#)


Test results: [Pass](#)

Special notes




Spurious emissions at antenna terminal:


Mod. iDEN (QAM)




9kHz-150kHz



150kHz-30MHz




30MHz-1GHz




1GHz-9GHz




Mod. FM




9kHz-150kHz



150kHz-30MHz




30MHz-1GHz




1GHz-9GHz




Mod. FM (Frequency band 806-809/851-854MHz)



Mask H



30MHz-1GHz



1GHz-9GHz

Clause 90.219(e)(3) Field strength of spurious radiation

§ 90.219(e)(3)

Spurious emissions from a signal booster must not exceed -13 dBm within any 100 kHz measurement bandwidth.

§ 2.1053 Measurements required: Field strength of spurious radiation.

(a) Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of §2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.

(b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:


- (1) Those in which the spurious emissions are required to be 60 dB or more below the mean power of the transmitter.
- (2) All equipment operating on frequencies higher than 25 MHz.
- (3) All equipment where the antenna is an integral part of, and attached directly to the transmitter.
- (4) Other types of equipment as required, when deemed necessary by the Commission.

Test date: 2014-03-07

Test results: **Pass**

Special notes

- The spectrum was searched from 30 MHz to the 10th harmonic.
- The EUT was measured on three orthogonal axis.
- All measurements were performed at a distance of 3 m.
- Only the worst data presented in the test report.

	Appendix A: Test Result
	Report Number: 254061-2
	Specification: FCC 90

Field Strength of spurious radiation, continued

Test data, continued


Test Data

The D.U.T. was positioned according to the radiated emissions set-up


The D.U.T. antenna connector was terminated by a 50 Ω shielded dummy load.

The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) & 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.


There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.




30MHz-1GHz – H Pol



30MHz-1GHz – V Pol



1GHz-18GHz – H Pol



1GHz-18GHz – V Pol

Clause 90.213 Frequency stability

Unless noted elsewhere, transmitters used in the services governed by this part must have a minimum frequency stability as specified in the following table.

Frequency range (MHz)	Fixed and base stations	Mobile stations	
		Over 2 W output power	2 W or less output power
Below 25	100	100	200
25–50	20	20	50
72–76	5	–	50
150–174	50	5	50
216–220	1.0	–	1.0
220–222	0.1	1.5	1.5
421–512	2.5	5	5
806–809	1.0	1.5	1.5
809–824	1.5	2.5	2.5
851–854	1.0	1.5	1.5
854–869	1.5	2.5	2.5
896–901	0.1	1.5	1.5
902–928	2.5	2.5	2.5
929–930	1.5	–	–
935–940	0.1	1.5	1.5
1427–1435	300	300	300
Above 2450	–	–	–

The units are in ppm

Test date:

Test results:

NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)

Special notes

Clause 90.213 Frequency stability, continued

Test data, continued

Down-link

Conditions	Frequency (Hz)	Offset (ppm)
+50 °C, Nominal power		
+40 °C, Nominal power		
+30 °C, Nominal power		
+20 °C, +15 % power		
+20 °C, Nominal power		
+20 °C, -15 % power		
+10 °C, Nominal power		
0 °C, Nominal power		
-10 °C, Nominal power		
-20 °C, Nominal power		
-30 °C, Nominal power		

Offset calculation: $\frac{F_{Measured} - F_{reference}}{F_{reference}} \times 1 \cdot 10^6$

Maximum frequency drift is kHz

Clause 90.214 Transient frequency behaviour

Transmitters designed to operate in the 150–174 MHz and 421–512 MHz frequency bands must maintain transient frequencies within the maximum frequency difference limits during the time intervals indicated:

Time Intervals	Maximum frequency difference	All equipment	
		150 to 174 MHz	421 to 512 MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels			
t1	±25.0 kHz	5.0 ms	10.0 ms
t2	±12.5 kHz	20.0 ms	25.0 ms
t3	±25.0 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels			
t1	±12.5 kHz	5.0 ms	10.0 ms
t2	±6.25 kHz	20.0 ms	25.0 ms
t3	±12.5 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels			
t1	±6.25 kHz	5.0 ms	10.0 ms
t2	±3.125 kHz	20.0 ms	25.0 ms
t3	±6.25 kHz	5.0 ms	10.0 ms

Test date: [NA](#)

Test results: -----

Special notes

[NOT APPLICABLE: different operating band](#)

Clause 90.219(e)(2) Noise Figure

§ 90.219(e)(2)

The noise figure of a signal booster must not exceed 9 dB in either direction.


Test date: [2014-03-07](#)

Test results: [Pass](#)

Special notes

In the Remote Unit, only up-link measurement can be performed (test probe is connect to antenna port)

Test data



Clause 935210 D02v02 Appendix D.3 (i) Intermodulation

Intermodulation – Test all modulation types [TDMA, CDMA, and FM (covers GSM and F1D)]

- (1) For part 90 boosters, apply the requirements of § 90.219(d) and (e).
- (2) For other boosters:
 - (i) CW signal rather than typical signal is acceptable (for FM).
 - (ii) At maximum drive level, for each modulation: one test with three tones, or two tests (high-band edge, low- band edge) with two tones
 - (iii) Limit usually is -13 dBm conducted.
 - (iv) Not needed for Single Channel systems.
 - (v) Combination of modulation types not needed.

Test date: [2014-03-07](#)


Test results: [Pass](#)

Clause 935210 D02v02 (D.3)(I) Out of band rejection

Out of Band Rejection – Test for rejection of out of band signals.
Filter frequency response plots are acceptable.


Test date: 2014-03-07

Test results: **Pass**



Appendix B: Block diagrams of test set-ups

Radiated emissions set-up



Appendix C: EUT photos

Photo Set up





Photo EUT





Appendix A: Test Result

Report Number: **254061-2**

Specification: FCC 90

Label EUT



WARNING. This is NOT a CONSUMER device. This is a 90.219 Class B signal booster. It is designed for installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENSE or express consent of an FCC Licensee to operate this device. You MUST register Class B signal boosters (as defined in 47 CFR 90.219) online at www.fcc.gov/signal-boosters/registration. Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$100,000 for each continuing violation.