



### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density  
P = power input to the antenna  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>29.03</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>799.834255</u>	(mW)
Antenna gain(maximum):	<u>13</u>	(dBi)
Maximum antenna gain:	<u>19.95262315</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>50</u>	(cm)
Prediction frequency:	<u>851</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>0.567</u>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.507984</b>	(mW/cm <sup>2</sup> )
Margin of compliance:	<b>-0.5</b>	(dB)
This equates to:	<b>5.079841097</b>	<b>W/m<sup>2</sup></b>



### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density  
P = power input to the antenna  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>29.03</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>799.834255</u>	(mW)
Antenna gain(maximum):	<u>15</u>	(dBi)
Maximum antenna gain:	<u>31.6227766</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>50</u>	(cm)
Prediction frequency:	<u>1710</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000</u>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.805101</b>	(mW/cm <sup>2</sup> )
Margin of compliance:	<b>-0.9</b>	(dB)
This equates to:	<b>8.051005574</b>	<b>W/m<sup>2</sup></b>



### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density  
P = power input to the antenna  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>29.03</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>799.834255</u>	(mW)
Antenna gain(maximum):	<u>15</u>	(dBi)
Maximum antenna gain:	<u>31.6227766</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>50</u>	(cm)
Prediction frequency:	<u>1850</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000</u>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.805101</b>	(mW/cm <sup>2</sup> )
Margin of compliance:	<b>-0.9</b>	(dB)
This equates to:	<b>8.051005574</b>	<b>W/m<sup>2</sup></b>



### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density  
P = power input to the antenna  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>29.03</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>799.834255</u>	(mW)
Antenna gain(maximum):	<u>15</u>	(dBi)
Maximum antenna gain:	<u>31.6227766</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>50</u>	(cm)
Prediction frequency:	<u>1930</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000</u>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.805101</b>	(mW/cm <sup>2</sup> )
Margin of compliance:	<b>-0.9</b>	(dB)
This equates to:	<b>8.051005574</b>	<b>W/m<sup>2</sup></b>



### Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density  
P = power input to the antenna  
G = power gain of the antenna in the direction of interest relative to an isotropic radiator  
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>29.03</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>799.834255</u>	(mW)
Antenna gain(maximum):	<u>15</u>	(dBi)
Maximum antenna gain:	<u>31.6227766</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>50</u>	(cm)
Prediction frequency:	<u>2110</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000</u>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.805101</b>	(mW/cm <sup>2</sup> )
Margin of compliance:	<b>-0.9</b>	(dB)
This equates to:	<b>8.051005574</b>	<b>W/m<sup>2</sup></b>