





Report Reference ID:	332502-10TRFWL
----------------------	----------------

Test specification:	Title 47 – Telecommunication Chapter I – Federal Communications Commission Subchapter B – Common carrier services Part 27 – Miscellaneous wireless communications services
---------------------	---

Applicant:	TEKO Telecom Srl. Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
Apparatus:	Medium Power Remote Unit
Model:	TRM7E8AE19HAWX23AT
FCC ID:	XM2-MP6B

Testing laboratory:	<b>Nemko Italy Spa</b> Via del Carroccio, 4 20853 Biassono (MB) – Italy Telephone: +39 039 2201201 Facsimile: +39 039 2201221
---------------------	---

	Name and title	Date
Tested by:	 G. Curioni, Wireless/EMC Specialist	06/29/2017
Reviewed by:	 P. Barbieri, Wireless/EMC Specialist	06/29/2017

**Nemko Spa, 20853 Biassono (MB) - Italy. All rights reserved.**

This publication may be reproduced in whole for non-commercial purposes as long as Nemko Spa is acknowledged as copyright owner and source of the material. Nemko Spa takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This test report may not be partially reproduced, except with the prior written permission of Nemko Spa. The test report merely corresponds to the test sample. The phase of sampling / collection of equipment under test is carried out by the customer.

This Test Report, when bearing the Nemko name and logo is only valid when issued by a Nemko laboratory, or by a laboratory having special agreement with Nemko.

Table of contents

<b>Section 1: Report summary</b> .....	<b>4</b>
1.1 Test specification .....	4
1.2 Statement of compliance .....	4
1.3 Exclusions .....	4
1.4 Registration number .....	4
1.5 Test report revision history .....	4
1.6 Limits of responsibility .....	4
<b>Section 2: Summary of test results</b> .....	<b>5</b>
2.1 FCC Part 27, test results .....	5
<b>Section 3: Equipment under test (EUT) and application details</b> .....	<b>6</b>
3.1 Applicant details .....	6
3.2 Modular equipment .....	6
3.3 Product details .....	6
3.4 Application purpose .....	6
3.5 Composite/related equipment .....	7
3.6 Sample information .....	7
3.7 EUT technical specifications .....	7
3.8 Accessories and support equipment .....	8
3.9 Operation of the EUT during testing .....	9
3.10 EUT setup diagram .....	9
<b>Section 4: Engineering considerations</b> .....	<b>10</b>
4.1 Modifications incorporated in the EUT .....	10
4.2 Deviations from laboratory tests procedures .....	10
4.3 Technical judgment .....	10
<b>Section 5: Test conditions</b> .....	<b>11</b>
5.1 Deviations from laboratory tests procedures .....	11
5.2 Test conditions, power source and ambient temperatures .....	11
5.3 Measurement uncertainty .....	12
5.4 Test equipment .....	12
<b>Appendix A: Test results</b> .....	<b>13</b>
Clause 935210 D05v01 (3.2) AGC threshold .....	13
Clause 935210 D05v01 (3.3) Out of band rejection .....	14
Clause 27.53(h)(3) Occupied bandwidth .....	15
Clause 27.50(d) Peak output power at RF antenna connector .....	17
Clause 27.53(h) Spurious emissions at RF antenna connector .....	20

Clause 27.53(h) Radiated Spurious emissions.....	25
<b>Appendix B: Block diagrams of test set-ups .....</b>	<b>35</b>
<b>Appendix C: EUT Photos.....</b>	<b>36</b>

## Section 1: Report summary

### 1.1 Test specification

<b>Specifications</b>	<b>Part 27 – Miscellaneous wireless communications services</b>
-----------------------	---

### 1.2 Statement of compliance

<b>Compliance</b>	<p>In the configuration tested the EUT was found compliant                  Yes <input checked="" type="checkbox"/> No <input type="checkbox"/></p> <p>This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Canada Inc. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 27. Radiated tests were conducted in accordance with ANSI C63.4-2003.</p>
-------------------	--

### 1.3 Exclusions

<b>Exclusions</b>	None
-------------------	------

### 1.4 Registration number

<b>Test site FCC ID number</b>	176392 (3 m Semi anechoic chamber)
--------------------------------	------------------------------------

### 1.5 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued
R1TRF	---

### 1.6 Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. Nemko Spa authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## Section 2: Summary of test results

2.1 FCC Part 27, test results			
Part	Methods	Test description	Verdict
	§ 935210 D05v01r01 (3.2)	AGC threshold	Pass
	§ 935210 D05v01r01 (3.3)	Out of band rejection	Pass
§27.53(h)(3)	§ 935210 D05v01r01 (3.4)	Occupied bandwidth	Pass
§27.50(d)	§ 935210 D05v01r01 (3.5)	Peak output power at RF antenna connector	Pass
§27.53(h)	§ 935210 D05v01r01 (3.6)	Spurious emissions at RF antenna connector	Pass
§27.53(h)	§ 935210 D05v01r01 (3.8)	Radiated spurious emissions	Pass
§27.54	§ 935210 D05v01r01 (3.7)	Frequency stability	N/A a)
<p>Notes:</p> <p style="padding-left: 40px;">a) NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)</p>			

## Section 3: Equipment under test (EUT) and application details

### 3.1 Applicant details

<b>Applicant complete business name</b>	Name:	Teko Telecom Srl
	Federal Registration Number (FRN):	0018963462
	Grantee code	XM2
<b>Mailing address</b>	Address:	Via Meucci, 24/a
	City:	Castel S. Pietro Terme
	Province/State:	Bologna
	Post code:	40024
	Country:	Italy

### 3.2 Modular equipment

<b>a) Single modular approval</b>	Single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Limited single modular approval</b>	Limited single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

### 3.3 Product details

<b>FCC ID</b>	Grantee code:	XM2
	Product code:	-MP6B
<b>Equipment class</b>	B2I	
<b>Description of product as it is marketed</b>	Booster	
	Model name/number:	TRM7E8AE19HAWX23AT
	Serial number:	1007061001

### 3.4 Application purpose

<b>Type of application</b>	<input checked="" type="checkbox"/> Original certification <input type="checkbox"/> Change in identification of presently authorized equipment Original FCC ID: _____ Grant date: _____ <input type="checkbox"/> Class II permissive change or modification of presently authorized equipment
----------------------------	--

Section 3: Equipment under test

3.5 Composite/related equipment

<b>a) Composite equipment</b>	The EUT is a composite device subject to an additional equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Related equipment</b>	The EUT is part of a system that operates with, or is marketed with, another device that requires an equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>c) Related FCC ID</b>	If either of the above is "yes": <input type="checkbox"/> has been granted under the FCC ID(s) listed below: <input type="checkbox"/> is in the process of being filled under the FCC ID(s) listed below: <input type="checkbox"/> is pending with the FCC ID(s) listed below: <input type="checkbox"/> has a mix of pending and granted statuses under the FCC ID(s) listed below: i FCC ID: ii FCC ID:

3.6 Sample information

<b>Receipt date:</b>	06/26/2017
<b>Nemko sample ID number:</b>	-----

3.7 EUT technical specifications

<b>Operating band:</b>	Down Link: 2180–2200 MHz
<b>Operating frequency:</b>	Wideband
<b>Modulation type:</b>	CDMA, WCDMA, LTE (QAM and QPSK)
<b>Occupied bandwidth:</b>	CDMA: 1,25 MHz, WCDMA: 5 MHz LTE: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz
<b>Channel spacing:</b>	standard
<b>Emission designator:</b>	CDMA, WCDMA: F9W, LTE: D7W
<b>RF Output</b>	Down Link: 33dBm (2W) Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Gain</b>	Down Link: 38dB Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Antenna type:</b>	External Antenna is not provided, equipment that has an external 50 Ω RF connector
<b>Power source:</b>	100-240 Vac

Section 3: Equipment under test

**3.8 Accessories and support equipment**  
 The following information identifies accessories used to exercise the EUT during testing:

Item # 1	
Type of equipment:	Master Unit - Subrack
Brand name:	Teko Telecom srl
Model name or number:	SUB-TRX-PSU
Serial number:	101083001
Nemko sample number:	-----
Connection port:	-----
Cable length and type:	-----
Item # 2	
Type of equipment:	Master Unit – Management Module
Brand name:	Teko Telecom srl
Model name or number:	TSPV-R
Serial number:	110942253
Nemko sample number:	-----
Connection port:	LAN port
Cable length and type:	-----
Item # 3	
Type of equipment:	Master Unit – Optical Module
Brand name:	Teko Telecom srl
Model name or number:	TTRU4W-S-M
Serial number:	110679007
Nemko sample number:	-----
Connection port:	DL/UL RF connector (to connect to the base station) Optical port (to connect to remote unit)
Cable length and type:	-----
Item # 4	
Type of equipment:	Master Unit – Power Supply
Brand name:	Teko Telecom srl
Model name or number:	TPSU/AC
Serial number:	081063004
Nemko sample number:	-----
Connection port:	-----
Cable length and type:	-----




3.9 Operation of the EUT during testing	
<b>Details:</b>	In down-link direction, normal working at max gain with max RF power output.

### 3.10 EUT setup diagram

In this system, Remote Unit is the EUT. Master Unit includes only management module and optical module (to convert RF signal in optical signal in down link direction and viceversa optical signal in RF signal in up link direction). As described in “Operational description”, master unit is connected directly to base station, so the system doesn’t use another equipment (under another FCC ID) to exercise the EUT. Signal generator is linked directly to the RF connector of optical module in the Master Unit.

**Test setup for output power, occupied bandwidth, spurious emissions:**



```

graph LR
    A[Signal modulated Generator] --> B[EUT]
    B --> C[Spectrum Analyzer]
    
```

**Procedure**  
 Connect the signal modulated generator to the input of the EUT, so that the EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT.

## Section 4: Engineering considerations

### 4.1 Modifications incorporated in the EUT

<b>Modifications</b>	Modifications performed to the EUT during this assessment None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> , performed by Client <input type="checkbox"/> or Nemko <input type="checkbox"/> Details:
----------------------	---

### 4.2 Deviations from laboratory tests procedures

<b>Deviations</b>	Deviations from laboratory test procedures None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> - details are listed below:
-------------------	---

### 4.3 Technical judgment

<b>Judgment</b>	None
-----------------	------

## Section 5: Test conditions

### 5.1 Deviations from laboratory tests procedures

No deviations were made from laboratory test procedures.

### 5.2 Test conditions, power source and ambient temperatures

<p>Normal temperature, humidity and air pressure test conditions</p>	<p>Temperature: 15–30 °C          Relative humidity: 20–75 %          Air pressure: 86–106 kPa</p> <p>When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.</p>
<p>Power supply range:</p>	<p>The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages <math>\pm 5\%</math>, for which the equipment was designed.</p>

Section 5: Test conditions, continued

5.3 Measurement uncertainty

Nemko S.p.A. measurement uncertainty has been calculated using the standard CISPR 16-4-2 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modeling – Uncertainty in EMC measurements“. All calculations can be found in Nemko S.p.A. document WML1002.

5.4 Test equipment

Equipment	Manufacturer	Model No.	Asset/Serial No.	Next cal.
Vector Signal Generator	Agilent	N5172B EXG	MY53051238	Jan 2018
Vector Signal Generator	Agilent	E4438C ESG	MY45094485	Ago 2019
Spectrum Analyzer	Agilent	N9030A PXA	MY53120882	Nov 2017
Network Analyzer	Agilent	E5071C ENA	MY46106183	Ago 2017
V-network	R & S	ESH2-Z5	872 460/041	10/2017
Trilog Broad Band Antenna 25-2000 MHz	Schwarzbeck	VULB 9168	VULB 9168-242	06/2018
Trilog Broad Band Antenna 25-8000 MHz	Schwarzbeck	VULB 9162	VULB 9162-25	07/2018
Antenna 1-18 GHz	Schwarzbeck	STLP 9148	STPL 9148-123	06/2018
Antenna horn	A.H.System Inc.	SAS-574	061106A40	10/2017
Preamplifier 18-40 GHz	Miteq	JS44	1648665	12/2017
Broadband preamplifier 1-18 GHz	Schwarzbeck	BBV 9718	9718-137	12/2017
EMI receiver 20 Hz ÷ 8 GHz	R&S	ESU8	100202	04/2018
EMI receiver 20 Hz ÷ 3 GHz	R&S	ESCI	100888	08/2017
Hydraulic revolving platform	Nemko	RTPL 01	4.233	NCR
Turning-table	R&S	HCT	835 803/03	NCR
Antenna mast	R&S	HCM	836 529/05	NCR
Controller	R&S	HCC	836 620/7	NCR
Spectrum Analyzer 9kHz ÷ 40GHz	R&S	FSEK	848255/005	01/2018
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530	10/2018
Shielded room	Siemens	10m control room	1947	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	70	NCR
Shielded Room	Siemens	3m semi-anechoic chamber	3	NCR
Motor controller	Emco	1051-25	9012-1559	NCR
Motor controller	Emco	1061-1.521	9012-1508	NCR
Antenna Tower	Emco	2071-2	9601-1940	NCR
Controller pole/table	Emco	2090	9511-1099	NCR

Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use  
 (\*) Equipment supplied by manufacturer's

## Appendix A: Test results

### Clause 935210 D05v01 (3.2) AGC threshold


Measure of EUT AGC Threshold

Test date: [06/28/2017](#)  
 Test results: [Pass](#)


Special notes

- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)

### Test data



**AWGN signal, nominal input signal**



**AWGN signal, nominal input signal +1 dB**


Clause 935210 D05v01 (3.3) Out of band rejection

Out of Band Rejection – Test for rejection of out of band signals.

Test date: 06/28/2017  
 Test results: Pass

Special notes  
 –

Test data



### Clause 27.53(h)(3) Occupied bandwidth

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Test date: 06/28/2017

Test results: Pass


### Special notes

- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)


Clause 27.53(h)(3) Occupied bandwidth, continued

Test data

AWGN signal, nominal input signal




Output




Input

AWGN signal, nominal input signal + 3dB



Output



Input



### Clause 27.50(d) Peak output power at RF antenna connector

**§ 27.50(d) The following power and antenna height requirements apply to stations transmitting in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz and 2180-2200 MHz bands:**

- (2) The power of each fixed or base station transmitting in the 1995-2000 MHz, the 2110-2155 MHz 2155-2180 MHz band, or 2180-2200 MHz band and situated in any geographic location other than that described in paragraph (d)(1) of this section is limited to:
  - (i) An equivalent isotropically radiated power (EIRP) of 1640 watts when transmitting with an emission bandwidth of 1 MHz or less;
  - (ii) An EIRP of 1640 watts/MHz when transmitting with an emission bandwidth greater than 1 MHz.
- (5) Equipment employed must be authorized in accordance with the provisions of §24.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (d)(6) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
- (8) A licensee operating a base or fixed station in the 2180-2200 MHz band utilizing a power greater than 1640 watts EIRP and greater than 1640 watts/MHz EIRP must be coordinated in advance with all AWS licensees authorized to operate on adjacent frequency blocks in the 2180-2200 MHz band.

Test date: [06/28/2017](#)

Test results: [Pass](#)

#### Special notes



- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)

Clause 27.50(d) Peak output power at RF antenna connector

Test data

AWGN signal, nominal input signal


Test data						
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	RF output Power (W/MHz)	PAR (dB)
Down-link	AWGN (LTE, 5MHz)	2190.0	33.08	2.032	0.41	10.72



PAR measure is performed by the “CCDF” function installed on Spectrum analyzer that provides average power (the same measured with “Channel power” function), peak power and PAR.

**AWGN signal, nominal input signal + 3dB**

Test data					
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	RF output Power (W/MHz)
Down-link	AWGN (LTE, 5MHz)	2190.0	33.77	2.38	0.48



## Clause 27.53(h) Spurious emissions at RF antenna connector

(h) AWS emission limits:

(1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

(3) Measurement procedure.

(i) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(ii) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(iii) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

Test date: [06/28/2017](#)

Test results: [Pass](#)

### Special notes

- Broadband amplifiers: AWGN test signal used (5 MHz LTE channel)

Clause 27.53 (h) Spurious emissions at RF antenna connector, continued

Test data

**See Plots below**


Spurious emissions measurement results:

Frequency (MHz)	Spurious emission (dBm)	Limit (dBm)	Margin (dB)
Low channel			
First channel	Negligible	-13	
Mid channel			
2190 MHz	Negligible	-13	
High channel			
Last channel	Negligible	-13	


Test data: spurious emissions at antenna terminal

**AWGN signal**


(Plots are referred to modulated carrier at the Middle Channel)




**9kHz-150kHz**



**150kHz-30MHz**




**30MHz-1GHz**




**1GHz-22GHz**

Test data, continued: band edges Inter modulation

AWGN signal, nominal input signal




Low Band Edge




High Band Edge

**AWGN signal, nominal input signal + 3dB**



**Low Band Edge**



**High Band Edge**



## Clause 27.53(h) Radiated Spurious emissions

(h) AWS emission limits:

(1) General protection levels. Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

(2) Additional protection levels. Notwithstanding the foregoing paragraph (h)(1) of this section:

(i) Operations in the 2180-2200 MHz band are subject to the out-of-band emission requirements set forth in §27.1134 for the protection of federal government operations operating in the 2200-2290 MHz band.

(3) Measurement procedure.

(i) Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(ii) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(iii) The measurements of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

Test date: [06/26/2017](#)

Test results: [Pass](#)

### Special notes

Clause 27.53(h) Radiated spurious emissions, continued

Test data

The D.U.T. was positioned according to the radiated emissions set-up

The D.U.T. antenna connector was terminated by a 50 Ω shielded dummy load.


The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) & 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.

There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.

Spurious emissions measurement results:


Frequency (MHz)	Polarization. V/H	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low channel				
Mid channel				
High channel				

Note: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.




Date: 26.JUN.2017 16:17:37

### 30MHz-1GHz – H Pol




Date: 26.JUN.2017 16:16:17

**30MHz-1GHz – V Pol**




Date: 26.JUN.2017 11:13:03

**1GHz-18GHz – H Pol**




Date: 26.JUN.2017 11:10:03

**1GHz-18GHz – V Pol**



Date: 26.JUN.2017 15:38:09

**18GHz-24GHz – H Pol**



Date: 26.JUN.2017 15:35:43


**18GHz-24GHz – V Pol**




Test data, continued: Radiated Spurious emissions, band 2200-2290MHz

Special notes

For AWS-4 operations, the power of any emissions on all frequencies between 2200-2290MHz shall not exceed an EIRP of -100.6 dBW/4 kHz  
 -100.6 dBW/4 kHz = -70.6 dBm/4 kHz  
 -70.6 dBm/4 kHz = -46.6 dBm/1MHz



Date: 26.JUN.2017 11:49:09  
**2200MHz-2290MHz – H Pol**




Date: 26.JUN.2017 11:45:47


2200MHz-2290MHz - V Pol

## Appendix B: Block diagrams of test set-ups

### Radiated emissions set-up



### Substitution method set-up



## Appendix C: EUT Photos

### Photo Set up





Photo EUT



