

<b>Report Reference ID:</b>	372837-10TRFWL
-----------------------------	----------------

<b>Test specification:</b>	Title 47 – Telecommunication Chapter I – Federal Communications Commission Subchapter A – General Part 24 – Personal Communication Services Subpart D – Narrowband PCS
----------------------------	--



<b>Applicant:</b>	TEKO Telecom Srl. Via Meucci, 24/a I-40024 Castel S. Pietro Terme (BO) (Italy)
-------------------	--

<b>Apparatus:</b>	Medium Power Remote Unit
-------------------	--------------------------

<b>Model:</b>	TRU7FL8P9PWM/AC-WT
---------------	--------------------

<b>FCC ID:</b>	XM2-MP7FL8P9PP
----------------	----------------

<b>Testing laboratory:</b>	<b>Nemko Italy Spa</b> Via del Carroccio, 4 20853 Biassono (MB) – Italy Telephone: +39 039 2201201 Facsimile: +39 039 2201221
----------------------------	---

	Name and title	Date
<b>Tested by:</b>	 P. Barbieri, Wireless/EMC Specialist	06/24/2019
<b>Reviewed by:</b>	 R. Giampaglia, Wireless/EMC Specialist	06/24/2019

**Nemko Spa, 20853 Biassono (MB) - Italy. All rights reserved.**

This publication may be reproduced in whole for non-commercial purposes as long as Nemko Spa is acknowledged as copyright owner and source of the material. Nemko Spa takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This test report may not be partially reproduced, except with the prior written permission of Nemko Spa. The test report merely corresponds to the test sample. The phase of sampling / collection of equipment under test is carried out by the customer.

This Test Report, when bearing the Nemko name and logo is only valid when issued by a Nemko laboratory, or by a laboratory having special agreement with Nemko.

## Table of contents

<b>Section 1: Report summary .....</b>	<b>4</b>
1.1 Test specification.....	4
1.2 Statement of compliance .....	4
1.3 Exclusions .....	4
1.4 Registration number .....	4
1.5 Test report revision history .....	4
1.6 Limits of responsibility .....	4
<b>Section 2: Summary of test results .....</b>	<b>5</b>
2.1 FCC Part 24, test results .....	5
<b>Section 3: Equipment under test (EUT) and application details.....</b>	<b>6</b>
3.1 Applicant details .....	6
3.2 Modular equipment.....	6
3.3 Product details .....	6
3.4 Application purpose.....	6
3.5 Composite/related equipment.....	7
3.6 Sample information .....	7
3.7 EUT technical specifications.....	7
3.8 Accessories and support equipment.....	8
3.9 Operation of the EUT during testing .....	9
3.10 EUT setup diagram .....	9
<b>Section 4: Engineering considerations.....</b>	<b>10</b>
4.1 Modifications incorporated in the EUT .....	10
4.2 Deviations from laboratory tests procedures.....	10
4.3 Technical judgment .....	10
<b>Section 5: Test conditions .....</b>	<b>11</b>
5.1 Deviations from laboratory tests procedures.....	11
5.2 Test conditions, power source and ambient temperatures.....	11
5.3 Measurement uncertainty .....	12
5.4 Test equipment .....	13
<b>Appendix A: Test results .....</b>	<b>14</b>
Clause 935210 D05v01 (3.2) AGC threshold.....	14
Clause 935210 D05v01 (3.3) Out of band rejection .....	15
Clause 24.131 Occupied bandwidth .....	16
Clause 24.132(c) Peak output power at RF antenna connector .....	18
Clause 24.133 Spurious emissions at RF antenna connector .....	21

Clause 24.133 Radiated Spurious emissions.....	26
<b>Appendix B: Block diagrams of test set-ups.....</b>	<b>32</b>
<b>Appendix C: EUT Photos .....</b>	<b>33</b>

## Section 1: Report summary

### 1.1 Test specification

<b>Specifications</b>	<b>Part 24 Subpart D, Narrowband PCS</b>
-----------------------	--

### 1.2 Statement of compliance

<b>Compliance</b>	<p>In the configuration tested the EUT was found compliant                  Yes <input checked="" type="checkbox"/> No <input type="checkbox"/></p> <p>This report contains an assessment of apparatus against specifications based upon tests carried out on samples submitted at Nemko Spa. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 24. Radiated tests were conducted in accordance with ANSI C63.26-2015.</p>
-------------------	--

### 1.3 Exclusions

<b>Exclusions</b>	None
-------------------	------

### 1.4 Registration number

<b>Test site FCC ID number</b>	682159
--------------------------------	--------

### 1.5 Test report revision history

Revision #	Details of changes made to test report
TRF	Original report issued
R1TRF	----

### 1.6 Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. Nemko Spa authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Spa accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

## Section 2: Summary of test results

2.1 FCC Part 24, test results			
Part	Methods	Test description	Verdict
	§ 935210 D05v01r03 (3.2)	AGC threshold	Pass
	§ 935210 D05v01r03 (3.3)	Out of band rejection	Pass
§24.131	§ 935210 D05v01r03 (3.4)	Occupied bandwidth	Pass
§24.132(c)	§ 935210 D05v01r03 (3.5)	Peak output power at RF antenna connector	Pass
§24.133	§ 935210 D05v01r03 (3.6)	Spurious emissions at RF antenna connector	Pass
§24.133	§ 935210 D05v01r03 (3.8)	Radiated spurious emissions	Pass
§24.135	§ 935210 D05v01r03 (3.7)	Frequency stability	N/A a)
<p>Notes:</p> <p style="padding-left: 40px;">a) NOT APPLICABLE: Modulation/frequency conversion circuitry not in use. No frequency change in EUT (input and output have same frequency)</p>			

## Section 3: Equipment under test (EUT) and application details

### 3.1 Applicant details

<b>Applicant complete business name</b>	Name:	Teko Telecom Srl
	Federal Registration Number (FRN):	0018963462
	Grantee code	XM2
<b>Mailing address</b>	Address:	Via Meucci, 24/a
	City:	Castel S. Pietro Terme
	Province/State:	Bologna
	Post code:	40024
	Country:	Italy

### 3.2 Modular equipment

<b>a) Single modular approval</b>	Single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>b) Limited single modular approval</b>	Limited single modular approval Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

### 3.3 Product details

<b>FCC ID</b>	Grantee code:	XM2
	Product code:	-MP7FL8P9PP
<b>Equipment class</b>	B2I	
<b>Description of product as it is marketed</b>	Booster	
	Model name/number:	TRU7FL8P9PWM/AC-WT
	Serial number:	1012793001

### 3.4 Application purpose

<b>Type of application</b>	<input checked="" type="checkbox"/> Original certification <input type="checkbox"/> Change in identification of presently authorized equipment Original FCC ID: _____ Grant date: _____ <input type="checkbox"/> Class II permissive change or modification of presently authorized equipment
----------------------------	--

Section 3: Equipment under test

3.5 Composite/related equipment

<b>a) Composite equipment</b>	The EUT is a composite device subject to an additional equipment authorization Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
<b>b) Related equipment</b>	The EUT is part of a system that operates with, or is marketed with, another device that requires an equipment authorization Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
<b>c) Related FCC ID</b>	If either of the above is "yes": <input type="checkbox"/> has been granted under the FCC ID(s) listed below: <input type="checkbox"/> is in the process of being filled under the FCC ID(s) listed below: <input type="checkbox"/> is pending with the FCC ID(s) listed below: <input type="checkbox"/> has a mix of pending and granted statuses under the FCC ID(s) listed below: i FCC ID: XM2-MP7FL8P9PP ii FCC ID:

3.6 Sample information

<b>Receipt date:</b>	05/27/2019
<b>Nemko sample ID number:</b>	-----

3.7 EUT technical specifications

<b>Operating band:</b>	Down Link 940-941 MHz; Up Link 901-902 MHz
<b>Operating frequency:</b>	Narrowband
<b>Modulation type:</b>	iDEN
<b>Occupied bandwidth:</b>	standard
<b>Channel spacing:</b>	standard
<b>Emission designator:</b>	D7W
<b>RF Output</b>	Down Link: 33dBm (2,00W) Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Gain</b>	Down Link: 38dB Up Link: N.A. (The EUT does not transmit over the air in the up-link direction)
<b>Antenna type:</b>	External Antenna is not provided, equipment that has an external 50 Ω RF connector
<b>Power source:</b>	100-240 Vac

Section 3: Equipment under test

**3.8 Accessories and support equipment**  
 The following information identifies accessories used to exercise the EUT during testing:

Item # 1	
Type of equipment:	Master Unit - Subrack
Brand name:	Teko Telecom srl
Model name or number:	SUB-TRX-PSU
Serial number:	101083001
Nemko sample number:	-----
Connection port:	-----
Cable length and type:	-----
Item # 2	
Type of equipment:	Master Unit – Management Module
Brand name:	Teko Telecom srl
Model name or number:	TSPV-R
Serial number:	110942253
Nemko sample number:	-----
Connection port:	LAN port
Cable length and type:	-----
Item # 3	
Type of equipment:	Master Unit – Optical Module
Brand name:	Teko Telecom srl
Model name or number:	TTRU4W-S-M
Serial number:	110679007
Nemko sample number:	-----
Connection port:	DL/UL RF connector (to connect to the base station) Optical port (to connect to remote unit)
Cable length and type:	-----
Item # 4	
Type of equipment:	Master Unit – Power Supply
Brand name:	Teko Telecom srl
Model name or number:	TPSU/AC
Serial number:	081063004
Nemko sample number:	-----
Connection port:	-----
Cable length and type:	-----



### 3.9 Operation of the EUT during testing

**Details:**

In down-link direction, normal working at max gain with max RF power output.

### 3.10 EUT setup diagram

In this system, Remote Unit is the EUT. Master Unit includes only management module and optical module (to convert RF signal in optical signal in down link direction and viceversa optical signal in RF signal in up link direction). As described in “Operational description”, master unit is connected directly to base station, so the system doesn’t use another equipment (under another FCC ID) to exercise the EUT. Signal generator is linked directly to the RF connector of optical module in the Master Unit.

**Test setup for output power, occupied bandwidth, spurious emissions:**



**Procedure**

Connect the signal modulated generator to the input of the EUT, so that the EUT works at the max gain. Raise the input level to the EUT until reach the maximum output power. Connect the spectrum analyzer to the RF output connector of the EUT.

## Section 4: Engineering considerations

### 4.1 Modifications incorporated in the EUT

<b>Modifications</b>	Modifications performed to the EUT during this assessment None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> , performed by Client <input type="checkbox"/> or Nemko <input type="checkbox"/> Details:
----------------------	---

### 4.2 Deviations from laboratory tests procedures

<b>Deviations</b>	Deviations from laboratory test procedures None <input checked="" type="checkbox"/> Yes <input type="checkbox"/> - details are listed below:
-------------------	---

### 4.3 Technical judgment

<b>Judgment</b>	None
-----------------	------

## Section 5: Test conditions

### 5.1 Deviations from laboratory tests procedures

No deviations were made from laboratory test procedures.

### 5.2 Test conditions, power source and ambient temperatures

<p>Normal temperature, humidity and air pressure test conditions</p>	<p>Temperature: 15–30 °C                  Relative humidity: 20–75 %                  Air pressure: 86–106 kPa</p> <p>When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.</p>
<p>Power supply range:</p>	<p>The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages <math>\pm 5\%</math>, for which the equipment was designed.</p>

Section 5: Test conditions, continued

5.3 Measurement uncertainty

EUT	Type	Test	Range and Setup features	Measurement Uncertainty	Notes
Transmitter	Conducted	Frequency error	0.001 MHz ÷ 40 GHz	0.08 ppm	(1)
		Carrier power RF Output Power	10 kHz ÷ 30 MHz	1.0 dB	(1)
			30 MHz ÷ 18 GHz	1.5 dB	(1)
			18 MHz ÷ 40 GHz	3.0 dB	(1)
		Adjacent channel power	1 MHz ÷ 18 GHz	1.6 dB	(1)
		Conducted spurious emissions	10 kHz ÷ 26 GHz	3.0 dB	(1)
			26 GHz ÷ 40 GHz	4.5 dB	(1)
		Intermodulation attenuation	1 MHz ÷ 18 GHz	2.2 dB	(1)
		Attack time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Attack time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Release time – frequency behaviour	1 MHz ÷ 18 GHz	2.0 ms	(1)
		Release time – power behaviour	1 MHz ÷ 18 GHz	2.5 ms	(1)
		Transient behaviour of the transmitter– Transient frequency behaviour	1 MHz ÷ 18 GHz	0.2 kHz	(1)
		Transient behaviour of the transmitter – Power level slope	1 MHz ÷ 18 GHz	9%	(1)
		Frequency deviation - Maximum permissible frequency deviation	0.001 MHz ÷ 18 GHz	1.3%	(1)
		Frequency deviation - Response of the transmitter to modulation frequencies above 3 kHz	0.001 MHz ÷ 18 GHz	0.5 dB	(1)
		Dwell time	-	3%	(1)
		Hopping Frequency Separation	0.01 MHz ÷ 18 GHz	1%	(1)
	Occupied Channel Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)	
	Modulation Bandwidth	0.01 MHz ÷ 18 GHz	2%	(1)	
Radiated	Radiated spurious emissions	10 kHz ÷ 26.5 GHz	6.0 dB	(1)	
		26.5 GHz ÷ 40 GHz	8.0 dB	(1)	
	Effective radiated power transmitter	10 kHz ÷ 26.5 GHz	6.0 dB	(1)	
		26,5 GHz ÷ 40 GHz	8.0 dB	(1)	
Receiver	Radiated	Radiated spurious emissions	10 kHz ÷ 26.5 GHz	6.0 dB	(1)
			26.5 GHz ÷ 40 GHz	8.0 dB	(1)
	Sensitivity measurement	1 MHz ÷ 18 GHz	6.0 dB	(1)	
		Conducted	Conducted spurious emissions	10 kHz ÷ 26 GHz	3.0 dB
			26 GHz ÷ 40 GHz	4.5 dB	(1)

(1) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k = 2$  which has been derived from the assumed normal probability distribution with infinite degrees of freedom and for a coverage probability of 95 %

5.4 Test equipment				
Equipment	Manufacturer	Model No.	Asset/Serial No.	Next cal.
Vector Signal Generator	Agilent	E4432B ESG	GB38450308	08/2019
Vector Signal Generator	Agilent	E4438C ESG	MY45094485	08/2019
Spectrum Analyzer	Agilent	N9030A PXA	MY53120882	12/2019
Trilog Broad Band Antenna 25-8000 MHz	Schwarzbeck	VULB 9162	VULB 9162-25	07/2021
Antenna 1-18 GHz	Schwarzbeck	STLP 9148	STPL 9148-123	07/2021
Double ridge horn antenna (4 ÷ 40 GHz)	RFSpin	DRH40	061106A40	02/2020
Broadband preamplifier (18 ÷ 40 GHz)	Miteq	JS44-18004000-35-8P-R	1.627	09/2019
Broadband preamplifier 1-18 GHz	Schwarzbeck	BBV 9718	9718-137	08/2019
EMI receiver 20 Hz ÷ 8 GHz	R&S	ESU8	100202	01/2020
EMI receiver 2 Hz ÷ 44 GHz	R&S	ESW44	101620	05/2019
Hydraulic revolving platform	Nemko	RTPL 01	4.233	NCR
Turning-table	R&S	HCT	835 803/03	NCR
Antenna mast	R&S	HCM	836 529/05	NCR
Controller	R&S	HCC	836 620/7	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	530	09/2021
Shielded room	Siemens	10m control room	1947	NCR
Semi-anechoic chamber	Nemko	10m semi-anechoic chamber	70	NCR
Shielded Room	Siemens	3m semi-anechoic chamber	3	NCR
Motor controller	Emco	1051-25	9012-1559	NCR
Motor controller	Emco	1061-1.521	9012-1508	NCR
Antenna Tower	Emco	2071-2	9601-1940	NCR
Controller pole/table	Emco	2090	9511-1099	NCR
Note: N/A = Not Applicable, NCR = No Cal Required, COU = CAL On Use (*) Equipment supplied by manufacturer's				

Appendix A: Test results


Clause 935210 D05v01 (3.2) AGC threshold

Measure of EUT AGC Threshold


Test date: 05/27/2019 to 06/24/2019  
 Test results: Pass

Special notes

Test data



iDEN signal, nominal input signal



iDEN signal, nominal input signal + 1dB


Clause 935210 D05v01 (3.3) Out of band rejection

Out of Band Rejection – Test for rejection of out of band signals.

Test date: 05/27/2019 to 06/24/2019  
 Test results: Pass

Special notes  
 –

Test data



### Clause 24.131 Occupied bandwidth

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Test date: [05/27/2019 to 06/24/2019](#)

Test results: [Pass](#)


Special notes




Clause 24.131 Occupied bandwidth, continued

Test data

iDEN signal, nominal input signal




Output




Input

iDEN signal, nominal input signal + 3dB



Output



Input

### Clause 24.132(c) Peak output power at RF antenna connector

(c) Base stations transmitting in the 930-931 MHz and 940-941 MHz bands are limited to 3500 watts e.r.p. per authorized channel and are unlimited in antenna height except as provided in paragraph (d) of this section.

Test date: 05/27/2019 to 06/24/2019

Test results: Pass



Special notes

Clause 24.132(c) Peak output power at RF antenna connector

Test data

iDEN signal, nominal input signal


Test data					
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)	PAR (dB)
Down-link	iDEN (25kHz)	940.5	33.00	2.00	5.78



PAR measure is performed by the “CCDF” function installed on Spectrum analyzer that provides average power (the same measured with “Channel power” function), peak power and PAR.

**iDEN signal, nominal input signal + 3dB**

Test data				
Direction	Modulation	Frequency (MHz)	RF output Power (dBm)	RF output channel Power (W)
Down-link	iDEN (25kHz)	940.5	33.43	2.20



### Clause 24.133 Spurious emissions at RF antenna connector

(a) The power of any emission shall be attenuated below the transmitter power (P), as measured in accordance with §24.132(f), in accordance with the following schedule:

- (1) For transmitters authorized a bandwidth greater than 10 kHz:
  - (i) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of up to and including 40 kHz: at least  $116 \text{ Log}_{10} ((f_d+10)/6.1)$  decibels or  $50 + 10 \text{ Log}_{10} (P)$  decibels or 70 decibels, whichever is the lesser attenuation;
  - (ii) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 40 kHz: at least  $43 + 10 \text{ Log}_{10} (P)$  decibels or 80 decibels, whichever is the lesser attenuation.
- (2) For transmitters authorized a bandwidth of 10 kHz:
  - (i) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of up to and including 20 kHz: at least  $116 \times \text{Log}_{10} ((f_d+5)/3.05)$  decibels or  $50 + 10 \times \text{Log}_{10} (P)$  decibels or 70 decibels, whichever is the lesser attenuation;
  - (ii) On any frequency outside the authorized bandwidth and removed from the edge of the authorized bandwidth by a displacement frequency ( $f_d$  in kHz) of more than 20 kHz: at least  $43 + 10 \text{ Log}_{10} (P)$  decibels or 80 decibels, whichever is the lesser attenuation.

Test date: 05/27/2019 to 06/24/2019

Test results: Pass

Special notes

Clause 24.133 Spurious emissions at RF antenna connector, continued

Test data

**See Plots below**


Spurious emissions measurement results:

Frequency (MHz)	Spurious emission (dBm)	Limit (dBm)	Margin (dB)
Low channel			
First channel	Negligible	-13	
Mid channel			
940,5 MHz	Negligible	-13	
High channel			
Last channel	Negligible	-13	


Test data: spurious emissions at antenna terminal

**iDEN signal**


(Plots are referred to modulated carrier at the Middle Channel)




9KHz-150KHz



150KHz-30MHz




30MHz-1GHz




1GHz-10GHz

Test data, continued: band edges Inter modulation

iDEN signal, nominal input signal




Low Band Edge




High Band Edge



MSK signal, nominal input signal + 3dB



Low Band Edge



High Band Edge

### Clause 24.133 Radiated Spurious emissions

a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \text{ Log (P) dB}$ .

Test date: 05/27/2019 to 06/24/2019

Test results: Pass

### Special notes

Clause 24.133 Radiated spurious emissions, continued

Test data

The D.U.T. was positioned according to the radiated emissions set-up

The D.U.T. antenna connector was terminated by a 50 Ω shielded dummy load.


The spectrum was searched from 30 MHz to 1 GHz (RBW 100 kHz) & 1 GHz (RBW 1 MHz) to the tenth harmonic of the carrier.

There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.

Spurious emissions measurement results:


Frequency (MHz)	Polarization. V/H	Field strength (dBm)	Limit (dBm)	Margin (dB)
Low channel				
First Channel	V/H	Negligible	-13	
Mid channel				
763.0	V/H	Negligible	-13	
High channel				
Last Channel	V/H	Negligible	-13	

Note: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.




Date: 19.JUN.2019 12:31:07

### 30MHz-1GHz – H Pol



Date: 19.JUN.2019 12:30:24


### 30MHz-1GHz – V Pol



10:39:46 18.06.2019

Page 1/1

### 1GHz-10GHz – H Pol



10:40:04 18.06.2019

Page 1 / 1

### 1GHz-10GHz – V Pol





## Appendix C: EUT Photos

### Photo Set up






Photo EUT









END OF REPORT