



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density
P = power input to the antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>43.00</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>19952.62315</u>	(mW)
Antenna gain(maximum):	<u>14</u>	(dBi)
Maximum antenna gain:	<u>25.11886432</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>200</u>	(cm)
Prediction frequency:	<u>1930</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000</u>	(mW/cm ²)
Power density at prediction frequency:	0.997080	(mW/cm ²)
Margin of compliance:	0.0	(dB)
This equates to:	9.970803206	W/m²



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density
P = power input to the antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>43.00</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>19952.62315</u>	(mW)
Antenna gain(maximum):	<u>14</u>	(dBi)
Maximum antenna gain:	<u>25.11886432</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>200</u>	(cm)
Prediction frequency:	<u>2110</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>1.000</u>	(mW/cm ²)
Power density at prediction frequency:	0.997080	(mW/cm ²)
Margin of compliance:	0.0	(dB)
This equates to:	9.970803206	W/m²



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density
P = power input to the antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<u>43.00</u>	(dBm)
Maximum peak output power at antenna input terminal:	<u>19952.62315</u>	(mW)
Antenna gain(maximum):	<u>11</u>	(dBi)
Maximum antenna gain:	<u>12.58925412</u>	(numeric)
Time Averaging:	<u>100</u>	(%)
Prediction distance:	<u>200</u>	(cm)
Prediction frequency:	<u>851</u>	(MHz)
MPE limit for uncontrolled exposure at prediction frequency:	<u>0.567</u>	(mW/cm ²)
Power density at prediction frequency:	0.499724	(mW/cm ²)
Margin of compliance:	-0.6	(dB)
This equates to:	4.997239276	W/m²