

RF EXPOSURE EVALUATION

EUT Specification

EUT	Car Multimedia System
Model Number	DMCPA8W
Series models	DMCPA80FL, DCPA813, DCPA81W, DMCPA10W, AVM2310W, J1CA10FL, CAR1013, CAR813, J1CA8FL, CVS8489W-SD, CVS1515W-SD, XDCPA73W, DCPA723W, DCA73W, DMCPA703W, CAR723W, J3CA7W, CVS7482W-SD
FCC ID	XMF-DMCPA8W
Antenna gain (Max)	1.59dBi
Operation Frequency	2402-2480MHz 2412-2462MHz
Input Rating	DC 12V
Standard	47 CFR Part 1.1307 47 CFR Part 1.1310 KDB447498D01 General RF Exposure Guidance v06
Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;

Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	60
3.0–30	1842/f	4.89/f	*(900/f ²)	60
30–300	61.4	0.163	1.0	60
300–1500	f/300	60
1500–100,000	5	60
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout * G) / (4 * Pi * R^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Calculated Result and Limit

BT:

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Maximum tune-up Power (mW)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
						(dBi)	(Linear)			
GFSK	2402	-1.535	0.702	0±1	1.25	1.59	1.44	0.0036	1	Complies
	2441	0.778	1.196	1±1	1.58	1.59	1.44	0.0045	1	Complies
	2480	1.374	1.372	1±1	1.58	1.59	1.44	0.0045	1	Complies
8DPSK	2402	-1.368	0.730	0±1	1.25	1.59	1.44	0.0036	1	Complies
	2441	1.072	1.280	1±1	1.58	1.59	1.44	0.0045	1	Complies
	2480	1.685	1.474	1±1	1.58	1.59	1.44	0.0045	1	Complies

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power (dBm)	Maximum tune-up Power (mW)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
						(dBi)	(Linear)			
IEEE 802.11b	2412	15.23	33.34	15±1	39.81	1.59	1.44	0.0796	1	Compiles
	2437	14.68	29.37	15±1	39.81	1.59	1.44	0.0796	1	Compiles
	2462	14.91	30.97	15±1	39.81	1.59	1.44	0.0796	1	Compiles
IEEE 802.11g	2412	16.43	43.95	16±1	50.11	1.59	1.44	0.1002	1	Compiles
	2437	16.09	40.64	16±1	50.11	1.59	1.44	0.1002	1	Compiles
	2462	17.15	51.88	17±1	63.09	1.59	1.44	0.1261	1	Compiles
IEEE 802.11n HT20	2412	17.48	55.97	17±1	63.09	1.59	1.44	0.1261	1	Compiles
	2437	17.52	56.49	17±1	63.09	1.59	1.44	0.1261	1	Compiles
	2462	17.89	61.51	17±1	63.09	1.59	1.44	0.1261	1	Compiles

Power Density (S) (mW/cm ²)			Limited of Power Density (S) (mW/cm ²)	Test Result
BT	WIFI	Sum		
0.0045	0.1261	0.1306	1	Complies

The Maximum power is less than the limit, complies with the exemption requirements, SAR is exempted.

Remark: The Max Conducted Peak Output Power data refer to report Report No.:
90454-23-72-23-PP001 , 90454-23-72-23-PP002