

Mimomax Wireless Ltd
540 Wairakei Road
PO Box 1645
Christchurch, New Zealand

mimomax

13 November 2023

To whom it may concern

Equivalence for FCC-ID: XMK-MMXTRNB007

Mimomax 440-470 MHz Tornado radios have been certification tested with during October/November 2023, Testing was carried out on an Encryption capable radio fitted with internal duplexers and 50kHz receiver filters. Equivalent radios with and without encryption capability, with internal vs external duplexers and with different bandwidth receiver filters are available in the Tornado Radios.

Encryption capability or lack of encryption capability makes no impact on the signal transmitted from the Radio. Internal duplexers radios have less rejection of unwanted signals and are consequently the worst case for the signals out of the radio. A radio with a 50 kHz receiver filter was tested as it can support all the bandwidths required for testing and the receiver filter bandwidth has no impact on the signals out of the radio.

Certification testing was complete on a MWL-TORNADO-BCCA model radio.

The below models are equivalent to the MWL-TORNADO-BCCA:

MWL-TORNADO-ACAA, MWL-TORNADO-ACBA, MWL-TORNADO-ACCA, MWL-TORNADO-BCAA,
MWL-TORNADO-BCBA, MWL-TORNADO-ACAB, MWL-TORNADO-ACBB, MWL-TORNADO-ACCB,
MWL-TORNADO-BCAB, MWL-TORNADO-BCBB, MWL-TORNADO-BCCB

Model numbering follows the format

MWL-TORNADO-1234

Where 1 = A for non-encryption capable radios, and B for encryption capable radios.

Where 2 = C for 440-470 MHz Frequency band radios.

Where 3 = A for 12.5kHz bandwidth Receiver filters, B for 25kHz bandwidth receiver filters and C for 50kHz bandwidth receiver filters.

Where 4 = A for internal duplexer radios and B for external duplexer radios.

Regards



James Dowle, Development Manager