



TEST REPORT

APPLICANT : MiMOMax Wireless Limited

PRODUCT NAME : 700MHz Upper A Block TornadoXR Transceiver

MODEL NAME : MWL-TORNADOX-*H*A/B/C

BRAND NAME : MiMOMax Wireless

STANDARD(S) : 47 CFR Part 15 Subpart A and B

FCC ID : XMK-MMXTRNXB002

RECEIPT DATE : 2021-04-21

TEST DATE : 2021-05-14 to 2021-05-18

ISSUE DATE : 2021-07-06

Edited by: He sinuo
He Sinuo(Rapporteur)

Approved by: Xiao Xiong
Xiao Xiong(Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information..... 3
 - 1.1. Applicant and Manufacturer Information..... 3
 - 1.2. Equipment Under Test (EUT) Description 3
- 2. Test Results 4
 - 2.1. Applied Reference Documents 4
 - 2.2. EUT Setup and Operating Conditions..... 5
- 3. 47 CFR Part 15B Requirements 6
 - 3.1. Radiated Emission..... 6
 - 3.2. Antenna Terminal Disturbance 16
- Annex A Test Uncertainty 25
- Annex B Testing Laboratory Information..... 26

Change History		
Version	Date	Reason for change
1.0	2021-07-06	First edition



1. Technical Information

Note: Provide by applicant

1.1. Applicant and Manufacturer Information

Applicant:	MiMOMax Wireless Limited
Applicant Address:	540 Wairakei Road, Christchurch 8053, New Zealand
Manufacturer:	MiMOMax Wireless Limited
Manufacturer Address:	540 Wairakei Road, Christchurch 8053, New Zealand

1.2. Equipment Under Test (EUT) Description

Product Name:	700MHz Upper A Block TornadoXR Transceiver
Serial No.:	N/A
Hardware Version:	P001
Software Version:	TRN_04.08.00.dev12
Tx Frequency:	757MHz ~ 758MHz; 787 MHz ~ 788 MHz
Rx Frequency:	757MHz ~ 758MHz; 787 MHz ~ 788 MHz
Operating Voltage:	10.5V~60V DC(Isolated)

Note: For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.



2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart A and B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are listed as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination Remark
1	15.101	Equipment authorization requirement	Receiver contained within a FCC Part 27 transceiver that has been certified. The receiver has therefore been verified.			No deviation
2	15.103	Exempted devices	Device is not exempt as it is a receiver that contains a digital device			No deviation
3	15.107	Conducted Emission	Not applicable			N/A ^{Note 1}
4	15.109	Radiated Emissions	2021.05.14	Yang Jie	PASS	No deviation
5	15.111	Antenna Terminal Disturbance	2021.05.18	Huang Zhiye	PASS	No deviation

Note 1:The test item is not applicable.

Note 2:Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: TORNADOXR TRANSCEIVER complies with FCC Part 15 Subparts A and B as a Class B Unintentional Radiator. Tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



2.2. EUT Setup and Operating Conditions

Test Item	
Radiated Emission	
Mode 1	: EUT + RJ45 Link + 10.5V DC Power + 757.050 Rx
Mode 2	: EUT + RJ45 Link + 24V DC Power + 787.95 Rx
Mode 3	: EUT + RJ45 Link + 60V DC Power + 757.050 Tx
Remark: The above test mode in boldface (Mode 1) was the worst case of radiated emission test, only the test data of these modes were reported.	

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

Receiver Test Frequencies:

Transmit Frequency (MHz)	Receiver Frequency (MHz)	Channel Bandwidth (KHz)	Modes of operation
757.050	787.950	12.5, 25.0, 50.0	QPSK,16QAM,64QAM,256QAM
787.950	757.050	12.5, 25.0, 50.0	QPSK,16QAM,64QAM,256QAM



3. 47 CFR Part 15B Requirements

3.1. Radiated Emission

3.1.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength Limitation at 3m Measurement Distance	
	($\mu\text{V/m}$)	($\text{dB}\mu\text{V/m}$)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in $\text{dB}\mu\text{V/m}$ is calculated by $20\log \text{Emission Level}(\mu\text{V/m})$.




3.1.2. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705 – 108	1000.
108 – 500	2000.
500 – 1000	5000.
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

3.1.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber, the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

For measurements below 1GHz the resolution bandwidth is set to 120 kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video bandwidth is set to 3MHz for peak measurements and as applicable for average measurements.




3.1.4. Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	70.7441	31.65	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
2	95.2875	28.71	N.A.	N.A.	N.A.	43.50	N.A.	V	PASS
3	118.0848	24.37	N.A.	N.A.	N.A.	43.50	N.A.	V	PASS
4	240.5111	32.44	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS
5	279.9940	27.04	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS
6	826.0616	31.61	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS



No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	1053.0106	41.63	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
2	1240.0480	40.66	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
3	1693.1386	41.29	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
4	2272.2545	38.23	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
5	3927.5855	42.71	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
6	5260.8522	44.43	N.A.	N.A.	74.00	N.A.	54.00	V	PASS



No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	34.5595	29.55	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
2	52.3122	27.06	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
3	105.7646	21.28	N.A.	N.A.	N.A.	43.50	N.A.	H	PASS
4	240.5111	35.15	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS
5	360.0270	25.13	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS
6	746.6107	30.58	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS



No.	Fre. MHz	Pk dBµV/m	QP dBµV/m	AV dBµV/m	Limit-PK dBµV/m	Limit-QP dBµV/m	Limit-AV dBµV/m	ANT	Verdict
1	1125.0250	36.56	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
2	1400.0800	37.91	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
3	1784.1568	43.46	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
4	2633.3267	38.99	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
5	4017.6035	43.07	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
6	5429.8860	44.20	N.A.	N.A.	74.00	N.A.	54.00	H	PASS



The test result for CB receiver RSE (25-30MHz) .

Test mode	Fre. MHz	QP dBμV/m	Limit-QP dBμV/m	ANT	Verdict
Mode 1	25.16	21.24	32.04	V	PASS
	26.34	20.17			PASS
	27.68	24.65			PASS
	28.33	22.94			PASS
	28.50	22.56			PASS
	29.49	24.74			PASS
	25.76	20.35	32.04	H	PASS
	26.49	24.49			PASS
	27.35	25.66			PASS
	28.56	21.79			PASS
	28.34	22.74			PASS
	29.87	21.64			PASS



3.2. Antenna Terminal Disturbance

3.2.1. Requirement

In addition to the radiated emission limits, receivers that operate (tune) in the frequency range 30 to 960 MHz and CB receivers that provide terminals for the connection of an external receiving antenna may be tested to demonstrate compliance with the provisions of §15.109 with the antenna terminals shielded and terminated with a resistive termination equal to the impedance specified for the antenna, provided these receivers also comply with the following: With the receiver antenna terminal connected to a resistive termination equal to the impedance specified or employed for the antenna, the power at the antenna terminal at any frequency within the range of measurements specified in §15.33 shall not exceed 2.0 nanowatts(-57dBm).

Measurements were attempted over the range of 30 MHz– 5 GHz




3.2.2. Test Result

Note: $P_{Final\ value}(dBm) = P_{Reading\ value}(dBm) + Factor(dB)$,
 $Factor = Cable\ loss(dB)$

H port, Operate at 757.050MHz, 30MHz -1000MHz

Fre. MHz	P _{Reading value} dBm	Factor dB	P _{Final value} dBm	Limit dBm	Verdict
242.43	-79.737	0.6	-79.137	-57	PASS
353.01	-80.019	0.6	-79.419	-57	PASS
526.64	-79.94	0.6	-79.34	-57	PASS
743.92	-80.248	0.6	-79.648	-57	PASS
899.12	-78.025	0.6	-77.425	-57	PASS
964.11	-80.746	0.6	-80.146	-57	PASS

Attach spectrum pictures of P_{Reading value} for this test here:






H port, Operate at 757.050MHz, 1GHz -5GHz

Fre. GHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
1.52	-68.848	0.6	-68.248	-57	PASS
2.428	-68.899	0.6	-68.299	-57	PASS
3.192	-66.652	0.6	-66.052	-57	PASS
3.3	-66.554	0.6	-65.954	-57	PASS
3.808	-69.027	0.6	-68.427	-57	PASS
4.44	-69.072	0.6	-68.472	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:






V port, Operate at 757.050MHz, 30MHz -1000MHz

Fre. MHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
216.24	-79.246	0.6	-78.646	-57	PASS
378.23	-80.035	0.6	-79.435	-57	PASS
426.73	-78.917	0.6	-78.317	-57	PASS
806.97	-78.491	0.6	-77.891	-57	PASS
889.42	-78.56	0.6	-77.96	-57	PASS
933.07	-79.527	0.6	-78.927	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:






V port, Operate at 757.050MHz, 1GHz -5GHz

Fre. GHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
1.464	-72.961	0.6	-72.361	-57	PASS
2.412	-68.669	0.6	-68.069	-57	PASS
3.232	-69.836	0.6	-69.236	-57	PASS
3.596	-71.134	0.6	-70.534	-57	PASS
3.976	-71.842	0.6	-71.242	-57	PASS
4.472	-69.542	0.6	-68.942	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:






H port, Operate at 787.950MHz, 30MHz -1000MHz

Fre. MHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
220.72	-80.539	0.6	-79.939	-57	PASS
365.62	-80.937	0.6	-80.337	-57	PASS
511.12	-79.667	0.6	-79.067	-57	PASS
789.51	-79.536	0.6	-78.936	-57	PASS
870.99	-79.032	0.6	-78.432	-57	PASS
956.35	-78.644	0.6	-78.044	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:






H port, Operate at 787.950MHz, 1GHz -5GHz

Fre. GHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
1.52	-69.988	0.6	-69.388	-57	PASS
2.672	-67.011	0.6	-66.411	-57	PASS
3.172	-67.492	0.6	-66.892	-57	PASS
3.576	-69.219	0.6	-68.619	-57	PASS
4.036	-69.197	0.6	-68.597	-57	PASS
4.64	-67.99	0.6	-67.39	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:






V port, Operate at 787.950MHz, 30MHz -1000MHz

Fre. MHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
225.94	-79.89	0.6	-79.29	-57	PASS
381.14	-80.136	0.6	-79.536	-57	PASS
494.63	-79.718	0.6	-79.118	-57	PASS
744.89	-80.077	0.6	-79.477	-57	PASS
891.36	-77.027	0.6	-76.427	-57	PASS
948.59	-79.937	0.6	-79.337	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:






V port, Operate at 787.950MHz, 1GHz -5GHz

Fre. GHz	P _{Reading} value dBm	Factor dB	P _{Final} value dBm	Limit dBm	Verdict
1.668	-70.831	0.6	-70.231	-57	PASS
2.412	-65.86	0.6	-65.26	-57	PASS
3.064	-66.988	0.6	-66.388	-57	PASS
3.44	-68.037	0.6	-67.437	-57	PASS
4.5	-68.69	0.6	-68.09	-57	PASS
4.868	-68.471	0.6	-67.871	-57	PASS

Attach spectrum pictures of P_{Reading} value for this test here:





Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	±5.06dB
	200MHz-1000MHz	±5.04dB
	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen ,GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen ,GuangDong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. Test firm registration number is 226174. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
TS+ -[JS32-RE]	Version 2.5.1.5	Tonscend

**5. Test Equipments Utilized**

Description	Model	Serial No.	Manufacturer	Cal. Date	Due. Date
Bi-Log Antenna	VULB 9163	9163-519	SCHWARZBEC K	2019/5/24	2022/5/23
Horn Antenna	BBHA 9120D	01774	SCHWARZBEC K	2019/7/26	2022/7/25
Receiver	N9038A	MY564000 93	KEYSIGHT	2021/3/9	2022/3/8
6db Attenuator	BW-N6W5+	E191001	Mini-circuits	2020/10/20	2021/10/19
Preamplifier	S020180L320 3	61171/6117 2	LUCIX CORP.	2020/7/21	2021/7/20
Preamplifier	S10M100L380 2	46732	LUCIX CORP.	2020/7/21	2021/7/20

————— END OF REPORT —————