

## 2.4. Radiated Spurious Emissions

### 2.4.1. Requirement

According to FCC section 2.1053 and section 24.133(a). For operations in the 901-902 MHz band , the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 901-902 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB;

### 2.4.2. Test Result

**Note 1:** No discrete emissions were detected.

**Note 2:** The power of the EUT transmitting frequency should be ignored.

**Note 3:** N/A means the frequency is the basic frequency; they are no need to verdict.

**Note 4:** For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements. For measurements above 1GHz the resolution bandwidth is set to 1MHz for peak measurements.

**Note 5:** All bandwidth and modulation were considered and evaluated respectively by performing full test, only the worst cases were recorded in this test report.

**Note 6:** The received power level is the measured power adjusted for measurement antenna gain, connecting cable loss, and any external signal amplification or attenuation used in the test configuration. Mathematically, as in Equation:

$$P_R = P_{\text{meas}} - G_R + L_C - G_{\text{amp}}$$

where


$P_{\text{meas}}$  measured power level, in dBm;

$G_R$  gain of the receive (measurement) antenna, in dBi;


$L_C$  signal loss in the measurement cable, in dB;

$G_{\text{amp}}$  value of external amplification, in dB.

Type 1:



Type 2:





## 2.5. Frequency Stability

### 2.5.1. Requirement

According to FCC section 2.1055 and FCC section 24.135.e frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 24.135, the test conditions are:

The frequency stability of the transmitter shall be maintained within  $\pm 0.0001$  percent ( $\pm 1$  ppm) of the center frequency over a temperature variation of  $-30$  °Celsius to  $+ 50$  °Celsius at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of  $20$  °Celsius..

### 2.5.2. Test Results

901.5MHz QPSK 12.5kHz Limit =Within Authorized Band					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
100	24.0	+20(Ref)	-8	-0.009	PASS
100		-40	19	0.021	
100		-30	18	0.020	
100		-20	13	0.014	
100		-10	0	0.000	
100		0	18	0.020	
100		+10	16	0.018	
100		+20	15	0.017	
100		+30	15	0.017	
100		+40	23	<b>0.026</b>	
100		+50	-11	-0.012	
100		+60	13	0.014	
100		+70	16	0.018	
115		27.6	+20	20	
85	20.4	+20	-7	-0.008	

901.5MHz QPSK 25.0kHz Limit =Within Authorized Band					
Voltage (%)	Power	Temp (°C)	Fre. Dev.	Deviation	Result





	(VDC)		(Hz)	(ppm)		
100	24.0	+20(Ref)	14	0.016	PASS	
100		-40	17	0.019		
100		-30	22	<b>0.024</b>		
100		-20	7	0.008		
100		-10	19	0.021		
100		0	18	0.020		
100		+10	13	0.014		
100		+20	19	0.021		
100		+30	-11	-0.012		
100		+40	20	0.022		
100		+50	16	0.018		
100		+60	-1	-0.001		
100		+70	14	0.016		
115		27.6	+20	15		0.017
85		20.4	+20	-17		-0.019

901.5MHz QPSK 50.0kHz Limit =Within Authorized Band						
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result	
100	24.0	+20(Ref)	15	0.017	PASS	
100		-40	22	0.024		
100		-30	-10	-0.011		
100		-20	14	0.016		
100		-10	-19	-0.021		
100		0	23	<b>0.026</b>		
100		+10	-6	-0.007		
100		+20	13	0.014		
100		+30	16	0.018		
100		+40	18	0.020		
100		+50	-11	-0.012		
100		+60	19	0.021		
100		+70	-2	-0.002		
115		27.6	+20	20		0.022
85		20.4	+20	18		0.020



## Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	$\pm 2.22$ dB
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77$ dB
Band Edge	$\pm 2.77$ dB
Equivalent Isotropic Radiated Power	$\pm 2.22$ dB
Radiated Spurious Emissions	$\pm 6$ dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .



## Annex B Testing Laboratory Information

### 1. Identification of the Responsible Testing Laboratory

<b>Company Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Laboratory Address:</b>	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
<b>Telephone:</b>	+86 755 36698555
<b>Facsimile:</b>	+86 755 36698525

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Shenzhen Morlab Communications Technology Co., Ltd.
<b>Address:</b>	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



#### 4. Test Equipment Utilized

##### 4.1 Conducted Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Power Splitter	NW521	1506A	Weinschel	N/A	N/A
Attenuator 1	(N/A.)	30.0dB	Resnet	N/A	N/A
Attenuator 2	(N/A.)	30.0dB	Resnet	N/A	N/A
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2023.06.21	2024.06.20
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Temperature Chamber	S022177101 00089002	KMT-36LF 1A0	KOMEG	2023.09.19	2024.09.18

##### 4.2 List of Software Used

Description	Manufacturer	Software Version
MORLAB EMCR	MORLAB	V1.2



### 4.3 Radiated Test Equipment

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Bi-Log Antenna	9163-274	VULB 9163	SCHWARZBECK	2023.06.27	2024.06.26
Horn Antenna	9120D-963	BBHA 9120D	SCHWARZBECK	2023.06.27	2024.06.26
Receiver	MY54130016	N9038A	Agilent	2023.06.21	2024.06.20
6db Attenuator	E191001	BW-N6W5+	Mini-circuits	2023.9.19	2024.9.18
Preamplifier (2GHz-18GHz)	61171.61172	S020180L32 03	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2023.06.27	2024.06.26

————— END OF REPORT —————