

3.5 Conducted Out of Band Emissions

3.5.1 Requirement

According to FCC section 22.717(a) and FCC section 24.235(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

3.5.2 Test Description

See section 3.1.2 of this report.

3.5.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the out of band emissions.

1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Spurious Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	-24.66	Plot A1/A2		PASS
	190	836.6	-24.87	Plot B1/B2	-13	PASS
	251	848.8	-24.94	Plot C1/C2		PASS
CCM	512	1850.2	-24.45	Plot D1/D2		PASS
USM 1900MHz	661	1880.0	-24.70	Plot E1/E2	-13	PASS
	810	1909.8	-27.71	Plot F1/F2		PASS
GPRS 850MHz	128	824.2	-26.37	Plot A3/A4		PASS
	190	836.6	-25.05	Plot B3/B4	-13	PASS
	251	848.8	-26.08	Plot C3/C4		PASS
GPRS 1900MHz	512	1850.2	-24.43	Plot D3/D4		PASS
	661	1880.0	-24.45	Plot E3/E4	-13	PASS
	810	1909.8	-25.04	Plot F3/F4	1	PASS

2. Test Plot for the Whole Measurement Frequency Range:

Note: the power of the EUT transmitting frequency should be ignored.















(Plot B1: GSM 850MHz Channel = 190, 30MHz to 1GHz)



(Plot B2:GSM 850MHz Channel = 190, 1GHz to 9GHz)





(Plot C1:GSM 850MHz Channel = 251, 30MHz to 1GHz)



(Plot C2:GSM 850MHz Channel = 251, 1GHz to 9GHz)





(Plot D1:GSM 1900MHz Channel = 512, 30MHz to 2GHz)



(Plot D2:GSM 1900MHz Channel = 512, 2GHz to 20GHz)





(Plot E1:GSM 1900MHz Channel = 661, 30MHz to 2GHz)



(Plot E2:GSM 1900MHz Channel = 661, 2GHz to 20GHz)





(Plot F1:GSM 1900MHz Channel = 810, 30MHz to 2GHz)



(Plot F2:GSM 1900MHz Channel = 810, 2GHz to 20GHz)































































3.6 Band Edge

3.6.1 Requirement

According to FCC section 22.717(b) and FCC section 24.235(b), in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth (26dB emission bandwidth) of the fundamental emission of the transmitter may be employed.

3.6.2 Test Description

See section 3.1.2 of this report.

3.6.3 Test Result

The lowest and highest channels are tested to verify the band edge emissions.

1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured Max. Band Edge Emission (dBm)	Refer to Plot	Limit (dBm)	Verdict
GSM	128	824.2	-14.24	Plat A1	12	PASS
850MHz	251	848.8	-14.05	Plot B1	-15	PASS
GSM	512	1850.2	-14.65	Plat C1	12	PASS
1900MHz	810	1909.8	-14.07	Plot D1	-13	PASS
GPRS	128	824.2	-13.43	Plat A2	12	PASS
850MHz	251	848.8	-13.81	Plot B2	-13	PASS
GPRS	512	1850.2	-16.34	Plat C2	12	PASS
1900MHz	810	1909.8	-14.97	Plot D2	-13	PASS



















3.7 Transmitter Radiated Power (EIRP/ERP)

3.7.1 Requirement

According to FCC section 22.713, the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7Watts, and FCC section 24.232, the broadband PCS mobile station is limited to 2Watts e.i.r.p. peak power.

3.7.2 Test Description

1. Test Setup:



The EUT, which is powered by the Battery charged with the AC Adapter, is located in a 3m Full-Anechoic Chamber; the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power i.e. GSM850MHz band Power Control Level (PCL) = 5 and Power Class = 4 and GSM1800MHz band Power Control Level (PCL) = 0 and Power Class = 1. A call is established between the EUT and the SS via a Common Antenna.

The Test Antenna is a Bi-Log one (used for 30MHz to 1GHz) or a Horn one (used for above 3GHz), and it's located at the same height as the EUT. The Filters consists of Notch Filters and High Pass Filter.



2. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
System Simulator	R&S	CMU200	105571	2009.12	1year
Spectrum Analyzer	Agilent	E4407B	MY44210631	2009.09	1 year
Full-Anechoic Chamber	ETS • LINDGREN	9m*6m*6m	(n.a.)	2008.10	2year
Bi-Log Antenna	R&S	HL562	100385	2009.10	1year
Horn Antenna	R&S	HF906	100565	2009.10	1year

3.7.3 Test Result

The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested.

- Frequency Measured ERP Limit Chann Band Verdict (MHz) dBm W W Refer to Plot dBm el 128 824.2 25.15 0.33 Plot A1 PASS GSM 190 0.34 Plot B1 PASS 836.6 25.32 35.45 7 850MHz 251 848.8 25.35 0.34 Plot C1 PASS 512 1850.2 24.36 0.27 Plot D1 PASS GSM 1880.0 Plot E1 2 PASS 661 25.6 0.36 33 1900MHz 1909.8 25.12 Plot F1 PASS 810 0.33 824.2 20.25 0.11 Plot A2 PASS 128 **GPRS** Plot B2 PASS 190 836.6 21.45 0.14 35.45 7 850MHz 251 848.8 21.48 0.14 Plot C2 PASS 22.89 0.19 Plot D2 PASS 512 1850.2 **GPRS** PASS Plot E2 33 2 661 1880.0 24.21 0.26 1900MHz 810 1909.8 23.7 0.23 Plot F2 PASS
- 1. Test Verdict:











(Plot B1: GSM 850MHz Channel = 190)













(Plot F1: GSM 1900MHz Channel = 810)











(Plot B2:GPRS 850MHz Channel = 190)



AA

Center 1.85 GHz #Res BW 1 MHz



(Plot D2:GPRS 1900MHz Channel = 512)

₩VBW 3 MHz

Span 10 MHz

#Sweep 200 ms (401 pts)







(Plot F2:GPRS 1900MHz Channel = 810)



3.8 Radiated Out of Band Emissions

3.8.1 Requirement

According to FCC section 22.717(a) and section 24.235(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

3.8.2 Test Description

See section 3.7.2 of this report.

3.8.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

1. Test Verdict:

Band	Channel	Frequency (MHz)	Measured M Emissio Test Antenna Horizontal	ax. Spurious n (dBm) Test Antenna Vertical	Limit (dBm)	Verdict
GSM 850MHz	128	824.2	<-30	<-30		PASS
	190	836.6	<-30	<-30	-13	PASS
	251	848.8	< -30	<-30		PASS
GSM 1900MHz	512	1850.2	< -25	< -25		PASS
	661	1880.0	< -25	< -25	-13	PASS
	810	1909.8	< -25	< -25		PASS



Appendix I: Photograph of the Test Setup

1. GV100 RF Test



Appendix II: Photograph of the EUT

1. Appearance of the GPS TRACKER







2. Inside of GPS TRACKER















2. Appearance of Accessories



3. Appearance of the Charge



** END OF REPORT **