

RF TEST REPORT



Report No.: 16050014-FCC-R1

Supersede Report No.: N/A

Applicant	Quectel Wireless Solutions Co., Ltd.	
Product Name	Multi-mode LTE module	
Model No.	EC20	
Serial No.	EC20 MiniPCle	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; FCC Part 27:2015; ANSI/TIA-603-D: 2010	
Test Date	March 17 to April 11, 2016	
Issue Date	May 09, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16050014-FCC-R1
Page	3 of 55

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION.....	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 RF EXPOSURE (SAR).....	9
6.2 RF OUTPUT POWER.....	10
6.4 OCCUPIED BANDWIDTH.....	19
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	24
6.6 SPURIOUS RADIATED EMISSIONS.....	30
6.7 BAND EDGE.....	37
6.8 FREQUENCY STABILITY	42
ANNEX A. TEST INSTRUMENT.....	47
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	48
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	51
ANNEX C.II. EUT OPERATING CONKITIONS.....	53
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST.....	54
ANNEX E. DECLARATION OF SIMILARITY.....	55

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16050014-FCC-R1	NONE	Original	May 09, 2016

2. Customer information

Applicant Name	Quectel Wireless Solutions Co., Ltd.
Applicant Add	Room501,Building 13,No.99 TianZhou Road,Xuhui District,Shanghai,China
Manufacturer	Quectel Wireless Solutions Co., Ltd.
Manufacturer Add	Room501,Building 13,No.99 TianZhou Road,Xuhui District,Shanghai,China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Multi-mode LTE module

Main Model: EC20

Serial Model: EC20 MiniPCle

Date EUT received: March 16, 2016

Test Date(s): March 17 to April 11, 2016

Equipment Category : PCB

Antenna Gain:

GSM850: 1dBi
 PCS1900: 1dBi
 UMTS-FDD Band 5:: 1dBi
 UMTS-FDD Band 4: 1dBi
 UMTS-FDD Band 2: 1dBi
 LTE Band 2: 1dBi
 LTE Band 4: 1dBi
 LTE Band 5: 1dBi
 LTE Band 12: 1dBi
 LTE Band 17: 1dBi

(Note: The radio module will be sold without antenna, this antenna only used limited to ERP/EIRP or radiated spurious emission test.)

Type of Modulation:

GSM / GPRS: GMSK
 EGPRS: GMSK,8PSK
 UMTS-FDD: QPSK, 16QAM, 64QAM
(Note: 16QAM and 64QAM only support UMTS downlink)
 LTE Band: QPSK, 16QAM, 64QAM
(Note: LTE downlink only support 64QAM)

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band 5 TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band 4 TX:1712.4 ~ 1752.6 MHz;
	RX : 2112.4 ~ 2152.6 MHz
RF Operating Frequency (ies):	UMTS-FDD Band 2 TX:1852.4 ~ 1907.6 MHz;
	RX: 1932.4 ~ 1987.6 MHz
	LTE Band 2 TX: 1852.5 ~ 1907.5 MHz; RX : 1932.5 ~ 1987.5 MHz
	LTE Band 4 TX: 1712.5 ~ 1752.5 MHz; RX : 2112.5 ~ 2152.5 MHz
	LTE Band 5 TX: 826.5 ~ 846.5 MHz; RX : 871.5 ~ 891.5 MHz
	LTE Band 12 TX:699.7 ~ 715.3 MHz; RX : 729.7~ 745.3MHz
	LTE Band 17 TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz
	GSM850: 32.34 dBm
Maximum Conducted	PCS1900:28.68 dBm
AV Power to Antenna:	UMTS-FDD Band 5: 23.21 dBm
	UMTS-FDD Band 2: 22.26 dBm
	UMTS-FDD Band 4: 22.30 dBm
	GSM 850: 124CH
	PCS1900: 299CH
Number of Channels:	UMTS-FDD Band 5: 102CH
	UMTS-FDD Band 4: 202CH
	UMTS-FDD Band 2: 277CH
Port:	N/A
Input Power:	Spec: DC 3.8V
Trade Name :	Quectel
GPRS/EGPRS Multi-slot class	8/10/12
FCC ID:	XMR201603EC20

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass

The EUT is a portable device, thus requires SAR evaluation;


Please refer to RF Exposure Evaluation Report: 16050014-FCC-H.

6.2 RF Output Power

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	March 23, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>
§27.50 (c)	c)	EIRP: 30dBm	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---

	<p>frequency was investigated.</p> <ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = 10 log (TX power in Watts/0.001) – the absolute level - Spurious attenuation limit in dB = 43 + 10 Log10 (power out in Watts).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.34	32.01	32.20	31.75±0.75	28.68	28.40	28.42	28.75±0.75
GPRS Multi-Slot Class 8 (1 uplink),GMSK	31.99	32.33	32.15	31.75±0.75	28.41	28.38	28.67	28.75±0.75
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.98	32.05	32.02	31.75±0.75	28.21	28.20	28.45	28.75±0.75
GPRS Multi-Slot Class 12 (4 uplink) GMSK	29.85	29.78	29.85	29.75±0.75	27.84	27.96	27.89	27.75±0.75
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	31.87	32.29	32.20	31.75±0.75	28.36	28.38	28.65	28.75±0.75
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.84	32.11	32.06	31.75±0.75	28.24	28.15	28.45	28.75±0.75
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	29.90	29.84	29.77	29.75±0.75	27.86	27.93	27.85	27.75±0.75
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	26.36	26.35	26.42	26.75±0.75	25.02	24.97	24.90	24.75±0.75
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	26.13	26.15	26.25	26.75±0.75	24.72	24.67	24.51	24.75±0.75
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	26.00	26.06	25.99	25.75±0.75	24.01	23.88	23.74	23.75±0.75

Test Report	16050014-FCC-R1
Page	13 of 55

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

Note: Since GSM mode has higher power, so the test items below were not performed to GPRS and EGPRS mode.

UMTS Mode:

UMTS-FDD Band 5

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	23.21	22.5±1
	4175	835	23.00	22.5±1
	4233	846.6	22.95	22.5±1
HSDPA Subtest1	4132	826.4	22.36	22.5±1
	4175	835	22.58	22.5±1
	4233	846.6	22.45	22.5±1
HSDPA Subtest2	4132	826.4	22.15	22.5±1
	4175	835	22.16	22.5±1
	4233	846.6	22.37	22.5±1
HSDPA Subtest3	4132	826.4	22.15	22.5±1
	4175	835	22.14	22.5±1
	4233	846.6	22.25	22.5±1
HSDPA Subtest4	4132	826.4	22.35	22.5±1
	4175	835	22.31	22.5±1
	4233	846.6	22.26	22.5±1
HSUPA Subtest1	4132	826.4	21.86	22±1
	4175	835	22.53	22±1
	4233	846.6	21.42	22±1
HSUPA Subtest2	4132	826.4	22.27	22±1
	4175	835	21.55	22±1
	4233	846.6	21.43	22±1
HSUPA Subtest3	4132	826.4	22.44	22.5±1
	4175	835	21.88	22.5±1
	4233	846.6	21.56	22.5±1
HSUPA Subtest4	4132	826.4	21.54	22.5±1
	4175	835	21.88	22.5±1
	4233	846.6	22.34	22.5±1
HSUPA Subtest5	4132	826.4	22.36	22±1
	4175	835	21.45	22±1
	4233	846.6	22.44	22±1

UMTS-FDD Band 2

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.26	22.5±1
	9400	1880	22.07	22.5±1
	9538	1907.6	21.93	22.5±1
HSDPA Subtest1	9262	1852.4	22.36	22±1
	9400	1880	21.53	22±1
	9538	1907.6	21.46	22±1
HSDPA Subtest2	9262	1852.4	21.55	22±1
	9400	1880	21.59	22±1
	9538	1907.6	21.58	22±1
HSDPA Subtest3	9262	1852.4	21.56	22±1
	9400	1880	21.46	22±1
	9538	1907.6	21.43	22±1
HSDPA Subtest4	9262	1852.4	21.38	22±1
	9400	1880	21.57	22±1
	9538	1907.6	21.24	22±1
HSUPA Subtest1	9262	1852.4	21.28	22±1
	9400	1880	21.80	22±1
	9538	1907.6	21.23	22±1
HSUPA Subtest2	9262	1852.4	21.34	22±1
	9400	1880	21.55	22±1
	9538	1907.6	21.64	22±1
HSUPA Subtest3	9262	1852.4	21.46	22±1
	9400	1880	21.47	22±1
	9538	1907.6	21.41	22±1
HSUPA Subtest4	9262	1852.4	21.24	22±1
	9400	1880	21.33	22±1
	9538	1907.6	21.53	22±1
HSUPA Subtest5	9262	1852.4	21.26	22±1
	9400	1880	21.29	22±1
	9538	1907.6	21.58	22±1


UMTS-FDD Band 4

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	21.86	22.5±1
	1413	1732.6	22.30	22.5±1
	1512	1752.4	21.77	22.5±1
HSDPA Subtest1	1313	1712.6	21.65	22.5±1
	1413	1732.6	21.53	22.5±1
	1512	1752.4	21.54	22.5±1
HSDPA Subtest2	1313	1712.6	21.59	22.5±1
	1413	1732.6	21.56	22.5±1
	1512	1752.4	21.57	22.5±1
HSDPA Subtest3	1313	1712.6	21.55	22±1
	1413	1732.6	21.36	22±1
	1512	1752.4	21.39	22±1
HSDPA Subtest4	1313	1712.6	21.48	22±1
	1413	1732.6	21.57	22±1
	1512	1752.4	21.53	22±1
HSUPA Subtest1	1313	1712.6	21.43	22±1
	1413	1732.6	21.65	22±1
	1512	1752.4	21.43	22±1
HSUPA Subtest2	1313	1712.6	21.23	22±1
	1413	1732.6	21.48	22±1
	1512	1752.4	21.66	22±1
HSUPA Subtest3	1313	1712.6	21.45	22±1
	1413	1732.6	21.61	22±1
	1512	1752.4	21.47	22±1
HSUPA Subtest4	1313	1712.6	21.35	22±1
	1413	1732.6	21.52	22±1
	1512	1752.4	21.44	22±1
HSUPA Subtest5	1313	1712.6	21.56	22±1
	1413	1732.6	21.58	22±1
	1512	1752.4	21.43	22±1

6.3 Peak-Average Ratio

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	March 23, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>According with KDB 971168 v02r02</p> <ol style="list-style-type: none"> 1. The signal analyzer' s CCDF measurement profile is enabled 2. Frequency = carrier center frequency 3. Measurement BW > Emission bandwidth of signal 4. The signal analyzer was set to collect one million samples to generate the CCDF curve 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal “ RF Burst” trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the “ on time” of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A
 Test Plot Yes (See below) N/A

GSM 1900 PK-AV POWER(PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.56	28.42	3.14
1880	31.26	28.4	2.86
1909.8	31.56	28.68	2.88

UMTS-FDD Band 2 PK-AV POWER(PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	25.35	22.26	3.09
1880	25.96	22.07	3.89
1907.6	25.48	21.93	3.55


UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	26.35	21.86	4.49
1732.6	25.68	22.30	3.38
1752.4	25.66	21.77	3.89

6.4 Occupied Bandwidth

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	March 23, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A

Test Plot Yes (See below) N/A

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	244.0649	318.105
190	836.6	243.7665	318.459
251	848.8	251.1488	322.426

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.4523	322.958
661	1880.0	241.8352	314.149
810	1909.8	243.7575	317.534

UMTS-FDD Band 5 (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1708	4.687
4175	835.0	4.1796	4.731
4233	846.6	4.1627	4.712


UMTS-FDD Band 2 (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1540	4.671
9400	1880.0	4.1573	4.695
9538	1907.6	4.1634	4.703


UMTS-FDD Band 4 (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.1524	4.691
1413	1732.6	4.1654	4.713
1512	1752.4	4.1609	4.696


Test Plots




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz




PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz




Band 5 BW - Low CH 826.6 MHz




Band 5 BW - Mid CH 835.0 MHz




Band 5 BW - High CH 846.4 MHz




Band 2 BW - Low CH 1852.4MHz




Band 2 BW - Mid CH 1880MHz




Band 2 BW - High CH 1907.6MHz



Band 4 BW - Low CH 1852.4MHz



Band 4 BW - Mid CH 1880MHz




Band 4 BW - High CH 1907.6MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25°C
Relative Humidity	57%
Atmospheric Pressure	1024mbar
Test date :	March 24, 2016
Tested By :	Winnie Zhang


Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log(P)$ dB	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data Yes N/A
 Test Plot Yes (See below) N/A

Test Plots


Cellular Band (Part 22H) result




PCS Band (Part24E) result




UMTS-FDD Band 5 (Part 22H)




Band 5 - Low Channel-1




Band 5 - Low Channel-2




Band 5 - Middle Channel-1



Band 5 - Middle Channel-2




Band 5 - High Channel-1




Band 5 - High Channel-2


UMTS-FDD Band 2 (Part 24E)




Band 2 - Low Channel-1




Band 2 - Low Channel-2




Band 2 - Middle Channel-1



Band 2 - Middle Channel-2




Band 2 - High Channel-1



Band 2 - High Channel-2

UMTS-FDD Band 4 (Part 27)



6.6 Spurious Radiated Emissions

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	March 23, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBµV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)
----------------	---

Test Report	16050014-FCC-R1
Page	31 of 55

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-41.38	V	7.95	0.78	-34.21	-13	-21.21
1648.4	-43.14	H	7.95	0.78	-35.97	-13	-22.97
353.6	-51.68	V	6.5	0.3	-45.48	-13	-32.48
726.9	-49.89	H	6.9	0.44	-43.43	-13	-30.43

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-41.65	V	7.95	0.78	-34.48	-13	-21.48
1673.2	-42.55	H	7.95	0.78	-35.38	-13	-22.38
353.1	-52.04	V	6.5	0.3	-45.84	-13	-32.84
735.8	-50.16	H	6.9	0.44	-43.7	-13	-30.70

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-41.74	V	7.95	0.78	-34.57	-13	-21.57
1697.6	-42.69	H	7.95	0.78	-35.52	-13	-22.52
353.9	-50.22	V	6.5	0.3	-44.02	-13	-31.02
736.1	-51.03	H	6.9	0.44	-44.57	-13	-31.57

Note:

- 1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-49.28	V	10.25	2.73	-41.76	-13	-28.76
3700.4	-48.43	H	10.25	2.73	-40.91	-13	-27.91
352.8	-50.84	V	6.5	0.3	-44.64	-13	-31.64
733.9	-51.46	H	6.9	0.44	-45	-13	-32.00

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-50.29	V	10.25	2.73	-42.77	-13	-29.77
3760	-49.57	H	10.25	2.73	-42.05	-13	-29.05
352.6	-50.81	V	6.5	0.3	-44.61	-13	-31.61
733.5	-52.11	H	6.9	0.44	-45.65	-13	-32.65

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-49.76	V	10.36	2.73	-42.13	-13	-29.13
3819.6	-48.17	H	10.36	2.73	-40.54	-13	-27.54
352.4	-50.26	V	6.5	0.3	-44.06	-13	-31.06
733.8	-51.63	H	6.9	0.44	-45.17	-13	-32.17

Note:

- 1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit

UMTS-FDD Band 5 (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-44.61	V	7.95	0.78	-37.44	-13	-24.44
1652.8	-45.25	H	7.95	0.78	-38.08	-13	-25.08
355.1	-50.49	V	6.5	0.3	-44.29	-13	-31.29
738.5	-51.83	H	6.9	0.44	-45.37	-13	-32.37

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-44.58	V	7.95	0.78	-37.41	-13	-24.41
1670	-45.31	H	7.95	0.78	-38.14	-13	-25.14
355.6	-50.46	V	6.5	0.3	-44.26	-13	-31.26
738.3	-51.79	H	6.9	0.44	-45.33	-13	-32.33

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-44.61	V	7.95	0.78	-37.44	-13	-24.44
1693.2	-43.27	H	7.95	0.78	-36.1	-13	-23.1
355.9	-50.42	V	6.5	0.3	-44.22	-13	-31.22
737.5	-51.68	H	6.9	0.44	-45.22	-13	-32.22

Note:

- 1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit

UMTS-FDD Band 2 (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-47.05	V	10.25	2.73	-39.53	-13	-26.53
3704.8	-47.58	H	10.25	2.73	-40.06	-13	-27.06
354.8	-50.32	V	6.5	0.3	-44.12	-13	-31.12
739.1	-51.27	H	6.9	0.44	-44.81	-13	-31.81

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-47.11	V	10.25	2.73	-39.59	-13	-26.59
3760	-47.48	H	10.25	2.73	-39.96	-13	-26.96
354.5	-50.29	V	6.5	0.3	-44.09	-13	-31.09
738.9	-51.33	H	6.9	0.44	-44.87	-13	-31.87

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-47.15	V	10.36	2.73	-39.52	-13	-26.52
3815.2	-47.62	H	10.36	2.73	-39.99	-13	-26.99
355.6	-50.38	V	6.5	0.3	-44.18	-13	-31.18
738.7	-51.41	H	6.9	0.44	-44.95	-13	-31.95

Note:

- 1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit

UMTS-FDD Band 4 (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.38	V	10.07	2.52	-38.83	-13	-25.83
3424.8	-47.82	H	10.07	2.52	-40.27	-13	-27.27
207.3	-51.65	V	6.4	0.26	-45.51	-13	-32.51
611.4	-52.76	H	7.1	0.42	-46.08	-13	-33.08

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-46.25	V	10.09	2.52	-38.68	-13	-25.68
3480	-47.31	H	10.09	2.52	-39.74	-13	-26.74
207.8	-51.55	V	6.4	0.26	-45.41	-13	-32.41
611.2	-52.48	H	7.1	0.42	-45.8	-13	-32.80

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-46.33	V	10.09	2.52	-38.76	-13	-25.76
3505.2	-47.18	H	10.09	2.52	-39.61	-13	-26.61
208.1	-51.47	V	6.4	0.26	-45.33	-13	-32.33
611.5	-52.32	H	7.1	0.42	-45.64	-13	-32.64

Note:


1, The testing has been conformed to $10 \times 1752.6 \text{ MHz} = 17.526 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

6.7 Band Edge

Temperature	24°C
Relative Humidity	56%
Atmospheric Pressure	1023mbar
Test date :	March 23, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup			
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data Yes N/A

Test Plot Yes (See below) N/A

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9925	-19.78	-13
849.0225	-18.81	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9800	-16.22	-13
1910.0150	-17.94	-13

UMTS-FDD Band 5 (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
822.900	-29.45	-13
849.100	-27.67	-13


UMTS-FDD Band 2 (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.875	-32.46	-13
1910.000	-30.15	-13

UMTS-FDD Band 4 (Part 27)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.125	-30.00	-13
1755.025	-25.46	-13

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.18/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.22/3)=4.0+0.3=4.3dB




PCS Band - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(3.22/3)=4.5+0.3=4.8dB




PCS Band - High Channel

Note: Offset=Cable loss (4.5) + 10log
(3.17/3)=4.5+0.2=4.7dB




UMTS-FDD Band 5- Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.87/30)=4.0+1.9=5.9dB




UMTS-FDD Band 5- High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.12/30)=4.0+2.0=6.0 dB




UMTS-FDD Band 2- Low Channel

Note: Offset=Cable loss (4.5) + 10log
(46.71/30)=4.5+1.9=6.4 dB




UMTS-FDD Band 2- High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.03/30)=4.5+2.0=6.5 dB



UMTS-FDD Band 4 - Low Channel

Note: Offset=Cable loss (4.5) + 10log
 (46.91/30)=4.5+1.9=6.4 dB




UMTS-FDD Band 4 - High Channel

Note: Offset=Cable loss (4.5) + 10log
 (46.96/30)=4.5+2.0=6.5 dB

6.8 Frequency Stability

Temperature	22°C
Relative Humidity	51%
Atmospheric Pressure	1009mbar
Test date :	April 09, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below: Frequency Tolerance for Transmitters in the Public Mobile Services	<input checked="" type="checkbox"/>																																
		<table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th> <th>Base, fixed (ppm)</th> <th>Mobile ≤ 3 watts (ppm)</th> <th>Mobile ≤ 3 watts (ppm)</th> </tr> </thead> <tbody> <tr> <td>25 to 50</td> <td>20.0</td> <td>20.0</td> <td>50.0</td> </tr> <tr> <td>50 to 450</td> <td>5.0</td> <td>5.0</td> <td>50.0</td> </tr> <tr> <td>45 to 512</td> <td>2.5</td> <td>5.0</td> <td>.0</td> </tr> <tr> <td>821 to 896</td> <td>1.5</td> <td>2.5</td> <td>2.5</td> </tr> <tr> <td>928 to 29.</td> <td>5.0</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>929 to 960.</td> <td>1.5</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>2110 to 2220</td> <td>10.0</td> <td>N/A</td> <td>N/A</td> </tr> </tbody> </table>		Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A
		Frequency Range (MHz)		Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																													
		25 to 50		20.0	20.0	50.0																													
		50 to 450		5.0	5.0	50.0																													
		45 to 512		2.5	5.0	.0																													
		821 to 896		1.5	2.5	2.5																													
		928 to 29.		5.0	N/A	N/A																													
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.																																			
																																			
Test setup																																			

Test Report	16050014-FCC-R1
Page	43 of 55

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	-16	0.0191	2.5
0		-14	0.0167	2.5
10		-15	0.0179	2.5
20		-11	0.0131	2.5
30		-14	0.0167	2.5
40		-17	0.0203	2.5
50		-20	0.0239	2.5
55		-21	0.0251	2.5
25		4.2	-20	0.0239
	3.5	-18	0.0215	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	-23	0.0122	2.5
0		-20	0.0106	2.5
10		-14	0.0074	2.5
20		-10	0.0053	2.5
30		-14	0.0074	2.5
40		-20	0.0106	2.5
50		-16	0.0085	2.5
55		-21	0.0112	2.5
25		4.2	-21	0.0112
	3.5	-22	0.0117	2.5

UMTS-FDD Band 5 (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	14	0.0120	2.5
0		12	0.0072	2.5
10		6	0.0060	2.5
20		6	0.0036	2.5
30		6	0.0108	2.5
40		12	0.0096	2.5
50		11	0.0084	2.5
55		14	0.0072	2.5
25	4.2	12	0.0132	2.5
	3.5	14	0.0120	2.5

UMTS-FDD Band 2 (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	11	0.0016	2.5
0		9	0.0021	2.5
10		7	0.0011	2.5
20		5	0.0016	2.5
30		6	0.0027	2.5
40		8	0.0021	2.5
50		10	0.0032	2.5
55		10	0.0032	2.5
25	4.2	8	0.0037	2.5
	3.5	9	0.0043	2.5

UMTS-FDD Band 4 (Part 27)


Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	6	0.0035	2.5
0		7	0.0040	2.5
10		6	0.0035	2.5
20		10	0.0058	2.5
30		7	0.0040	2.5
40		4	0.0023	2.5
50		10	0.0058	2.5
55		9	0.0052	2.5
25		4.2	8	0.0046
	3.5	10	0.0058	2.5

Annex A. TEST INSTRUMENT


Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/16/2015	09/15/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-1000/2000-S	AM 4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo




EUT- Front View




EUT -Rear Side


Annex B.ii. Photograph: EUT Internal Photo



Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Lenovo Laptop	E40	CY1121013521

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	CY1121013521

Test Report	16050014-FCC-R1
Page	53 of 55

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	16050014-FCC-R1
Page	54 of 55

Annex D. User Manual / Block Diagram / Schematics / Partlist

N/A

Annex E. DECLARATION OF SIMILARITY

Quectel Wireless Solutions Co., Ltd

Statement

We Quectel Wireless Solutions Co., Ltd declare the following models as series application.

Name: Multi-mode LTE Module

Model number:EC20-A/EC20-A Mini PCIe

EC20-A and EC20-A Mini PCIe Module are both Multi-mode LTE modules. EC20-A Mini PCIe Module makes up of EC20-A module and PCIe transferred board. The transferred board switches EC20-A module to follow PCI Express Mini Card 1.2 standard connector protocol. No any other internal changes in EC20-A module.

We hereby state that two models are identical in interior structure and components, and just connector interface is different for the marketing requirement.

Your assistance on this matter is highly appreciated.

Sincerely,

Name: Johnny

Title: Test Engineer



Signature: