



RF Exposure Evaluation Declaration

FCC ID: XMR2020BG95M2
Application: Quectel Wireless Solutions Company Limited
Product: LTE Cat M1 & Cat NB2 Module
Model No.: BG95-M2
Brand Name: Quectel
FCC Rule Part(s): Part 2.1091
Test Procedure(s): KDB 447498 D01v06
Test Date: November 29, 2021 ~ January 13, 2022

Reviewed By:

Sunny Sun

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2111RSU084-U3	Rev. 01	Initial Report	01-30-2022	Valid

1.4. Product Information

Product Name	LTE Cat M1 & Cat NB2 Module
Model No.	BG95-M2
Brand Name	Quectel
IMEI	Conducted Measurement:863859046086315 Radiated Measurement: 863859046094152
Operating Temp.	-40 ~ 85 °C
Supply Voltage	2.6 ~ 4.8Vdc, typical 3.3Vdc
CAT-M Band	Band 2, 4, 5, 8, 12, 13, 25, 26, 66, 85
NB-IoT Band	Band 2, 4, 5, 8, 12, 13, 25, 66, 71, 85
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	LTE Cat M1 & Cat NB2 Module
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Tune-up Power (dBm)	Antenna Gain (dBi)	EIRP or ERP (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
LTE B8	897.5 ~ 900.5	22.00	2.46	22.31	0.0339	1.0000

Appendix A – EUT Photograph

Refer to “2111RSU084-UE” file.

The End