




# MEASUREMENT REPORT

## FCC PART 27

---

**FCC ID:** XMR2020EM120RGL  
**Application:** Quectel Wireless Solutions Company Limited  
**Application Type:** Certification  
**Product:** LTE-A Cat 12 M.2 Module  
**Model No.:** EM120R-GL  
**Brand Name:**   
**FCC Rule Part(s):** Part 27 Subpart D  
**Classification:** PCB Licensed Transmitter (PCB)  
**Test Procedure(s):** ANSI C63.26-2015, KDB 971168 D01v03r01  
**Test Date:** June 12 ~ August 17, 2020

Reviewed By:   
\_\_\_\_\_  
( Sunny Sun )  
Approved By:   
\_\_\_\_\_  
( Robin Wu )



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.26-2015. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

Report No.	Version	Description	Issue Date	Note
2006RSU085-U5	Rev. 01	Initial Report	08-20-2020	Valid

---

## CONTENTS

Description	Page
<b>1. INTRODUCTION .....</b>	<b>6</b>
1.1. Scope .....	6
1.2. MRT Test Location .....	6
<b>2. PRODUCT INFORMATION .....</b>	<b>7</b>
2.1. Equipment Description .....	7
2.2. Product Specification Subjective to this Report .....	7
2.3. Description of Available Antennas .....	8
2.4. EMI Suppression Device(s)/Modifications .....	8
2.5. Maximum Power, Frequency Tolerance, and Emission Designator .....	8
2.6. Configuration of Tested System .....	9
2.7. Test Environment Condition .....	9
<b>3. TEST EQUIPMENT CALIBRATION DATE.....</b>	<b>10</b>
<b>4. MEASUREMENT UNCERTAINTY.....</b>	<b>12</b>
<b>5. TEST RESULT.....</b>	<b>13</b>
5.1. Summary .....	13
5.2. Occupied Bandwidth.....	14
5.2.1. Test Limit .....	14
5.2.2. Test Procedure.....	14
5.2.3. Test Setting .....	14
5.2.4. Test Setup .....	14
5.2.5. Test Result .....	15
5.3. Frequency Stability Measurement.....	17
5.3.1. Test Limit .....	17
5.3.2. Test Procedures Used.....	17
5.3.3. Test Setting .....	17
5.3.4. Test Setup .....	18
5.3.5. Test Result .....	19
5.4. Equivalent Isotropically Radiated Power Measurement .....	20
5.4.1. Test Limit .....	20
5.4.2. Test Procedures Used.....	20
5.4.3. Test Setting .....	20
5.4.4. Test Setup .....	21
5.4.5. Test Result .....	22
5.5. Band Edge Measurement .....	25

5.5.1.	Test Limit .....	25
5.5.2.	Test Procedure Used.....	25
5.5.3.	Test Setting .....	25
5.5.4.	Test Setup .....	26
5.5.5.	Test Result .....	27
5.6.	Conducted Spurious Emissions.....	30
5.6.1.	Test Limit .....	30
5.6.2.	Test Procedure Used.....	30
5.6.3.	Test Setting .....	30
5.6.4.	Test Setup .....	31
5.6.5.	Test Result .....	32
5.7.	Radiated Spurious Emissions Measurements .....	34
5.7.1.	Test Limit .....	34
5.7.2.	Test Procedure Used.....	34
5.7.3.	Test Setting .....	34
5.7.4.	Test Setup .....	35
5.7.5.	Test Result .....	36
<b>6.</b>	<b>CONCLUSION .....</b>	<b>37</b>
	<b>Appendix A - Test Setup Photograph .....</b>	<b>38</b>
	<b>Appendix B - EUT Photograph.....</b>	<b>39</b>

## General Information

<b>Applicant:</b>	Quectel Wireless Solutions Company Limited
<b>Applicant Address:</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
<b>Manufacturer:</b>	Quectel Wireless Solutions Company Limited
<b>Manufacturer Address:</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
<b>Test Site:</b>	MRT Technology (Suzhou) Co., Ltd
<b>Test Site Address:</b>	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China

### Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is an FCC accredited testing laboratory (MRT Designation No. CN1166) on the FCC website.
- MRT facility is an ISED recognized testing laboratory (MRT Reg. No. CN0001) on the ISED website.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the A2LA under the A2LA Program (Cert. No. 3628.01) and CNAS under the CNAS Program (Cert. No. L10551) in EMC, Safety, Radio, Telecommunications and SAR testing.

## 1. INTRODUCTION

### 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

### 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name:	LTE-A Cat 12 M.2 Module
Model No.:	EM120R-GL
Brand Name:	<b>QUECTEL</b>
IMEI:	864292050003514
Single Band:	Band 2, 4, 5, 7, 12, 13, 14, 25, 26, 30, 38, 41, 48, 66
Intra-Band:	CA_41C
Category:	Category 12
Operating Temperature:	-25 ~ 75 °C
Power Type:	3.1 ~ 4.4Vdc, typical 3.7Vdc

### 2.2. Product Specification Subjective to this Report

FDD Tx Frequency Range:	Band 30: 2305 ~ 2315 MHz
FDD Rx Frequency Range:	Band 30: 2350 ~ 2360 MHz
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM (DL)

Note 1: For other features of this EUT, test report will be issued separately.

Note 2: The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

### 2.3. Description of Available Antennas

Technology	Frequency Range (MHz)	Antenna Type	Max Peak Gain (dBi)
LTE Band 2	1850 ~ 1910	Dipole	1.15
LTE Band 4	1710 ~ 1755		-0.50
LTE Band 5	824 ~ 849		1.85
LTE Band 7	2500 ~ 2570		1.32
LTE Band 12	699 ~ 716		-2.43
LTE Band 13	777 ~ 787		-0.10
LTE Band 14	788 ~ 798		2.40
LTE Band 25	1850 ~ 1915		1.15
LTE Band 26	814 ~ 849		1.85
LTE Band 30	2305 ~ 2315		-3.64
LTE Band 38	2570 ~ 2620		0.93
LTE Band 41	2496 ~ 2690		0.93
LTE Band 48	3550 ~ 3700		-3.37
LTE Band 66	1710 ~ 1780		-0.50

Note: All antenna information (Antenna type and Peak Gain) is provided by the manufacturer.

### 2.4. EMI Suppression Device(s)/Modifications


No EMI suppression device(s) were added and/or no modifications were made during testing.

### 2.5. Maximum Power, Frequency Tolerance, and Emission Designator

LTE Band 14		QPSK			16QAM			64QAM		
BW (MHz)	Feq. (MHz)	Designator	Tolerance (ppm)	Max Power Density (W/5MHz)	Designator	Tolerance (ppm)	Max Power Density (W/5MHz)	Designator	Tolerance (ppm)	Max Power Density (W/5MHz)
5	2305 ~ 2315	4M45G7D	-	0.2203	4M46W7D	-	0.1782	4M47W7D	-	0.17824
10	2310	8M93G7D	0.0053	0.2280	8M92W7D	-	0.1945	8M92W7D	-	0.19454



## 2.6. Configuration of Tested System



## 2.7. Test Environment Condition

Ambient Temperature	15°C~35°C
Relative Humidity	20%RH ~75%RH

### 3. TEST EQUIPMENT CALIBRATION DATE

#### Radiated Emission - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2021/08/01
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2020/11/07
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2020/09/03
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2020/11/10
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2021/03/31
Broad Band Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2020/10/13
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2021/02/23
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2020/11/15
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
EMC Cable	HUBER+SUHN ER	SF126-2M	MRTSUE06732	1 year	2021/04/11
Thermohyrometer	Testo	608-H1	MRTSUE06403	1 year	2021/08/08
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2021/04/30

#### Radiated Emission - AC2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Keysight	N9038A	MRTSUE06125	1 year	2021/08/01
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2020/11/07
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2020/11/10
Bilog Period Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2020/10/13
Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06171	1 year	2020/10/27
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2021/02/23
Broadband Coaxial Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2020/11/15
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
EMC Cable	HUBER+SUHN ER	SF126-2M	MRTSUE06733	1 year	2021/04/10
Temperature/Humidity Meter	Minggao	ETH529	MRTSUE06170	1 year	2020/12/15
Anechoic Chamber	RIKEN	Chamber-AC2	MRTSUE06213	1 year	2021/04/30

## Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2021/04/15
EXA Signal Analyzer	Keysight	N9010B	MRTSUE06452	1 year	2021/07/11
Signal Analyzer	R&S	FSV40	MRTSUE06218	1 year	2021/04/15
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2020/11/07
Power Meter	Agilent	U2021XA	MRTSUE06030	1 year	2020/11/18
DC Power Supply	GWINSTEK	DPS-3303C	MRTSUE06064	N/A	N/A
True RMS Clamp Meter	Fluke	319	MRTSUE06080	1 year	2021/05/06
Directional Coupler	Agilent	87301D	MRTSUE06082	1 year	2021/03/25
Attenuator	MVE	6dB	MRTSUE06534	1 year	2020/12/12
Attenuator	MVE	10dB	MRTSUE06543	1 year	2020/12/12
Temperature & Humidity Chamber	BAOYT	BYH-150CL	MRTSUE06051	1 year	2020/11/07
Thermohygrometer	testo	608-H1	MRTSUE06401	1 year	2021/08/08

Software	Version	Function
EMI Software	V3	EMI Test Software

#### 4. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

<b>Radiated Emission Measurement</b>
Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): Horizontal: 9kHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 9kHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
<b>Spurious Emissions, Conducted</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.78dB
<b>Output Power</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.13dB
<b>Power Spectrum Density</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 1.15dB
<b>Occupied Bandwidth</b>
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ): 0.28%

## 5. TEST RESULT

### 5.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	Conducted	Pass	Section 5.2
2.1055, 27.54	Frequency Stability	Within the band		Pass	Section 5.3
27.50(a)(3)	Equivalent Isotropic Radiated Power Density	< 250mW/5MHz		Pass	Section 5.4
2.1051, 27.53(a)(4)	Band Edge	Refer to section 5.5		Pass	Section 5.5, 5.6
2.1051, 27.53(a)(4)	Spurious Emission	< 70 + 10log10 (P <sub>[Watts]</sub> )			
2.1053, 27.53(a)(4)	Spurious Emissions	< 70 + 10log10 (P <sub>[Watts]</sub> )	Radiated	Pass	Section 5.7

#### Notes:

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) All supported modulation types were evaluated. The worst-case emission of modulation was selected. Therefore, the Frequency Stability, Occupied Bandwidth, Channel Band Edge, Radiated & Conducted Spurious Emission were presented in the test report.
- 3) This report is supplemented to MRT Original "2006RSU008-U5" Report, FCC ID: XMR2020EM160RGL updating product name and model number.

## 5.2. Occupied Bandwidth

### 5.2.1. Test Limit

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.


### 5.2.2. Test Procedure

ANSI C63.26-2015 - Section 5.4

### 5.2.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency
2. RBW = The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

### 5.2.4. Test Setup




**5.2.5. Test Result**


Product	LTE-A Cat 12 M.2 Module	Test Engineer	Candy Luo
Test Date	2020/06/22	Test Site	SR6
Test Band	Band 30		

Modulation	Frequency (MHz)	Bandwidth (MHz)	99% Bandwidth (MHz)
QPSK	2310	5	4.45
		10	8.93
16QAM	2310	5	4.46
		10	8.92
64QAM	2310	5	4.47
		10	8.92


**99% Bandwidth - QPSK**



**99% Bandwidth - 16QAM**



**99% Bandwidth - 64QAM**





### **5.3. Frequency Stability Measurement**

#### **5.3.1. Test Limit**

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

#### **5.3.2. Test Procedures Used**

ANSI C63.26-2015 - Section 5.6

#### **5.3.3. Test Setting**

##### **Frequency Stability Under Temperature Variations:**


The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to highest. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C decreased per stage until the lowest temperature reached.

##### **Frequency Stability Under Voltage Variations:**

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ( $\pm 15\%$ ) and endpoint, record the maximum frequency change.

### 5.3.4. Test Setup



**5.3.5. Test Result**

Product	LTE-A Cat 12 M.2 Module	Temperature	-30 ~ 50°C
Test Engineer	Candy Luo	Relative Humidity	53%
Test Site	TR3	Test Date	2020/06/19
Test Band	LTE Band 30		

Voltage (%)	Power (VAC)	Temp (°C)	Frequency Tolerance (ppm)
100%	3.7	- 30	0.0044
		- 20	0.0044
		- 10	0.0048
		0	0.0044
		+ 10	0.0053
		+ 20 (Ref)	0.0044
		+ 30	0.0034
		+ 40	0.0043
		+ 50	0.0047
115%	4.2	+ 20	0.0032
85%	3.1	+ 20	0.0051

## 5.4. Equivalent Isotropically Radiated Power Measurement

### 5.4.1. Test Limit

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, except that for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth

### 5.4.2. Test Procedures Used

ANSI C63.26-2015 - Section 5.2.4.4.2 & 5.2.5.5

### 5.4.3. Test Setting

When the fundamental condition for average power measurements cannot be realized (i.e., the EUT cannot be configured to transmit at full-power on a continuous basis (i.e., duty cycle < 98%) and the instrumentation cannot be configured to measure only during active full-power transmissions), then the following procedure can be used if the EUT duty cycle is constant (i.e., duty cycle variations are less than or equal to  $\pm 2\%$ ).

- a) Set span to  $2 \times$  to  $3 \times$  the OBW.
- b) Set RBW = 1% to 5% of the OBW.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Set number of measurement points in sweep  $\geq 2 \times$  span / RBW.
- e) Sweep time:
  - 1) Set = auto-couple, or
  - 2) Set  $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$  for single sweep (automation-compatible) measurement.
- f) Detector = power averaging (rms).
- g) Set sweep trigger to "free run."
- h) Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple.

To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time.

i) Using the marker function to identify the maximum PSD.

j) Add  $10 \log (1/\text{duty cycle})$  to the measured power level to compute the average power during continuous transmission. For example, add  $[10 \log (1/0.25)] = 6 \text{ dB}$  if the duty cycle is a constant 25%.

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation (1) as follows:

$$\text{ERP or EIRP} = \text{PMeas} + \text{GT} \quad (1)$$

where


ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as PMeas, e.g., dBm or dBW)

PMeas measured transmitter output power or PSD, in dBm or dBW

GT gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

For devices utilizing multiple antennas, see 6.4 for guidance with respect to determining the effective array transmit antenna gain term to be used in the above equation.

#### 5.4.4. Test Setup



**5.4.5. Test Result**

Product	LTE-A Cat 12 M.2 Module	Test Engineer	Candy Luo
Test Date	2020/08/17	Test Site	SR6
Test Band	LTE Band 30		

Channel No.	Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Power Density (dBm/5MHz)	EIRP Density (dBm/5MHz)	Limit (dBm/5MHz)
<b>QPSK</b>							
27685	2307.5	5	1	0	23.43	19.79	< 23.98
27710	2310.0				23.07	19.43	< 23.98
27735	2312.5				23.21	19.57	< 23.98
27685	2307.5	5	1	12	23.11	19.47	< 23.98
27710	2310.0				23.35	19.71	< 23.98
27735	2312.5				23.06	19.42	< 23.98
27685	2307.5	5	1	24	23.35	19.71	< 23.98
27710	2310.0				23.00	19.36	< 23.98
27735	2312.5				23.04	19.40	< 23.98
27685	2307.5	5	25	0	23.03	19.39	< 23.98
27710	2310.0				23.10	19.46	< 23.98
27735	2312.5				23.08	19.44	< 23.98
27710	2310.0	10	1	0	23.54	19.90	< 23.98
			1	24	23.46	19.82	< 23.98
			1	49	23.58	19.94	< 23.98
			50	0	23.06	19.42	< 23.98

Note: The EIRP Power Density (dBm/5MHz) = Power Density (dBm) + Antenna Gain (dBi)

Channel No.	Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Power Density (dBm/5MHz)	EIRP Density (dBm/5MHz)	Limit (dBm/5MHz)
16QAM							
27685	2307.5	5	1	0	22.22	18.58	< 23.98
27710	2310.0				22.11	18.47	< 23.98
27735	2312.5				21.87	18.23	< 23.98
27685	2307.5	5	1	12	21.88	18.24	< 23.98
27710	2310.0				22.51	18.87	< 23.98
27735	2312.5				21.81	18.17	< 23.98
27685	2307.5	5	1	24	22.04	18.40	< 23.98
27710	2310.0				21.93	18.29	< 23.98
27735	2312.5				21.63	17.99	< 23.98
27685	2307.5	5	25	0	21.36	17.72	< 23.98
27710	2310.0				21.38	17.74	< 23.98
27735	2312.5				21.40	17.76	< 23.98
27710	2310.0	10	1	0	22.64	19.00	< 23.98
			1	24	22.89	19.25	< 23.98
			1	49	22.85	19.21	< 23.98
			50	0	21.33	17.69	< 23.98
Note: The EIRP Power Density (dBm/5MHz) = Power Density (dBm) + Antenna Gain (dBi)							

Channel No.	Frequency (MHz)	Channel Bandwidth (MHz)	RB Size	RB Offset	Power Density (dBm/5MHz)	EIRP Density (dBm/5MHz)	Limit (dBm/5MHz)
64QAM							
27685	2307.5	5	1	0	21.81	18.17	< 23.98
27710	2310.0				21.96	18.32	< 23.98
27735	2312.5				21.37	17.73	< 23.98
27685	2307.5	5	1	12	22.23	18.59	< 23.98
27710	2310.0				22.18	18.54	< 23.98
27735	2312.5				21.20	17.56	< 23.98
27685	2307.5	5	1	24	22.20	18.56	< 23.98
27710	2310.0				22.06	18.42	< 23.98
27735	2312.5				21.20	17.56	< 23.98
27685	2307.5	5	25	0	20.19	16.55	< 23.98
27710	2310.0				20.29	16.65	< 23.98
27735	2312.5				20.24	16.60	< 23.98
27710	2310.0	10	1	0	21.67	18.03	< 23.98
			1	24	21.91	18.27	< 23.98
			1	49	21.90	18.26	< 23.98
			50	0	18.37	14.73	< 23.98
Note: The EIRP Power Density (dBm/5MHz) = Power Density (dBm) + Antenna Gain (dBi)							



## 5.5. Band Edge Measurement

### 5.5.1. Test Limit

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

- (1) By a factor of not less than:  $43 + 10 \log (P)$  dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than  $55 + 10 \log (P)$  dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than  $61 + 10 \log (P)$  dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than  $67 + 10 \log (P)$  dB on all frequencies between 2328 and 2337 MHz;
- (2) By a factor of not less than  $43 + 10 \log (P)$  dB on all frequencies between 2300 and 2305 MHz,  $55 + 10 \log (P)$  dB on all frequencies between 2296 and 2300 MHz,  $61 + 10 \log (P)$  dB on all frequencies between 2292 and 2296 MHz,  $67 + 10 \log (P)$  dB on all frequencies between 2288 and 2292 MHz, and  $70 + 10 \log (P)$  dB below 2288 MHz;
- (3) By a factor of not less than  $43 + 10 \log (P)$  dB on all frequencies between 2360 and 2365 MHz, and not less than  $70 + 10 \log (P)$  dB above 2365 MHz.

### 5.5.2. Test Procedure Used

ANSI C63.26-2015 - Section 5.7


### 5.5.3. Test Setting

1. Set the analyzer frequency to low or high channel
2.  $RBW \geq$  The nominal RBW shall be in the range of 1% of the anticipated OBW (in the 1MHz band immediately outside and adjacent to the band edge). For improvement of the accuracy in the measurement of the average power of a noise-like emission, a RBW narrower than the specified reference bandwidth can be used (generally limited to no less than 1% of the OBW), provided that a subsequent integration is performed over the full required measurement bandwidth. This integration should be performed using the spectrum analyzer's band power functions.
3.  $VBW \geq 3 * RBW$
4. Sweep time = auto
5. Detector = power averaging (rms)
6. Set sweep trigger to "free run."
7. User gate triggered such that the analyzer only sweeps when the device is transmitting at full

power


- Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time.

#### 5.5.4. Test Setup




### 5.5.5. Test Result

Product	LTE-A Cat 12 M.2 Module	Test Engineer	Gordon Qi
Test Date	2020/06/27	Test Site	SR6
Test Band	Band 30	Test Result	Pass




## 10MHz Channel Bandwidth 1RB


## Lower ACP




## Lower Extended Band Edge



## Upper ACP




## Upper Extended Band Edge




### 5MHz Channel Bandwidth Full RB


#### Lower ACP




#### Lower Extended Band Edge



#### Upper ACP




#### Upper Extended Band Edge




### 10MHz Channel Bandwidth Full RB


#### Lower ACP




#### Lower Extended Band Edge



#### Upper ACP



#### Upper Extended Band Edge



## **5.6. Conducted Spurious Emissions**

### **5.6.1. Test Limit**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst-case configuration. All modes of operation were investigated and the worst-case configuration results are reported in this section.

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $70 + 10 \log (P)$  dB.

### **5.6.2. Test Procedure Used**


ANSI C63.26-2015 - Section 5.7

### **5.6.3. Test Setting**

1. Set the analyzer frequency to low, mid, high channel.
2. RBW = 1MHz
3. VBW  $\geq 3 \cdot$ RBW
4. Sweep time = auto
5. Detector = power averaging (rms)
6. Set sweep trigger to "free run."
7. User gate triggered such that the analyzer only sweeps when the device is transmitting at full power.
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple.

To accurately determine the average power over the on and off time of the transmitter, it can be necessary to increase the number of traces to be averaged above 100, or if using a manually configured sweep time, increase the sweep time.


### 5.6.4. Test Setup




**5.6.5. Test Result**

Product	LTE-A Cat 12 M.2 Module	Test Engineer	Candy Luo
Test Date	2020/08/04	Test Site	SR6
Test Band	Band 30	Test Result	Pass

Channel	Frequency (MHz)	Channel Bandwidth (MHz)	Frequency Range (MHz)	Max Spurious Emissions (dBm)	Limit (dBm)	Result
<b>QPSK</b>						
27685	2307.5	5	30 ~ 25000	-45.82	≤ -40.00	Pass
27710	2310.0	5	30 ~ 25000	-46.78	≤ -40.00	Pass
27735	2312.5	5	30 ~ 25000	-46.40	≤ -40.00	Pass
27710	2310.0	10	30 ~ 25000	-44.81	≤ -40.00	Pass







## **5.7. Radiated Spurious Emissions Measurements**

### **5.7.1. Test Limit**

Out of band emissions: The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $70 + 10 \log (P)$  dB.

$E$  (dB $\mu$ V/m) = EIRP (dBm) -  $20 \log D$  + 104.8; where D is the measurement distance in meters. The emission limit equal to 55.3dB $\mu$ V/m.

### **5.7.2. Test Procedure Used**


ANSI C63.26-2015 - Section 5.2.7 & 5.5

### **5.7.3. Test Setting**


1. RBW = 1MHz
2. VBW  $\geq$  3\*RBW
3. Sweep time  $\geq$   $10 \times$  (number of points in sweep)  $\times$  (transmission symbol period)
4. Detector = Peak
5. Trace mode = max hold
6. The trace was allowed to stabilize

### 5.7.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



### 5.7.5. Test Result

Product	LTE-A Cat 12 M.2 Module	Test Engineer	Buter Shi
Test Site	AC1	Test Date	2020/07/02
Test Mode	LTE Band 30 - 5MHz Bandwidth, 1RB, QPSK		

Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level(dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
<b>Bottom CH 27685 (2307.5MHz)</b>							
309.4	29.1	20.3	49.4	55.3	-5.9	Peak	Horizontal
361.3	26.9	21.3	48.2	55.3	-7.1	Peak	Horizontal
311.3	20.3	20.4	40.7	55.3	-14.6	Peak	Vertical
361.3	21.2	21.3	42.5	55.3	-12.8	Peak	Vertical
4612.0	31.5	3.4	34.9	55.3	-20.4	Peak	Horizontal
6916.0	31.3	9.9	41.2	55.3	-14.1	Peak	Horizontal
4612.0	31.7	3.4	35.1	55.3	-20.2	Peak	Vertical
6916.0	38.5	5.9	44.4	55.3	-10.9	Peak	Vertical
<b>Middle CH 27710 (2310.0MHz)</b>							
311.8	30.2	20.4	50.6	55.3	-4.7	Peak	Horizontal
361.7	26.8	21.3	48.1	55.3	-7.2	Peak	Horizontal
309.8	20.7	20.3	41.0	55.3	-14.3	Peak	Vertical
360.8	21.3	21.3	42.6	55.3	-12.7	Peak	Vertical
4616.0	31.6	3.4	35.0	55.3	-20.3	Peak	Horizontal
6924.0	31.2	10.2	41.4	55.3	-13.9	Peak	Horizontal
4616.0	31.0	3.4	34.4	55.3	-20.9	Peak	Vertical
6924.5	38.8	6.1	44.9	55.3	-10.4	Peak	Vertical
<b>Top CH 27735 (2312.5MHz)</b>							
311.3	29.9	20.4	50.3	55.3	-5.0	Peak	Horizontal
359.3	27.7	21.3	49.0	55.3	-6.3	Peak	Horizontal
311.8	22.0	20.4	42.4	55.3	-12.9	Peak	Vertical
361.3	21.0	21.3	42.3	55.3	-13.0	Peak	Vertical
4620.0	31.4	3.4	34.8	55.3	-20.5	Peak	Horizontal
5513.0	32.4	4.6	37.0	55.3	-18.3	Peak	Horizontal
4620.0	31.9	3.4	35.3	55.3	-20.0	Peak	Vertical
5513.5	32.4	4.6	37.0	55.3	-18.3	Peak	Vertical

Note: Measure Level (dBm) = Reading Level (dBm) + Factor (dB).

## 6. CONCLUSION

The data collected relate only the item(s) tested and show that unit is compliance with FCC Rules.

## **Appendix A - Test Setup Photograph**

Refer to "2006RSU085-UT" file.

## **Appendix B - EUT Photograph**

Refer to "2006RSU085-UE" file.