





# MEASUREMENT REPORT

## FCC PART 96

---

**FCC ID:** XMR2020EM120RG2  
**Application:** Quectel Wireless Solutions Company Limited  
  
**Application Type:** Class II Permissive Change  
**Product:** LTE-A Cat 12 M.2 Module  
**Model No.:** EM120R-GL  
**Brand Name:** Quectel  
**FCC Rule Part(s):** Part 96  
**Test Procedure(s):** ANSI C63.26: 2015  
**Test Date:** January 10 ~ 24, 2021

Reviewed By:   
Sunny Sun  
Approved By:   
Robin Wu



The test results relate only to the samples tested.  
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.26-2015. Test results reported herein relate only to the item(s) tested.  
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
2101RSU061-U1	Rev. 01	Initial Report	02-04-2021	Valid

---

## CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1. Applicant .....	4
1.2. Manufacturer .....	4
1.3. Testing Facility.....	4
<b>2. PRODUCT INFORMATION .....</b>	<b>5</b>
2.1. Equipment Description .....	5
2.2. Product Specification Subjective to this Report .....	5
2.3. Test Methodology .....	5
2.4. EMI Suppression Device(s)/Modifications.....	5
2.5. Configuration of Tested System .....	6
2.6. Test Environment Condition.....	6
<b>3. TEST EQUIPMENT CALIBRATION DATE.....</b>	<b>7</b>
<b>4. MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>5. TEST RESULT .....</b>	<b>9</b>
5.1. Summary.....	9
5.2. Radiated Spurious Emissions Measurements .....	10
5.2.1. Test Limit .....	10
5.2.2. Test Procedure Used .....	10
5.2.3. Test Setting.....	10
5.2.4. Test Setup .....	10
5.2.5. Test Result.....	12
<b>6. CONCLUSION .....</b>	<b>13</b>
<b>Appendix A - Test Setup Photograph.....</b>	<b>14</b>
<b>Appendix B - EUT Photograph.....</b>	<b>15</b>

## 1. GENERAL INFORMATION

### 1.1. Applicant

Quectel Wireless Solutions Company Limited  
 Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District,  
 Shanghai, China 200233

### 1.2. Manufacturer

Quectel Wireless Solutions Company Limited  
 Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District,  
 Shanghai, China 200233

### 1.3. Testing Facility

<input checked="" type="checkbox"/>	<b>Test Site - MRT Suzhou Laboratory</b>
	<b>Laboratory Location (Suzhou - Wuzhong)</b> D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	<b>Laboratory Location (Suzhou - SIP)</b> 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	<b>Laboratory Accreditations</b>
	A2LA: 3628.01 <span style="float: right;">CNAS: L10551</span>
	FCC: CN1166 <span style="float: right;">ISED: CN0001</span>
	VCCI: R-20025, G-20034, C-20020, T-20020
<input type="checkbox"/>	<b>Test Site - MRT Shenzhen Laboratory</b>
	<b>Laboratory Location (Shenzhen)</b> 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	<b>Laboratory Accreditations</b>
	A2LA: 3628.02 <span style="float: right;">CNAS: L10551</span>
	FCC: CN1284 <span style="float: right;">ISED: CN0105</span>
<input type="checkbox"/>	<b>Test Site - MRT Taiwan Laboratory</b>
	<b>Laboratory Location (Taiwan)</b> No. 38, Fuxing 2 <sup>nd</sup> Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	<b>Laboratory Accreditations</b>
	TAF: L3261-190725
	FCC: 291082, TW3261 <span style="float: right;">ISED: TW3261</span>

## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name:	LTE-A Cat 12 M.2 Module
Model No.:	EM120R-GL
Brand Name:	Quectel
IMEI:	864292050000700
LTE Specification:	Band 2, 4, 5, 7, 12, 13, 14, 25, 26, 30, 38, 41, 48, 66
Intra-Band:	CA_41C
Category:	Category 16
Operating Temperature:	-25 ~ 75 °C
Power Type:	3.1 ~ 4.4Vdc, type 3.7Vdc

### 2.2. Product Specification Subjective to this Report

Frequency Range:	TDD Band 48: 3550 ~ 3700 MHz
Device Type:	End User Device
Type of Modulation:	QPSK, 16QAM, 64QAM, 256QAM (DL)

Note: For other features of this EUT, test report will be issued separately.

### 2.3. Test Methodology


According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.26:2015
- FCC CFR 47 Part 96
- FCC KDB 971168 D01 v03r01: Power Meas License Digital Systems
- FCC KDB 971168 D02 v02r01: Misc Rev Approv License Devices
- FCC KDB 412172 D01 v01r01: Determining ERP and EIRP
- FCC KDB 940660 D01 v03 Part 96 CBRS Eqpt
- WINNF-TS-0122 V1.0.0: Test and Certification for Citizens Broadband Radio Service (CBRS); Conformance and Performance Test Technical Specification; CBS/D/DP as Unit Under Test (UUT)

### 2.4. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

## 2.5. Configuration of Tested System



## 2.6. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20% ~ 75%RH

### 3. TEST EQUIPMENT CALIBRATION DATE

#### Radiated Emission (WZ-AC1)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	MRTSUE06001	1 year	2021/08/01
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2021/11/07
PXA Signal Analyzer	Keysight	9030B	MRTSUE06395	1 year	2021/09/03
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/11/10
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2021/03/31
Broad Band Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06023	1 year	2021/10/13
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2021/02/23
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2021/11/15
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
Thermohyrometer	Testo	608-H1	MRTSUE06403	1 year	2021/08/08
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2021/04/30

#### Radiated Emission (WZ-AC2)

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Keysight	N9038A	MRTSUE06125	1 year	2021/08/01
Wideband Radio Communication Tester	R&S	CMW 500	MRTSUE06243	1 year	2021/11/07
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2021/11/10
Bilog Period Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2021/10/13
Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06171	1 year	2021/10/27
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06597	1 year	2021/02/23
Broad Band Coaxial Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2021/11/15
Preamplifier	Schwarzbeck	BBV 9721	MRTSUE06121	1 year	2021/06/11
Temperature/Humidity Meter	Minggao	ETH529	MRTSUE06170	1 year	2021/12/15
Anechoic Chamber	RIKEN	Chamber-AC2	MRTSUE06213	1 year	2021/04/30

Software	Version	Function
EMI Software	V3	EMI Test Software

#### 4. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

##### Radiated Spurious Emissions

Measurement Uncertainty for a Level of Confidence of 95% ( $U=2Uc(y)$ ):

Horizontal: 9kHz~300MHz: 5.04dB

300MHz~1GHz: 4.95dB

1GHz~40GHz: 6.40dB

Vertical: 9kHz~300MHz: 5.24dB

300MHz~1GHz: 6.03dB

1GHz~40GHz: 6.40dB



## 5. TEST RESULT

### 5.1. Summary

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1053, 96.41(e)	Spurious Emissions	Refer to section 5.2	Radiated	Pass	Section 5.2

**Notes:**

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations the worst-case was found.
- 3) This report is supplemented to MRT Original "2101RSU059-U1" Report, FCC ID: XMR2020EM120RGL updating FCC ID.

## 5.2. Radiated Spurious Emissions Measurements

### 5.2.1. Test Limit

Out of band emissions: The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed  $-40\text{dBm/MHz}$ .

$E \text{ (dB}\mu\text{V/m)} = \text{EIRP (dBm)} - 20 \log D + 104.8$ ; where D is the measurement distance in meters. The emission limit equal to  $55.3\text{dB}\mu\text{V/m}$ .

### 5.2.2. Test Procedure Used


ANSI C63.26-2015 - Section 5.2.7 & 5.5

### 5.2.3. Test Setting


1. RBW = 1MHz
2. VBW  $\geq 3 \times \text{RBW}$
3. Sweep time  $\geq 10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})$
4. Detector = Peak
5. Trace mode = max hold
6. The trace was allowed to stabilize

### 5.2.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



### 5.2.5. Test Result

Product	LTE-A Cat 12 M.2 Module	Test Site	WZ-AC2
Test Engineer	Buter Shi	Test Date	2021/01/24
Test Band	LTE Band 48 - 5MHz Bandwidth, 1RB, QPSK		

Frequency (MHz)	Reading Level (dB $\mu$ V)	Factor (dB)	Measure Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Detector	Polarization
<b>Bottom CH 55265 (3552.5MHz)</b>							
4669.0	37.3	4.4	41.7	55.3	-13.6	Peak	Horizontal
5596.0	36.7	5.5	42.2	55.3	-13.1	Peak	Horizontal
4681.0	36.1	4.6	40.7	55.3	-14.6	Peak	Vertical
5572.0	36.1	5.6	41.7	55.3	-13.6	Peak	Vertical
<b>Middle CH 55900 (3625.0MHz)</b>							
4642.0	35.6	4.3	39.9	55.3	-15.4	Peak	Horizontal
5947.0	35.5	6.9	42.4	55.3	-12.9	Peak	Horizontal
5431.0	35.5	5.3	40.8	55.3	-14.5	Peak	Vertical
6649.0	35.6	9.7	45.3	55.3	-10.0	Peak	Vertical
<b>Top CH 56715 (3697.5MHz)</b>							
5194.0	36.0	5.0	41.0	55.3	-14.3	Peak	Horizontal
6679.0	35.0	9.9	44.9	55.3	-10.4	Peak	Horizontal
5131.0	35.3	5.2	40.5	55.3	-14.8	Peak	Vertical
6541.0	34.6	9.5	44.1	55.3	-11.2	Peak	Vertical

## 6. CONCLUSION

The data collected relate only the item(s) tested and show that unit is compliance with FCC Rules.

## **Appendix A - Test Setup Photograph**

Refer to "2101RSU061-UT" file.

## **Appendix B - EUT Photograph**

Refer to "2101RSU061-UE" file.