## Quectel Wireless Solutions Company Limited

Date: February 24, 2021

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233



## Request for Modular/Limited Modular Approval

Subject: Manufacturer's Declaration for $oxtimes$ - Modular Approval $oxtimes$ - Spli $oxtimes$ - Limited Modular Approval $oxtimes$ - Limited Spli	it Modular A		
□ - Limited Modular Approvar □ - Limited Spir	it iviodulai 7	ңриоvан	
Confidentiality Request for: XMR2020RM510QGL			
8 Basic Requirements – FCC Part 15.212(a)(1) For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the F	Following P:	anes	
Modular Approval Requirement			
1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)	
Details: <example a="" all="" antenna="" board="" component="" connector="" contains="" covers="" is="" located="" metal="" module="" next="" of="" on="" rf="" shield="" the="" to="" top="" which="" –=""></example>	ts and circul	itry. The	
<ol> <li>The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)</li> </ol>	⊠ - YES	□ - NO(*)	
Details: <example application="" as="" buffered="" circuit="" data="" described="" in="" is="" modulation="" operatory="" provided="" the="" to="" with="" –=""></example>	tional descri	iption	
3. The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)	
Details: <example application="" contains="" its="" module="" own="" please="" power="" refer="" regulation.="" supply="" the="" this="" –=""></example>	to schemat	ic filed with	
4. The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)	
Details: <example a="" an="" and="" antenna="" antennas="" application="" approved="" be="" connector="" connector.="" connects="" device="" four="" its="" list="" may="" module="" of="" provided="" standard="" tested="" the="" this="" to="" ufl="" using="" which="" with="" –=""></example>			
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)	
Details: <example as="" in="" module="" photograpplication="" setup="" shown="" stand-alone="" test="" tested="" the="" was="" –=""></example>	aphs filed w	rith this	

	Modular Approval Requirement	Require	ment Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748).  If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XMR2020RM510QGL" or "Contains FCC ID: XMR2020RM510QGL" Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.  If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization.	⊠ - YES	□ - NO(*)
	Details: <example .filed="" a="" ap<="" are="" as="" exhibit="" filed="" host="" in="" installation="" instructions="" is="" label="" labeling="" manual="" module="" on="" shown="" specific="" td="" the="" there="" this="" with="" –=""><td></td><td>plication.</td></example>		plication.
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <example 15c="" application.="" are="" complies="" fcc="" filed="" in="" installation="" instructions="" manual="" module="" part="" provided="" requirements.="" the="" this="" with="" –=""></example>	to the OEN	l installer
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <example as="" exclusion="" exp<br="" in="" levels="" meets="" module="" portable="" rf="" shown="" the="" –="">with this application.&gt;</example>	oosure infor	mation filed

## **Limited Module Description – When Applicable**

\* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)		
Requirement	Requirement Met Requirement Met	
<ol> <li>For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.</li> </ol>	☐ - Provided in Separate Cover Letter	⊠ - N/A
Details: <example a="" adjusted="" application.="" as="" be="" by="" can="" cover="" described="" device="" end="" filed="" firmware="" in="" letter="" modified="" not="" of="" or="" separate="" the="" this="" user="" with="" –=""></example>		
<ol> <li>For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.</li> </ol>	☐ - Provided in Separate Cover Letter	⊠ - N/A
Details: <example a="" –n=""></example>		

Split Modular Requirements				
Requirement	Provided in Manual			
<ol> <li>For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained.</li> </ol>	☐ - Provided in Separate Cover Letter	⊠ - N/A		
Details: <example a="" n="" –=""></example>				

## OEM Integration Manual Guidance - KDB 996369 D03 Section 2

Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures for third-parties to use and/or integrate the module into a host device.

for third-parties to use and/or integrate the module into a host device.				
Requirement				
Is this module intended for sale to third parties?	□ - No,  If No, and LMA applies, the applicant can optionally choose to not make the following detailed info public. However there still needs to be basic integration instructions for a users manual and the information below must still be included in the			
As of May 1, 2019, the FCC	requires ALL the follow	ual – See KDB 996369 D03, Section 2 ing information to be in the installation		
		heir instructions for all these items indice antenna design could indicate "Not		
		d not intended for sale to third parties,		
	nd the following items ca	an be placed in the operational descript letter as cited above.		
List of applicable FCC rules.				
	elated to the transmitter.			
Summarize the specific opera	ational use conditions. KD	B 996369 D03, Section 2.3		
		ble loss, reduction of power for point to		
	professional installation inf			
<ol><li>Limited Module Procedures. I</li></ol>	KDB 996369 D03, Section	2.4		
<ol> <li>Describe alterna</li> </ol>	ative means that the grant	ee uses to verify the host meets the		
necessary limiti		•		
		ary, state how control will be maintained	to the left are provided	
such that compl	iance is ensured, such as	Class II for new hosts, etc.	in the Modular	
<ol><li>Trace antenna designs. KDB</li></ol>	996369 D03, Section 2.5		Integration Guide (or	
		, connectors, isolation requirements,	UM) for Full Modular	
		on test procedures for ensuring	Approval (MA) or	
		sed to keep confidential must be	LMA.	
	formation provided in the			
<ol><li>RF exposure considerations.</li></ol>			☐ - An LMA applies	
		allow host manufacturers to use the	and is approved	
		cessary: first to the host manufacturer	ONLY for use by the	
		cm from body) and second additional	grantee in their own	
		er in the host product manuals.	products, and not	
6. Antennas. KDB 996369 D03,			intended for sale to 3 <sup>rd</sup>	
		n and all applicable professional	parties as provided in	
		e antenna list shall also identify the	a separate cover	
		etc – note that "omni-directional" is not	letter. Therefore the	
considered a typ		Spation 2.9	information shown to	
7. Label and compliance informa		bection 2.8 to provide a physical or e-label stating	the left is found in the	
	ntegrators that they need to the state of th		theory of operation.	
		ements. KDB 996369 D03, Section 2.9		
		sideration by host integrators including		
		nd simultaneous configurations.		
	tion on how to configure to			
Additional testing, Part 15 Sul				
5. Additional testing, Fait 15 Su	Spart D disolatifier. NDD 3	20000 D00, 0000011 2.10		

Sincerely,

Jean Hu

Quectel Wireless Solutions Company Limited.

Jean Hu

TEL: +86-21-51086236 ext 6511