



# RF Exposure Evaluation Declaration

---

**FCC ID:** XMR2021EC25AFDL  
**Application:** Quectel Wireless Solutions Co., Ltd  
**Application Type:** Certification  
**Product:** LTE Module  
**Model No.:** EC25-AFDL, EC25-AFDL MINIPCIE  
**Brand Name:** Quectel  
**Test Procedure(s):** KDB 447498 D01v06  
**Test Date:** December 08 ~ 28, 2021

**Reviewed By:**

\_\_\_\_\_  
Sunny Sun

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

Report No.	Version	Description	Issue Date	Note
2112RSU017-U2	Rev. 01	Initial Report	01-13-2022	Valid



**1.4. Product Information**

Product Name	LTE Module
Model No.	EC25-AFDL, EC25-AFDL MINIPCIE
Brand Name	Quectel
IMEI	Conducted Measurement: 863368050002846 Radiated Measurement: 863368050002507
E-UTRA Specification	
Single Band	Band 2, 4, 5, 12, 13, 14, 66, 71
Modulation	Uplink up to 16QAM
Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	LTE Module
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum Conducted Power (dBm)	Limit (mW/cm <sup>2</sup> )	EIRP according to Pd (dBm)	Gain according to Pd (dBi)
LTE B2	1850 ~ 1910	25.00	1.0000	37.01	12.01
LTE B4	1710 ~ 1755	25.00	1.0000	37.01	12.01
LTE B5	824 ~ 849	25.00	0.5493	34.41	9.41
LTE B12	699 ~ 716	25.00	0.4660	33.70	8.70
LTE B13	777 ~ 787	25.00	0.5180	34.16	9.16
LTE B14	788 ~ 798	25.00	0.5253	34.22	9.22
LTE B66	1710 ~ 1780	25.00	1.0000	37.01	12.01
LTE B71	663 ~ 698	25.00	0.4420	33.47	8.47

Note: The compliance distance is 20cm.

## Appendix A – EUT Photograph

Refer to “2112RSU017-UE” file.

---

The End