



## RF Exposure Evaluation Declaration

---

**FCC ID:** XMR2021SC20ALD  
**Application:** Quectel Wireless Solutions Co., Ltd  
**Application Type:** Certification  
**Product:** LTE Module  
**Model No.:** SC20-ALD  
**Brand Name:** Quectel  
**Test Procedure(s):** KDB 447498 D01v06  
**Test Date:** December 21 ~ 27, 2021

**Reviewed By:**

\_\_\_\_\_  
Sunny Sun

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

Report No.	Version	Description	Issue Date	Note
2112RSU025-U6	Rev. 01	Initial Report	01-13-2022	Valid



#### 1.4. Product Information

Product Name	LTE Module
Model No.	SC20-ALD
Serial No.	D1Y21L22E000063
Brand Name	Quectel
Operating Temperature	-35 ~ 75°C
Wi-Fi Specification	802.11a/b/g/n
Bluetooth Specification	V4.1 dual mode
E-UTRA Band	Band 2, 4, 5, 7, 12, 13, 25, 26
Note: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

r = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	LTE Module
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Tune-up Power (dBm)	Antenna Gain (dBi)	EIRP or ERP (dBm)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
LTE B2	1850 ~ 1910	25.00	2.00	27.00	0.0997	1.0000
LTE B4	1710 ~ 1755	25.00	2.00	27.00	0.0997	1.0000
LTE B5	824 ~ 849	25.00	2.00	24.85	0.0608	0.5493
LTE B7	2500 ~ 2570	25.00	3.00	28.00	0.1255	1.0000
LTE B12	699 ~ 716	25.00	3.00	25.85	0.0765	0.4660
LTE B13	777 ~ 787	25.00	4.00	26.85	0.0963	0.5180
LTE B25	1850 ~ 1915	25.00	2.00	27.00	0.0997	1.0000
LTE B26	814 ~ 849	25.00	2.00	24.85	0.0608	0.5427
Bluetooth	2402 ~ 2480	7.32	3.0	10.32	0.0021	1.0000
2.4G Wi-Fi	2412 ~ 2462	21.81	3.0	24.81	0.0602	1.0000
5G Wi-Fi	5180 ~ 5825	11.96	4.0	15.96	0.0078	1.0000

WWAN Power Density / Limit	Bluetooth Power Density / Limit	Wi-Fi Power Density / Limit	Σ (Power Density / Limit)
0.1255	0.0021	0.0602 + 0.0078	0.1956

Note:

- For colocation analysis, LTE Band 7 is chosen for summation due to the highest (power density / limit) among all WWAN wireless modes.
- Σ(Power Density / Limit): This is a summation of [(power density for each transmitter / antenna included in the simultaneous transmission) / (corresponding MPE limit)], for WWAN + Bluetooth + Wi-Fi

## Appendix A – EUT Photograph

Refer to “2112RSU025-UE” file.

---

The End