



# RF Exposure Evaluation Declaration

---

**FCC ID:** XMR202205EC200UAU  
**Applicant:** Quectel Wireless Solutions Co., Ltd  
**Product:** LTE Module  
**Model No.:** EC200U-AU  
**Brand Name:** Quectel  
**FCC Rule Part(s)** FCC Part 2.1091

**Reviewed By:**

\_\_\_\_\_  
Sunny Sun

**Approved By:**

\_\_\_\_\_  
Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

### Revision History

Report No.	Version	Description	Issue Date	Note
2203RSU034-U6	Rev. 01	Initial Report	04-13-2022	Valid

---

## CONTENTS

Description	Page
<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1. Applicant.....	4
1.2. Manufacturer.....	4
1.3. Testing Facility .....	4
1.4. Product Information.....	5
<b>2. RF Exposure Evaluation .....</b>	<b>6</b>
2.1. Limits.....	6
2.2. Test Result of RF Exposure Evaluation.....	7
<b>Appendix A – EUT Photograph .....</b>	<b>8</b>



**1.4. Product Information**

Product Name	LTE Module
Model No.	EC200U-AU
IMEI	Conducted Measurement: 867869060001682 Radiated Measurement: 867869060001626
Wi-Fi Specification	802.11b Rx Scan
Bluetooth Specification	V4.2 BR/EDR
GSM Specification	GSM 850/1900
LTE Specification	LTE Band 2/4/5/7/38/41/66
Working Voltage	3.3 ~ 4.3Vdc, 3.8Vdc Typ.
Remark:	The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	LTE Module
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Tune-up Power (dBm)	Antenna Gain (dBi)	EIRP or ERP (dBm)	Power Density at 20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
GSM 850	824 ~ 849	26.00	2.53	26.38	0.0864	0.5493
PCS 1900	1850 ~ 1910	23.00	1.59	24.59	0.0572	1.0000
LTE B2	1850 ~ 1910	25.00	1.59	26.59	0.0907	1.0000
LTE B4	1710 ~ 1755	25.00	2.00	27.00	0.0997	1.0000
LTE B5	824 ~ 849	25.00	2.53	25.38	0.0687	0.5493
LTE B7	2500 ~ 2570	25.00	3.00	28.00	0.1255	1.0000
LTE B38	2570 ~ 2620	25.00	2.30	27.30	0.1068	1.0000
LTE B41	2496 ~ 2690	25.00	3.00	28.00	0.1255	1.0000
LTE B66	1710 ~ 1780	25.00	2.00	27.00	0.0997	1.0000
Bluetooth	2402 ~ 2480	7.66	0.50	8.16	0.0013	1.0000

WWAN Power Density / Limit	Bluetooth Power Density / Limit	Σ (Power Density / Limit)
0.1255	0.0013	0.1268

Note:

1. For colocation analysis, LTE Band 7 is chosen for summation due to the highest (power density / limit) among all WWAN wireless modes;
2.  $\Sigma(\text{Power Density} / \text{Limit})$ : This is a summation of [(power density for each transmitter / antenna included in the simultaneous transmission) / (corresponding MPE limit)], for WWAN + Bluetooth;
3. The EIRP = Tune-up power + Antenna Gain; ERP = Tune-up power + Antenna Gain – 2.15.

## Appendix A – EUT Photograph

Refer to “2203RSU034-UE” file.

---

The End