Quectel Wireless Solutions Co., Ltd

Request for Modular/Limited Modular Approval

Date: January 24, 2024					
bject: Manufacturer's Declaration for				approval	
Confidentiality Request for: <u>XMR2022EM060KGL</u>					
8 Basic Requirements – FCC Part 15.212(a)(1)					
For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the Following Pages Modular Approval Requirement Requirement Met					
1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)		⊠ - YES	□ - NO(*)		
Details: <example a="" all="" and="" antenna="" board="" circuitry.="" components="" connector="" contains="" covers="" is="" located="" metal="" module="" next="" of="" on="" rf="" shield="" the="" to="" top="" which="" –=""></example>					
2. The modular transmitter must have buffere ensure that the module will comply with FO over-modulation. 15.212(a)(1)(ii)			⊠ - YES	□ - NO(*)	
Details: <example application="" as="" buffered="" circuit="" data="" described="" description="" in="" is="" modulation="" operational="" provided="" the="" to="" with="" –=""></example>					
The modular transmitter must have its own ensure that the module will comply with FG supplying circuitry in the device into which	CC requirements regardless of the design	of the power	⊠ - YES	□ - NO(*)	
Details: <example application="" contains="" filed="" its="" module="" own="" please="" power="" refer="" regulation.="" schematic="" supply="" the="" this="" to="" with="" –=""></example>					
4. The modular transmitter must comply with §§ 15.203, 15.204(b), 15.204(c), 15.212(a) attached or employ a "unique" antenna co antenna, including the cable). The "profess to modules but can apply to limited modula	, and 2.929(b). The antenna must either bupler (at all connections between the mostional installation" provision of § 15.203	e permanently dule and the is not applicable	⊠ - YES	□ - NO(*)	
Details: <example a="" an="" and="" antenna="" antennas="" application="" approved="" be="" connector="" connector.="" connects="" considered="" device="" found="" in="" is="" its="" list="" manual="" may="" module="" non-standard="" of="" provided="" tested="" the="" this="" to="" ufl="" users="" using="" which="" with="" –=""></example>					
5. The modular transmitter must be tested in a inside another device during testing. This is complying with Part 15 emission limits reg Unless the transmitter module will be batte requirements found in Section 15.207. AC the module must not contain ferrites, unless 15.27(a)). The length of these lines shall be least 10 centimeters to insure that there is nequipment. Any accessories, peripherals, o shall be unmodified or commercially availar.	s intended to demonstrate that the module ardless of the device into which it is ever ry powered, it must comply with the AC or DC power lines and data input/output is they will be marketed with the module (elength typical of actual use or, if that ler to coupling between the case of the modur support equipment connected to the module.	e is capable of ntually installed. line conducted lines connected to (see Section ngth is unknown, at alle and supporting dule during testing	⊠ - YES	□ - NO(*)	
Details: <example application="" as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" test="" tested="" the="" this="" was="" with="" –=""></example>					

Quectel Wireless Solutions Co., Ltd

	Modular Approval Requirement	Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XMR2022EM060KGL" or "Contains FCC ID: XMR2022EM060KGL." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use	⊠ - YES	□ - NO(*)
	wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi) Details: <example -="" a="" application="" application.<="" as="" exhibit="" filed="" in="" is="" label="" labeling="" module="" on="" shown="" td="" the="" there="" this="" with=""><td>olication. Hos</td><td>et specific</td></example>	olication. Hos	et specific
	labeling instructions are shown in the installation manual filed with this application.>		
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <example 15c="" application.="" complies="" fcc="" filed="" installation="" instructions="" manual="" module="" oem="" part="" requirements.="" the="" this="" to="" with="" –=""></example>	I installer are	provided in
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <example application.="" as="" exclusion="" exposure="" in="" inform="" levels="" meets="" module="" portable="" rf="" shown="" the="" –=""></example>	ation filed wi	th this

Sincerely,

Jean Hu

Email: jean.hu@quectel.com