

Report No.: SEWM2209000164RG07

Rev.: 1 of 8 Page:

TEST REPORT

Application No.: SEWM2209000164RG

Applicant: Quectel Wireless Solutions Co., Ltd.

Address of Applicant: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin

Road, Minhang District, Shanghai, China 200233

Manufacturer: Quectel Wireless Solutions Co., Ltd.

Address of Manufacturer: Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin

Road, Minhang District, Shanghai, China 200233

EUT Description: Multi-mode Smart LTE Module

Model No.: SC206E-NA

Trade Mark: Quectel

FCC ID: XMR2022SC206ENA

Standards: FCC 47 CFR Part 2.1091

FCC KDB 447498 D01 v06

Date of Receipt: 2022/05/07 Date of Issue: 2022/09/07

Test Result: PASS*

Authorized Signature:

Panta Sun Wireless Laboratory Manager



South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国•苏州•中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 sgs.china@sgs.com

In the configuration tested, the EUT complied with the standards specified above.



Report No.: SEWM2209000164RG07

Rev.: 01 Page: 2 of 8

Version

Revision Record							
Version Chapter Date Modifier Remark							
01		2022/09/07		Original			

Prepared By	weller lin		
	(Weller Liu) / Test Engineer		
Checked By	well wei'		
	(Well Wei) / Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Conditions/Terms

t (86-512) 62992980



Report No.: SEWM2209000164RG07

Rev.: 01 Page: 3 of 8

Contents

1	Ver	sion	2
		neral Information	
		Client Information Test Facility	
	2.3	General Description of EUT	
3	RF	Exposure Evaluation	6
	3.1	RF Exposure Compliance Requirement	6
	_	.1 Limits	_
	3.1.	.2 Test Procedure	7
	3.1.	.3 EUT RF Exposure Evaluation	7
	3.1.	.4 Exposure calculations for multiple sources	8



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en/Conditions/Terms

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Plat Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜裔1号的6号厂房南部 邮编: 215000 t (86–512) 62992980 www.sgsgroup.com.cn t (86–512) 62992980 sgs.china@sgs.com

00-012) 02032300



Report No.: SEWM2209000164RG07

Rev.: 01 Page: 4 of 8

2 General Information

2.1 Client Information

Applicant:	Quectel Wireless Solutions Co., Ltd.
Address of Applicant:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Manufacturer:	Quectel Wireless Solutions Co., Ltd.
Address of Manufacturer:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

• Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC –Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327





Report No.: SEWM2209000164RG07

Rev.: 01 Page: 5 of 8

2.3 General Description of EUT

EUT Description:	Multi-mode Smart LTE M	Multi-mode Smart LTE Module						
Model No.:	SC206E-NA							
Trade Mark:	Quectel							
Hardware Version:	LPDDR4X: R1.0	LPDDR4X: R1.0						
naidwaie version.	LPDDR3: R1.1	LPDDR3: R1.1						
Software Version:	SC206ENANAR60A02							
Antenna Type:		d						
	LTE Band 2:	1.59dBi	LTE Band 4:	2dBi				
	LTE Band 5:	2.13dBi	LTE Band 7:	3dBi				
	LTE Band 12:	3.26dBi	LTE Band 13:	3.63dBi				
	LTE Band 14:	3.47dBi	LTE Band 17:	3.26dBi				
	LTE Band 25:	1.59dBi	LTE Band 26:	2.13dBi				
Antenna Gain:	LTE Band 41:	3dBi	LTE Band 66:	2dBi				
	LTE Band 71:	1.13dBi	BT/BLE/2.4GWIFI:	0.47dBi				
	5150MHz to 5250MHz:	-0.67dBi	5250MHz to 5350MHz:	-0.19dBi				
	5470MHz to 5725MHz:	1.28dBi	5725MHz to 5850MHz:	1.1dBi				
	Note:							
	The antenna gain are del manufacturer.	rived from the g	gain information report provi	ded by the				

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Remark for SEWA2205000012RG07 issue on 2022/06/08:

According to customer statement, SC200E-NA has two versions of samples, because the RF performance of the two version is exactly the same, the data of the LPDDR4X version and the LPDDR3 version can be shared.

Remark for SEWM2209000164RG07 issue on 2022/09/07:

This test report (Report No.: SEWM2209000164RG07 issue on 2022/09/07) is based on the original report with report number SEWA2205000012RG07 issue on 2022/06/08.

Review this report and original report, this report just changing FCC ID, Model No. and Software Version, Which according to the declaration letter from client.

Therefore in this report all items do not need to recalculate and all test data in this report are based on the previous report with report number SEWA2205000012RG07 issue on 2022/06/08.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.appx and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-C

South of No. 6 Plant, No. 1, Runsheng Road, Suchou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜商1号的6号厂房南部 邮编: 215000 t (86-512) 62992980 t (86-512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com



Report No.: SEWM2209000164RG07

Rev.: 01 Page: 6 of 8

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)				Averaging time (minutes)
	(A) Limits for Occup	ational/Controlled Expo	sures	
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f2)	6
30-300	61.4	0.163	1.0	6
300-1500	1	1	f/300	6
1500-100,000	1	1	5	6
	(B) Limits for General P	opulation/Uncontrolled I	Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500	1	1	f/1500	30
1500-100,000	1	1	1.0	30

F=frequency in MHz

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*Pi*R^2)$

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.apxx and, for electronic format documents, subject to Terms and Conditions after lectronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.apxx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please creatined for 30 days only.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pllot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路(号的6号厂房南部 邮编: 215000 t (86-512) 62992980 t (86-512) 62992980

www.sgsgroup.com.cn sgs.china@sgs.com

^{*=}Plane-wave equivalent power density



Report No.: SEWA2205000012RG07

Rev.: 01 Page: 7 of 8

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

3.1.3 EUT RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 / 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Operating Band	Frequenc y (MHz)	Antenna Gain (dBi)	Max Conducted Average Output Power (dBm)	Output Power to Antenna (dBm)	EIRP(ERP) Limit (dBm)	Output Power to Antenna (mw)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusion
LTE B2	1880	1.59	25.00	26.59	33.00	316.2278	0.0907	1.0000	8.00	12.01	8.00	Pass
LTE B4	1710.7	2.00	25.00	27.00	30.00	316.2278	0.0997	1.0000	5.00	12.01	5.00	Pass
LTE B5	824.70	2.13	25.00	24.98	38.45	316.2278	0.1027	0.5498	11.30	9.41	9.41	Pass
LTE B7	2502.50	3.00	25.00	28.00	33.00	316.2278	0.1255	1.0000	8.00	12.01	8.00	Pass
LTE B12	699.70	3.26	25.00	26.11	34.77	316.2278	0.1333	0.4665	7.62	8.70	7.62	Pass
LTE B13	779.50	3.63	25.00	26.48	34.77	316.2278	0.1451	0.5197	7.62	9.16	7.62	Pass
LTE B14	790.5	3.47	25.00	26.32	34.77	316.2278	0.1399	0.5270	7.62	9.23	7.62	Pass
LTE B17	706.5	3.26	25.00	26.11	34.77	316.2278	0.1333	0.4710	7.62	8.74	7.62	Pass
LTE B25	1850.7	1.59	25.00	26.59	33.00	316.2278	0.0907	1.0000	8.00	12.01	8.00	Pass
LTE B26(814-824)	814	2.13	25.00	24.98	NA	316.2278	0.1027	0.5427	NA	9.35	9.35	Pass
LTE B26(824-849)	824.7	2.13	25.00	24.98	38.45	316.2278	0.1027	0.5498	11.30	9.41	9.41	Pass
LTE B41	2498.5	3.00	25.00	28.00	33.00	316.2278	0.1255	1.0000	8.00	12.01	8.00	Pass
LTE B66	1710.7	2.00	25.00	27.00	30.00	316.2278	0.0997	1.0000	5.00	12.01	5.00	Pass
LTE B71	665.5	1.13	25.00	23.98	34.77	316.2278	0.0816	0.4437	7.62	8.48	7.62	Pass
BT	2402	0.47	10.00	10.47	30.00	10.0000	0.0022	1.0000		•		Pass
2.4GWIFI	2412	0.47	19.50	19.97	30.00	89.1251	0.0198	1.0000		NA		Pass
5GWIFI	5320	1.28	18.50	19.78	30.00	70.7946	0.0189	1.0000				Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sps.com/en/Terms-and-Conditions.app.and, for electronic Documents as this:

Author of the Conditions for Electronic Documents at http://www.sps.com/en/Terms-and-Conditions/Terms-en-Document.app.

Author of Italians of Italians and Italians



Report No.: SEWM2209000164RG07

Rev.: 01 Page: 8 of 8

3.1.4 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table(A) and Table(B). To comply with the MPE, the fraction of the MPE in terms of E2, H2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^{n} \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
	LTE + Bluetooth
1	LTE + WiFi 2.4G
	LTE + WiFi 5G
2	Bluetooth + WiFi 2.4G
2	Bluetooth + WiFi 5G

No.	Mode	Power Density (W/cm2)	MPE Limit (W/cm2)	Result Ratio	Total Ratio	Limit	Result
	LTE Band 12	0.1333	0.4665	0.2857	0.0070	4.00	D
	Bluetooth	0.0022	1.0000	0.0022	0.2879	1.00	Pass
4	LTE Band 12	0.1333	0.4665	0.2857	0.2055	4.00	Pass
'	WiFi 2.4G	0.0198	1.0000	0.0198	0.3055	1.00	
	LTE Band 12	0.1333	0.4665	0.2857	0.3046	1.00	Pass
	WiFi 5G	0.0189	1.0000	0.0189	0.3046		
	Bluetooth	0.0022	1.0000	0.0022	0.0000	4.00	Daga
2	WiFi 2.4G	0.0198	1.0000	0.0198	0.0220 1.00		Pass
	Bluetooth	0.0022	1.0000	0.0022	0.0211	4.00	Dana
	WiFi 5G	0.0189	1.0000	0.0189	0.0211	1.00	Pass

---End of Report---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions/Terms-en/C

South of No. 6 Plant. No. 1, Runsheng Road, Suchou Industrial Park, Suchou Area, China (Liangsu) Plot Free Tade Zone 215000 t (86—512) 62992980 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州 F区苏州工业园区润胜商1号的6号厂房南部 邮编: 215000 t (86—512) 62992980

www.sgsgroup.com.cn

sgs.china@sgs.com