

# MPE TEST REPORT

<b>Applicant</b>	Quectel Wireless Solutions Company Limited
<b>FCC ID</b>	XMR202309AF55C
<b>Product</b>	Wi-Fi & Bluetooth Module
<b>Brand</b>	Quectel
<b>Model</b>	AF55C
<b>Report No.</b>	R2308A0966-M1
<b>Issue Date</b>	December 8, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

*Prepared by: Wei Fangying*

*Approved by: Fan Guangchang*

## **TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## Table of Contents

1	Test Laboratory.....	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility.....	3
1.3	Testing Location.....	3
1.4	Laboratory Environment.....	3
2	Description of Equipment Under Test.....	4
3	Maximum Output Power and Antenna Gain.....	5
4	Test Result.....	6
	ANNEX A: The EUT Appearance.....	8

# 1 Test Laboratory

## 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

## 1.2 Test Facility

### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

## 1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Fan Guangchang  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [fanguangchang@ta-shanghai.com](mailto:fanguangchang@ta-shanghai.com)

## 1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 $\Omega$
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

## 2 Description of Equipment Under Test

### Client Information

<b>Applicant</b>	Quectel Wireless Solutions Company Limited
<b>Applicant address</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China, 200233
<b>Manufacturer</b>	Quectel Wireless Solutions Company Limited
<b>Manufacturer address</b>	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China, 200233

### General Technologies

EUT Description			
Model	AF55C		
SN	P1C23GK0B001141		
Hardware Version	R1.0		
Software Version	NA		
Frequency	Band	TX (MHz)	RX (MHz)
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	Wi-Fi 5G (U-NII-1)	5150 ~ 5250	5150 ~ 5250
	Wi-Fi 5G (U-NII-2A)	5250 ~ 5350	5250 ~ 5350
	Wi-Fi 5G (U-NII-2C)	5470 ~ 5600	5470 ~ 5600
		5650 ~ 5725	5650 ~ 5725
Wi-Fi 5G (U-NII-3)	5725 ~ 5850	5725 ~ 5850	
Date of Testing	September 22, 2023~ November 20, 2023		
Date of Sample Received	September 11, 2023		
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

### 3 Maximum Output Power and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by  

$$\text{Numeric gain (G)} = 10^{(\text{antenna gain}/10)}$$

Band	Maximum Output Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
Bluetooth	8.03	6.353	-0.10	0.977
Bluetooth LE	7.72	5.916	-0.10	0.977
Wi-Fi 2.4G	18.72	74.473	-0.10	0.977
Wi-Fi 5G (U-NII-1)	19.11	81.470	-0.90	0.813
Wi-Fi 5G (U-NII-2A)	18.78	75.509	-1.40	0.724
Wi-Fi 5G (U-NII-2C)	18.24	66.681	-0.30	0.933
Wi-Fi 5G (U-NII-3)	18.72	74.473	0.40	1.096

## 4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0 .....	614	1.63	*(100)	6
3-30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300 .....	61.4	0.163	1.0	6
300-1500 .....			f/300	6
1500-100,000 .....			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34 .....	614	1.63	*(100)	30
1.34-30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300 .....	27.5	0.073	0.2	30
300-1500 .....			f/1500	30
1500-100,000 .....			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm <sup>2</sup> )
Bluetooth	1.000
Bluetooth LE	1.000
Wi-Fi 2.4G	1.000
Wi-Fi 5G	1.000

### RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Output Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm <sup>2</sup> )	Limit Value (mW/cm <sup>2</sup> )
Bluetooth	8.03	-0.10	7.930	6.209	0.001	1.000
Bluetooth LE	7.72	-0.10	7.620	5.781	0.001	1.000
Wi-Fi 2.4G	18.72	-0.10	18.620	72.778	0.014	1.000
Wi-Fi 5G (U-NII-1)	19.11	-0.90	18.210	66.222	0.013	1.000
Wi-Fi 5G (U-NII-2A)	18.78	-1.40	17.380	54.702	0.011	1.000
Wi-Fi 5G (U-NII-2C)	18.24	-0.30	17.940	62.230	0.012	1.000
Wi-Fi 5G (U-NII-3)	18.72	0.40	19.120	81.658	0.016	1.000
Note: R = 20cm						
π= 3.1416						

Bluetooth antenna and Wi-Fi 2.4G antenna and Wi-Fi 5G antenna can't transmit simultaneously.

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

## ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

\*\*\*\*\*END OF REPORT \*\*\*\*\*