

RF Exposure Evaluation Report

APPLICANT : Quectel Wireless Solutions Co., Ltd.
EQUIPMENT : LTE Module
BRAND NAME : Quectel
MODEL NAME : EG912U-GL
FCC ID : XMR2023EG912UGL
STANDARD : 47 CFR Part 2.1091

The product evaluation date was started from Feb. 08, 2023 and completed on Feb. 08, 2023. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA2D1203	Rev. 01	Initial issue of report.	Feb. 22, 2023



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Quectel Wireless Solutions Co., Ltd.
Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233, China

Manufacturer	
Company Name	Quectel Wireless Solutions Co., Ltd.
Address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, 200233, China



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	LTE Module
Brand Name	Quectel
Model Name	EG912U-GL
FCC ID	XMR2023EG912UGL
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 66: 1710 MHz ~ 1780 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS LTE: QPSK, 16QAM Bluetooth BR/EDR/LE
Antenna Gain	Bluetooth: 0.47 dBi
Antenna Type	Bluetooth: Folded Dipole Antenna
HW Version	R1.0
SW Version	EG912UGLAAR03A04M08
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:
1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF average output tune up power among production units

<GSM>

Mode	Burst average power(dBm)	
	GSM850	GSM1900
GSM (GMSK, 1 Tx slot)	35.0	31.0
GPRS (GMSK, 1 Tx slot)	35.0	31.0
GPRS (GMSK, 2 Tx slots)	32.0	30.0
GPRS (GMSK, 3 Tx slots)	31.0	28.0
GPRS (GMSK, 4 Tx slots)	29.0	26.0

<LTE>

Mode	Maximum Average power(dBm)	
LTE	Band 2	25.00
	Band 4	25.00
	Band 5	25.00
	Band 7	25.00
	Band 12	25.00
	Band 13	25.00
	Band 17	25.00
	Band 25	25.00
	Band 26	25.00
	Band 38	25.00
	Band 41	25.00
	Band 66	25.00

<Bluetooth>

Mode	Maximum Average power(dBm)	
Bluetooth	BR/EDR	6.00
	LE	6.00



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = Power Density
- P = Output Power at Antenna Terminals
- G = Gain of Transmit Antenna (linear gain)
- R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Maximum Power (dBm)	MPE evaluation distance (cm)	FCC ERP/EIRP Limit (W)	Limit (mW/cm ²)	Ant Gain to meet FCC MPE limit (dBi)	Ant Gain to meet FCC ERP/EIRP limit (dBi)	Max Gain to meet FCC ERP/EIRP and MPE limit (dBi)	Max gain allowed (dBi)
GSM 850 (1 Tx slot)	824	35.00	20.00	7.000	0.549	8.4	3.5	3.5	3.5
GPRS 850 (1 Tx slot)	824	35.00	20.00	7.000	0.549	8.4	3.5	3.5	
GPRS 850 (2 Tx slots)	824	32.00	20.00	7.000	0.549	8.4	6.5	6.5	
GPRS 850 (3 Tx slots)	824	31.00	20.00	7.000	0.549	7.7	7.5	7.5	
GPRS 850 (4 Tx slots)	824	29.00	20.00	7.000	0.549	8.4	9.5	8.4	
GSM 1900 (1 Tx slot)	1850	31.00	20.00	2.000	1.000	15.0	2.0	2.0	2.0
GPRS 1900 (1 Tx slot)	1850	31.00	20.00	2.000	1.000	15.0	2.0	2.0	
GPRS 1900 (2 Tx slots)	1850	30.00	20.00	2.000	1.000	13.0	3.0	3.0	
GPRS 1900 (3 Tx slots)	1850	28.00	20.00	2.000	1.000	13.3	5.0	5.0	
GPRS 1900 (4 Tx slots)	1850	26.00	20.00	2.000	1.000	14.0	7.0	7.0	
LTE Band 2	1850.0	25.00	20.00	2.000	1.000	12.0	8.0	8.0	8.0
LTE Band 4	1710.0	25.00	20.00	1.000	1.000	12.0	5.0	5.0	5.0
LTE Band 5	824.0	25.00	20.00	7.000	0.549	9.4	13.5	9.4	9.4
LTE Band 7	2500.0	25.00	20.00	2.000	1.000	12.0	8.0	8.0	8.0
LTE Band 12	699.0	25.00	20.00	3.000	0.466	8.7	9.8	8.7	8.7
LTE Band 13	777.0	25.00	20.00	3.000	0.518	9.2	9.8	9.2	9.2
LTE Band 17	704.0	25.00	20.00	3.000	0.469	8.7	9.8	8.7	8.7
LTE Band 25	1850.0	25.00	20.00	2.000	1.000	12.0	8.0	8.0	8.0
LTE Band 26	814.0	25.00	20.00	7.000	0.543	9.4	13.5	9.4	9.4
LTE Band 38	2496.0	25.00	20.00	2.000	1.000	12.0	8.0	8.0	8.0
LTE Band 41	2496.0	25.00	20.00	2.000	1.000	12.0	8.0	8.0	8.0
LTE Band 66	1710.0	25.00	20.00	1.000	1.000	12.0	5.0	5.0	5.0

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
Bluetooth	2402	0.47	6.00	6.470	4.436	0.001	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, WWAN and Bluetooth cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----